

### Headquarters P.O. Box 3000 Johnstown Castle Estate County Wexford Ireland

# WASTE LICENCE **Proposed Decision**

Licence Register Number:	W0220-01	
Applicant/Licensee:	Greenstar Limited	
Location of Facility:	Ramstown, Gorey, County Wexford	

## **INTRODUCTION**

This introduction is not part of the licence and does not purport to be a legal interpretation of the licence.

This licence relates to the operation of a Waste Transfer Facility by Greenstar Limited at Ramstown, Gorey, Co Wexford.

The facility will be allowed to accept up to 30,000 tonnes of waste per annum consisting of household, commercial, industrial and C&D wastes for disposal and recovery off site. Recyclable waste will be segregated on site while the residual fraction will be bulked and sent to landfill for disposal. All wastes handled are non-hazardous in nature however hazardous waste received as part of municipal waste will be segregated and stored within a bunded quarantine area until it can be disposed of at an appropriate facility.

The licensee must manage and operate the facility, which will be fully enclosed, to ensure that the activities do not cause environmental pollution. The licensee is required to carry out regular environmental monitoring and submit all monitoring results, and a wide range of reports on the operation and management of the facility to the Agency.

The licence sets out in detail the conditions under which Greenstar Limited will operate and manage this facility.

## Table of Contents

Glossary of Terms.		1
Decision & Reason	s for the Decisions	5
Part I Schedule of A	Activities Licensed	6
Part II Schedule of	Activities Refused	6
Part III Conditions.		7
Condition 1.	Scope	7
Condition 2.	Management of the Facility	8
Condition 3.	Infrastructure and Operation	9
Condition 4.	Interpretation	14
Condition 5.	Emissions	15
Condition 6.	Control and Monitoring	15
Condition 7.	Resource Use and Energy Efficiency	18
Condition 8.	Materials Handling	18
Condition 9.	Accident Prevention and Emergency Response	20
Condition 10.	Closure, Restoration and Aftercare	21
Condition 11.	Notifications, Records and Reports	21
Condition 12.	Financial Charges and Provisions	23
SCHEDULE C: SCHEDULE D:	Emission Limits Control & Monitoring Specified Engineering Works	25 25 26 31
SCHEDULE E: SCHEDULE F:	Reporting Annual Environmental Report	31 32

## **Glossary of Terms**

All terms in this licence should be interpreted in accordance with the definitions in the Environmental Protection Agency Acts 1992 -2003 / Waste Management Acts 1996 to 2005, unless otherwise defined in this section.

Aerosol	A suspension of solid or liquid particles in a gaseous medium.	
Adequate lighting	20 lux measured at ground level.	
AER	Annual Environmental Report.	
Agreement	Agreement in writing.	
Annually	At approximately twelve monthly intervals.	
Attachment	Any reference to Attachments in this licence refers to attachments submitted as part of this licence application.	
Application	The application by the licensee for this licence.	
Appropriate facility	A waste management facility, duly authorised under relevant law and technically suitable.	
BAT	Best Available Techniques.	
<b>Bi-annually</b>	All or part of a period of six consecutive months.	
Biennially	Once every two years.	
Biodegradable waste	Any waste that is capable of undergoing anaerobic or aerobic decomposition, such as food, garden waste, sewage sludge, paper and paperboard.	
BOD	5 day Biochemical Oxygen Demand.	
CEN	Comité Européen De Normalisation – European Committee for Standardisation.	
COD	Chemical Oxygen Demand.	
Commercial Waste	As defined in Section 5(1) of the Waste Management Acts 1996 to 2005.	
Construction and Demolition Waste	Wastes that arise from construction, renovation and demolition activities: Chapter 17 of the EWC or as otherwise may be agreed.	
Containment boom	A boom which can contain spillages and prevent them from entering drains or watercourses or from further contaminating watercourses.	
Daily	During all days of plant operation, and in the case of emissions, when emissions are taking place; with at least one measurement on any one day.	
Day	Any 24 hour period.	
Daytime	0800 hrs to 2200 hrs.	
dB(A)	Decibels (A weighted).	

DO	Dissolved Oxygen.		
Documentation	Any report, record, result, data, drawing, proposal, interpretation or other document in written or electronic form which is required by this licence.		
Drawing	Any reference to a drawing or drawing number means a drawing or drawing number contained in the application, unless otherwise specified in this licence.		
EMP	Environmental Management Programme.		
Emission Limits	Those limits, including concentration limits and deposition rates established in <i>Schedule B: Emission Limits</i> of this licence.		
Environmental Damage	Has the meaning given it in Directive 2004/35/EC.		
EPA	Environmental Protection Agency.		
European Waste Catalogue (EWC)	A harmonised, non-exhaustive list of wastes drawn up by the European Commission and published as Commission Decision 2000/532/EC and any subsequent amendment published in the Official Journal of the European Community.		
Facility	Any site or premises used for the purposes of the recovery or disposal of waste.		
Fortnightly	A minimum of 24 times per year, at approximately two week intervals.		
GC/MS	Gas Chromatography/Mass Spectroscopy.		
Green waste	Waste wood (excluding timber), plant matter such as grass cuttings, and other vegetation.		
Heavy Metals	This term is to be interpreted as set out in "Parameters of Water Quality, Interpretation and Standards" published by the Agency in 2001. ISBN 1-84095- 015-3.		
HFO	Heavy Fuel Oil.		
Hours of Operation	The hours during which the facility is authorised to be operational.		
Hours of Waste Acceptance	The hours during which the facility is authorised to accept waste.		
ICP	Inductively Coupled Plasma Spectroscopy.		
Incident	The following shall constitute an incident for the purposes of this licence:		
	(i) an emergency;		
	(ii) any emission which does not comply with the requirements of this licence;		
	(iii) any exceedence of the daily duty capacity of the waste handling equipment;		
	(iv) any trigger level specified in this licence which is attained or exceeded; and,		
	(v) any indication that environmental pollution has, or may have, taken place.		

Industrial Waste	As defined in Section 5(1) of the Waste Management Acts 1996 to 2005.	
Inert waste	Waste that does not undergo any significant physical, chemical or biological transformations. Inert waste will not dissolve, burn or otherwise physically or chemically react, biodegrade or adversely affect other matter with which it comes into contact in a way likely to give rise to environmental pollution or harm human health. The total leachability and pollutant content of the waste and the ecotoxicity of the leachate must be insignificant, and in particular not endanger the quality of surface water and/or groundwater.	
IPPC	Integrated Pollution Prevention & Control.	
K	Kelvin.	
kPa	Kilo Pascals.	
Leq	Equivalent continuous sound level.	
Licence	A Waste Licence issued in accordance with the Waste Management Acts 1996 to 2005.	
Licensee	Greenstar Limited, Unit 6, Ballyogan Business Park, Ballyogan Road, Sandyford, Dublin 18.	
Liquid Waste	Any waste in liquid form and containing less than 2% dry matter.	
List I	As listed in the EC Directives 76/464/EEC and 80/68/EEC and amendments.	
List II	As listed in the EC Directives 76/464/EEC and 80/68/EEC and amendments.	
Local Authority	Wexford County Council.	
Maintain	Keep in a fit state, including such regular inspection, servicing, calibration and repair as may be necessary to adequately perform its function.	
Mass Flow Limit	An Emission Limit Value which is expressed as the maximum mass of a substance which can be emitted per unit time.	
Mass Flow Threshold	A mass flow rate, above which, a concentration limit applies.	
Mobile Plant	Self propelled machinery used for the emplacement of wastes or for the construction of specified engineering works.	
Monthly	A minimum of 12 times per year, at approximately monthly intervals.	
Municipal waste	As defined in Section 5(1) of the Waste Management Acts 1996 to 2005.	
Night-time	2200 hrs to 0800 hrs.	
Noise Sensitive Location (NSL)	Any dwelling house, hotel or hostel, health building, educational establishment, place of worship or entertainment, or any other facility or area of high amenity which for its proper enjoyment requires the absence of noise at nuisance levels.	
Oil Separator	Device installed according to the International Standard I.S.EN 858-2:2003 (Separator systems for light liquids, (e.g. oil and petrol)-Part 2:Selection of nominal size, installation, operation and maintenance.	

PER	Pollution Emission Register.	
Quarterly	All or part of a period of three consecutive months beginning on the first day of January, April, July or October.	
Recyclable Materials	Those waste types, such as cardboard, batteries, gas cylinders, etc, which may be recycled.	
Regional Fisheries Board	South Eastern Regional Fisheries Board.	
Sanitary Authority	Wexford County Council.	
Sanitary Effluent	Waste water from facility toilet, washroom and canteen facilities.	
Sample(s)	Unless the context of this licence indicates to the contrary, samples shall include measurements by electronic instruments.	
SOP	Standard Operating Procedure.	
Specified Emissions	Those emissions listed in Schedule B: Emission Limits of this licence.	
Specified Engineering Works	Those engineering works listed in <i>Schedule D: Specified Engineering Works</i> of this licence.	
Standard Method	A National, European or internationally recognised procedure (eg, I.S. EN, ISO, CEN, BS or equivalent), as an in-house documented procedure based on the above references, a procedure as detailed in the current edition of "Standard Methods for the Examination of Water and Wastewater", (prepared and published jointly by A.P.H.A., A.W.W.A & W.E.F), American Public Health Association, 1015 Fifteenth Street, N.W., Washington DC 20005, USA; or, an alternative method as may be agreed by the Agency.	
Storm Water	Rain water run-off from roof and non-process areas.	
Temporary storage	In relation to waste is a period of less than six months as defined in the Waste Management Acts 1996 to 2005.	
The Agency	Environmental Protection Agency.	
тос	Total Organic Carbon.	
Trade Effluent	Trade Effluent has the meaning given in the Water Pollution Acts 1977 and 1990.	
Trigger Level	A parameter value, the achievement or exceedance of which requires certain actions to be taken by the licensee.	
Weekly	During all weeks of plant operation, and in the case of emissions, when emissions are taking place; with at least one measurement in any one week.	
WEEE	As defined in S.I. No. 340 of 2005.	
WWTP	Waste Water Treatment Plant.	

## Decision & Reasons for the Decisions Reasons for the Decision

The Agency is satisfied, on the basis of the information available, that subject to compliance with the conditions of this licence, any emissions from the activity will comply with and will not contravene any of the requirements of Section 40(4) of the Waste Management Acts 1996 to 2005.

In reaching this decision the Environmental Protection Agency has considered the application and supporting documentation received from the applicant, all submissions received from other parties and the report of its inspector.

## Part I Schedule of Activities Licensed

In pursuance of the powers conferred on it by the Waste Management Acts 1996 to 2005, the Environmental Protection Agency (the Agency) proposes, under Section 40(1) of the said Acts to grant this Waste Licence to Greenstar Limited, Unit 6, Ballyogan Business Park, Ballyogan Road, Sandyford, Dublin 18 to carry on the waste activities listed below at Ramstown, Gorey, County Wexford subject to conditions, with the reasons therefore and the associated schedules attached thereto set out in the licence.

#### Licensed Waste Disposal Activities, in accordance with the Third Schedule of the Waste Management Acts 1996 to 2005

Class 11.	Blending or mixture prior to submission to any activity referred to in a preceding paragraph of this Schedule.
Class 12.	Repackaging prior to submission to any activity referred to in a preceding paragraph of this Schedule.
Class 13.	Storage prior to submission to any activity referred to in a preceding paragraph of this Schedule, other than temporary storage, pending collection, on the premises where the waste concerned is produced.

#### Licensed Waste Recovery Activities, in accordance with the Fourth Schedule of the Waste Management Acts 1996 to 2005

Class 2.	Recycling or reclamation of organic substances which are not used as solvents (including composting and other biological processes).
Class 3.	Recycling or reclamation of metals and metal compounds.
Class 4.	Recycling or reclamation of other inorganic materials.
Class 13.	Storage of waste intended for submission to any activity referred to in a preceding paragraph of this Schedule, other than temporary storage, pending collection, on the premises where such waste is produced.

## Part II Schedule of Activities Refused

None of the proposed activities as set out in the licence application have been refused.

## Part III Conditions

### Condition 1. Scope

- 1.1 The facility shall be controlled, operated, and maintained and emissions shall take place as set out in this licence. All programmes required to be carried out under the terms of this licence, become part of this licence.
- 1.2 Waste Acceptance Hours and Hours of Operation
  - 1.2.1 Unless otherwise agreed in writing, the facility shall be operated only during the hours of 0800 and 1800 Monday to Friday inclusive and 0800 to 1400 on Saturdays.
  - 1.2.2 The facility shall not operate or accept/despatch waste on Sundays or on Bank Holidays without the agreement of the Agency.
- 1.3 Waste activities at this facility shall be restricted to those listed and described in *Part I Activities Licensed* and shall be as set out in the licence application or as modified under Condition 1.6 of this licence and subject to the conditions of this licence.
- 1.4 Activities at this facility shall be limited as set out in *Schedule A: Limitations*, of this licence.
- 1.5 For the purposes of this licence, the facility authorised by this licence, is the area of land outlined in red on Drawing No. B.2.2 of the application. Any reference in this licence to "facility" shall mean the area thus outlined in red. The licensed activities shall be carried on only within the area outlined.
- 1.6 No alteration to, or reconstruction in respect of, the activity or any part thereof which would, or is likely to, result in
  - (i) a material change or increase in:
    - The nature or quantity of any emission,
    - The abatement/treatment or recovery systems,
    - The range of processes to be carried out,
    - The fuels, raw materials, intermediates, products or wastes generated, or
  - (ii) any changes in:
    - Site management infrastructure or control with adverse environmental significance,

shall be carried out or commenced without prior notice to, and without the agreement of, the Agency.

1.7 This licence is for the purposes of waste licensing under the Waste Management Acts 1996 to 2005 only and nothing in this licence shall be construed as negating the licensee's statutory obligations or requirements under any other enactments or regulations.

*Reason:* To clarify the scope of this licence.

### **Condition 2.** Management of the Facility

- 2.1 Facility Management
  - 2.1.1 The licensee shall employ a suitably qualified and experienced facility manager who shall be designated as the person in charge. The facility manager or a nominated, suitably qualified and experienced, deputy shall be present on the facility at all times during its operation or as otherwise required by the Agency.
  - 2.1.2 The licensee shall ensure that personnel performing specifically assigned tasks shall be qualified on the basis of appropriate education, training and experience, as required and shall be aware of the requirements of this licence. In addition, the facility manager and his/her deputy shall successfully complete FAS waste management training programme or equivalent agreed by the Agency.
- 2.2 Environmental Management System (EMS)
  - 2.2.1 The licensee shall establish and maintain an Environmental Management System (EMS) within six months of the date of grant of this licence. The EMS shall be updated on an annual basis.
  - 2.2.2 The EMS shall include as a minimum the following elements:
    - 2.2.2.1 Management and Reporting Structure.
    - 2.2.2.2 Schedule of Environmental Objectives and Targets.

The licensee shall prepare a Schedule of Environmental Objectives and Targets. The schedule shall as a minimum provide for a review of all operations and processes, including an evaluation of practicable options, for energy and resource efficiency, the use of cleaner technology, cleaner production, and the prevention, reduction and minimisation of waste, and shall include waste reduction targets. The schedule shall include time frames for the achievement of set targets and shall address a five year period as a minimum. The schedule shall be reviewed annually and amendments thereto notified to the Agency for agreement as part of the Annual Environmental Report (AER).

2.2.2.3 Environmental Management Programme (EMP)

The licensee shall, not later than six months from the date of grant of this licence, submit to the Agency for agreement an EMP, including a time schedule, for achieving the Environmental Objectives and Targets prepared under Condition 2.2.2.2. Once agreed the EMP shall be established and maintained by the licensee. It shall include:

- (i) designation of responsibility for targets;
- (ii) the means by which they may be achieved;
- (iii) the time within which they may be achieved.

The EMP shall be reviewed annually and amendments thereto notified to the Agency for agreement as part of the Annual Environmental Report (AER) (Condition 11.11).

A report on the programme, including the success in meeting agreed targets, shall be prepared and submitted to the Agency as part of the AER. Such reports shall be retained on-site for a period of not less than seven years and shall be available for inspection by authorised persons of the Agency.

- 2.2.2.4 Documentation
  - (i) The licensee shall establish and maintain an environmental management documentation system which shall be to the satisfaction of the Agency.
  - (ii) The licensee shall issue a copy of this licence to all relevant personnel whose duties relate to any condition of this licence.
- 2.2.2.5 Corrective Action

The licensee shall establish procedures to ensure that corrective action is taken should the specified requirements of this licence not be fulfilled. The responsibility and authority for initiating further investigation and corrective action in the event of a reported nonconformity with this licence shall be defined.

2.2.2.6 Awareness and Training

The licensee shall establish and maintain procedures for identifying training needs, and for providing appropriate training, for all personnel whose work can have a significant effect upon the environment. Appropriate records of training shall be maintained.

2.2.2.7 Communications Programme

The licensee shall establish and maintain a Public Awareness and Communications Programme to ensure that members of the public are informed, and can obtain information at the facility, at all reasonable times, concerning the environmental performance of the facility.

2.3 Maintenance Programme

The licensee shall establish and maintain within six months of the date of grant of this licence a structured programme for maintenance and service of vehicles and equipment. This programme shall be supported by appropriate record keeping systems and diagnostic testing.

*Reason:* To make provision for management of the activity on a planned basis having regard to the desirability of ongoing assessment, recording and reporting of matters affecting the environment.

### **Condition 3.** Infrastructure and Operation

- 3.1 The licensee shall establish all infrastructure referred to in this licence in advance of the commencement of the licensed activities or as required by the conditions of this licence.
- 3.2 Unless otherwise agreed in writing, the building (s) to enclose the waste activities shall be constructed as described in the Application.
- 3.3 Specified Engineering Works
  - 3.3.1 The licensee shall submit proposals for all Specified Engineering Works, as defined in *Schedule D: Specified Engineering Works*, of this licence, to the Agency for its agreement at least two months prior to the intended date of

commencement of any such works. No such works shall be carried out without the prior agreement of the Agency.

- 3.3.2 All specified engineering works shall be supervised by a competent person(s) and that person, or persons, shall be present at all times during which relevant works are being undertaken.
- 3.3.3 Following the completion of all specified engineering works, the licensee shall complete a construction quality assurance validation. The validation report shall be made available to the Agency on request. The report shall, as appropriate, include the following information:-
  - (i) A description of the works;
  - (ii) As-built drawings of the works;
  - (iii) Any other information requested in writing by the Agency.
- 3.4 Facility Notice Board
  - 3.4.1 The licensee shall provide and maintain a Facility Notice Board on the facility so that it is legible to persons outside the main entrance to the facility. The minimum dimensions of the board shall be 1200mm by 750mm.
  - 3.4.2 The board shall clearly show:-
    - (i) the name and telephone number of the facility;
    - (ii) the normal hours of operation;
    - (iii) the name of the licence holder;
    - (iv) an emergency out of hours contact telephone number;
    - (v) the licence reference number; and
    - (vi) where environmental information relating to the facility can be obtained.
  - 3.4.3 A plan of the facility clearly identifying the location of each storage and treatment area shall be displayed as close as is possible to the entrance to the facility. The plan shall be displayed on a durable material such that it is legible at all times. The plan shall be replaced as material changes to the facility are made.
- 3.5 Facility Security
  - 3.5.1 Security and stockproof fencing and gates shall be installed and maintained. The base of the fencing shall be set in the ground. Subject to the implementation of the restoration and aftercare plan and to the agreement of the Agency, the requirement for such site security may be removed.
  - 3.5.2 The licensee shall install a CCTV system which record all truck movement into and out of the facility. The CCTV system shall be operated at all times the facility is in operation and copies of recording kept on site for a minimum of one year and made available to the Agency on request.
  - 3.5.3 Gates shall be locked shut when the facility is unsupervised.
  - 3.5.4 The licensee shall remedy any defect in the gates and/or fencing as follows:-
    - (i) A temporary repair shall be made by the end of the working day; and
    - (ii) A repair to the standard of the original gates and/or fencing shall be undertaken within three working days.
  - 3.5.5 Any boundary facility wall, which also acts as a boundary to a waste processing area, shall be constructed of suitable materials of sufficient

strength to withstand a normal operational environment (including impact from mobile plant).

- 3.6 Facility Roads and Site Surfaces
  - 3.6.1 Effective site roads shall be provided and maintained to ensure the safe and nuisance free movement of vehicles within the facility.
  - 3.6.2 The licensee shall provide, and maintain an impermeable hardstanding surface in the areas of the facility shown on Drawing No. 1.1.2. In addition the floor of the buildings and hardstanding areas at the facility shall be concreted and constructed to British Standard 8110 or an alternative as agreed by the Agency. The licensee shall remedy any defect in concrete surfaces within ten working days.
- 3.7 Facility Office
  - 3.7.1 The licensee shall provide and maintain an office at the facility. The office shall be constructed and maintained in a manner suitable for the processing and storing of documentation.
  - 3.7.2 The licensee shall provide and maintain a working telephone and a method for electronic transfer of information at the facility.
- 3.8 Waste Inspection and Quarantine Areas
  - 3.8.1 A Waste Inspection Area and a Waste Quarantine Area shall be provided and maintained at the facility.
  - 3.8.2 These areas shall be constructed and maintained in a manner suitable, and be of a size appropriate, for the inspection of waste and subsequent quarantine if required. The waste inspection area and the waste quarantine area shall be clearly identified and segregated from each other.
  - 3.8.3 Drainage from these areas shall be directed to the on site storage tanks described in condition 3.11.2.
- 3.9 Weighbridge and Wheel Cleaner
  - 3.9.1 The licensee shall provide and maintain a weighbridge and wheel cleaners at the facility.
  - 3.9.2 The wheel cleaners shall be used by all vehicles leaving the facility as required to ensure that no trade effluent, or waste is carried off-site. All water from the wheel cleaning area shall be directed to trade effluent drainage network.
  - 3.9.3 The wheel-wash shall be inspected on a daily basis and drained as required. Silt, stones and other accumulated material shall be removed as required from the wheel-wash and disposed of appropriately.
- 3.10 Waste handling, ventilation and processing plant
  - 3.10.1 Items of plant deemed critical to the efficient and adequate processing of waste at the facility (including *inter alia* waste loading vehicles and ejector trailers) shall be provided on the following basis:-
    - (i) 100% duty capacity;
    - (ii) 20% standby capacity available on a routine basis; and
    - (iii) Provision of contingency arrangements and/or back up and spares in the case of breakdown of critical equipment.
  - 3.10.2 Within three months from the date of grant of this licence, the licensee shall provide a report for the agreement of the Agency detailing the duty and standby capacity in tonnes per day, of all waste handling and processing equipment to be used at the facility. These capacities shall be based on the licensed waste intake, as per *Schedule A: Limitations*, of this licence.

- 3.10.3 The quantity of waste to be accepted at the facility on a daily basis shall not exceed the duty capacity of the equipment at the facility. Any exceedance of this intake shall be treated as an incident.
- 3.11 Wastewater Management
  - 3.11.1 The licensee shall provide and maintain a Wastewater Treatment System at the facility for the treatment of sanitary effluent arising on-site. The percolation area shall satisfy the criteria set out in the Wastewater Treatment Manual, Treatment Systems for Single Houses, published by the Environmental Protection Agency.
  - 3.11.2 Unless treated on the facility, trade effluent stored in the on-site storage tanks shall be tankered off-site in fully enclosed road tankers to an agreed Wastewater Treatment Plant and disposed of there.
  - 3.11.3 Prior to the roofing of the yard area, the yard drainage discharge via the holding tanks to percolation areas shall be monitored as per Schedule C.2.2. Following the roofing of the yard area, the outlet from the discharge holding tank to the percolation area shall be closed.
- 3.12 Construction and Demolition Waste Recovery Area
  - 3.12.1 In advance of the commencement of waste activities, the licensee shall provide and maintain a construction and demolition waste recovery area. This infrastructure shall at a minimum comprise the following:-
    - (i) an impermeable concrete slab;
    - (ii) collection and disposal infrastructure for all run-off;
    - (iii) appropriate bunding to provide visual and noise screening;
    - (iv) all stockpiles shall be adequately contained to minimise dust generation;
    - (v) in advance of the commencement of waste activities the licensee shall implement measures to minimise dust generation at this facility and shall as instructed by the Agency install a sprinkling irrigation system for the control of dust nuisance from the facility. Any remedial works necessary to control dust must be implemented within a time-scale to be agreed by the Agency.
  - 3.12.2 Only Construction and Demolition waste shall be accepted at this Area. Wastes which are capable of being recovered shall be separated and shall be stored temporarily in this area prior to being subjected to other recovery activities at the facility or transport off site.
- 3.13 The licensee shall install on all emission points such sampling points or equipment, including any data-logging or other electronic communication equipment, as may be required by the Agency. All such equipment shall be consistent with the safe operation of all sampling and monitoring systems.
- 3.14 Sampling equipment shall be operated and maintained such that sufficient sample is collected to meet both internal monitoring requirements and those of the Agency. A separate composite sample or homogeneous sub-sample (of sufficient volume as advised) should be retained as required for EPA use.
- 3.15 Dust/Odour Control
  - 3.15.1 All waste for disposal stored overnight at the facility, shall be stored in suitably covered and enclosed containers within the Waste Transfer Building, and shall be removed from the facility within forty eight hours of its arrival at the facility and at Bank Holiday weekends within seventy two hours of its arrival at the facility.

- 3.15.2 In dry weather, site roads and any other external areas used by vehicles shall be sprayed with water as and when required to minimise airborne dust nuisance.
- 3.15.3 The licensee shall provide and maintain adequate measures for the control of odours and dust emissions, including fugitive dust emissions, from the facility. Such measures shall at a minimum include the following:-
  - 3.15.3.1 Unless otherwise agreed in advance by the Agency dust curtains shall be maintained on the entry/exit points from the waste transfer building. Doors in the waste transfer building shall be kept closed where possible.
  - 3.15.3.2 Installation and maintenance of integrity and negative pressure throughout the building to ensure no significant escape of odours or dust.
  - 3.15.3.3 Installation of an odour management system.
  - 3.15.3.4 Provision of 100% duty capacity and 20% stand by capacity, back ups and spares must be provided for the air handling, ventilation and abatement plant.
- 3.16 Operational controls

The licensee shall provide and use adequate lighting during the operation of the facility in hours of darkness.

- 3.17 The licensee shall clearly label and provide safe and permanent access to all on-site sampling and monitoring points and to off-site points as required by the Agency.
- 3.18 Tank, Container and Drum Storage Areas
  - 3.18.1 All tank, container and drum storage areas shall be rendered impervious to the materials stored therein. Bunds should be designed having regard to Agency guidelines 'Storage and Transfer of Materials for Scheduled Activities' (2004).
  - 3.18.2 All tank and drum storage areas shall, as a minimum, be bunded, either locally or remotely, to a volume not less than the greater of the following:-
    - 3.18.2.1 110% of the capacity of the largest tank or drum within the bunded area; or
    - 3.18.2.2 25% of the total volume of substance which could be stored within the bunded area.
  - 3.18.3 All drainage from bunded areas shall be treated as hazardous waste unless it can be demonstrated to be otherwise. All drainage from bunded areas shall be diverted for collection and safe disposal.
  - 3.18.4 All inlets, outlets, vent pipes, valves and gauges must be within the bunded area.
  - 3.18.5 The integrity and water tightness of all the bunding structures, tanks and containers and their resistance to penetration by water or other materials stored therein shall be tested and demonstrated by the licensee at least once every three years. This testing shall be carried out in accordance with any guidance published by the Agency.
  - 3.18.6 All tanks containers and drums shall be labelled to clearly indicate their contents.

- 3.19 The licensee shall have in storage an adequate supply of containment booms and/or suitable absorbent material to contain and absorb any spillage at the facility. Once used the absorbent material shall be disposed of at an appropriate facility.
- 3.20 Silt Traps and Oil Separators

Prior to the commencement of the licensed activity the licensee shall install and maintain silt traps and oil separator at the facility to ensure that all storm water (excluding storm water from roof buildings) and trade effluent discharges from the facility pass through a silt trap and oil separator in advance, of discharge. The separator shall be a Class I full retention separator and the silt traps and separator shall be in accordance with I.S. EN 585-2:2003 (separator systems for light liquids)

- 3.21 All pump sumps, holding tanks, or other treatment plant chambers from which spillage of environmentally significant materials might occur in such quantities as are likely to breach local or remote containment or separator, shall be fitted with high liquid level alarms (or oil detectors as appropriate) within 3 (three) months from the date of grant of this licence.
- 3.22 The provision of a catchment system to collect any leaks from flanges and valves of all over ground pipes used to transport material other than water shall be examined. This shall be incorporated into a schedule of objectives and targets set out in Condition 2.2 of this licence for the reduction in fugitive emissions.
- 3.23 The wellhead, whose location is shown on Drawing No 1.1.2, Attachment 3 of the application shall be adequately protected to prevent contamination or physical damage within 3 (three) months from the date of grant of this licence.
- 3.24 Monitoring Infrastructure

Groundwater

- (i) Within 3 (three) months from the date of grant of this licence, the licensee shall install monitoring facilities to the site well in Recycling Building as shown in Figure 1.1.2 of the application to allow for the sampling and analyses of groundwater.
- (ii) Groundwater monitoring wells shall be constructed having regard to the guidance given in the Agency's landfill manual "Landfill Monitoring".

Reason: To provide for appropriate operation of the facility to ensure protection of the environment.

### **Condition 4.** Interpretation

- 4.1 Emission limit values for emissions to sewer/waters in this licence shall be interpreted in the following way:-
  - 4.1.1 Continuous monitoring:
    - (i) No flow value shall exceed the specified limit.
    - (ii) No pH value shall deviate from the specified range.
    - (iii) No temperature value shall exceed the limit value.
  - 4.1.2 Composite Sampling:
    - (i) No pH value shall deviate from the specified range.

- (ii) For parameters other than pH and flow, eight out of ten consecutive composite results, based on flow proportional composite sampling, shall not exceed the emission limit value. No individual result similarly calculated shall exceed 1.2 times the emission limit value.
- 4.1.3 Discrete Sampling

For parameters other than pH and temperature, no grab sample value shall exceed 1.2 times the emission limit value.

- 4.2 Where the ability to measure a parameter is affected by mixing before emission, then, with agreement from the Agency, the parameter may be assessed before mixing takes place.
- 4.3 Noise

Noise from the facility shall not give rise to sound pressure levels (Leq,T) measured at noise sensitive locations adjacent to the facility which exceed the limit value(s).

*Reason:* To clarify the interpretation of limit values fixed under the licence.

### **Condition 5. Emissions**

5.1 Emissions to Surface Water

Unless otherwise agreed by the Agency, no trade effluent, leachate and/or contaminated storm water shall be discharged to surface water drains and surface water courses.

- 5.2 There shall be no direct emissions to groundwater.
- 5.3 No specified emission from the facility shall exceed the emission limit values set out in *Schedule B: Emission Limits* of this licence. There shall be no other emissions of environmental significance.
- 5.4 The licensee shall ensure that the activities shall be carried out in a manner such that emissions including odours do not result in significant impairment of, and/or significant interference with amenities or the environment beyond the facility boundary.
- 5.5 No substance shall be discharged in a manner, or at a concentration that, following initial dilution, causes tainting of fish or shellfish.
- 5.6 The licensee shall ensure that vermin, birds, flies, mud, dust, litter and odours do not give rise to nuisance at the facility or in the immediate area of the facility. Any method used by the licensee to control any such nuisance shall not cause environmental pollution.

*Reason:* To provide for the protection of the environment by way of control and limitation of emissions.

### Condition 6. Control and Monitoring

- 6.1 Litter Control
  - 6.1.1 The measures and infrastructure as described in the Application documentation for this licence shall be applied to control litter at the facility.

- 6.1.2 All loose litter or other waste, placed on or in the vicinity of the facility, other than in accordance with the requirements of this licence, shall be removed, subject to the agreement of the landowners, immediately and in any event by 10.00am of the next working day after such waste is discovered.
- 6.1.3 The licensee shall ensure that all vehicles delivering waste to and removing waste and materials from the facility are appropriately covered.

#### 6.2 Dust/Odour Control

- 6.2.1 All waste stored overnight at the facility, shall be stored in suitably covered and enclosed containers within the Waste Transfer Building. Waste for disposal shall be removed from the facility within forty-eight hours of its arrival on site, except at Bank Holiday weekends when waste for disposal shall be removed within seventy-two hours of its arrival on site.
- 6.2.2 In dry weather, site roads and any other areas used by vehicles shall be sprayed with water as and when required to minimise airborne dust nuisance.
- 6.3 Operational Controls
  - 6.3.1 The floor of the waste transfer building shall be cleaned on a weekly basis and on a daily basis where putrescible waste is handled. The floor of the storage bays for recovered wastes shall be washed down and cleaned on each occasion such bays are emptied, or as a minimum on a weekly basis.
  - 6.3.2 Scavenging shall not be permitted at the facility.
  - 6.3.3 All tanks and drums shall be labelled to clearly indicate their contents.
  - 6.3.4 There shall be no casual public access to the facility.
- 6.4 Monitoring Locations

Within three months of the date of grant of this licence, the licensee shall submit to the Agency an appropriately scaled drawing(s) showing all the monitoring locations that are stipulated in this licence including any noise sensitive locations and private wells to be monitored. The drawing shall include the eight-digit national grid reference of each monitoring point.

6.5 Nuisance Monitoring

The licensee shall, at a minimum of one week intervals, inspect the facility and its immediate surrounds for nuisances caused by litter, vermin, birds, flies, mud, dust and odours. The licensee shall maintain a record of all nuisance inspections.

6.6 Vermin and Flies

Prior to the commencement of waste activities, the licensee shall submit to the Agency for its agreement a proposal for the control and eradication of vermin and fly infestations at the facility. This proposal should include as a minimum, operator training, details on the rodenticide(s) and insecticide(s) to be used, mode and frequency of application and measures to contain sprays within the facility boundary.

- 6.7 The licensee shall carry out such sampling, analyses, measurements, examinations, maintenance and calibrations as set out below and as in accordance with *Schedule C* : *Control & Monitoring* of this licence:
  - 6.7.1 Analysis shall be undertaken by competent staff in accordance with documented operating procedures.
  - 6.7.2 Such procedures shall be assessed for their suitability for the test matrix and performance characteristics determined.
  - 6.7.3 Such procedures shall be subject to a programme of Analytical Quality Control using control standards with evaluation of test responses.
  - 6.7.4 Where analysis is sub-contracted it shall be to a competent laboratory.

- 6.8 All automatic monitors and samplers shall be functioning at all times (except during maintenance and calibration) when the activity is being carried on unless alternative sampling or monitoring has been agreed in writing by the Agency for a limited period. In the event of the malfunction of any continuous monitor, the licensee shall contact the Agency as soon as practicable, and alternative sampling and monitoring facilities shall be put in place. Agreement for the use of alternative equipment, other than in emergency situations, shall be obtained from the Agency.
- 6.9 Monitoring and analysis equipment shall be operated and maintained as necessary so that monitoring accurately reflects the emission or discharge.
- 6.10 All treatment/abatement and emission control equipment shall be calibrated and maintained, in accordance with the instructions issued by the manufacturer/supplier or installer.
- 6.11 The frequency, methods and scope of monitoring, sampling and analyses, as set out in this licence, may be amended with the agreement of the Agency following evaluation of test results.
- 6.12 The licensee shall prepare a programme, to the satisfaction of the Agency, for the identification and reduction of fugitive emissions. This programme shall be included in the Environmental Management Programme.
- 6.13 All tanks and pipelines shall be maintained impervious to the materials carried out or stored therein. The integrity and water tightness of all underground pipes and tanks and their resistance to penetration by water or other materials carried or stored therein shall be tested and demonstrated by the licensee. This testing shall be carried out by the licensee at least once every three years thereafter and reported to the Agency on each occasion. A written record of all integrity tests and any maintenance or remedial work arising from them shall be maintained by the licensee.
- 6.14 Process Effluent

The drainage system, bunds, silt traps and oil separators shall be inspected weekly, desludged as necessary and properly maintained at all times. All sludge and drainage from these operations shall be collected for safe disposal.

- 6.15 Storm water
  - 6.15.1 A visual examination of the storm water discharge shall be carried out daily. A log of such inspections shall be maintained.
  - 6.15.2 The licensee shall carry out an investigation into the source of storm water contamination outlined in the Article 16(1) response dated 23<sup>rd</sup> February 2006. A report detailing the results of this investigation with an assessment and recommendations shall be submitted to the Agency within six months of the date of grant of this licence. Any actions arising out of this report and/or such other works as the Agency considers necessary are to be implemented within a timeframe specified by the Agency.
- 6.16 Ground Water

The licensee shall ensure that groundwater monitoring well sampling equipment is available/installed on-site and is fit for purpose at all times. The sampling equipment shall be to Agency specifications

6.17 Noise

The licensee shall carry out a noise survey of the site operations annually. The survey programme shall be undertaken in accordance with the methodology specified in the 'Environmental Noise Survey Guidance Document' as published by the Agency.

6.18 Pollution Emission Register (PER)

The licensee shall prepare and maintain a PER for the site. The substances to be included in the PER shall be agreed by the Agency each year by reference to the list

specified in the Agency's AER Guidance Note. The PER shall be prepared in accordance with any relevant guidelines issued by the Agency and shall be submitted as part of the AER.

- 6.19 The licensee shall, within six months of the date of grant of this licence, develop and establish a Data Management System for collation, archiving, assessing and graphically presenting the environmental monitoring data generated as a result of this licence.
- 6.20 Sampling and analysis of all pollutants as well as reference measurement methods to calibrate automated measurement systems shall be carried out in accordance with CEN-standards. If CEN standards are not available, ISO, national or international standards which will ensure the provision of data of an equivalent scientific quality shall apply.

*Reason:* To provide for the protection of the environment by way of treatment and monitoring of emissions.

### Condition 7. Resource Use and Energy Efficiency

- 7.1 The licensee shall carry out an audit of the energy efficiency of the site within one year of the date of grant of this licence. The audit shall be carried out in accordance with the guidance published by the Agency; "Guidance Note on Energy Efficiency Auditing". The energy efficiency audit shall be repeated at intervals as required by the Agency.
- 7.2 The audit shall identify all opportunities for energy use reduction and efficiency and the recommendations of the audit will be incorporated into the Schedule of Environmental Objectives and Targets under Condition 2 above.
- 7.3 The licensee shall identify opportunities for reduction in the quantity of water used on site including recycling and reuse initiatives, wherever possible. Reductions in water usage shall be incorporated into Schedule of Environmental Objectives and Targets.
- 7.4 The licensee shall undertake an assessment of the efficiency of use of raw materials in all processes, having particular regard to the reduction in waste generated. The assessment should take account of best international practice for this type of activity. Where improvements are identified, these shall be incorporated into the Schedule of Environmental Objectives and Targets.

Reason: To provide for the efficient use of resources and energy in all site operations.

### **Condition 8.** Materials Handling

- 8.1 All waste processing shall be carried out inside the waste transfer building
- 8.2 Waste Acceptance and Characterisation Procedures
  - 8.2.1 Waste shall only be accepted at the facility, from Local Authority waste collection or transport vehicles or holders of waste permits, unless exempted or excluded, issued under the the Waste Management Acts 1996 to 2005. Copies of these waste collection permits must be maintained at the facility.

- 8.2.2 Prior to commencement of waste acceptance at the facility, the licensee establish and maintain detailed written procedures for the acceptance and handling of wastes.
- 8.2.3 Waste arriving at the facility shall be inspected at the point of entry to the facility and subject to this inspection, weighed, documented and directed to the Waste Transfer Building. Each load of waste arriving at the Waste Transfer Building shall be inspected upon tipping within this building. Only after such inspections shall the waste be processed for disposal or recovery.
- 8.2.4 Any waste deemed unsuitable for processing at the facility and/or in contravention of this licence shall be immediately separated and removed from the facility at the earliest possible time. Temporary storage of such wastes shall be in a designated Waste Quarantine Area. Waste shall be stored under appropriate conditions in the quarantine area to avoid putrefaction, odour generation, the attraction of vermin and any other nuisance or objectionable condition.
- 8.2.5 Waste shall be accepted at the facility only from known customers or new customers subject to initial waste profiling and waste characterisation offsite. The written records of this off-site waste profiling and characterisation shall be retained by the licensee for all active customers and for a two year period following termination of licensee/customer agreements. There shall be no casual public access to the facility.
- 8.3 Disposal or recovery of waste on-site shall only take place in accordance with the conditions of this licence and in accordance with the appropriate National and European legislation and protocols.
- 8.4 Waste sent off-site for recovery or disposal shall be transported only by an authorised waste contractor. The waste shall be transported only from the site of the activity to the site of recovery/disposal in a manner that will not adversely affect the environment and in accordance with the appropriate National and European legislation and protocols.
- 8.5 The licensee shall ensure that waste in advance of transfer to another person shall be classified packaged and labelled in accordance with National, European and any other standards which are in force in relation to such labelling.
- 8.6 The loading and unloading of materials shall be carried out in designated areas protected against spillage and leachate run-off.
- 8.7 Waste shall be stored in designated areas, protected as may be appropriate, against spillage and leachate run-off. The waste is to be clearly labelled and appropriately segregated.
- 8.8 No waste classified as green list waste in accordance with the EU Transfrontier Shipment of Waste Regulations (Council Regulation EEC No.259/1993, as amended) shall be consigned for recovery without the agreement of the Agency.
- 8.9 Waste for disposal/recovery off-site shall be analysed in accordance with *Schedule C: Control & Monitoring* of this licence.
- 8.10 Unless approved in writing by the Agency the licensee is prohibited from mixing a hazardous waste of one category with a hazardous waste of another category or with any other non-hazardous waste.

*Reason:* To provide for the appropriate handling of materials and the protection of the environment.

### Condition 9. Accident Prevention and Emergency Response

- 9.1. Emergencies
  - 9.1.1. In the event of a breakdown of equipment or any other occurrence which results in the closure of the transfer station building, any waste arriving at or already collected at the facility shall be transferred directly to appropriate landfill sites or any other appropriate facility until such time as the transfer station building is returned to a fully operational status. Such a breakdown event will be treated as an emergency and rectified as soon as possible.
  - 9.1.2. All significant spillages occurring at the facility shall be treated as an emergency and immediately cleaned up and dealt with so as to alleviate their effects.
  - 9.1.3. No waste shall be burnt within the boundaries of the facility. A fire at the facility shall be treated as an emergency and immediate action shall be taken to extinguish it and notify the appropriate authorities.
  - 9.1.4. In the event that monitoring of local wells indicates that the facility is having a significant adverse effect on the quantity and/or quality of the water supply this shall be treated as an emergency and the licensee shall provide an alternative supply of water to those affected.
- 9.2 The licensee shall, in advance of the commencement of the activity, ensure that a documented Accident Prevention Policy is in place which will address the hazards on-site, particularly in relation to the prevention of accidents with a possible impact on the environment. This procedure shall be reviewed annually and updated as necessary.
- 9.3 The licensee shall, in advance of the date of commencement of the activity ensure that a documented Emergency Response Procedure is in place, which shall address any emergency situation which may originate on-site. This procedure shall include provision for minimising the effects of any emergency on the environment. This procedure shall be reviewed annually and updated as necessary.
- 9.4 Incidents
  - 9.4.1 In the event of an incident the licensee shall immediately:-
    - (i) isolate the source of any such emission;
    - (ii) carry out an immediate investigation to identify the nature, source and cause of the incident and any emission arising therefrom;
    - (iii) evaluate the environmental pollution, if any, caused by the incident;
    - (iv) identify and execute measures to minimise the emissions/malfunction and the effects thereof;
    - (v) identify the date, time and place of the incident;
    - (vi) notify the Agency and other relevant authorities.
  - 9.4.2 The licensee shall provide a report to the Agency for its agreement within one month of the incident occurring or as otherwise agreed by the Agency to:-
    - (i) identify and put in place measures to avoid reoccurrence of the incident; and
    - (ii) identify and put in place any other appropriate remedial action.

*Reason:* To provide for the protection of the environment.

### **Condition 10.** Closure, Restoration and Aftercare

10.1 Following termination, or planned cessation for a period greater than six months, of use or involvement of all or part of the site in the licensed activity, the licensee shall, to the satisfaction of the Agency, decommission, render safe or remove for disposal/recovery, any soil, subsoils, buildings, plant or equipment, or any waste, materials or substances or other matter contained therein or thereon, that may result in environmental pollution. The licensee shall carry out such tests, investigation or submit certification, as requested by the Agency, to confirm that there is no risk to the environment.

*Reason:* To make provision for the proper closure of the activity ensuring protection of the environment.

### **Condition 11.** Notifications, Records and Reports

- 11.1 The licensee shall notify the Agency, in writing, one month in advance, of the intended date of commencement of the Scheduled Activity.
- 11.2 A record shall be kept of each consignment of trade effluent, leachate and/or contaminated storm water removed from the facility. The record shall include the following:-
  - (i) the name of the carrier;
  - (ii) the date and time of removal of trade effluent, leachate and/or contaminated storm water from the facility;
  - (iii) the volume of trade effluent, leachate and/or contaminated storm water, in cubic metres, removed from the facility on each occasion;
  - (iv) the name and address of the Waste Water Treatment Plant to which the trade effluent, leachate and/or contaminated storm water was transported; and
  - (v) any incidents or spillages of trade effluent, leachate and/or contaminated storm water during its removal or transportation.
- 11.3 Waste Recovery Reports

The licensee shall as part of the EMP submit a report on the contribution by this facility to the achievement of the recovery targets stated in National and European Union waste policies and shall include the following:-

- proposals for the contribution of the facility to the achievement of targets for the reduction of biodegradable waste to landfill as specified in the Landfill Directive;
- (ii) the separation of recyclable materials from the waste;
- (iii) the recovery of Construction and Demolition Waste;
- (iv) the recovery of metal waste and WEEE.

#### 11.4 Vermin and Flies

A record shall be kept at the facility of the programme for the control and eradication of vermin and fly infestations at the facility. A report on the programme shall be prepared and submitted to the Agency as part of the AER.

- 11.5 The licensee shall notify the Agency by both telephone and either facsimile or electronic mail, if available, to the Agency's Headquarters in Wexford, or to such other Agency office as may be specified by the Agency, as soon as practicable after the occurrence of any of the following:
  - (i) Any emission which does not comply with the requirements of this licence.
  - (ii) Any malfunction or breakdown of key control equipment or monitoring equipment set out in *Schedule C: Control & Monitoring* which is likely to lead to loss of control of the abatement system.
  - (iii) Any incident with the potential for environmental contamination of surface water or groundwater, or posing an environmental threat to air or land, or requiring an emergency response by the Local Authority.
  - (iv) The licensee shall include as part of the notification, date and time of the incident, summary details of the occurrence, and where available, the steps taken to minimise any emissions.
  - (v) In the event of any incident which relates to discharges to sewer, having taken place, the licensee shall notify the Local and Sanitary Authority as soon as practicable, after such an incident.
- 11.6 In the event of any incident which relates to discharges to sewer, having taken place, the licensee shall notify the Local and Sanitary Authority as soon as practicable, after such an incident.
- 11.7 In the case of any incident which relates to discharges to water, the licensee shall notify the Local Authority and the South Eastern Regional Fisheries Board as soon as practicable after such an incident.
- 11.8 The licensee shall make a record of any incident. This record shall include details of the nature, extent, and impact of, and circumstances giving rise to, the incident. The record shall include all corrective actions taken to; manage the incident, minimise wastes generated and the effect on the environment, and avoid recurrence. The licensee shall as soon as practicable following incident notification, submit to the Agency the incident record.
- 11.9 The licensee shall record all complaints of an environmental nature related to the operation of the activity. Each such record shall give details of the date and time of the complaint, the name of the complainant and give details of the nature of the complaint. A record shall also be kept of the response made in the case of each complaint.
- 11.10 The licensee shall record all sampling, analyses, measurements, examinations, calibrations and maintenance carried out in accordance with the requirements of this licence and all other such monitoring which relates to the environmental performance of the facility.
- 11.11 The licensee shall as a minimum keep the following documents at the site:-
  - (i) the licences relating to the facility;
  - (ii) the current EMS for the facility;
  - (iii) the previous year's AER for the facility;
  - (iv) records of all sampling, analyses, measurements, examinations, calibrations and maintenance carried out in accordance with the requirements of this

licence and all other such monitoring which relates to the environmental performance of the facility;

- (v) relevant correspondence with the Agency;
- (vi) up to date site drawings/plans showing the location of key process and environmental infrastructure, including monitoring locations and emission points

and this documentation shall be available to the Agency for inspection at all reasonable times.

- 11.12 The licensee shall submit to the Agency, by the 31<sup>st</sup> March of each year, an AER covering the previous calendar year. This report, which shall be to the satisfaction of the Agency, shall include as a minimum the information specified in *Schedule F: Annual Environmental Report* of this licence and shall be prepared in accordance with any relevant guidelines issued by the Agency.
- 11.13 A full record, which shall be open to inspection by authorised persons of the Agency at all times, shall be kept by the licensee on matters relating to the waste management operations and practices at this site. This record shall be maintained on a monthly basis and shall as a minimum contain details of the following:
  - (i) The tonnages and EWC Code for the waste materials imported and/or sent off-site for disposal/recovery.
  - (ii) The names of the agent and carrier of the waste, and their waste collection permit details, if required (to include issuing authority and vehicle registration number).
  - (iii) Details of the ultimate disposal/recovery destination facility for the waste and its appropriateness to accept the consigned waste stream, to include its permit/licence details and issuing authority, if required.
  - (iv) Written confirmation of the acceptance and disposal/recovery of any hazardous waste consignments sent off-site.
  - (v) Details of all wastes consigned abroad for Recovery and classified as 'Green' in accordance with the EU Transfrontier Shipment of Waste Regulations (Council Regulation EEC No. 259/1993, as amended). The rationale for the classification must form part of the record.
  - (vi) Details of any rejected consignments.
  - (vii) Details of any approved waste mixing.
  - (viii) The results of any waste analyses required under *Schedule C: Control & Monitoring*, of this licence.
  - (ix) The tonnages and EWC Code for the waste materials recovered/disposed on-site.

*Reason:* To provide for the collection and reporting of adequate information on the activity.

### **Condition 12.** Financial Charges and Provisions

- 12.1 Agency Charges
  - 12.1.1 The licensee shall pay to the Agency an annual contribution of €9,989 or such sum as the Agency from time to time determines, having regard to variations in the extent of reporting, auditing, inspection, sampling and analysis or other functions carried out by the Agency, towards the cost of monitoring the activity as the Agency considers necessary for the

performance of its functions under the Waste Management Acts 1996 to 2005. The first payment shall be a pro-rata amount for the period from the date of this licence to the 31st day of December, and shall be paid to the Agency within one month from the date of the licence. In subsequent years the licensee shall pay to the Agency such revised annual contribution as the Agency shall from time to time consider necessary to enable performance by the Agency of its relevant functions under the Waste Management Acts 1996 to 2005, and all such payments shall be made within one month of the date upon which demanded by the Agency.

12.1.2 In the event that the frequency or extent of monitoring or other functions carried out by the Agency needs to be increased the licensee shall contribute such sums as determined by the Agency to defraying its costs in regard to items not covered by the said annual contribution.

#### 12.2 Environmental Liabilities

12.2.1 The licensee shall as part of the AER provide an annual statement as to the measures taken or adopted at the site in relation to the prevention of environmental damage, and the financial provisions in place in relation to the underwriting of costs for remedial actions following anticipated events (including closure) or accidents/incidents, as may be associated with the carrying on of the activity.

*Reason:* To provide for adequate financing for monitoring and financial provisions for measures to protect the environment.

### **SCHEDULE A:** Limitations

The following waste related processes are authorised:

- Sorting, shredding, crushing, baling, repackaging processes
- Non-hazardous C & D waste recovery (incl. crushing, screening, sorting, blending)
- Storage of waste
- Receipt and transfer of waste
- Recovery of Dry Recyclables

No addition to these processes are permitted unless agreed in advance by the Agency.

-----**:** 

#### A.1 Waste Acceptance

Table A.1 We	aste Categories	and Quantities
--------------	-----------------	----------------

WASTE TYPE Note 1	MAXIMUM (TONNES PER ANNUM) Note 2
Household waste	18,000
<b>Non-hazardous</b> Commercial, Industrial and C&D waste	12,000
TOTAL	30,000

**Note 1:** Any proposals to accept other compatible waste streams must be agreed in advance by the Agency and the total amount of waste must be within that specified.

**Note 2:** The individual limitation on waste streams may be varied with the agreement of the Agency subject to the overall total limit staying the same.



### **SCHEDULE B:** Emission Limits

#### **B.1** Emissions to Air

There are no Emissions to Air of environmental significance.

\_\_\_\_\_**%**\_\_\_\_\_

#### **B.2** Emissions to Water

There are no Emissions to Water of environmental significance.

-----**>**------

#### **B.3** Emission to Sewer

There are no Process Effluent Emissions to Sewer.



#### **B.4.** Noise Emissions

Daytime dB(A) L <sub>Aeq</sub> (30 minutes)	Night-time dB(A) L <sub>Aeq</sub> (30 minutes)
55 <sup>Note 1</sup>	45 <sup>Note 1</sup>

Note 1: There shall be no clearly audible tonal component or impulsive component in the noise emission from the activity at any noise sensitive location.

\*\*

### SCHEDULE C: Control & Monitoring

C.1.1 Control of Emissions to Air

There are no Emissions to Air of environmental significance.

-----**&**-----

C.1.2 Monitoring of Emissions to Air

There are no Emissions to Air of environmental significance.

\_\_\_\_\_**%**\_\_\_\_\_

#### C.2.1 Control of Emissions to Ground

**Emission Reference No.:** 

Description of Treatment:

Discharge holding tank Yard 3-chamber interceptors

<b>Control Parameter</b>	Monitoring	Key Equipment <sup>Note 1</sup>
Desludging	Visual - weekly	Sludge transfer pumps
<b>Note 1:</b> The licensee shall maintain appropriate access to standby and/or spares to ensure the operation of the abatement system.		



### C.2.2 Monitoring of Emissions to Ground

**Emission Point Reference No.:** 

Discharge holding tank to Percolation Note 1

Parameter	Monitoring Frequency	Analysis Method/Technique
рН	Daily	pH electrode/meter and recorder
Chemical Oxygen Demand	Monthly	Standard Method
Sulphate (SO <sub>4</sub> )	Monthly	Standard Method
Chloride	Daily	Standard Method
Ammonia (as N)	Monthly	Ion selective electrode
Total Phosphorus (as P)	Quarterly	Standard Method
Metals (specify)	Quarterly	Atomic Absorption/ICP
Organic Solvents Note 2	Quarterly	Gas Chromatography
Oils, fats & greases	Quarterly	Standard Method

**Note 1:** This monitoring may cease following the covering of the yard area and cessation of discharge of run-off to percolation area.

**Note 2:** Screening for priority pollutant list substances. (such as US EPA volatile and/or semi-volatile compounds). This analysis shall include those organic solvents in use in the process, which are likely through normal process operations to be diverted to the waste water streams.

#### C.2.3 Monitoring of Storm Water Emission

Emission Point Reference No.: Following reconfiguration of building and roof drainage, location of storm water emission point to be agreed.

Visual Inspection Weekly Sample and examine for colour and odour	Parameter	Monitoring Frequency	Analysis Method/Technique
	Visual Inspection	Weekly	



#### C.3.1 Control of Sanitary Waste Water Emissions

Emission Point Reference No.:	Waste Water Treatment Plant to Percolation
<b>Description of Treatment:</b>	Packaged Waste Water Treatment

#### **Equipment:**

Control Parameter	Monitoring	Key Equipment <sup>Note 1</sup>
Aeration	Visual (Weekly)	Fans
Sludge levels	Visual (Weekly)	Sludge pumps
Note 1: The licensee shall maintain appropriate access to standby and/or spares to ensure the operation of the abatement		

**Note 1:** The licensee shall maintain appropriate access to standby and/or spares to ensure the operation of the aba system.



#### C.3.2 Monitoring of Emissions to Sewer

#### There are no Process Effluent Emissions to Sewer.



Waste Class	Frequency	Parameter	Method
Trade effluent from holding	Per consignment	Chloride	Standard method
tank pending off site	Per consignment	Ammonia	Standard method
disposal	Per consignment	COD	Standard method
	Biannually	Metals	Standard method
	Biannually	Organohalogens Note 1	
Sludge	Annually	Oils	Standard method
	Biannually	Metals	Standard method
	Biannually	Organohalogens Note 1	GC-MS
Other Note 2			
Note 1: Screening for priority pollutant list substances (such as US EPA volatile and/or semi-volatile compounds).			
Note 2: Analytical requirements t	o be determined on a case by cas	e basis.	

#### C.4 Waste Monitoring

C.5 Noise Monitoring

There is no additional noise monitoring required in this schedule other than as required by Condition 6.17.

•:•



C.6 Ambient Monitoring

There is no ambient monitoring required in this licence.

### C.7 Groundwater Monitoring

#### Site Well in Recycling Building

Parameter	Monitoring Frequency	Analysis Method/Technique	
рН	Annually	pH electrode/meter	
Conductivity	Annually	Standard Method	
Dissolved Oxygen	Annually	Standard Method	
Ammoniacal Nitrogen	Annually	Standard Method	
Total Cyanide	Annually	Standard Method	
Patassium	Annually	Standard Method	
Sodium	Annually	Standard Method	
Sulphate	Annually	Standard Method	
Nitrite as NO <sub>2</sub>	Annually	Standard Method	
Nitrate as NO <sub>3</sub>	Annually	Standard Method	
Chloride	Annually	Standard Method	
Fluoride	Annually	Standard Method	
Total Oxidised Nitrogen	Annually	Standard Method	
Total Alkalinity as CaCO <sub>3</sub>	Annually	Standard Method	
Total Organic Carbon	Annually	Standard Method	
Total Solids	Annually	Standard Method	
Total Phenols	Annually	Standard Method	
Ortho Phosphate as PO <sub>4</sub>	Annually	Standard Method	
Metals	Annually	Standard Method	
Organohalogens Note 1	Annually	GC-MS	
Total Coliforms	Annually	Standard Method	
Faecal Coliforms	Annually	Standard Method	

Note 1:

Screening for priority pollutant list substances (such as US EPA volatile and/or semi-volatile compounds).

Page 30 of 32

•:•

### SCHEDULE D: Specified Engineering Works

#### **Specified Engineering Works**

Development of the facility including installation of waste handling processing recycling/recovery infrastructure and installation of increased waste processing capacity as well as any abatement system(s).

Installation of drainage network including silt traps and oil interceptors.

Installation of dust/odour system.

Installation and maintenance of Sanitary Wastewater Treatment System and associated percolation area. Installation/Upgrade of an impermeable hardstanding surface within the area of the facility shown and perimeter wall of the facility shown in Drawing No 1.1.2.

Any other works notified in writing by the Agency.

### SCHEDULE E: Reporting

Reports are required to be forwarded as required in the licence and as may be set out below:

Report	Reporting Frequency <sup>Note 1</sup>	Report Submission Date
Environmental Management Systems Update	Annually	As part of AER.
Annual Environment Report (AER)	Annually	By 31 <sup>st</sup> March of each year.
Record of incidents	As they occur	Within five days of the incident.
Specified Engineering Works reports	As they arise	In advance, of the works commencing.
Bund, tank and container integrity assessment	Every three years	Six months from the date of grant of licence thereafter as part of the AER.
Specified Engineering Works reports	As they arise	Prior to the work commencing.
Monitoring of Trade Effluent	Quarterly	Ten days after end of the quarter being reported on.
Monitoring of Surface Water Quality	Quarterly	Ten days after end of the quarter being reported on.
Monitoring of Groundwater Quality	Annually	As part of AER.
Drawing with Monitoring locations	-	Within three months of date of grant of licence.
Any other monitoring	As they occur	Within ten days of obtaining results.

**Note 1:** Unless altered at the request of the Agency.

### **SCHEDULE F:** Annual Environmental Report

Annual Environmental Report Content <sup>Note 1</sup>
Emissions from the facility.
Waste management record.
Resource consumption summary.
Complaints summary.
Schedule of Environmental Objectives and Targets.
Environmental management programme – report for previous year.
Environmental management programme - proposal for current year.
Pollution emission register – report for previous year.
Pollution emission register – proposal for current year.
Noise monitoring report summary.
Ambient monitoring summary.
Tank and pipeline testing and inspection report.
Reported incidents summary.
Energy efficiency audit report summary.
Report on the assessment of the efficiency of use of raw materials in processes and the reduction in waste generated.
Report on progress made and proposals being developed to minimise water demand and the volume of trade effluent discharge.
Development / Infrastructural works summary (completed in previous year or prepared for current year).
Reports on management and staffing structure of the facility, and a programme for public information.
Statement of measures in relation to prevention of environmental damage and remedial actions (Environmental Liabilities).
Any other items specified by the Agency.
<b>Note 1:</b> Content may be revised subject to the agreement of the Agency.

may be revised subject to the agreement of the Agency.

### Signed on behalf of the said Agency

on the 11th day of May, 2006

Dr. Tom McLoughlin, Authorised Person