

## AMENDMENTS UNDER S42B(1) OF THE WASTE MANAGEMENT ACTS 1996 TO 2005

This licence was amended on 9 August 2005 under Section 42B(1) of the Waste Management Acts, 1996 to 2003. The details of the amendment must be read in conjunction with this licence. The amendment document is entitled 191-1S42B(1)AmendmentA.

This licence was amended on 4<sup>th</sup> January 2006 under Section 42B(1) of the Waste Management Acts, 1996 to 2005. The details of the amendment must be read in conjunction with this licence. The amendment document is entitled 191-1S42B(1)AmendmentB.

**LICENCE REG. NO. W0191-01 HAS BEEN REVISED.**  
Please note that licence Reg. No. W0191-01 was reviewed and replaced by the revised licence Reg. No. W0191-02



Headquarters  
P.O. Box 3000  
Johnstown Castle Estate  
County Wexford  
Ireland

## WASTE LICENCE LANDFILL FOR NON-HAZARDOUS WASTE

<b>Waste Licence</b>	191-1
<b>Register Number:</b>	
<b>Licensee:</b>	Wexford County Council
<b>Location of Facility:</b>	Within the townlands of Holmestown Great, Glenduff, Bolgerstown, Muchwood, Ballyeaton, County Wexford.

# INTRODUCTION

This introduction is not part of the licence and does not purport to be a legal interpretation of the licence.

“The proposed facility is an integrated waste management facility comprising the following: recycling infrastructure including a Civic Waste Facility for use by member of the public for the recycling of household waste; a Materials Recovery Facility or MRF, a composting facility and a landfill for the disposal of non-hazardous household and commercial waste up to a maximum quantity of 55,000 tonnes per annum”.

The licence sets out in detail the conditions under which Wexford County Council will operate and manage this facility.

# *Table of Contents*

	Page No.
<b>DECISION &amp; REASONS FOR THE DECISION</b>	<b>1</b>
<b>INTERPRETATION</b>	<b>1</b>
<b>PART I: SCHEDULE OF ACTIVITIES LICENSED</b>	<b>5</b>
<b>PART II: SCHEDULE OF ACTIVITIES REFUSED</b>	<b>7</b>
<b>PART III CONDITIONS</b>	<b>8</b>
<b>CONDITION 2 SCOPE OF THE LICENCE</b>	<b>8</b>
<b>CONDITION 3 MANAGEMENT OF THE FACILITY</b>	<b>9</b>
<b>CONDITION 4 FACILITY INFRASTRUCTURE</b>	<b>10</b>
<b>CONDITION 5 RESTORATION AND AFTERCARE</b>	<b>16</b>
<b>CONDITION 6 FACILITY OPERATION AND WASTE MANAGEMENT</b>	<b>17</b>
<b>CONDITION 7 EMISSIONS</b>	<b>22</b>
<b>CONDITION 8 NUISANCE CONTROL</b>	<b>24</b>
<b>CONDITION 9 MONITORING</b>	<b>25</b>
<b>CONDITION 10 CONTINGENCY ARRANGEMENTS</b>	<b>27</b>
<b>CONDITION 11 RECORDS</b>	<b>28</b>
<b>CONDITION 12 REPORTS AND NOTIFICATIONS</b>	<b>30</b>
<b>CONDITION 13 CHARGES AND FINANCIAL PROVISIONS</b>	<b>32</b>
<b>SCHEDULE A : WASTE ACCEPTANCE</b>	<b>34</b>
<b>SCHEDULE B : SPECIFIED ENGINEERING WORKS</b>	<b>34</b>
<b>SCHEDULE C : EMISSION LIMITS</b>	<b>35</b>
<b>SCHEDULE D : MONITORING</b>	<b>37</b>
<b>SCHEDULE E : COMPOST PROCESS MANAGEMENT</b>	<b>42</b>
<b>SCHEDULE F : RECORDING AND REPORTING TO THE AGENCY</b>	<b>43</b>
<b>SCHEDULE G : COMPOST QUALITY</b>	<b>44</b>
<b>SCHEDULE H : CONTENT OF THE ANNUAL ENVIRONMENTAL REPORT</b>	<b>46</b>

# DECISION & REASONS FOR THE DECISION

## *Reasons for the Decision*

On the basis of the information before it, the Environmental Protection Agency (the Agency) is satisfied, for the reasons set out in the following Schedule of Activities Licensed, that the requirements of Section 40(4) of the Waste Management Act, 1996 have been complied with in respect of the application for a waste licence for the activities listed hereunder in Part I.

In reaching this decision the Agency has considered the application and supporting documentation received from the applicant, all submissions and objections received from other parties and the reports of its inspectors.

## INTERPRETATION

All terms in this licence should be interpreted in accordance with the definitions in the Waste Management Act, 1996, (the Act), unless otherwise defined in this section.

<b>Aerosol</b>	A suspension of solid or liquid particles in a gaseous medium.
<b>Adequate lighting</b>	20 lux measured at ground level.
<b>Agreement</b>	Agreement in writing.
<b>Annually</b>	At approximately twelve monthly intervals.
<b>Attachment</b>	Any reference to Attachments in this licence refers to attachments submitted as part of the waste licence application.
<b>Application</b>	The application by the licensee for this waste licence.
<b>Appropriate facility</b>	A waste management facility, duly authorised under relevant law and technically suitable.
<b>BAT</b>	Best Available Techniques as defined in Article 2(11) of Council Directive 96/61/EC concerning integrated pollution prevention and control.
<b>Biodegradable waste</b>	Any waste that is capable of undergoing anaerobic or aerobic decomposition, such as food, garden waste, sewage sludge, paper and paperboard.
<b>CEN</b>	Comité Européen De Normalisation – European Committee for Standardisation
<b>Condition</b>	A condition of this licence.
<b>Construction and Demolition Waste</b>	All wastes which arise from construction, renovation and demolition activities.
<b>Containment boom</b>	A boom which can contain spillages and prevent them from entering drains or watercourses.
<b>Cover material</b>	Bricks, crushed concrete, tarmac, earth, soil, sub-soil, stone, rock or other similar natural materials; or

other cover material the use of which has been agreed by the Agency.

<b>Daily Cover</b>	Is the term used to describe material spread (about 150mm if soil cover is used) over deposited waste at the end of each day. Synthetic materials may also be used. Its objective is to minimise odour, the amount of litter generated and to control flies and access to the waste by birds and vermin. Where soils are used for daily cover, it is recommended that they be removed at the start of the day and subsequently reused as much as possible.
<b>Daytime</b>	0800 hrs to 2200 hrs.
<b>Documentation</b>	Any report, record, result, data, drawing, proposal, interpretation or other document in written or electronic form which is required by this licence.
<b>Drawing</b>	Any reference to a drawing or drawing number means a drawing or drawing number contained in the application, unless otherwise specified in this licence.
<b>Emergency</b>	Those occurrences defined in Condition 9.4.
<b>Emission Limits</b>	Those limits, including concentration limits and deposition levels established in <i>Schedule C: Emission Limits</i> , of this licence.
<b>European Waste Catalogue (EWC)</b>	A harmonised, non-exhaustive list of wastes drawn up by the European Commission and published as Commission Decision 94/3/EC and any subsequent amendment published in the Official Journal of the European Community.
<b>Green waste</b>	Waste wood (excluding timber), plant matter such as grass cuttings, and other vegetation.
<b>Hours of Operation</b>	The hours during which the facility is authorised to be operational. The hours of operation of a facility are usually longer than the hours of waste acceptance to facilitate preparatory and completion works, such as the removal and laying of daily cover. Different activities within the facility, such as the landfill and the civic waste facility, may have different hours of waste acceptance.
<b>Hours of Waste Acceptance</b>	The hours during which the facility is authorised to accept waste. Different activities within the facility, such as the landfill and the civic waste facility, may have different hours of waste acceptance.
<b>Incident</b>	The following shall constitute an incident for the purposes of this licence: <ul style="list-style-type: none"><li>a) an emergency;</li><li>b) any emission which does not comply with the requirements of this licence;</li><li>c) any exceedance of the daily duty capacity of the waste handling equipment;</li><li>d) any trigger level specified in this licence which is attained or exceeded; and,</li><li>e) any indication that environmental pollution has, or may have, taken place.</li></ul>
<b>Inert waste</b>	Waste that does not undergo any significant physical, chemical or biological transformations. Inert waste will not dissolve, burn or otherwise physically or chemically react, biodegrade or adversely affect other matter with which it comes into contact in a way likely to give rise to environmental pollution or harm human health. The total leachability and pollutant content of the waste and the ecotoxicity of the leachate must be insignificant, and in particular not endanger the quality of surface water and/or groundwater.

<b>Intermediate Cover</b>	Refers to placement of material (minimum 300mm if soil is used) for a period of time prior to restoration or prior to further disposal of waste.
<b>Landfill</b>	Refers to the area of the facility where the waste is disposed of by placement on the ground or on other waste.
<b>Landfill Gas</b>	Gases generated from the landfilled waste.
<b>LEL (Lower Explosive Limit)</b>	The lowest percentage concentration by volume of a mixture of flammable gas with air which will propagate a flame at 25°C and atmospheric pressure.
<b>Licence</b>	A waste licence issued in accordance with the Act.
<b>Licensee</b>	Wexford County Council.
<b>List I/II Organics</b>	Substances classified pursuant to EC Directives 76/464/EEC and 80/68/EEC.
<b>Liquid Waste</b>	Any waste in liquid form and containing less than 2% dry matter. Any waste tankered to the facility.
<b>Maintain</b>	Keep in a fit state, including such regular inspection, servicing and repair as may be necessary to adequately perform its function.
<b>Mobile Plant</b>	Self-propelled machinery used for the emplacement of wastes or for the construction of specified engineering works.
<b>Monthly</b>	A minimum of 12 times per year, at approximately monthly intervals.
<b>Night-time</b>	2200 hrs to 0800 hrs.
<b>Noise Sensitive Location</b>	Any dwelling house, hotel or hostel, health building, educational establishment, place of worship or entertainment, or any other facility or area of high amenity which for its proper enjoyment requires the absence of noise at nuisance levels.
<b>Non-hazardous Asbestos Waste</b>	Includes bonded asbestos, such as tiles, which are not classified as hazardous waste and which are authorised for disposal at the facility.
<b>Recyclable Materials</b>	Those waste types, such as cardboard, batteries, gas cylinders, etc which may be recycled.
<b>Quarterly</b>	At approximately three monthly intervals.
<b>Sample(s)</b>	Unless the context of this licence indicates to the contrary, samples shall include measurements by electronic instruments.
<b>SCADA system</b>	Supervisory Control and Data Acquisition system.
<b>Sludge</b>	The accumulation of solids resulting from chemical coagulation, flocculation and/or sedimentation after water or wastewater treatment with > 2% dry matter.
<b>SOP</b>	Standard Operating Procedure.
<b>Specified Emissions</b>	Those emissions listed in <i>Schedule C: Emission Limits</i> , of this licence.
<b>Specified Engineering Works</b>	Those engineering works listed in <i>Schedule B: Specified Engineering Works</i> , of this licence.
<b>TOC</b>	Total Organic Carbon.

<b>Treated Sludge</b>	Sludge which has undergone biological, chemical or heat treatment, long-term storage or any other appropriate process so as significantly to reduce its fermentability and the health hazards resulting from its use.
<b>Treatment</b>	Treatment means the physical, thermal, chemical or biological processes, including sorting, that change the characteristics of the waste in order to reduce its volume or hazardous nature, facilitate its handling or enhance recovery.
<b>Trigger Level</b>	A parameter value specified in the licence, the achievement or exceedance of which requires certain actions to be taken by the licensee.
<b>Wastewater</b>	Contaminated water including water that has been used for washing and/or flushing (including sanitary effluent).
<b>White Goods</b>	Refrigerators, cookers, ovens and other similar appliances.
<b>EPA Working Day</b>	Refers to the following hours: 0900 hrs to 1730 hrs Monday to Friday inclusive.
<b>Working Face</b>	The area of the site in which waste other than cover material or material for the purposes of the construction of specified engineering works is being deposited.

## ***Part I: Schedule of Activities Licensed***

On the basis of the information before it, the Agency, pursuant to its powers under Section 40(1) of the Waste Management Act, 1996, hereby grants this Waste Licence to Wexford County Council to carry on the waste activities, that are the subject of Waste Licence Register Number 191-1, listed below at Holmestown Wood, within the townlands of Holmestown Great, Glenduff, Bolgerstown, Muchwood, Ballyeaton, County Wexford subject to conditions, with the reasons therefor and the associated schedules attached thereto set out in the licence.

### *Licensed Waste Disposal Activities, in accordance with the Third Schedule of the Waste Management Act, 1996*

<b>Class 1</b>	<b>Deposit on, in or under land (including landfill):</b>  This activity is limited to the landfilling of non-hazardous household and commercial wastes.
<b>Class 4</b>	<b>Surface impoundment, including placement of liquid or sludge discards into pits, ponds or lagoons:</b>  This activity is limited to the temporary storage of leachate in a lagoon, prior to its removal offsite for treatment.
<b>Class 5</b>	<b>Specially engineered landfill, including placement into lined discrete cells which are capped and isolated from one another and the environment:</b>  This activity is limited to the landfilling of non-hazardous household and commercial wastes.
<b>Class 6</b>	<b>Biological treatment not referred to elsewhere in this Schedule which results in final compounds or mixtures which are disposed of by means of any activity referred to in paragraphs 1 to 10 of this Schedule:</b>  This activity is limited to the disposal of material which is composted on-site, which fails to comply with the standards set out in <i>Schedule G: Compost Quality</i> of this licence.
<b>Class 7</b>	<b>Physico-chemical treatment not referred to elsewhere in this Schedule (including evaporation, drying and calcination) which results in final compounds or mixtures which are disposed of by means of any activity referred to in paragraphs 1 to 10 of this Schedule:</b>  This activity is limited to the pre-treatment of leachate on-site prior to its removal offsite for treatment and disposal.
<b>Class 11</b>	<b>Blending or mixture prior to submission to any activity referred to in a preceding paragraph of this Schedule:</b>  This activity is limited to the mixing of non-hazardous waste at the Civic Waste Facility, Materials Recovery Facility and composting facility prior to disposal at the landfill.
<b>Class 12</b>	<b>Repackaging prior to submission to any activity referred to in a preceding paragraph of this Schedule:</b>  This activity is limited to the mixing or compaction of waste and the reloading of waste tipped for inspection into a container prior to landfilling or disposal offsite.
<b>Class 13</b>	<b>Storage prior to submission to any activity referred to in a preceding paragraph of this Schedule, other than temporary storage, pending collection, on the premises where the waste concerned is produced:</b>  This activity is limited to the temporary storage of waste in the Civic Waste facility prior to disposal at the landfill.



*Licensed Waste Recovery Activities, in accordance with the  
Fourth Schedule of the Waste Management Act, 1996*

<b>Class 2</b>	<b>Recycling or reclamation of organic substances which are not used as solvents (including composting and other biological transformation processes):</b>  This activity is limited to the collection of organic wastes at the Civic Waste Facility and the composting or recovery of organic waste.
<b>Class 3</b>	<b>Recycling or reclamation of metals and metal compounds:</b>  This activity is limited to the collection of metal at the Civic Waste Facility e.g. scrap metal, white goods, cans, batteries and the removal of metals from other waste in the Civic Waste Facility and Materials Recovery Facility.
<b>Class 4</b>	<b>Recycling or reclamation of other inorganic materials:</b>  This activity is limited to the collection inorganic recyclables such as glass, textiles and clothing, batteries, fluorescent tubes and construction and demolition wastes in the Civic Waste Facility. It also refers to the use of construction and demolition wastes in restoration and engineering projects.
<b>Class 10</b>	<b>The treatment of any waste on land with a consequential benefit for an agricultural activity or ecological system:</b>  This activity is limited to the possible future spreading of composts or treated sludges on the landfill as part of its restoration.
<b>Class 11</b>	<b>Use of waste obtained from any activity referred to in a preceding paragraph of this Schedule:</b>  This activity is limited to the use of composted waste and construction and demolition waste in recovery or restoration projects at the landfill.
<b>Class 12</b>	<b>Exchange of waste for submission to any activity referred to in a preceding paragraph of this Schedule:</b>  This activity is limited to the exchange of waste at the Civic Waste Facility.
<b>Class 13</b>	<b>Storage of waste intended for submission to any activity referred to in a preceding paragraph of this Schedule, other than temporary storage, pending collection, on the premises where such waste is produced:</b>  This activity is limited to the storage of waste on-site prior to recycling or reclamation activities.

## ***Part II: Schedule of Activities Refused***

On the basis of the information before it, the Agency, pursuant to its powers under Section 40(1) of the Waste Management Act, 1996, hereby refuses the following classes of activity that are the subject of Waste Licence Register No. 191-1.

*Refused waste disposal activities, in accordance with the  
Third Schedule of the Waste Management Act, 1996*

<b>Class 2</b>	<b>Land treatment, including biodegradation of liquid or sludge discards in soils:</b>  Reason: The applicant proposes that the disposal of sludges at the landfill will fall under this class of activity. The Agency however deems that the disposal of sludge to landfill is governed by Classes 1 and 4.
----------------	--

*Refused waste disposal activities, in accordance with the  
Fourth Schedule of the Waste Management Act, 1996*

<b>Class 9</b>	<b>Use of any waste principally as a fuel or other means to generate energy:</b>  Reason: This is not an appropriate Class for the activity. The burning of landfill gas is not covered by the fourth schedule of the Waste Management Act, 1996.
----------------	---

## ***PART III CONDITIONS***

### **CONDITION 1 SCOPE OF THE LICENCE**

- 1.1. Waste activities at the facility shall be restricted to those listed and described in Part I: Activities Licensed and authorised by this licence.
- 1.2. For the purposes of this licence, the facility is the area of land outlined in red on Figure B.2.2 of the application. Any reference in this licence to “facility” shall mean the area thus outlined in red.
- 1.3. This licence is for the purposes of waste licensing under the Waste Management Act, 1996 only and nothing in this licence shall be construed as negating the licensee’s statutory obligations or requirements under any other enactments or regulations.
- 1.4. Municipal Waste, Commercial Waste and Industrial Waste may be recovered and disposed of at the facility subject to the maximum quantities and other constraints listed in *Schedule A: Waste Acceptance*, of this licence. In relation to composting, only the wastes as outlined in *Schedule A: Waste Acceptance* of this licence and as listed under Annex 1 of the EC Working Document ‘Biological Treatment of Biowaste’ (2<sup>nd</sup> draft) or subsequent amendments shall be accepted at the facility for the production of compost. Waste types outlined in *Schedule A: Waste Acceptance* of this licence and not listed under Annex 1 of the EC Working Document ‘Biological Treatment of Biowaste’ (2<sup>nd</sup> draft) shall be disposed of unless otherwise agreed by the Agency. Hazardous wastes shall not be accepted for composting at the facility.
- 1.5. Waste Acceptance Hours and Hours of Operation
  - 1.5.1. Landfill
    - 1.5.1.1. Waste may be accepted at the facility for disposal or recovery at the landfill only between the hours of 08.30 and 16.30 Monday to Saturday.
    - 1.5.1.2. The facility may be operated only during the hours of 08.00 and 17.00.
    - 1.5.1.3. Waste shall not be accepted at the landfill on Bank Holidays.
  - 1.5.2. Civic Waste Facility and Materials Recovery Facility
    - 1.5.2.1. Waste shall be accepted at the Civic Waste Facility and Materials Recovery Facility only between the hours of 08.30 and 16.30 Monday to Saturday.
- 1.6. Every plan, programme or proposal submitted to the Agency for its agreement pursuant to any condition of this licence shall include a proposed timescale for its implementation. The Agency may modify or alter any such plan, programme or proposal in so far as it considers such modification or alteration to be necessary and shall notify the licensee in writing of any such modification or alteration. Every such plan, programme or proposal shall be carried out within the timescale fixed by the Agency but shall not be undertaken without the agreement of the Agency. Every such plan, programme or proposal agreed by the Agency shall be covered by the conditions of this licence.

*REASON: To clarify the scope of this licence.*

## **CONDITION 2 MANAGEMENT OF THE FACILITY**

### **2.1 Facility Management**

- 2.1.1 The licensee shall employ a suitably qualified and experienced facility manager who shall be designated as the person in charge. The facility manager or a nominated, suitably qualified and experienced, deputy shall be present on the facility at all times during its operation.
- 2.1.2 The Civic Waste Facility shall be supervised by an appropriately qualified and competent person at all times while waste may be accepted.
- 2.1.3 Both the facility manager and deputy, and any replacement manager or deputy, shall successfully complete both the FAS Waste Management Training Programme (or equivalent agreed by the Agency) and associated on site assessment appraisal within twelve months of appointment.
- 2.1.4 The licensee shall ensure that personnel performing specifically assigned tasks shall be qualified on the basis of appropriate education, training and experience, as required and shall be aware of the requirements of this licence.

### **2.2 Management Structure**

- 2.2.1 Prior to the commencement of waste activities, the licensee shall submit written details of the management structure of the facility to the Agency. Any proposed replacement in the management structure shall be notified in advance in writing to the Agency. Written details of the management structure shall include the following information:-
  - a) The names of all persons who are to provide the management and supervision of the waste activities authorised by the licence, in particular the name of the facility manager and any nominated deputies;
  - b) Details of the responsibilities for each individual named under a) above; and
  - c) Details of the relevant education, training and experience held by each of the persons nominated under a) above.

### **2.3 Environmental Management System (EMS)**

- 2.3.1 The licensee shall establish and maintain an EMS. Within six months from the date of commencement of waste activities, the licensee shall submit to the Agency for its agreement a proposal for a documented Environmental Management System (EMS) for the facility. Following the agreement of the Agency, the licensee shall establish and maintain such a system. The EMS shall be updated on an annual basis with amendments being submitted to the Agency for its agreement.

- 2.3.2 The EMS shall include as a minimum the following elements.

#### **2.3.2.1 Schedule of Environmental Objectives and Targets**

The objectives should be specific and the targets measurable. The schedule shall address a five-year period as a minimum. The schedule shall include a time-scale for achieving the objectives and targets and shall comply with any other written guidance issued by the Agency.

#### **2.3.2.2 Environmental Management Plan (EMP)**

The EMP shall include, as a minimum, the following: -

- a) The items specified to be contained in an Environmental Management Plan in the Landfill Operational Practices Manual published by the Agency;
- b) Methods by which the objectives and targets will be achieved and the identification of those responsible for achieving those objectives and targets; and
- c) Any other items required by written guidance issued by the Agency.

#### 2.3.2.3 Corrective Action Procedures

The Corrective Action Procedures shall detail the corrective actions to be taken should any of the procedures detailed in the EMS not be followed.

#### 2.3.2.4 Awareness and Training Programme

The Awareness and Training Programme shall identify training needs, for personnel who work in or have responsibility for the licensed facility.

### 2.4 Communications Programme

- 2.4.1 The licensee shall establish and maintain a Communications Programme to ensure that members of the public can obtain information at the facility, at all reasonable times, concerning the environmental performance of the facility. This shall be established within six months of the date of grant of the licence.

*REASON: To make provision for the proper management of the activity on a planned basis having regard to the desirability of ongoing assessment, recording and reporting of matters affecting the environment.*

## CONDITION 3 FACILITY INFRASTRUCTURE

- 3.1 The licensee shall establish all infrastructure referred to in this licence prior to the commencement of the licensed activities or as required by the conditions of this licence.

### 3.2 Specified Engineering Works

- 3.2.1 The licensee shall submit proposals for all Specified Engineering Works, as defined in *Schedule B: Specified Engineering Works*, of this licence, to the Agency for its agreement at least two months prior to the intended date of commencement of any such works. No such works shall be carried out without the prior agreement of the Agency.
- 3.2.2 All specified engineering works shall be supervised by a competent person(s) and that person, or persons, shall be present at all times during which relevant works are being undertaken.
- 3.2.3 Following the completion of all specified engineering works, the licensee shall complete a construction quality assurance validation. The validation report shall be made available to the Agency on request. The report shall include the following information:-
  - a) A description of the works;
  - b) As-built drawings of the works;
  - c) Records and results of all tests carried out (including failures);

- d) Drawings and sections showing the location of all samples and tests carried out;
- e) Daily record sheets/diary;
- f) Name(s) of contractor(s)/individual(s) responsible for undertaking the specified engineering works;
- g) Name(s) of individual(s) responsible for supervision of works and for quality assurance validation of works;
- h) Records of any problems and the remedial works carried out to resolve those problems; and
- i) Any other information requested in writing by the Agency.

### 3.3 Facility Notice Board

3.3.1 The licensee shall provide and maintain a Facility Notice Board on the facility so that it is legible to persons outside the main entrance to the facility. The minimum dimensions of the board shall be 1200 mm by 750 mm.

3.3.2 The board shall clearly show:-

- a) The name and telephone number of the facility;
- b) The normal hours of opening;
- c) The name of the licence holder;
- d) An emergency out of hours contact telephone number;
- e) The licence reference number; and
- f) Where environmental information relating to the facility can be obtained.

### 3.4 Facility Security

3.4.1 Security and stockproof fencing and gates shall be installed and maintained as described in Section 5.3 of the EIS Addendum. The base of the fencing shall be set in the ground. Subject to the implementation of the restoration and aftercare plan and to the agreement of the Agency, the requirement for such site security may be removed.

3.4.2 The licensee shall remedy any defect in the gates and/or fencing as follows:-

- a) A temporary repair shall be made by the end of the working day; and
- b) A repair to the standard of the original gates and/or fencing shall be undertaken within three working days.

### 3.5 Facility Roads and Hardstanding

3.5.1 Effective site roads shall be provided and maintained to ensure the safe movement of vehicles within the facility.

3.5.2 The facility entrance area, the access road to the Civic Waste Facility, the Civic Waste Facility itself and the Materials Recovery Facility Area shall be paved and maintained as described in Section 5.38 of the EIS Addendum.

### 3.6 Facility Office

3.6.1 The licensee shall provide and maintain an office at the facility. The office shall be constructed and maintained in a manner suitable for the processing and storing of documentation.

- 3.6.2 The licensee shall provide and maintain a working telephone and a method for electronic transfer of information at the facility.
- 3.7 Waste Inspection and Quarantine Areas
- 3.7.1 A Waste Inspection Area and a Waste Quarantine Area shall be provided and maintained at the facility.
- 3.7.2 These areas shall be constructed and maintained in a manner suitable, and be of a size appropriate, for the inspection of waste and subsequent quarantine if required. The waste inspection area and the waste quarantine area shall be clearly identified and segregated from each other.
- 3.7.3 Drainage from these areas shall be directed to the on-site leachate treatment plant.
- 3.8 Weighbridge and Wheel Cleaner
- 3.8.1 The licensee shall provide and maintain a weighbridge and a wheel cleaner at the facility.
- 3.8.2 The wheel cleaner shall be used by all vehicles leaving the facility as required to ensure that no process water or waste is carried off-site. All water from the wheel cleaning area shall be directed to the waste water interceptor.
- 3.9 Waste Water Treatment Plant
- 3.9.1 The licensee shall provide and maintain a Wastewater Treatment plant at the facility for the treatment of sanitary effluent arising on-site. Any percolation area shall satisfy the criteria set out in the *Wastewater Treatment Manual, Treatment Systems for Single Houses*, published by the Environmental Protection Agency.
- 3.10 Tank and Drum Storage Areas
- 3.10.1 All tank and drum storage areas shall be rendered impervious to the materials stored therein.
- 3.10.2 All tank and drum storage areas shall, as a minimum, be bunded, either locally or remotely, to a volume not less than the greater of the following:-
- (a) 110% of the capacity of the largest tank or drum within the bunded area; or
  - (b) 25% of the total volume of substance which could be stored within the bunded area.
- 3.10.3 All drainage from bunded areas shall be diverted for collection and safe disposal.
- 3.10.4 All inlets, outlets, vent pipes, valves and gauges must be within the bunded area.
- 3.10.5 The integrity and water tightness of all the bunds and their resistance to penetration by water or other materials stored therein shall be confirmed by the licensee and shall be reported to the Agency following their installation and prior to their use as storage areas. This confirmation shall be repeated at least once every three years thereafter and reported to the Agency on each occasion.
- 3.10.6 The licensee shall install and maintain silt traps and oil interceptors at the facility to ensure that all surface water discharges from the facility pass through a silt trap and oil interceptor prior to discharge. The interceptors shall be Class I full retention interceptors and the silt traps and interceptors shall be in accordance with European Standard prEN 858 (installations for the separation of light liquids).
- 3.10.7 All wastewater gullies, drainage grids and manhole covers shall be painted with red squares whilst all surface water discharge gullies, drainage grids and manhole covers

shall be painted with blue triangles. These colour codes shall be maintained so as to be visible at all times during facility operation, and any identification designated in this licence (e.g. SW1) shall be inscribed on these manholes.

- 3.10.8 The drainage system, bunds, silt traps and oil separators shall be inspected weekly, desludged as necessary and properly maintained at all times. All sludge and drainage from these operations shall be collected for safe disposal. A written record shall be kept of the inspections, desludging, cleaning, disposal of associated waste products, maintenance and performance of the interceptors, bunds and drains.

### 3.11 Landfill Lining

- 3.11.1 Unless otherwise agreed in writing the landfill liner shall comprise:-

- a) A composite liner consisting of a 1m layer of compacted soil with a hydraulic conductivity of less than or equal to  $1 \times 10^{-9}$  m/s, (or equivalent to be agreed by the Agency) overlain by a 2mm thick high density polyethylene (HDPE) layer;
- b) A geotextile protection layer placed over the HDPE layer;
- c) A 500mm thick drainage layer placed over the geotextile layer with a minimum hydraulic conductivity of  $1 \times 10^{-3}$  m/s, of pre-washed, uncrushed, granular, rounded stone (16 - 32mm grain size) incorporating leachate collection drains; and
- d) The side walls shall be designed and constructed to achieve an equivalent protection.

- 3.11.2 The liner detailed design and its construction shall be in accordance with the guidelines provided in the Agency's *Landfill Manual, Landfill Site Design*.

- 3.11.3 A screen of tree planting shall also be provided at either side of the site access road, outside the acoustic barriers within the facility boundary as shown on Figure B.2.2 of the application. The trees to be planted shall have a minimum age of three years.

### 3.12 Buffer Zone/Tree Planting

- 3.12.1 In so far as practically possible, forestry stands shall be provided and maintained within the facility boundary. Clear-felled areas shall be reinstated without delay to enhance screening of the facility.

- 3.12.2 A Buffer Zone, in which no waste shall be landfilled and which shall be used for the planting of forestry, shall be provided and maintained within the facility, with the exception of the site access road. The Buffer Zone shall have a minimum width of 50m.

- 3.12.3 A screen of tree planting shall also be provided at either side of the site access road, outside the acoustic barriers within the facility boundary as shown on Figure B.2.2 of the application. The trees to be planted shall be a minimum of 1.5m height.

### 3.13 Leachate Management Infrastructure

- 3.13.1 Leachate management infrastructure shall be provided and maintained at the facility as described in Sections 5.39 - 5.46 of the EIS Addendum.

- 3.13.2 All structures for the storage and/or treatment of leachate shall be fully enclosed except for inlet and outlet piping.

### 3.14 Landfill Gas Management



3.14.1 Landfill gas management infrastructure shall be provided and maintained at the facility as described in Sections 5.49 – 5.54 of the EIS. The flare shall be of an enclosed type design.

3.14.2 All buildings constructed on the facility shall have regard to the guidance given in the Department of Environment 1994 publication “Protection of New Buildings and Occupants from Landfill Gas” and any subsequent revisions.

3.14.3 Landfill Gas Combustion Plant

The licensee shall install continuous carbon monoxide monitors on the outlets of the gas engine(s).

### 3.15 Surface Water Management

3.15.1 Effective surface water management infrastructure shall be provided and maintained at the facility during construction, operation, restoration and aftercare of the facility. As a minimum, the infrastructure shall be capable of the following:-

- a) The prevention of contaminated water and leachate discharges into surface water drains and courses.
- b) The containment of surface water discharge during peak flows via a system of weirs, drains and retention ponds, as described in Section 9.62 of the EIS Addendum and Section C.3(b) of the Article 12 response received by the Agency on 06/05/04.
- c) The collection/diversion of run off arising from capped and restored areas.
- d) The diversion of runoff from the waste handling, inspection, quarantine and storage areas of the Civic Waste Facility, Materials Recovery Facility and Composting facility to the leachate treatment plant.
- e) The diversion of runoff other than runoff from the waste handling and storage areas of the Civic Waste Facility, Materials Recovery Facility and Composting facility to a soakaway via a grit trap and a Class 1 oil interceptor.

### 3.16 Groundwater Management

3.16.1 Effective groundwater management infrastructure shall be provided and maintained at the facility during construction, operation, restoration and aftercare of the facility. As a minimum, the infrastructure shall be capable of the following:-

- a) the protection of the groundwater resources from pollution by the waste activities; and
- b) The protection of other infrastructure, such as the liner, from any adverse effects caused by the groundwater.

### 3.17 Noise Abatement Infrastructure

3.17.1 Effective infrastructure shall be provided for the abatement of noise emissions from the facility. This infrastructure shall as a minimum include the following:

- a) permanent acoustic barriers to be erected along either side of the access road extending from the junction with the N25 to the entrance area.
- b) Temporary acoustic screens and/or bunds to be erected along the perimeter of phases 1, 2, 3, and 4 at the north and north-east of the site. They are to be constructed and maintained throughout the development, operation and restoration of these phases.

- c) Acoustic screens or bunds to provide noise attenuation along the southern and south-western perimeter of the proposed site.
- d) Any other noise abatement infrastructure deemed necessary.

### 3.18 Construction and Demolition Waste Recovery Area

3.18.1 Prior to commencement of recovery operations, the licensee shall provide and maintain a construction and demolition waste recovery area. This infrastructure shall at a minimum comprise the following:-

- a) An impermeable concrete slab; and
- b) Collection and disposal infrastructure for all run-off.

### 3.19 Civic Waste Facility

3.19.1 The licensee shall establish and maintain the Civic Waste Facility infrastructure referred to in Section 5.103 – 5.105 of the EIS Addendum.

3.19.2 The licensee shall provide and maintain the receptacles at the Civic Waste Facility as shown in Drawing No. 5.7a (Rev A) of the EIS Addendum unless otherwise agreed by the Agency.

### 3.20 Compost facility

3.20.1 Appropriate infrastructure for the composting of waste shall be established and maintained at the facility prior to any waste being composted. This infrastructure shall be as described in Section 5.107 – 5.117 of the EIS Addendum.

3.20.2 Biofilters shall be used to control odours from the air extracted from the in-vessel composting containers.

3.20.3 Provision of 100% duty capacity and 50% stand by capacity, back ups and spares shall be provided for the air handling, ventilation and abatement plant.

### 3.21 Materials Recovery Facility (MRF)

3.21.1 The licensee shall establish and maintain the Materials Recovery Facility infrastructure described to in Section 5.106 of the EIS Addendum and as shown in Drawing No. 5.7a (Rev A) of the EIS Addendum unless otherwise agreed by the Agency.

### 3.22 External Access Road

3.22.1 No waste activity shall be carried on at the facility until such time as one of the options for road improvements as described in Chapter 7 of the EIS, or equivalent works, are carried out.

### 3.23 Telemetry

3.23.1 A telemetry system shall be installed and maintained at the facility. This system shall include for:-

- a) Recording of leachate levels in the lined cells and lagoon;
- b) Recording of levels in the surface water retention ponds and flows to the perimeter streams;
- c) Quality of the surface water at the inlet to the surface water lagoons and being discharged to the perimeter streams; and

- d) Permanent gas monitoring system to be installed in the site office and any other enclosed structures at the facility.

### 3.24 Monitoring Infrastructure

#### 3.24.1 Landfill Gas

- a) The licensee shall install the monitoring points listed in Table D.1.1 *Schedule D: Monitoring*, of this licence ; and
- b) Upon construction of the structures, the licensee shall install an effective permanent gas monitoring system in the site office and any other enclosed structures at the facility.

#### 3.24.2 Groundwater

- a) Within six months from the date of grant of this licence, the licensee shall install the monitoring points listed in Table D.1.1 *Schedule D: Monitoring*, of this licence to allow for the sampling and analyses of groundwater.

#### 3.24.3 Leachate

- a) Prior to commencement of waste for disposal in each cell/area, the licensee shall install the monitoring points listed in Table D.1.1, *Schedule D: Monitoring*, of this licence to allow for the sampling and analyses of leachate.

#### 3.24.4 Replacement of Infrastructure

- a) Monitoring infrastructure which is damaged or proves to be unsuitable for its purpose shall be replaced within three months of it being damaged or recognised as being unsuitable.

### 3.25 Wildlife

3.25.1 The licensee shall ensure that the following works are carried out in consultation with the National Parks and Wildlife Service staff of the Department of the Environment, Heritage and Local Government:

- a) an artificial badger set shall be constructed within the site where trees are to be retained;
- b) 30 bat boxes are to be erected in trees to be retained around the site;
- c) 20 hole nesting and 20 open fronted bird boxes are to be erected within the site.

*REASON: To provide appropriate infrastructure for the protection of the environment.*

## CONDITION 4 RESTORATION AND AFTERCARE

4.1. The licensee shall restore the landfill facility on a phased basis. The clear-felling of any of phases 1-10 as shown on Figure 5.4 Rev A of the EIS Addendum shall not take place until such time as the previous phase is operational. The Restoration and Aftercare Plans for the facility shall be as shown in Figure 5.8 (Rev A) of the EIS Addendum and shall include the plan submitted in Sections 5.61 – 5.81 of the EIS.

4.2. The final (pre-settlement) contours of the facility shall be as shown in Drawing No. 2.8 Rev A of the EIS Addendum (mOD Malin).

#### 4.3. Final Capping

4.3.1. Unless otherwise agreed in writing the final capping shall consist of the following:-

- a) Top soil (150 -300mm);

- b) Subsoils, such that total thickness of top soil and subsoils is at least 1m;
  - c) Drainage layer of 0.5m thickness having a minimum hydraulic conductivity of  $1 \times 10^{-4}$  m/s;
  - d) Compacted mineral layer of a minimum 0.6m thickness with a permeability of less than  $1 \times 10^{-9}$  m/s or a geosynthetic material (e.g. GCL) or similar that provides equivalent protection; and
  - e) Gas collection layer of natural material (minimum 0.3m) or a geosynthetic layer.
- 4.4. No material or object that is incompatible with the proposed restoration of the facility shall be present within one metre of the final soil surface levels.
- 4.5. Where tree planting is to be carried out above waste-filled areas, a synthetic barrier shall be used to augment the clay cap. Combined topsoil and subsoil depths shall be a minimum of 1m.
- 4.6. Soil Storage
- 4.6.1. All soils shall be stored to preserve the soil structure for future use.

*REASON: To provide for the restoration of the facility.*

## **CONDITION 5 FACILITY OPERATION AND WASTE MANAGEMENT**

- 5.1 Wastes shall not be deposited in any cell or part of the landfill without the prior agreement of the Agency.
- 5.2 Waste Acceptance and Characterisation Procedures
- 5.2.1 Prior to commencement of waste acceptance at the facility, the licensee shall submit to the Agency for its agreement written procedures for the acceptance and handling of all wastes. These procedures shall include details of the pre-treatment of all waste to be carried out prior to acceptance at the facility and shall also include methods for the characterisation of waste in order to distinguish between inert, non-hazardous and hazardous wastes. The procedures shall have regard to the EU Decision (2003/22/EC) on establishing the criteria and procedures for the acceptance of waste at landfills pursuant to Article 16 and Annex II of Directive (1999/31/EC) on the landfill of waste.
- 5.2.2 Waste shall be accepted at the facility, only from customers who are holders of a waste permit, unless exempted, under the Waste Management (Collection Permit) Regulations 2001 or from other licensed/permitted facilities.
- 5.2.3 Whole used tyres (other than bicycle tyres and tyres with an outside diameter greater than 1400mm) shall not be disposed of at the facility. Shredded tyres shall not be disposed of at the facility from 16 July 2006.
- 5.2.4 No hazardous wastes or liquid wastes shall be disposed of at the facility.
- 5.2.5 The licensee shall ensure that inert waste accepted at the facility is subject to treatment where technically feasible.
- 5.3 All wastes shall be checked at the working face. Any wastes not suitable for acceptance shall be removed for recovery or disposal at an appropriate alternative facility. Such waste shall be stored in the Waste Quarantine Area only. No waste shall be stored in the Waste Quarantine Area for more than three months.
- 5.4 Working Face

- 5.4.1 Unless the prior agreement of the Agency is given, the following shall apply at the landfill:-
- a) Only one working face shall exist at the landfill at any one time for the deposit of waste other than cover or restoration materials; and
  - b) The working face of the landfill shall be no more than 2.5 metres in height after compaction, no more than 25 metres wide and have a slope no greater than 1 in 3.
- 5.4.2 All waste deposited at the working face shall be compacted, using a steel wheeled compactor, and covered as soon as is practicable and at any rate prior to the end of the working day.
- 5.4.3 The working face, or faces, shall each day at the end of the day, be covered with suitable material.
- 5.5 Daily and Intermediate Cover
- 5.5.1 Any cover material at any location within the facility which is eroded, washed off or otherwise removed shall be replaced by the end of the working day.
- 5.5.2 Within three months of the date of commencement of waste disposal activities, appropriate cover material shall be placed across the whole landfill so that no waste, other than the following is exposed:-
- a) Waste suitable for specified engineering works; and
  - b) Waste on the working face during the operational hours of the facility.
- 5.6 Landscaping
- 5.6.1 The existing hedgerow network within the facility shall, where possible be retained and reinforced if necessary by the licensee.
- 5.7 Operational Controls
- Landfill
- 5.7.1 The landfill shall be filled in accordance with the 10 phase sequence outlined in Figure 5.4 Rev A of the EIS Addendum.
- 5.7.2 All large hollow objects and other large articles deposited at the facility shall be crushed, broken up, flattened or otherwise treated.
- 5.7.3 Wastes once deposited and covered shall not be excavated, disturbed or otherwise picked over unless with the prior agreement from the Agency.
- 5.7.4 Completed areas of the landfill shall be profiled so that no depressions exist in which water may accumulate. Any depressions arising after profiling shall be rectified by the emplacement of suitable capping or restoration materials.
- 5.7.5 Filled cells shall be permanently capped within twenty four months of the cells having been filled to the required level.
- 5.7.6 Scavenging shall not be permitted at the facility.
- 5.7.7 Gates shall be locked shut when the facility is unsupervised.
- 5.7.8 The licensee shall provide and use adequate lighting during the operation of the facility in hours of darkness.
- 5.7.9 Fuels shall be stored only at appropriately bunded locations on the facility.
- 5.7.10 All tanks and drums shall be labelled to clearly indicate their contents.
- Composting

- 5.7.11 All waste accepted into the biowaste composting building (apart from bulking agents/green waste) shall be transferred to a composting vessel within 60 hours of receipt unless otherwise agreed in advance with the Agency.
- 5.7.12 All entry and exit doors to the biowaste and sludge reception buildings shall be on automatic open/close switches in order to minimise the time spent open.
- 5.7.13 The floor of the composting building shall be cleaned of waste on a daily basis.
- 5.7.14 No waste shall be stored overnight at the facility in other than designated storage areas in the biowaste reception buildings.
- 5.7.15 Apart from compost at the in-vessel stage of treatment, all waste processing and storage shall occur inside an appropriate building, unless otherwise agreed by the Agency.
- 5.7.16 Only source separated and separately collected commercial and municipal biowaste may be accepted at the facility.
- 5.7.17 Unless otherwise agreed by the Agency one in twenty loads shall be tipped into the waste inspection area and examined and recorded.

#### Materials Recovery Facility

- 5.7.18 Unless otherwise agreed by the Agency all waste processing and storage shall occur inside an appropriate building.

### 5.8 Waste Handling

#### 5.8.1 Sludges

- 5.8.1.1 Treated industrial and treated sewage sludges shall be accepted at the facility only between the hours of 0830 hrs and 14.00 hrs Monday to Friday inclusive. All sludges shall be covered immediately with other waste.
- 5.8.1.2 In addition to the characterisation required under the Waste Acceptance Procedures, the licensee shall carry out analyses on a minimum of two samples per annum for all industrial sludges being accepted at the facility. The results of these analyses shall be presented in the Annual Environmental Report (AER).

#### 5.8.2 Compost

- 5.8.2.1 In order not to be considered a waste, compost produced by the facility shall comply with the quality established in *Schedule G: Compost Quality*, of this licence. Analysis of the compost shall be in accordance with the requirements of that Schedule.

#### 5.8.3 Inert Waste

- 5.8.3.1 Inert waste accepted at the facility shall comply with the standards established in EC Council Decision 2003/33/EC.

#### 5.8.4 Non-hazardous Asbestos Waste

- 5.8.4.1 Only non-hazardous asbestos waste shall be disposed of at the facility.
- 5.8.4.2 Non-hazardous asbestos based construction and demolition waste must be double wrapped in heavy gauge plastic, which is clearly labelled to indicate the presence of asbestos.
- 5.8.4.3 Disposal of non-hazardous asbestos waste shall be into prepared bays or trenches of at least 2 metres in depth.
- 5.8.4.4 Deposited non-hazardous asbestos waste shall be covered immediately with at least 250mm of suitable material. At the end of the day, the waste shall be covered with a minimum of 500mm of suitable material.
- 5.8.4.5 No non-hazardous asbestos waste shall be present within 2.5 metres of the final surface levels.

### 5.9 Off-site Disposal and Recovery

- 5.9.1 Waste sent off-site for recovery or disposal shall be conveyed only by a waste contractor agreed by the Agency.
- 5.9.2 All waste transferred from the facility shall be transferred only to an appropriate facility agreed by the Agency.
- 5.9.3 All wastes removed off-site for recovery or disposal shall be transported from the facility to the consignee in a manner which will not adversely affect the environment.
- 5.10 Civic Waste Facility
- 5.10.1 The Civic Waste Facility shall be used only by private vehicles. The facility shall not be used as a transfer station for disposal of waste by commercial waste disposal contractors or local authority waste collection vehicles.
- 5.10.2 All waste deposited in the Civic Waste Facility shall be either:-
- a) Into a skip;
  - b) Into the hopper of the compactor for disposal;
  - c) Into a receptacle for recovery; and
  - d) In the case where inspection is required, into a designated inspection area.
- 5.10.3 The licensee shall assign and clearly label each container at the Civic Waste Facility to indicate their contents.
- 5.10.4 At the end of the working day the floor of the Civic Waste Facility shall be cleared of waste.
- 5.11 Construction and Demolition Waste Recovery Area
- 5.11.1 Only Construction and Demolition waste shall be accepted at this Area. Wastes which are capable of being recovered shall be separated and shall be stored temporarily in this area prior to being subjected to other recovery activities at the facility or transport off the facility.
- 5.11.2 All stockpiles shall be maintained so as to minimise dust generation.
- 5.12 Leachate Management
- 5.12.1 Leachate treatment shall be as specified in Sections 5.4.4 – 5.4.6 of the EIS Addendum.
- 5.12.2 Leachate levels in the waste shall not exceed a level of 1.0m over the top of the liner at the base of the landfill.
- 5.12.3 The frequency of leachate removal/discharge from the leachate lagoon shall be such that a minimum freeboard of 0.75m shall be maintained in the leachate lagoon at all times.
- 5.12.4 Unless treated on the facility, leachate stored in the leachate storage lagoon shall be disposed of by tankering off-site in fully enclosed road tankers.
- 5.12.5 Recirculation of leachate or other contaminated water shall not be undertaken without the prior agreement of the Agency and, in any case, shall be undertaken only within cells which have been lined to the satisfaction of the Agency.
- 5.13 Maintenance
- 5.13.1 All treatment/abatement and emission control equipment shall be calibrated and maintained, in accordance with the instructions issued by the manufacturer/supplier or installer. Written records of the calibrations and maintenance shall be made and kept by the licensee.

- 5.13.2 All lagoon structures on the facility shall be inspected and certified fit for purpose every three years by an independent and appropriately qualified chartered engineer.
- 5.13.3 The licensee shall maintain and clearly label and name all sampling and monitoring locations.
- 5.13.4 The wheel-wash shall be inspected on a daily basis and drained as required. Silt, stones and other accumulated material shall be removed as required from the wheel-wash and disposed of at the working face or to a skip.
- 5.14 Written procedures for the acceptance and handling of animal by-product waste shall include the following requirements (unless otherwise agreed by the Agency):
  - 5.14.1 Vehicles delivering animal by-product waste to the facility shall be leak-proof and adequately covered.
  - 5.14.2 Containers and vehicles used for transporting untreated animal by-product waste shall be cleaned and disinfected prior to leaving the facility. They shall be cleaned and disinfected in a designated area designed to prevent contamination of treated products.
  - 5.14.3 All composting residues including process wastewater shall be handled in such a way as to prevent recontamination from untreated products.
  - 5.14.4 Composting bays/containers shall be designated and labelled so as to ensure that animal by-product waste is treated in the same designated vessels, in so far as is practicable.
  - 5.14.5 These procedures shall be updated prior to the acceptance of new waste types (when necessary), as required to reflect changes in National or EU Legislation or as agreed by the Agency.
- 5.15 Compost Process Management and validation
  - 5.15.1 All composting shall be executed in line with the treatment regimes outlined in *Schedule E: Compost Process Management* of this licence, unless otherwise instructed by the Agency.
  - 5.15.2 All Category 3 animal by-product waste accepted at the facility for treatment shall be treated in accordance with the requirements of the EU regulation 1774/2002, laying down health rules concerning animal by-products not intended for human consumption and associated National Legislation.
  - 5.15.3 All landspreading of compost containing Category 2 or 3 animal by-products as a constituent shall be carried out in accordance with the 'European Parliament and Council Regulation No 1774/2002 laying down health rules concerning animal by-products not intended for human consumption' or other National Regulations.
  - 5.15.4 An indicator organism shall be used to validate the compost sanitation steps. This shall be carried out as outlined in *Schedule E: Compost Process Management* of this licence.
- 5.16 Compost Use
  - 5.16.1 In order to be considered a product, compost shall comply with the Quality Standards as outlined in *Schedule G: Compost Quality* of this licence, unless otherwise agreed by the Agency. Compost not complying with Class 1 or Class 2 of these Quality Standards shall, as with Stabilised Biowaste be considered a waste and shall be disposed/recovered to an authorised outlet, as agreed by the Agency and the details recorded as per Condition 10.6.
  - 5.16.2 Compost of Class 1 Standard shall be considered a product. All landspreading of compost of Class 1 Standard shall be in accordance with best agronomic practice.



- 5.16.3 Compost of Class 2 Standard shall be considered a product and shall be used in accordance with best agronomic practice. Unless otherwise agreed by the Agency it shall be used in a quantity not exceeding 30 tonnes dry matter per hectare (on a three year average).
- 5.16.4 The recovery or disposal of compost not reaching the standards designated Class 1 or Class 2, shall be recorded as required under Condition 10.6.

*REASON: To provide for appropriate operation of the facility to ensure protection of the environment.*

## CONDITION 6 EMISSIONS

- 6.1. No specified emission from the facility shall exceed the emission limit values set out in *Schedule C: Emission Limits*, of this licence. There shall be no other emissions of environmental significance.
- 6.2. The licensee shall ensure that the activities shall be carried out in a manner such that emissions do not result in significant impairment of, or significant interference with the environment beyond the facility boundary.
- 6.3. Landfill Gas
- 6.3.1. The following are the trigger levels for landfill gas emissions from the facility measured in any service duct or manhole on, at or immediately adjacent to the facility and/or at any other point located outside the body of the waste:-
- a) Methane, greater than or equal to 1.0% v/v; or
  - b) Carbon dioxide, greater than or equal to 1.5% v/v.
- 6.3.2. The concentration limits for emissions to atmosphere specified in this licence shall be achieved without the introduction of dilution air and shall be based on gas volumes under standard conditions of :-
- a) In the case of landfill gas flare:  
Temperature 273 K, pressure 101.3 kPa, dry gas at 3% oxygen; and
  - b) In the case of landfill gas combustion plant:  
Temperature 273 K, pressure 101.3 kPa, dry gas; 5% oxygen.
- 6.3.3. Emission limits for emissions from landfill gas flare/combustion plant to atmosphere in this licence shall be interpreted in the following way.
- 6.3.3.1. Continuous monitoring
- a) No 24 hour mean value shall exceed the emission limit value;
  - b) 97% of all 30 minute mean values taken continuously over an annual period shall not exceed 1.2 times the emission limit value; and
  - c) No 30 minute mean value shall exceed twice the emission limit value.
- 6.3.3.2 Non-Continuous Monitoring
- a) For any parameter where, due to sampling/analytical limitations, a 30 minute samples is inappropriate, a suitable sampling period should be employed and the value obtained therein shall not exceed the emission limit value;

- b) For all other parameters, no 30 minute mean value shall exceed the emission limit value; and
- c) For flow, no hourly or daily mean value shall exceed the emission limit value.

#### 6.4. Groundwater

6.4.1 There shall be no direct emissions to groundwater.

6.4.2 Prior to the acceptance of waste at the facility, the licensee shall submit to the Agency for its agreement, groundwater monitoring trigger levels in accordance with the requirements of Directive 1999/31/EC.

#### 6.5. Emissions to Surface Water

6.5.1. No raw leachate, treated leachate or potentially contaminated water shall be discharged to surface water.

6.5.2. No substance shall be discharged in a manner, or at a concentration which, following initial dilution causes tainting of fish or shellfish.

6.5.3. Within three months of the date of grant of this licence, the applicant shall submit to the Agency for its agreement proposals for continuous monitoring of water in the surface water retention ponds. These proposals shall include the criteria/trigger levels which will determine when the outlet from these ponds shall be closed. Such continuous monitoring shall, as a minimum, include conductivity, pH and TOC and shall be carried out on the inlet to the storm water retention pond.

##### Compost

6.5.4. Any surface runoff or process waste water collected in storage tanks shall be pumped/directed back into the process, unless otherwise agreed by the Agency. In the case of Category 3 waste material, unsanitised process waste water shall not be added to the process after the compost sanitisation phase.

#### 6.6 Noise Emissions

6.6.1 Prior to the commencement of waste activities testing of the effectiveness of various acoustic barriers shall be carried out. Waste activities shall not commence until it has been shown to the satisfaction of the Agency that activities at the proposed facility will not cause a significant impairment of, or significant interference with the environment beyond the facility boundary and at noise sensitive locations 1-9.

6.6.2 Speed restrictions and traffic calming measures within the facility boundary shall be adopted in consultation with Wexford County Council's roads department.

6.6.3 In addition the licensee shall ensure the following:

- a) That low sound level plant is used on-site.
- b) That all heavy machinery used on-site is fitted with acoustic panels in the engine bays and acoustic mufflers (exhaust silencers).

#### 6.7. Disposal of Leachate

6.7.1. Unless otherwise approved in writing no treated leachate shall be discharged to surface water.

#### 6.8 Trigger Level for PM<sub>10</sub>

- 6.8.1 The trigger level for PM<sub>10</sub> from the facility measured at any location on the boundary of the facility is:-
- a) PM<sub>10</sub> greater than 50µg/m<sup>3</sup> for a daily sample.
- 6.8.2 Emission limit values for emissions to sewer/waters in this licence shall be interpreted in the following way:-
- a) Continuous monitoring.  
No flow value shall exceed the specified limit.
  - b) Non-Continuous monitoring.  
Eight out of ten consecutive results, calculated as daily mean concentration or mass emission values on the basis of flow proportional composite sampling shall not exceed 1.2 times the emission limit value.
  - c) No grab sample shall exceed 1.2 times the emission limit value.

*REASON: To control emissions from the facility and provide for the protection of the environment.*

## **CONDITION 7 NUISANCE CONTROL**

- 7.1 The licensee shall ensure that vermin, birds, flies, mud, dust, litter and odours do not give rise to nuisance at the facility or in the immediate area of the facility. Any method used by the licensee to control any such nuisance shall not cause environmental pollution.
- 7.2 The road network in the vicinity of the facility shall be kept free from any debris caused by vehicles entering or leaving the facility. Any such debris or deposited materials shall be removed without delay.
- 7.3 Litter Control
- 7.3.1 Litter fencing shall be installed and maintained around the perimeter of the active tipping area prior to the disposal of any waste in any cell.
  - 7.3.2 All litter control infrastructure shall be inspected on a daily basis. The licensee shall remedy any defect in the litter netting as follows:-
    - a) A temporary repair shall be made by the end of the working day; and
    - b) A repair to the standard of the original netting shall be undertaken within three working days.
  - 7.3.3 All loose litter or other waste, placed on or in the vicinity of the facility, other than in accordance with the requirements of this licences, shall be removed, subject to the agreement of the landowners, immediately and in any event by 10.00am of the next working day after such waste is discovered.
  - 7.3.4 The licensee shall ensure that all vehicles delivering waste to and removing waste and materials from the facility are appropriately covered.
- 7.4 Dust Control
- 7.4.1 In dry weather, site roads and any other areas used by vehicles shall be sprayed with water as and when required to minimise airborne dust nuisance.

7.5 Prior to exiting the facility, all waste vehicles shall use the wheelwash.

7.6 Bird Control

7.6.1 Birds shall be prevented from gathering on and feeding at the facility by the use of birds of prey and/or other bird scaring techniques. The birds of prey and/or other techniques shall be in place on the facility at least two weeks prior to any waste being disposed of and shall maintain their presence every day, from before dawn to after dark, until the waste activities cease and all the waste is capped to the written satisfaction of the Agency. The use of gas operated bird scaring devices is prohibited at the facility.

7.7 Visual Intrusion

7.7.1 The licensee shall ensure that acoustic barriers and bunds assist in the mitigation of visual intrusion of the landfill and do not contribute to visual intrusion.

*REASON: To provide for the control of nuisances.*

## CONDITION 8 MONITORING

8.1 The licensee shall carry out such monitoring and at such locations and frequencies as set out in *Schedule D: Monitoring*, of this licence and as specified in this licence. Unless otherwise specified by this licence, all environmental monitoring shall commence no later than two months after the date of grant of this licence.

8.2 The licensee shall amend the frequency, locations, methods and scope of monitoring as required by this licence only upon the written instruction of the Agency and shall provide such information concerning such amendments as may be requested in writing by the Agency. Such alterations shall be carried out within any timescale nominated by the Agency.

8.3 Monitoring and analysis equipment shall be operated and maintained in accordance with the manufacturers' instructions (if any) so that all monitoring results accurately reflect any emission, discharge or environmental parameter.

8.4 The licensee shall provide safe and permanent access to all on-site sampling and monitoring points and to off-site points as required by the Agency.

8.5 Prior to the commencement of waste activities, the licensee shall install a permanent gas monitoring system in the site office and any other enclosed structures at the facility. All landfill gas monitoring equipment, other than permanent monitoring systems within buildings, shall be certified as being intrinsically safe.

8.6 Two months prior to the commencement of waste activities for new facilities the following information shall be submitted to the Agency for its agreement: the names, qualifications and a summary of the relevant experience of all persons that will carry out all sampling and monitoring as required by this licence and who carry out the interpretation of the results of such sampling and monitoring. Any proposed changes to the above shall be submitted to the Agency for its agreement.

8.7 to the commencement of waste activities the licensee shall submit to the Agency for its agreement an updated appropriately scaled drawing showing all the monitoring locations that are stipulated in this licence. The drawing shall include the twelve figure National Grid Reference for the various monitoring points.

8.8 Groundwater Monitoring

8.8.1 Subject to the agreement of the well owners, all private wells within 250m of the facility shall be included in the monitoring programme set out in *Schedule D: Monitoring*, of this licence.

8.8.2 Prior to the excavation of ground for the installation of the landfill lining system groundwater levels within the landfill footprint area should be monitored, at least monthly throughout a period spanning the months September to March.

## 8.9 Surface Water Inspection

8.9.1 The licensee shall ensure that

- (i) the surface water weirs and drainpipes and sediment debris screens and;
- (ii) the surface water channels both in the vicinity of the facility and downstream

are checked for clogging with debris and if necessary cleared on a weekly basis at a minimum.

## 8.10 Meteorological Monitoring

8.10.1 Prior to the commencement of waste disposal activities the licensee shall provide and maintain a meteorological station at the facility, which shall be known by the point reference number MET1, capable of monitoring the parameters listed in *Schedule D.6: Meteorological Monitoring*, of this licence.

## 8.11 Biological Assessment

8.11.1 A biological assessment of the adjacent surface water streams shall be undertaken prior to the commencement of facility development and annually thereafter. This assessment shall use appropriate biological methods such as the EPA Q-rating system for the assessment of rivers and streams. The location of monitoring points shall be as agreed by the Agency.

## 8.12 Leachate Monitoring

8.12.1 The licensee shall, prior to acceptance of waste for disposal at the facility submit to the Agency for its agreement a proposal for the monitoring of dissolved methane, prior to discharge to pipeline/ sewer.

## 8.13 Archaeological Assessment

8.13.1 Prior to the development of any undisturbed area, the advice of the Heritage Section of the Department of the Environment, Heritage and Local Government (formerly Dúchas) shall be sought. On completion of such development a report of the results of any archaeological monitoring shall be submitted to The Development Applications Section and to the Agency.

## 8.14 Stability Assessment

8.14.1 Upon commencement of waste activities, and annually thereafter, the licensee shall carry out a stability assessment of the side slopes of the facility.

## 8.15 Nuisance Monitoring

8.15.1 The licensee shall, at a minimum of one-week intervals, inspect the facility and its immediate surrounds for nuisances caused by litter, vermin, birds, flies, mud, dust and odours.

8.15.2 The licensee shall prior to the commencement of waste activities submit to the Agency for its agreement a proposal for the monitoring of odours at the facility in accordance with *Schedule D: Monitoring*, of this licence.

- 8.16 The licensee shall, within six months of the date of grant of this licence, develop and establish a Data Management System for collation, archiving, assessing and graphically presenting the environmental monitoring data generated as a result of this licence.
- 8.17 Compost quality monitoring
- 8.17.1 Compost quality shall be monitored at the frequencies set out in *Schedule G: Compost Quality* of this licence, unless otherwise agreed by the Agency.
- 8.18 Prior to commencement of waste activities, the licensee shall submit to the Agency for its agreement details of the sampling protocol and methods of analyses for the composting operations.

*REASON: To ensure compliance with the conditions of this licence by provision of a satisfactory system of monitoring of emissions.*

## **CONDITION 9 CONTINGENCY ARRANGEMENTS**

- 9.1. In the event of an incident the licensee shall immediately:-
- a) Identify the date, time and place of the incident;
  - b) Carry out an immediate investigation to identify the nature, source and cause of the incident and any emission arising therefrom;
  - c) Isolate the source of any such emission;
  - d) Evaluate the environmental pollution, if any, caused by the incident;
  - e) Identify and execute measures to minimise the emissions/malfunction and the effects thereof; and
  - f) Provide a proposal to the Agency for its agreement within one month of the incident occurring to:-
    - i) Identify and put in place measures to avoid reoccurrence of the incident;
    - ii) Identify and put in place any other appropriate remedial action.
- 9.2. The licensee shall, prior to commencement of any waste activities, submit a written Emergency Response Procedure (ERP) to the Agency for its agreement. The ERP shall address any emergency situations which may originate on the facility and shall include provision for minimising the effects of any emergency on the environment. This shall include a risk assessment to determine the requirements at the facility for fire fighting and fire water retention facilities. The Fire Authority shall be consulted by the licensee during this assessment.
- 9.3. The licensee shall have in storage an adequate supply of containment booms and/or suitable absorbent material to contain and absorb any spillage at the facility. Once used the absorbent material shall be disposed of at an appropriate facility.
- 9.4. Emergencies
- 9.4.1. All significant spillages occurring at the facility shall be treated as an emergency and immediately cleaned up and dealt with so as to alleviate their effects.
- 9.4.2. No waste shall be burnt within the boundaries of the facility. A fire at the facility shall be treated as an emergency and immediate action shall be taken to extinguish it and notify the appropriate authorities.

9.4.3. In the event that monitoring of local wells indicates that the facility is having a significant adverse effect on the quantity and/or quality of the water supply this shall be treated as an emergency and the licensee shall provide an alternative supply of water to those affected.

9.4.4. In the event that monitoring of the slide slopes of the facility indicate that there may be a risk of slope failure this will be treated as an emergency.

9.5 Tree Felling

9.5.1 Any tree felling to be carried out within the facility shall be carried out during the period September to February.

9.6 Badgers

9.6.1 Works required to exclude/ live trap badgers from within the facility shall be carried out and this work shall be carried out in consultation with the National Parks and Wildlife Service staff of the Department of Environment, Heritage and Local Government.

9.7 The licensee shall provide and maintain a storage tank for the temporary storage of liquid runoff/ liquid waste from the composting process.

*REASON: To ensure compliance with the conditions of this licence by provision of a satisfactory system of monitoring of emissions.*

## **CONDITION 10 RECORDS**

10.1 The licensee shall keep the following documents at the facility office:-

- a) The current waste licence relating to the facility;
- b) The current EMS for the facility;
- c) The previous year's AER for the facility; and
- d) All written procedures produced by the licensee which relate to the licensed activities.

10.2 The licensee shall maintain a written record for each load of waste arriving at the facility, including those arriving at the Materials Recovery Facility but excluding those arriving at the Civic Waste Facility. The licensee shall record the following:-

- a) The date;
- b) The name of the carrier (including if appropriate, the waste carrier registration details);
- c) The vehicle registration number;
- d) The name of the producer(s)/collector(s) of the waste as appropriate;
- e) The name of the waste facility (if appropriate) from which the load originated including the waste licence or waste permit register number;
- f) A description of the waste including the associated EWC codes and animal by-product Waste Category designation (where appropriate);
- g) The quantity of the waste, recorded in tonnes;
- h) The name of the person checking the load; and
- i) Where loads or wastes are removed or rejected, details of the date of occurrence, the types of waste and the facility to which they were removed.

10.3 Written Records

The following written records shall be maintained by the licensee:-

- a) The types and quantities of waste recovered and disposed of at the facility each year. These records shall include the relevant EWC Codes and animal by-product designation Waste Category (as appropriate);
  - b) All training undertaken by facility staff;
  - c) Results from all integrity tests of bunds and other structures and any maintenance or remedial work arising from them;
  - d) Details of all nuisance and surface water inspections, daily odour and biofilter inspections;
  - e) The names and qualifications of all persons who carry out all sampling and monitoring as required by this licence and who carry out the interpretation of the results of such sampling and monitoring; and
  - f) Records of waste inspections carried out in accordance with Condition 5.7.17.
- 10.4 The licensee shall maintain a written record of all complaints relating to the operation of the facility. Each such record shall give details of the following:-
- a) Date and time of the complaint;
  - b) The name of the complainant;
  - c) Details of the nature of the complaint;
  - d) Actions taken on foot of the complaint and the results of such actions; and
  - e) The response made to each complainant.
- 10.5 A written record shall be kept of the quantities of leachate removed from the facility/discharged to sewer. The record shall include the following:-
- a) The name of the carrier;
  - b) The date and time of removal of leachate from the facility;
  - c) The volume of leachate, in cubic metres, removed/discharged from the facility on each occasion;
  - d) The name and address of the Waste Water Treatment Plant to which the leachate was transported/ discharged; and
  - e) Any incidents or spillages of leachate during its removal/discharge or transportation.
- 10.6 A written record shall be kept for each load of waste departing from the Civic Waste Facility, composting facility and Materials Recovery Facility. The following shall be recorded:-
- a) The name of the carrier;
  - b) The vehicle registration number;
  - c) The destination of the waste (facility name and waste licence/permit number as appropriate);
  - d) A description of the waste (if recovered or rejected waste, the specific nature of the waste);
  - e) The quantity of waste, recorded in tonnes;
  - f) The name of the person checking the load; and
  - g) The time and date of departure.
- 10.7 A written record shall be kept at the facility of the programme for the control and eradication of vermin and fly infestations at the facility. These records shall include as a minimum the following:-
- a) The date and time during which spraying of insecticide is carried out;
  - b) Contractor details;
  - c) Contractor logs and site inspection reports;
  - d) Details of the rodenticide(s) and insecticide(s) used;



- e) Operator training details;
  - f) Details of any infestations;
  - g) Mode, frequency, location and quantity of application; and
  - h) Measures to contain sprays within the facility boundary.
- 10.8 The licensee shall assign and clearly label a unique reference code to each composting vessel at the facility. In addition, the following shall be recorded:
- a) the time at which composting of the container contents commenced;
  - b) the time at which composting of the container contents ceased; and
  - c) the presence or absence of Animal by-product Category 3 waste as an ingredient of the container.

*REASON: To provide for the keeping of proper records of the operation of the facility.*

## **CONDITION 11 REPORTS AND NOTIFICATIONS**

- 11.1 Unless otherwise agreed by the Agency, all reports and notifications submitted to the Agency shall:-
- a) Be sent to the Agency's Headquarters;
  - b) Comprise one original and two copies unless additional copies are required;
  - c) Be formatted in accordance with any written instruction or guidance issued by the Agency;
  - d) Include whatever information as is specified in writing by the Agency;
  - e) Be identified by a unique code, indicate any modification or amendment, and be correctly dated to reflect any such modification or amendment;
  - f) Be submitted in accordance to the relevant reporting frequencies specified by this licence, such as in *Schedule F: Recording and Reporting to the Agency*, of this licence;
  - g) Be accompanied by a written interpretation setting out their significance in the case of all monitoring data; and
  - h) Be transferred electronically to the Agency's computer system if required by the Agency.
- 11.2 In the event of an incident occurring on the facility, the licensee shall:-
- a) Notify the Agency as soon as practicable and in any case not later than 1000 hrs the following working day after the occurrence of any incident;
  - b) Submit a written record of the incident, including all aspects described in Condition 9.1(a-e), to the Agency as soon as practicable and in any case within five working days after the occurrence of any incident;
  - c) In the event of any incident which relates to discharges to surface water/sewer, notify the Eastern Regional Fisheries Board/ wastewater treatment plant operators as soon as practicable and in any case not later than 1000 hrs on the following working day after such an incident; and
  - d) Should any further actions be taken as a result of an incident occurring, the licensee shall forward a written report of those actions to the Agency as soon as practicable and no later than ten days after the initiation of those actions.

### 11.3 Waste Recovery Reports

Prior to the acceptance of waste for disposal, a report examining waste recovery options shall be submitted to the Agency for its agreement. This report shall address methods to contribute to the achievement of the recovery targets stated in national and European Union waste policies and shall include the following:-

- a) Proposals for the contribution of the facility to the achievement of targets for the reduction of biodegradable waste to landfill, going to landfills as specified in the Landfill Directive;
- b) The separation of recyclable materials from the waste;
- c) The recovery of Construction and Demolition Waste;
- d) The recovery of metal waste and white goods including written procedures for the de-gassing of CFC's from refrigerators;
- e) The recovery of commercial waste, including cardboard;
- f) Composting of biodegradable or green waste at the facility having regard to good practice and sustainability;
- g) Inert waste to be used for cover/restoration material at the facility;
- h) Proposals regarding the utilisation of energy from the gas utilisation plant;
- i) The feasibility of using landfill gas as a fuel for on-site vehicles; and
- j) Other wastes.

#### 11.4 Reports relating to Facility Operations

##### 11.4.1 Leachate Handling Procedures

11.4.1.1 The licensee shall submit to the Agency for its agreement three months prior to the commencement of waste disposal activities leachate Handling Procedures for the handling of leachate on the facility and during removal from the lagoon and subsequent discharge to the sewer.

##### 11.4.2 Operation in Adverse Wind Conditions

11.4.2.1 Prior to the acceptance of waste for disposal the licensee shall submit to the Agency for its agreement proposals for the operation of the facility in adverse wind conditions.

#### 11.5 Vermin and Flies

11.5.1 Prior to the commencement of waste disposal, the licensee shall submit to the Agency for its agreement a proposal for the control and eradication of vermin and fly infestations at the facility. This proposal should include as a minimum, operator training, details on the rodenticide(s) and insecticide(s) to be used, mode and frequency of application and measures to contain sprays within the facility boundary.

#### 11.6 Monitoring Locations

11.6.1 Within six months of the date of grant of this licence, the licensee shall submit to the Agency an appropriately scaled drawing(s) showing all the monitoring locations that are stipulated in this licence. The drawing(s) shall include the reference code of each monitoring point.

#### 11.7 Annual Environmental Report

- 11.7.1 The licensee shall submit to the Agency for its agreement, by 31<sup>st</sup> March of each year thereafter, an Annual Environmental Report (AER).
- 11.7.2 The AER shall include as a minimum the information specified in *Schedule H: Content of Annual Environmental Report*, of this licence and shall be prepared in accordance with any relevant written guidance issued by the Agency.

*REASON: To provide for proper reports to and notifications to the Agency.*

## **CONDITION 12 CHARGES AND FINANCIAL PROVISIONS**

### 12.1 Agency Charges

- 12.1.1 The licensee shall pay to the Agency an annual contribution of €30,399 or such sum as the Agency from time to time determines, towards the cost of monitoring the activity or otherwise in performing any functions in relation to the activity, as the Agency considers necessary for the performance of its functions under the Waste Management Act, 1996. The licensee shall in 2005 and subsequent years, not later than January 31 of each year, pay to the Agency this amount updated in accordance with changes in the Public Sector Average Earnings Index from the date of the licence to the renewal date. The updated amount shall be notified to the licensee by the Agency. For 2004, the licensee shall pay a pro rata amount from the date of this licence to 31<sup>st</sup> December. This amount shall be paid to the Agency within one month of the date of grant of this licence.
- 12.1.2 In the event that the frequency or extent of monitoring or other functions carried out by the Agency needs to be increased the licensee shall contribute such sums as determined by the Agency to defraying its costs in regard to items not covered by the said annual contribution.

### 12.2 Financial Provision for Closure, Restoration and Aftercare

- 12.2.1 The licensee shall prior to the commencement of waste disposal activities establish and maintain a fund, or provide a written guarantee, that is adequate to assure the Agency that the licensee is at all times financially capable of implementing the Restoration and Aftercare Plan required by Condition 4. The type of fund established and means of its release/recovery shall be agreed by the Agency prior to its establishment.
- 12.2.2 Any fund established shall be maintained in an amount always sufficient to underwrite the current Restoration and Aftercare Plan.
- 12.2.3 The licensee shall revise the cost of restoration and aftercare annually and any details of the necessary adjustments to the fund or guarantee must, within two weeks of the revision, be forwarded to the Agency for its agreement. Any adjustment agreed by the Agency shall be effected within four weeks of said written agreement.
- 12.2.4 Unless otherwise agreed any revision to the fund shall be computed using the following formula:-

$$\text{Cost} = (\text{ECOST} \times \text{WPI}) + \text{CiCC}$$

Where:-

Cost = Revised restoration and aftercare cost

ECOST = Existing restoration and aftercare cost

- WPI = Appropriate Wholesale Price Index [Capital Goods, Building & Construction (i.e. Materials & Wages) Index], as published by the Central Statistics Office, for the year since last closure calculation/revision.
- CiCC = Change in compliance costs as a result of change in site conditions, changes in law, regulations, regulatory authority charges, or other significant changes.

#### 12.4 Cost of landfill of waste

The licensee shall provide a statement in writing to the Agency on an annual basis as part of the AER in respect of the determination of charges for the disposal of waste. The Statement shall be in accordance with the requirements of S.I. No. 337 of 2002 European Communities (Amendment of Waste Management (Licensing) Regulations, 2000) Regulation, 2002.

#### 12.5 Community Support and Development Scheme

The licensee shall each year pay €0.50 (Index Linked) for every tonne of waste accepted for disposal in the landfill in the previous calendar year, into a ring-fenced community support and development fund. Prior to the commencement of waste disposal activities the licensee shall establish a community managed charitable trust (or equivalent) to manage and discharge this fund for the benefit of the social and physical environment of the local community

*REASON: To provide for adequate financing for monitoring and financial provisions for measures to protect the environment.*

# SCHEDULE A : Waste Acceptance

## A.1 Waste Acceptance

*Table A.1 Waste Categories and Quantities*

Waste Type	Maximum (Tonnes Per Annum) Note 1
Non-hazardous household and commercial waste	55,000
Waste for composting	5,000
Construction and Demolition Waste for recovery	8,000
Household and commercial waste accepted for recovery at the Civic Waste Facility and Materials Recovery Facility	12,000
<b>TOTAL</b>	<b>80,000</b>

**Note 1:** Individual tonnages may be varied if agreed in advance by the Agency, subject to the maximum tonnage.

# SCHEDULE B : Specified Engineering Works

Specified Engineering Works
Development of the facility including preparatory works and lining.
Final capping.
Installation of Compost Facility.
Installation of the Materials Recovery Facility.
Installation of the Civic Waste Facility.
Installation of Landfill Gas Management Infrastructure.
Installation of Leachate Management Infrastructure.
Installation of Groundwater Control Infrastructure.
Installation of Surface Water Management Infrastructure.
Any other works notified in writing by the Agency.

## SCHEDULE C : Emission Limits

### C.1 Noise Emissions:

(Measured at the noise sensitive locations indicated in [Table D.1.1](#)).

Day Db(A) L <sub>Aeq</sub> (15 minutes)	Night dB(A) L <sub>Aeq</sub> (15 minutes)
55	45

### C.2 Landfill Gas Concentration Limits:

(Measured in any building on or adjacent to the facility).

Methane	Carbon Dioxide
20 % LEL (1% v/v)	1.5 % v/v

### C.3 Dust Deposition Limits:

(Measured at the monitoring points indicated in [Table D.1.1](#)).

Level (mg/m <sup>2</sup> /day) <sup>Note 1</sup>
350

**Note 1:** 30 day composite sample with the results expressed as mg/m<sup>2</sup>/day.

### C.4 Surface Water Discharge Limits:

Measured at the outlet from the **surface water lagoons/ponds**.

Level (Suspended Solids mg/l)
25

### C.5 Air Emission Limits:

#### C.5.1 Emission Limits Values for Biofilters

Emission Point reference no: **Biofilter 1**

Parameter	Emission Limit Value
Ammonia	50 mg/m <sup>3</sup>
Hydrogen sulphide	5 mg/m <sup>3</sup>
Mercaptans	5 mg/m <sup>3</sup>

#### C.6 Emission Limits Values for Landfill Gas Plant

Emission Point Reference numbers: **GF1 and GF2** <sup>Note 3</sup>

Volume to be emitted: 3000m<sup>3</sup>/hr (unless results from modelling suggests otherwise)

Minimum discharge height: 5m (unless results from modelling suggests otherwise)

Parameter	Flare (enclosed) Emission Limit Value <sup>Note 1</sup>	Utilisation Plant Emission Limit Value <sup>Note 1</sup>
Nitrogen oxides (NO <sub>x</sub> )	150 mg/m <sup>3</sup>	500 mg/m <sup>3</sup>
CO	50 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>
Particulates	Not applicable	130 mg/m <sup>3</sup>
Total organic carbon (TOC)	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>

**Note 1:** Dry gas referenced to 5% oxygen by volume for utilisation plants and 3% oxygen by volume for flares.

***C.7 Emission Limits for Leachate Being Discharged to Sewer/ from on-site leachate treatment plant***

Emission Point Reference No. LTP3, location to be agreed by the Agency.

Volume to be emitted: Maximum in any one day: **80 m<sup>3</sup>**

Parameter	Emission Limit Value	
	Grab Sample (mg/l)	Daily Mean Concentration (mg/l)
BOD	25	10
COD		500
Ammoniacal Nitrogen (NH <sub>4</sub> -N)		10
Nitrate Nitrogen		1500
Alkalinity		1000
Dissolved methane		0.2

# SCHEDULE D : Monitoring

## D.1 Monitoring Locations

Monitoring locations shall be those as set out in Table D.1.1, Attachment F of the application and Figure 5.12 of the EIS Addendum.

**Table D.1.1** Monitoring Locations

Landfill Gas within Waste and Boundary Locations	Landfill Gas Flare/Utilisation Plant <sup>Note 2</sup>	Dust PM <sub>10</sub> Deposition / Odour/ Bioaerosols	Noise	Surface Water <sup>Note 5</sup>	Ground Water	Leachate
Stations		Stations	Stations	Stations	Stations	Stations
In waste: to be agreed	GF1, GF2 etc. Location to be agreed	D.1, D.2, D.3, D.4, D.5, D.6, D.7, D.8, D.9, D.10.	Noise sensitive locations: N1, N2, N3, N4, N5, N6, N7, N8, N9.	SW1, SW2, SW2A, SW3, SW3a, SW4, SW5, SW6, SW7, SW8, SW9	BH1, BH2, BH3, BH6, BH7, BH8, BH9.	LTP-1, LTP-2, LTP-3 Exact locations to be agreed <sup>Note 3/4</sup>
Boundary locations: GS1, GS2, GS3, GS4, GS5, GS6, GS7, GS8, GS9, GS10, GS11, GS12, GS13, GS14, GS15, GS16, GS17, GS18, GS19, GS20, GS21, GS22, GS23		Odour: to be agreed including 3 fixed locations and 2 locations to be chosen on the day (upwind/ downwind)		Surface water pond: SWP1 (inlet), SWP2 (outlet)	Private wells <sup>Note 1</sup> : PW1, PW2, PW2a, PW3, PW4, PW5, PW6, PW7, PW8, PW9, PW10, PW11.	Within Cells: LW1, LW2, LW3, LW4, LW5, LW6, LW7, LW8, LW9, LW10 <sup>Note 4</sup>
		Biofilter 1		Biological monitoring points: to be agreed		

**Note 1:** Subject to the agreement of the well owners.

**Note 2:** GF1 and GF2 refer to the emissions points from the flare and utilisation plant respectively. Any additional points to be agreed in advance by the Agency.

**Note 3:** LTP-1 refers to the raw leachate at the influent point. LTP-2 refers to the monitoring point in the sequencing batch reactor. LTP-3 refers to treated leachate at the effluent point.

**Note 4:** Leachate monitoring locations LTP-1, LTP-2, LTP-3, LW1, LW5 and LW10 should be analysed for leachate composition. All other locations should be monitored for levels.

**Note 5:** SW3 should be located further north of the position as shown on Figure 5.12 of the EIS Addendum, just downstream of the confluence of the three streams shown. An additional monitoring point SW3a should be located on the eastern stream, adjacent to dust monitoring point D3. SWP1 and SWP2 are monitoring points at the inlet and outlet points of the final (i.e. furthest downstream) surface water pond.



## D.2 Landfill Gas

**Table D.2.1** Landfill Gas Monitoring Parameters, Frequency and Technique

Parameter	Monitoring Frequency		Analysis Method <sup>Note1</sup> /Technique <sup>Note2</sup>
	Gas Boreholes/ Vents/Wells	Site Office	
Methane (CH <sub>4</sub> ) % v/v	Monthly	Weekly	Infrared analyser/flame ionisation detector
Carbon dioxide (CO <sub>2</sub> ) % v/v	Monthly	Weekly	Infrared analyser/ flame ionisation detector
Oxygen(O <sub>2</sub> ) % v/v	Monthly	Weekly	Electrochemical cell
Atmospheric Pressure	Monthly	Weekly	Standard
Temperature	Monthly	Weekly	Standard

**Note 1:** All monitoring equipment used should be intrinsically safe.

**Note 2:** Or other methods agreed in advance by the Agency.

## D.3 Dust/Odour/PM10 Monitoring

**Table D.3.1** Dust Monitoring Frequency and Technique

Parameter (mg/m <sup>2</sup> /day)	Monitoring Frequency	Analysis Method/Technique
Dust	Three times a year <sup>Note 2</sup>	Standard Method <sup>Note 1</sup>
Odour	Quarterly	See Note 3
PM <sub>10</sub> ( µg/m <sup>3</sup> )	Annually	See Note 4
<i>Aspergillus fumigatus</i>	Annually	Grab sample <sup>Note 5</sup>
Mesophilic bacteria	Annually	Grab sample <sup>Note 5</sup>

**Note 1:** Standard method VDI2119 (Measurement of Dustfall, Determination of Dustfall using Bergerhoff Instrument (Standard Method) German Engineering Institute). Any modifications to eliminate interference due to algae growth in the gauge should be reported to the Agency.

**Note 2:** Twice during the period May to September.

**Note 3:** To be agreed by the Agency.

**Note 4:** As described in prEN12341 "Air Quality - field test procedure to demonstrate reference equivalence of sampling methods for PM10 fraction of particulate matter" or an alternative agreed in writing by the Agency.

**Note 5:** Enumeration of colonies to be carried out as described in 'Standardised Protocol for the Sampling and Enumeration of Airborne Micro-organisms at composting Facilities' the UK Composting Association 1999.

## D.4 Noise

**Table D.4.1** Noise Monitoring Frequency and Technique

Parameter	Monitoring Frequency	Analysis Method/Technique
L(A) <sub>EQ</sub> [30 minutes]	Quarterly	Standard <sup>Note 1</sup>
L(A) <sub>10</sub> [30 minutes]	Quarterly	Standard <sup>Note 1</sup>
L(A) <sub>90</sub> [30 minutes]	Quarterly	Standard <sup>Note 1</sup>
Frequency Analysis (1/3 Octave band analysis)	Quarterly	Standard <sup>Note 1</sup>

**Note 1:** "International Standards Organisation. ISO 1996. Acoustics - description and Measurement of Environmental noise. Parts 1, 2 and 3."

## D.5 Surface Water, Groundwater and Leachate

**Table D.5.1** Water and Leachate - Parameters / Frequency

<b>PARAMETER</b> <sup>Note 1</sup>	<b>SURFACE WATER</b> <sup>Note 2</sup> <b>Monitoring Frequency</b>	<b>GROUNDWATER</b> <b>Monitoring Frequency</b>	<b>LEACHATE</b> <b>Monitoring Frequency</b>
<b>Visual Inspection/Odour</b> <sup>Note 2</sup>	Weekly	Quarterly	Quarterly
<b>Groundwater Level</b>	Not Applicable	Monthly	Not Applicable
<b>Leachate Level</b>	Not Applicable	Not Applicable	Continuous
<b>Ammoniacal Nitrogen</b>	Quarterly	Quarterly	Annually
<b>BOD</b>	Quarterly	Not Applicable	Annually
<b>COD</b>	Quarterly	Not Applicable	Annually
<b>Chloride</b>	Quarterly	Quarterly	Annually
<b>Dissolved Oxygen</b>	Quarterly	Quarterly	Not Applicable
<b>Dissolved Methane</b>	Not Applicable	Not Applicable	To be agreed
<b>Electrical Conductivity</b>	Quarterly	Quarterly	Annually
<b>Ph</b>	Quarterly	Quarterly	Annually
<b>Total Suspended Solids</b>	Quarterly	Not Applicable	Not Applicable
<b>Temperature</b>	Quarterly	Quarterly	Quarterly
<b>Metals / non metals</b> <sup>Note 3</sup>	Annually	Annually	Annually
<b>Cyanide (Total)</b>	Not Applicable	Annually	Annually
<b>Fluoride</b>	Not Applicable	Annually	Annually
<b>List I/II organic substances</b> <sup>Note 4</sup>	Once off <sup>Note 5</sup>	Annually <sup>Note 5</sup>	Once off <sup>Note 5</sup>
<b>Mercury</b>	Annually	Annually	Annually
<b>Sulphate</b>	Annually	Annually	Annually
<b>Total Alkalinity</b>	Annually	Annually	Not applicable
<b>Total P/orthophosphate</b>	Annually	Annually	Annually
<b>Total Oxidised Nitrogen</b>	Annually	Annually	Annually
<b>Total Organic Carbon</b>	Not Applicable	Quarterly	Not Applicable
<b>Residue on evaporation</b>	Not Applicable	Annually	Not Applicable
<b>Biological Assessment</b>	Annually <sup>Note 6</sup>	Not Applicable	Not Applicable

**Note 1:** All the analysis shall be carried out by a competent laboratory using standard and internationally accepted procedures.

**Note 2:** Where there is evident gross contamination of leachate, additional samples should be analysed.

**Note 3:** Metals and elements to be analysed by AA/ICP should include as a minimum: boron, cadmium, calcium, chromium (total), copper, iron, lead, magnesium, manganese, nickel, potassium, sodium and zinc.

**Note 4:** Samples screened for the presence of organic compounds using Gas Chromatography / Mass Spectrometry (GC/MS) or other appropriate techniques and using the list I/II Substances from EU Directive 76/464/EEC and 80/68/EEC as a guideline. Recommended analytical techniques include: volatiles (US Environmental Protection Agency method 524 or equivalent), semi-volatiles (USEPA method 525 or equivalent, and pesticides (USEPA method 608 or equivalent).

**Note 5:** 2 surface water locations, 3 groundwater locations and 2 leachate locations to be agreed by the Agency for these parameters.

**Note 6:** Appropriate biological methods (such as EPA Q-Rating System) to be used for the assessment of rivers and streams.

## D.6 Meteorological Monitoring

**Table D.6.1** Meteorological Monitoring: at a location on the facility.

Parameter	Monitoring Frequency	Analysis Method/Technique
Precipitation Volume	Daily	Standard
Temperature (min/max.)	Daily	Standard
Wind Force and Direction	Daily	Standard
Evaporation	Daily	Standard
Evapotranspiration <sup>Note 1</sup>	Daily	Standard
Humidity	Daily	Standard
Atmospheric Pressure <sup>Note 1</sup>	Daily	Standard

**Note 1:** Monitoring frequency for these parameters may be decreased with the agreement of the Agency.

## D.7 Landfill Gas Combustion Plant/Enclosed Flare

Location: Utilisation plant and enclosed flare

**Table D.7.1** Landfill Gas Utilisation Plant/Enclosed Flare Parameters and Monitoring Frequency

Parameter	Flare (enclosed) Monitoring Frequency	Utilisation Plant Monitoring Frequency	Analysis Method <sup>Note1</sup> /Technique <sup>Note2</sup>
Inlet			
Methane (CH <sub>4</sub> ) % v/v	Continuous	Weekly	Infrared analyser/flame ionisation detector/thermal conductivity
Carbon dioxide (CO <sub>2</sub> ) % v/v	Continuous	Weekly	Infrared analyser/thermal conductivity
Oxygen (O <sub>2</sub> ) % v/v	Continuous	Weekly	Electrochemical/thermal conductivity
Total Sulphur	Annually	Annually	Ion chromatography
Process Parameters			
Combustion Temperature	Continuous	Quarterly	Temperature Probe/datalogger
Outlet			
CO	Continuous	Continuous	Flue gas analyser/datalogger
Nox	Annually	Annually	Flue gas analyser
SO <sub>2</sub>	Annually	Annually	Flue gas analyser
Particulates	Not applicable	Annually	Isokinetic/Gravimetric
TOC	Annually	Not applicable	Flame ionisation

**Note 1:** All monitoring equipment used should be intrinsically safe.

**Note 2:** Or other methods agreed in advance by the Agency.

### D.8 Monitoring of Emissions to Sewer

Emission Point Reference No.: LTP-3

Location: Treated leachate outlet point.

**Table D.8.1** Sewer Monitoring - Parameters/Frequency

Parameter	Monitoring Frequency	Analysis Method/Technique <sup>Note 1</sup>
<b>Flow</b>	Continuous	Flow meter/recorder
<b>Biochemical Oxygen Demand</b>		Standard Method <sup>Note 1</sup>
<b>Chemical Oxygen Demand</b>		Standard Method <sup>Note 1</sup>
<b>Ammoniacal nitrogen</b>		Standard Method <sup>Note 1</sup>
<b>Nitrate Nitrogen</b>		Standard Method <sup>Note 1</sup>
<b>Alkalinity</b>		Standard Method <sup>Note 1</sup>
<b>Dissolved Methane</b>		Dissolved Methane Probe <sup>Note 1</sup>

**Note 1:** All analyses shall be carried out by a competent laboratory using standard and internationally acceptable techniques.

### D.9 Monitoring of Composting Process

Parameter	Monitoring Frequency	Monitoring equipment/method
<ul style="list-style-type: none"> <li>Composting piles</li> </ul> <i>Temperature vs. time</i>	Continuous	Temperature probe/recorder
<ul style="list-style-type: none"> <li>Compost maturation (curing) piles</li> </ul> <i>Temperature</i>		
<i>Moisture</i>	Daily	Temperature probe
	Daily	Subjective by operator.

### D.10 Air & Odour Monitoring <sup>Note 1</sup>

#### Biofilters

Parameter	Monitoring Frequency	Analysis Method/Technique
<b>Bed Media</b>		
Odour assessment <sup>Note 2</sup>	Daily	Subjective Inspection
Condition and depth of biofilter <sup>Note 3</sup>	Daily	Visual Inspection
Moisture content	Bi-annually	Standard laboratory method
pH	Bi-annually	pH probe
Ammonia	Bi-annually	Standard laboratory method
Total viable counts	Bi-annually	Standard laboratory method
<b>Inlet and Outlet Gas</b>		
Ammonia	Bi-annually	Colourimetric Indicator Tubes
Hydrogen sulphide	Bi-annually	Colourimetric Indicator Tubes
Mercaptans	Bi-annually	Colourimetric Indicator Tubes

**Note 1:** All analyses shall be carried out by a competent laboratory using standard and internationally acceptable techniques. The testing laboratory and the testing technique shall be agreed by the Agency in advance.

**Note 2:** This subjective assessment should be carried out by a staff member immediately upon arriving on-site.

**Note 3:** The biofilter shall be examined to ensure that no channelling is evident, and that moisture content is adequate. Watering, turning, restructuring and the addition of supplementary bed materials, or total bed replacement shall be carried out, as required, subject to bed performance.

## SCHEDULE E : Compost Process Management

**Table E.1 Composting.** During the composting process the entire quantity of biowaste being composted shall be exposed to the following temperature :

Temperature	Treatment time
At least 60°C	1 week

**Table E.2 Category 3 Material.** All Category 3 Animal By-Product Waste shall be exposed to the following processing regime:

Temperature	Particle Size	Treatment Time
70 °C	12 mm <sup>Note 1</sup>	60 minutes

**Note 1:** Unless otherwise agreed by the Agency.

**Table E.3 Process validation.** The composting process shall be tested using the following indicator organism <sup>Note 1</sup>:

Indicator Organism	Frequency
<i>Salmonella spp.</i>	Annually <sup>Note 2</sup>

**Note 1:** Unless otherwise agreed by the Agency.

**Note 2:** This test shall be repeated if major changes to either the composition of the incoming biowaste or the treatment process are made.

## SCHEDULE F : Recording and Reporting to the Agency

Report	Reporting Frequency <sup>Note1</sup>	Report Submission Date
<b>Environmental Management System Updates</b>	Annually	As part of the AER
<b>Annual Environment Report (AER)</b>	Annually	By 31 March of each year.
<b>Record of incidents</b>	As they occur	Within five days of the incident.
<b>Bund, tank and container integrity assessment</b>	Every three years	Six months from the date of grant of licence and every 3 years thereafter as part of the AER
<b>Specified Engineering Works reports</b>	As they arise	Prior to the works commencing.
<b>Monitoring of landfill gas</b>	Quarterly	Ten days after end of the quarter being reported on.
<b>Monitoring of Surface Water Quality</b>	Quarterly	Ten days after end of the quarter being reported on.
<b>Monitoring of Groundwater Quality</b>	Quarterly	Ten days after end of the quarter being reported on.
<b>Monitoring of Leachate</b>	Quarterly	Ten days after end of the quarter being reported on.
<b>Meteorological Monitoring</b>	Annually	As part of the AER
<b>Dust Monitoring</b>	Three times a year	As part of the AER
<b>Noise Monitoring</b>	Quarterly	Ten days after end of the quarter being reported on.
<b>Compost Quality Monitoring</b>	Quarterly	Ten days after end of the quarter being reported on.
<b>PM<sub>10</sub> and Bioaerosol monitoring</b>	Annually	As part of the AER.
<b>Odour assessment and condition and depth of biofilters</b>	Daily	To be recorded by licensee.
<b>Biofilter air monitoring</b>	Biannually	Ten days after end of the period being reported on.
<b>Any other monitoring</b>	As they occur	Within ten days of obtaining results.

**Note 1:** Unless altered at the request of the Agency.

## SCHEDULE G : Compost Quality

Compost shall be deemed unsatisfactory if more than 25% of samples fail the criteria below. No sample shall exceed 1.2 times the quality limit values set.

[The following criteria are deemed a quality standard for the use of compost as a soil improver and should not be deemed as criteria for fertiliser. In addition N, P, K, NH<sub>4</sub>-N, NO<sub>3</sub>-N, pH and dry matter content should also be measured]

### 1. Maturity

The state of the curing pile must be conducive to aerobic biological activity.

Compost shall be deemed to be mature if it meets two of the following groups of requirements:

1. Respiration activity after four days AT<sub>4</sub> is ≤10mg/O<sub>2</sub>/g dry matter or Dynamic Respiration Index is ≤1,000mgO<sub>2</sub>/kg VS/h.

2. Germination of cress (*Lepidium sativum*) seeds and of radish (*Raphanus sativus*) seeds in compost must be greater than 90 percent of the germination rate of the control sample, and the growth rate of plants grown in a mixture of compost and soil must not differ more than 50 percent in comparison with the control sample.

3. Compost must be cured for at least 21 days; and  
Compost will not reheat upon standing to greater than 20°C above ambient temperature.

4. If no other determination of maturity is made, the compost must be cured for a six month period. In addition, offensive odours from the compost shall be minimal for the compost to be deemed mature.

5. Or other maturity tests as may be agreed by the Agency.

### 2. Trace Elements <sup>Note 1/ 2/3</sup>

Maximum Trace Element Concentration Limits for Compost

Parameter (mg/kg, dry mass)	Compost Quality Standards <sup>Note 4</sup>		Stabilised Biowaste
	Class 1	Class 2	
Cadmium (Cd)	0.7	1.5	5
Chromium (Cr)	100	150	600
Copper (Cu)	100	150	600
Mercury (Hg)	0.5	1	5
Nickel (Ni)	50	75	150
Lead (Pb)	100	150	500
Zinc (Zn)	200	400	1500
PolyChlorintated Biphenyls (PCB's)	-	-	0.4
Polynuclear Aromatic Hydrocarbons (PAH's)	-	-	3
Impurities >2mm <sup>Note 5</sup>	<0.5%	<0.5%	<3%
Gravel and Stones >5mm <sup>Note 5</sup>	<5%	<5%	-

**Note 1:** These limits apply to the compost just after the composting phase and prior to mixing with any other materials.

**Note 2:** Incoming sludges shall be monitored quarterly (on a client by client basis) for the parameters outlined in this table.

**Note 3:** These limits alone should not be taken as an indication of suitability for addition to soil as the cumulative metal additions to soil should be first calculated.

**Note 4:** Normalised to 30% organic matter content.

**Note 5:** Compost must not contain any sharp foreign matter measuring over a 2 mm dimension that may cause damage or injury to humans, animals and plants during or resulting from its intended use.

### 3. Pathogens

Pathogenic organism content must not exceed the following limits:

<i>Salmonella sp.</i>	Absent in 50g	n=5
<i>Faecal Coliforms</i>	≤ 1000 Most Probable Number (MPN) in 1g	n=5

Where: n = Number of samples to be tested;

### 4. Monitoring

The licensee shall monitor the compost product at least biannually. The licensee shall submit to the Agency for its agreement, prior to commencement of the composting and/or anaerobic digestion operations, details of the sampling protocol, methods of analyses and sample numbers.



# SCHEDULE H : Content of the Annual Environmental Report

## Annual Environmental Report Content

Reporting Period.

Waste activities carried out at the facility.

Quantity and Composition of waste received, disposed of and recovered during the reporting period and each previous year. This should include a separate section detailing all animal by-product wastes treated.

Calculated remaining capacity of the facility and year in which final capacity is expected to be reached.

Methods of deposition of waste.

Summary report on emissions.

Summary of results and interpretation of environmental monitoring.

Resource and energy consumption summary.

Proposed development of the facility and timescale of such development.

Volume of leachate produced and volume of leachate transported / discharged off-site.

Report on development works undertaken during the reporting period, and a timescale for those proposed during the coming year.

Report on restoration of completed cells/ phases.

Meteorological monitoring.

Dust monitoring.

PM<sub>10</sub> and bio aerosol monitoring.

Site survey showing existing levels of the facility at the end of the reporting period.

Estimated annual and cumulative quantities of landfill gas emitted from the facility.

Estimated annual and cumulative quantity of indirect emissions to groundwater.

Annual water balance calculation and interpretation.

Report on the progress towards achievement of the Environmental Objectives and Targets contained in previous year's report.

Environmental Management System updates

Schedule of Environmental Objectives and Targets for the forthcoming year.

Full title and a written summary of any procedures developed by the licensee in the year which relates to the facility operation.

Tank, pipeline and bund testing and inspection report.

Reported incidents and Complaints summaries.

Review of Nuisance Controls.

Reports on financial provision made under this licence, management and staffing structure of the facility, and a programme for public information.

Report on training of staff.

Any other items specified by the Agency.

Sealed by the seal of the Agency on this the 10th day of December, 2004

PRESENT when the seal of the Agency  
was affixed hereto:

---

Padraic Larkin, **Director/Authorised Person**

