

## ATTACHMENT NO. 7

### PROCESS CONTROL SYSTEM

For inspection purposes only.  
Consent of copyright owner required for any other use.



Mooresfort,  
Lattin,  
Co Tipperary,  
**Tel 062 55385**  
**Fax 062 55483**  
E-mail [NRGE@iol.ie](mailto:NRGE@iol.ie)

## SCADA Description

Project No.:

Made by: M Mc Eniry

Issued: 13<sup>th</sup> March 2008

For inspection purposes only.  
Consent of copyright owner required for any other use.

## Contents

1 Description .....	3
1.1 Installations .....	3
1.1.2 Electrical Switchboards and Installations .....	3
1.2 SCADA System .....	4
1.2.1 System Software .....	5
1.2.2 User Interface.....	5
1.2.3 Curves .....	5
1.2.4 Reporting.....	6
1.2.5 Handling of Alarms .....	6
1.2.6 Equipment for Main Station and Operator Station.....	6
1.2.7 IGSS Software.....	6
1.2.8 IGSS Introduction .....	6
1.2.9 Data Exchange.....	7
1.2.10 Scaling.....	7
1.2.11 Alarm Function .....	7
1.2.12 Login Safety System.....	7
2 Layout of pictures.....	8
2.1 Overall View.....	8
2.2 Biogas Plant .....	9
2.3 Operation Parameters 1 .....	10
2.4 Operation Parameters 2 .....	11
2.5 Summing Up.....	12
2.6 Operation Hours and Starts 1+2.....	13
2.7 Heating Module.....	15
2.8 Gas Blower Controller.....	16
2.9 Controller for Oxygen Dosing Blower .....	17
2.10 Controller for Heating Valve on Heating Module .....	18
2.11 Gas Engine .....	19
2.12 Service .....	20
2.13 Batch Reports .....	21

Consent of Food inspection purposes only:  
Copyright owner required for any other use:

# 1 Description

This material describes the SCADA-structure of a biogas plant. The scope of supply and interfaces are described in the quotation. This material is not part of an offer and is not a description of the scope of supply, but it only information to support the plant description.

## 1.1 Installations

### 1.1.1.1 Instrumentation

Instrumentation is delivered according to the flow charts and this description.

Flow and energy meters are mounted with flow distances in accordance with the directions of the supplier.

All instruments, machinery, etc. located in gas classified areas are delivered with approval and are mounted in accordance with the valid rules for this.

Gas blowers are frequency controlled and delivered as gastight blowers.

Temperature transmitters are mounted in sleeves welded on the tubes in lengths corresponding to the insulation thickness.

Pressure transmitters (liquid systems) are mounted on pressure gauge pipes for pressure relief and constant liquid column.

Pressure gauges are glycerine filled (e.g. disc diameter 100 mm, 0-10 bar, ½" pipe thread). A shut-off valve is mounted in front of all pressure gauges.

Thermometers (disc diameter 100 mm, 0-200°C) are mounted with pockets.

All indicating instruments will be located in positions, which can easily be read from the floor.

All pressure switches and thermostats, etc., which are to be operated, are mounted in a height suitable for operation.

### 1.1.2 Electrical Switchboards and Installations

#### 1.1.2.1 Panels

A main distribution switchboard with a field for power meter is installed. Switchboards and control panels for gas engine, boiler and auxiliary equipment are installed.

Panels for receiving station, healing modules and biogas part are installed.

The distribution panel is designed according to EN 60 439-1 and 439-3, while panels and switchboard for the machinery is designed according to EN 60 204-1.

Panels located in panel / control room are supplied in IP41, while panels for location in machinery plant are supplied in IP44.

The SCADA system is made with functions for automatic and manual operation of each motor starter.

PLC equipment is mounted in separate panel field and I/O' for instrumentation is connected in terminals.

Frequency converters are normally located outside the panels.

Standard components of Western European quality are used in the panel and for machinery components.

#### 1.1.2.2 Electrical installations

Electrical installations are performed for the machinery plant.

All other installations such as internal supply cable and medium voltage cable between middle voltage switchboard plants are purchased/Performed by the Client.

Electricity for machinery and buildings shall be installed in separate cable trays.

Cable trays are supplied in materials suitable for mounting in the specific environment.

All cables from cable trays to electronic components are located either in a pipe or a flexible cable. Alternatively, strips are used.

Cables in the terrain buried directly in the ground.

## 1.2 SCADA System


The SCADA system is based on the make IGSS from Seven Technologies A/S.

IGSS is running on a standard PC with Windows XP. IGSS is constantly developed and thus fulfil all requirements regarding openness in relation to data exchange with other PC based systems. The system is designed with one main station and one operator station in the control room. The software is installed on standard PC according to present standard.

The quotation also includes a standard modular PLC system of make as Siemens S7-300 series. The PLC can be programmed in both off-line and on-line mode, and programming is performed through a program designed in accordance with approved IEC norm. It is possible to program the PLCs locally or through a modem.

As shown on the below diagram of the design of the SCADA system, a service modem is installed. This modem serves two purposes: Service and remote monitoring in connection with ordinary service, remote user instruction, updates, etc. and for remote plant operation by the operating crew on duty.

UPS is installed for supply of PLC and PC with a capacity of 10 minutes of battery operation. The figure below shows an example of the configuration for a biogas plant.



### 1.2.1 System Software

The operating system is Windows XP. IGSS software is supplied in a runtime version.

### 1.2.2 User Interface

The user interface is an industry standard user interface with symbols for valves, engines, instrumentation, etc. The system is designed with clear screen pictures which make it possible for the operating crew to get a quick overview of each part of the plant with regard to reading of dynamic values, functionality and operator possibilities. P&I diagrams are used as a starting points for the screen pictures for each section. The system is built up as a function hierachic system.

The SCADA system is secured against unintentional changes of e.g. set points and against operating errors by means of personal passwords, which give access to defined user and operation levels.

The interface is designed in a logic way with icons and general menus in order to secure a constant overview of the present operation condition of the plant.

The system is designed as an object orientated system with TAG numbers. An object is e.g. a pump, a blower, a pump or a valve.

### 1.2.3 Curves

The system is designed with a number of fixed curves. However, it is very easy for the operator to set up individual curves with up to 5 analogue values at the time. The values can be selected from a

list or pointed out by means of the mouse on the screen. Zooming is easily made by means of the mouse directly on the curve picture.

#### 1.2.4 Reporting

Reports and curves are made on the basis of a proposal, which is forwarded to the Client for approval. Reports can be printed both automatically and upon request.

#### 1.2.5 Handling of Alarms

Alarms are presented on the screen and on the alarm printer. The system is designed with the necessary safety circuits hard-wired to the safety relays, in order to ensure that a stop of the plant due to disconnection of a safety component requires manual reset of the safety relay on the panel front. Alarms are registered on the system with time stamping for both on and off acknowledgement of alarms. The alarms can be divided into several levels.

#### 1.2.6 Equipment for Main Station and Operator Station

The quotation includes two of the below PC's. The hardware is specified at the time of purchase as the development within PCs constantly moves performance in relation to price. Therefore, the specification below is intended as an indication only. One of the computers will be equipped with a modem to enable remote control by the personnel on duty.

Hardware : 2 GHz Intel Pentium 4 CPU, 512 MB RAM, 80 GB hard disc, CD-RW, 20" screen, key board and mouse, net card  
Printer: Inkjet printer  
Software: Windows XP

#### 1.2.7 IGSS Software

The SCADA software is Windows based and is a complete system for data acquisition, storage and calculation of derived values for data from the substations. The quotation is based on IGSS SCADA software from seven - Technologies for main station and operator stations. Xergi has installed IGSS SCADA software on energy plants since 1992 and thus holds extensive knowledge of this system.

The basis of the software is a reliable data acquisition, safe storage of data and functions relevant for handling of the connected substations.

#### 1.2.8 IGSS Introduction

IGSS is a SCADA system used for monitoring and controlling processes. IGSS is used within a wide range of areas including water supply, heat supply, food industry and railway security. More than 25,000 licenses have been sold since the system was first launched in 1984.

IGSS is an object orientated program. This gives a number of useful advantages for the system designer and the operator. The most important feature of the system is that a process component consisting of a number of I/O points is treated as an individual object in IGSS. This means that the system designer and operator has the same understanding of an object and that the characteristics of the object can be seen and adjusted from one dialogue box. Types and templates are other expressions used in IGSS. Templates are useful for the system designer in the way that he can define

one template than the base as many objects with identical characteristics on this template as required.

### 1.2.9 Data Exchange

Openness is one of the cornerstones in the IGSS system. Therefore, IGSS supports many different standards, including DDE, ODBC, OPC, OLE Automation and ActiveX. This makes it possible to extend IGSS data with 3<sup>rd</sup> party programs. If a large configuration is to be made, it may be required to define the process components in an external data base and then import the data to IGSS.

### 1.2.10 Scaling

The possibility of scaling is a key function in IGSS. As the system is based on a genuine client/server architecture, it is easy to increase the number of operator stations or the number of objects in the configuration. If the company covers a large area, remote operator station can be connected by means of dial-up lines or directly on LAN.

When choosing IGSS it is necessary to acquire the number of objects and operator stations required at present. The number of objects and operator stations can be increased at any time if required.

### 1.2.11 Alarm Function

The system includes a conventional alarm list in which all alarms are presented with identification, etc. The alarm list icon is always visible and the alarm list can be called up from all screen pictures when activating the icon. Notification is given on all incoming alarms, no matter where the operator is working in the program; an alarm remains on the screen until they have been signed for. All alarms can be printed.

### 1.2.12 Login Safety System

The system is secured with a login procedure controlling rights for operation in the system by means of login name and password.

For inspection purposes only.  
Consent of copyright owner required for any other use

## 2 Layout of pictures

In the following you see different pictures from a typical Biogas Plant.

### 2.1 Overall View




Figure 1 Overall View

## 2.2 Biogas Plant




Figure 2 Biogas Plant

## 2.3 Operation Parameters 1

The screenshot shows a software application window titled "foss Überwachung" with a sub-tab "Betriebsparameter 1". The main content is a table of operational parameters:

Kategorie	Parameter	Wert	Einheit
		Start	Stop
Signale zum Gasmotor	Freigabe Gasmotor, Gas Niveaumessung	80.0 %	40.0 %
	Freigabe Gasfackel, Gas Niveaumessung	98.0 %	96.0 %
Mischbehälter	Rührwerk 1 Laufzeit	80 min	29 min
	Rührwerk 1 Pausenzeit	43 min	0 min
Rührwerk 2	Rührwerk 2 Laufzeit	60 min	28 min
	Rührwerk 2 Pausenzeit	43 min	0 min
Bierektorkomplex	Rührwerk vorwärts Laufzeit	210 min	0 min
	Mixer Verlauf Pausenzeit	0 min	0 min
Rührwerk rückwärts	Rührwerk rückwärts Laufzeit	8 min	0 min
	Mixer rückwärts Pausenzeit	280 min	121 min
Reinigung transmitter H1bPT2	Öffnungszeit	30 sek	0 sek
	Pausenzeit	720.0 h	145.2 h
Top Rührwerk	Laufzeit	30 min	0 min
	Verlauf Pausenzeit	30 min	0 min
Top Rührwerk stop delay after filling			
Entlaugen über H1bPUS und H1bMV2			
Zeit zwischen Entlaeungen	Entlaeren zu	30 min	19 min
	1530 cm		


Below the table, there is a footer row with columns for Objekttyp, Bereich, Objektname, Objektwert, and Objektbeschreibung. A red watermark "For inspection purposes only. Consent of copyright owner required for any other use." is diagonally across the table area. The bottom right corner shows the date "14.06.2006 13:38:38".

Fig. 3 Operation Parameters 1

## 2.4 Operation Parameters 2

Figure 4 Operation Parameters 2

## 2.5 Summing Up



## Figure 5 Summing Up

For inspection purposes only,  
Consent of copyright owner required for any other use.

## 2.6 Operation Hours and Starts 1+2

Figure 6.1 Operation Hours and Starts 1

and Starts 1  
Consent of copyright owner required for any other use.




Figure 6.2 Operation Hours and Starts 2

10/1/2017  
and Starts 2  
For inspection purposes only.  
Consent of copyright owner required for any other use.

## 2.7 Heating Module

**FCCS Overheadline**

Daten Bearbeiten Ansicht Anwendungsprogramme Bereich Diagramm Kurve Optionen Fenster Hilfe

Aktuelle / letzte Mischung

Gemeinschaftsdaten	Aktuell	Rezeptdaten	Rezept	Mischung
Start Tageszyklus Zeit	12.30	13.39	Rezeptnr.	1
Anzahl Misch. Rezept 1	14	0	Mischungen ID	2009
Anzahl Misch. Rezept 2	0	0	Rühren im Mischtank	0 min
Anzahl Misch. Rezept 3	0	0	Güle vom Mischtank	7561 kg
Rühren bei Leerung	Ja		Güle vom Reaktor	0 kg
Schneiden bei Leerung	Ja		Aufwärmzeit	2 min
Temp. SP reaktor	48.0 °C	48.5 °C	Entfeerung zu	200 kg
Temp. SP Erw. max	50.0 °C		Min Rezeptzeit	102 min
Temp. SP Erw. min	40.0 °C		Rühren Erw.modul	120 min
Temp. SP Erw. fließend	43.0 °C	44.0 °C	Zerkl.Zeit Erw. Modul	120 min
Temp. SP Erw. fest	52.0 °C		Mischung Startzeit	12:30 14-08-06
Temp. SP , Wahl	Fließend		Mischung Stopzeit	0:00 00-00-00
Freig. Wärme.	2200 kg			
Freig. Zerk.	1200 kg			
Freig. RÜhrw.	2200 kg			
Menge Erw.modul	7101 kg			

SP\_TErw = SP\_Treaktor + 10 x (SP\_Treaktor - Treaktor)

**Sequenz**

- Tageszyklus läuft
- Warten 30 sek bis zur nächsten
- Start neue Mischung
- Rühren Mischtank
- Tara
- Einpumpen Güle vom Mischtank
- Tara Güle vom Mischtank
- Einpumpen Güle vom Reaktor
- Warten auf Temp.Setpoint
- Erwärmen in Zeit
- Entfeeren
- Warte auf min. Rezeptzeit
- Ende Mischung

Sequenz

**rezepte**

Rezeptnr.	1	2	3
Rühren im Mischtank	0 min	0 min	0 min
Güle vom Mischtank	7500 kg	0 kg	0 kg
Güle von Reaktor (Rezirk.)	0 kg	0 kg	0 kg
Aufwärmzeit	2 min	0 min	0 min
Ausleeren nach	200 kg	0 kg	0 kg
Minimum Rezeptzeit	102 min	0 min	0 min
Rühren Erw. Modul	120 min	0 min	0 min
Zerkl.Erwärmungsmodul	120 min	0 min	0 min

④ Fehlereingabe Rezept 1-3, Menge zu groß  
④ Fehlereingabe aktuelles Rezept, Mengen zu groß

Hilfe über die F1-Taste

T+06-2006 13:39:53

Figure 7 Heating Module

## 2.8 Gas Blower Controller




Figure 8 Gas Blower Controller

## 2.9 Controller for Oxygen Dosing Blower




Figure 9 Controller for Oxygen Dosing Blower

## 2.10 Controller for Heating Valve on Heating Module




Figure 10 Controller for Heating Valve

## 2.11 Gas Engine




Figure 11 Gas Engine

## 2.12 Service




Figure 12 Service

## 2.13 Batch Reports

The screenshot shows a software application window titled 'Batch Report - [Biogas anlage]'. The menu bar includes 'File', 'Bediener', 'Indset', 'Poster', 'Vindue', and 'Hjælp'. The title bar has standard window controls. The main area is titled 'Mischung Berichte' and contains a table with two rows of data. The table columns are: Misch. ID, Rezeptnr., Misch.beh. [m3], Reaktor [m3], Erw.SP [°C], Misch.zeit [Min], Enl. zu [kg], Startzeit, and Stopzeit. The data rows are:

Misch. ID	Rezeptnr.	Misch.beh. [m3]	Reaktor [m3]	Erw.SP [°C]	Misch.zeit [Min]	Enl. zu [kg]	Startzeit	Stopzeit
312	1	8000	0	50,3	50,3	352	17-02-2006 15:39:00	17-02-2006 18:19:00
317	1	7989	0	50,8	50,8	350	17-02-2006 18:20:00	17-02-2006 20:55:00

At the bottom left, there is a note: 'Receive settlement No'. On the right side, there is a logo for 'xergi' with a stylized 'X' icon. The bottom right corner of the window has scroll bars.

Figure 13.1 Overall View of Batch Reports

For inspection purposes only.  
Consent of copyright owner required for any other use.

Für Vertrieb und  
Verarbeitung

Emerald Irish Park, Biogasanlage  
Mischung Berichts

Mischung ID	317
Rezeptnr.	1
Güte vom Mischtank	7989 kg
Güte vom Reaktor	0 kg
Erwärmungs setpoint	50,8 °C
Aufwärmzeit	5 min
Mischung zeit	130 min
Entfernung zu	350 kg
Rührzeit Mischtank	10 min
Rührzeit Erwärmungsmodul	120 min
Zerkleinerungszeit Erwärmungsmodul	112 min
Mischung Startzeit	17-02-2006 18:20:00
Mischung Stopzeit	17-02-2006 20:55:00

Printed on: 22.01.2008 13:32:29

Sieb Test 1

For inspection purposes only.  
Consent of copyright owner required for any other use.

Figure 13.2 Example of Batch Report

## ATTACHMENT NO. 8

### TRAFFIC ASSESSMENT BY M & J MCENIRY ENGINEERS

For inspection purposes only:  
Consent of copyright owner required for any other use.

**Assessment of Sightlines at the entrance to  
Woodville Pig Farm,  
Woodville,  
Ballymackey,  
Nenagh**

For inspection purposes only.  
Consent of copyright owner required for any other use.



**Mooresfort  
Lattin,  
Co Tipperary,  
Tel 062 55385**

**Fax 062 55483**

**E-mail [NRGE@iol.ie](mailto:NRGE@iol.ie)**

## **Introduction**

An assessment of the entrance to the Pig Breeding Unit at Woodville Ballymackey Nenagh was made in May 2009 in order to ascertain that adequate sight lines were available to support the Planning application to construct A new loose dry Sow House, which is required for animal welfare regulation compliance and Staff service building with office, canteen, shower facilities, and associated site works.

## **Existing Situation.**

The entrance to the Pig Breeding Unit is currently located at the Eastern extremity of the site's Road Frontage. The entrance is 10m wide opening onto the Public road which is 5m wide at their intersection. The entrance abuts the front boundary wall of the adjoining dwelling which is situated 0.6m back from the road carriageway. The boundary wall is overhung by mature screening hedge approximately 3.5m tall. This slightly restricts the visibility to the east (Left) when exiting from the farmyard. The adjoining Dwelling to the West of the farmyard is setback over 2m from the road carriageway. The current entrance location is on the crest of a slight incline on the road. The road Speed limit is 80Km/Hr. The road is straight for more than 300m in both directions from the entrance, the photos attached in appendix 1 show there are unobstructed views of more than 300m at the entrance in both directions.

*For inspection purposes only  
Consent of copyright owner required for any other use*

## **Proposed Improvements**

In order to improve the sightlines is necessary to relocate the point of access from the farmyard to the Public approximately 30m to the West of its current location. The existing Hedgerow would be removed and relocated 2.3m back from its current location at the site boundaries and Drawing No 007 attached,

this will achieve a horizontal sightline of 160m in both directions. The reconstructed roadside boundary will be screen planted in the first growing season after the entrance has been reconstructed. The relocated entrance is down the incline. The crest of the incline will now be located 30m east of the entrance the Vertical alignment in the attached Drawing No007 shows that the crest does not impede the sightlines. It must highlighted that the vertical alignment is further improved from a commercial or agricultural vehicle because of the higher vantage point approximately 2.0m above ground level than that from a car 1.15m this is also demonstrated on Drawing No 007.

The desirable Stopping Distances for a vehicle travelling at 85Km/hr as per Table 3, Design Speed Related Parameters NRA TD 9/00 is 160m this can be achieved at the realigned entrance.

## Conclusion

In our opinion sightlines in excess of 160m can be achieved at the realigned entrance

J. McEniry

BE MIEI

NRGE LTD.

For inspection purposes only.  
Consent of copyright owner required for any other use.

## Appendix 1


### Photos



View West from Current Entrance



View East from Current Entrance



View Travelling East 300m from Current Entrance



View Travelling East 100m from Current Entrance



View Travelling East at the proposed Entrance




View Travelling West 300m from Current Entrance



View Travelling West 200m from Current Entrance



View Travelling West 150m from Current Entrance



View Travelling West 100m from Current Entrance



View Travelling West at the Current Entrance

For inspection purposes only  
Consent of copyright owner required for any other use.

