

Accreditation Certificate

Cork County Council

Wastewater Testing Laboratory, Inniscarra, Co. Cork

Testing Laboratory

Registration number: 016T

is accredited by the Irish National Accreditation Board (INAB) to undertake testing as detailed in the Schedule bearing the Registration Number detailed above, in compliance with the International Standard ISO/IEC 17025:2005 2nd Edition "General Requirements for the Competence of Testing and Calibration Laboratories" (This Certificate must be regal in conjunction with the Annexed Schedule of Accreditation)

Date of award of accreditation: 01:10:2002

Date of last renewal of accreditation: 20:09:2007

Expiry date of this certificate of accreditation: 20:09:2012

This Accreditation shall remain in force until further notice subject to continuing compliance with INAB accreditation criteria, ISO/IEC 17025 and any further requirements specified by the Irish National Accreditation Board.

Manager: Jom Domphey

Mr Tom Dempsey

Chairperson:


D. 11/1... W. L.L.

Issued on 20th September 2007

Organisations are subject to annual surveillance and are re-assessed every five years. The renewal date on this Certificate confirms the latest date of renewal of accreditation. To confirm the validity of this Certificate, please contact the Irish National Accreditation Board.

The INAB is a signatory of the European co-operation for Accreditation (EA) Testing Multilateral Agreement (MLA) and the International Laboratory Accreditation Cooperation (ILAC) Mutual Recognition Arrangement.

Wilton Park House, Wilton Place, Dublin 2, Ireland. Tel +353 1 607 3003 Fax +353 1 607 3109 E-mail inab@inab.ie Web www.inab.ie



Tel +353 1 607 3003 Fax +353 1 607 3109

Schedule of Accreditation



(Annex to Accreditation Certificate)

Permanent Laboratory: Category A

CORK COUNTY COUNCIL

Chemistry Testing Laboratory

Initial Registration Date : 25-April-1991

iton purposes only any other use. Waste Water Laboratory Postal Address:

Inniscarra 🞺 (Address of other locations

Co. Cork as they apply) +353 (24) 4532700 Telephone:

+353 (21) 4532777 Fax:

E-mail:

Contact Name: Ms M Cherry

Facilities: Normally not available for Public testing



Wilton Park House, Wilton Place, Dublin 2, Ireland Tel +353 1 607 3003 Fax +353 1 607 3109 E-mail inab@inab.ie Web www.inab.ie

Schedule of Accreditation



Permanent Laboratory: Category A

THE IRISH NATIONAL ACCREDITATION BOARD (INAB) is the Irish body for the accreditation of organisations including laboratories.

Laboratory accreditation is available to testing and calibration facilities operated by manufacturing organisations, government departments, educational institutions and commercial testing/calibration services. Indeed, any organisation involved in testing, measurement or calibration in any area of technology can seek accreditation for the work it is undertaking.

Each accredited laboratory has been assessed by skilled specialist assessors and found to meet criteria which are in compliance with ISO/IEC 17025 or ISO/IEC 15189 (medical laboratories). Frequent audits, together with periodic inter-laboratory test programmes, ensure that these standards of operation are maintained.

Testing and Calibration Categories:

Category A: Permanent laboratory calibration and testing where the laboratory is erected on a fixed

location for a period expected to be greater than three years.

Category B: Site calibration and testing that is performed by staff sent out on site by a permanent

laboratory that is accredited by the Irish National Accreditation Board.

Category C: Site calibration and esting that is performed in a site/mobile laboratory or by staff sent

out by such a laboratory, the operation of which is the responsibility of a permanent

laboratory accredited by the Irish National Accreditation Board.

Category D: Site calibration and testing that is performed on site by individuals and organisations that

do not have a permanent calibration/testing laboratory. Testing may be performed using

(a) portable test equipment

(b) a site laboratory

(c) a mobile laboratory or

equipment from a mobile or site laboratory

Standard Specification or Test Procedure Used:

The standard specification or test procedure that is accredited is the issue that is current on the date of the most recent visit, unless otherwise stated.

Glossary of Terms

Facilities:

Public calibration/testing service: Commercial operations which actively seek work from others.

Conditionally available for public Established for another primary purpose but, more commonly than not,

calibration/testing: is available for outside work.

Normally not available for public Unavailable for public calibration/testing more often than not.

calibration/testing:

Laboratory users wishing to obtain assurance that calibration or test results are reliable and carried out to the Irish National Accreditation Board criteria should insist on receiving an accredited calibration certificate or test report. Users should contact the laboratory directly to ensure that this scope of accreditation is current. INAB will, on request, verify the status and scope.



Cork County Council

Chemical Testing Laboratory

Permanent Laboratory: Category A

| INAB Classification number (P9) Materials/products tested | | Type of test/properties measured Range of measurement | Standard specifications Equipment/techniques used | |
|---|------------------------------|--|---|--|
| 766 | Waters | Chemical analysis: | Documented in-house methods based on Standard Methods for the Examination of Water | |
| .01 | Waters for domestic purposes | Biochemical Oxygen Demand | & Wastewater 21 st Edition APHA (See Note 1) | |
| | Surface and ground waters | 2 - 145,000 mg/l | No. 1 membrane electrode | |
| | | Chloride 5 - 1,000 mg/l Speciforn Purple Reliable Speciforn Purple Relia | CP No. 7 Argentometric method | |
| | | Biochemical Oxygen Demand 2 - 145,000 mg/l Chloride 5 - 1,000 mg/l ph 2 - 12 Consent of copyright owner resulting for the copyright owne | CP No. 5 Electrometry | |
| | | Suspended Solids 0.5 - 17,500 mg/l | CP No. 3 Gravimetric | |
| | | Chemical Oxygen Demand 21 - 135 mg/l 120 - 670,000 mg/l | CP No. 6 Reflux - colourmetric method | |
| | | Total phosphorus 0.2 - 5,300 mg/l | US-EPA Approved method/HACH Method CP No.20 | |
| | | Ammonia 0.1 - 1,000 mg/l NH ₃ - N | Documented in-house method CP22 by Konelab based on Method for the Examination of Waters and Associated Material HMSO:1981 | |



Cork County Council

Chemical Testing Laboratory

Permanent Laboratory:
Category A

| Waters Waters for domestic purposes | Orthophosphate as P (Konelab) | |
|-------------------------------------|--|---|
| domestic purposes | Orthophosphate as P (Konelab) | |
| | B 0.005 4.00 0.004.04 | CP No. 23 Ascorbic Acid Method |
| | Range: 0.005-1.00 mg O-PO4 P/L | A 115°C. |
| Surface and ground waters | High Range: 1000 mg O-P04 P/L Method Detection Limit: 0.02 mg O-P04 P/L | other tise. |
| | Chloride (Konelab) Range: 25-250 mg/L Cl- High Range Conc.: 88,000 mg/L Cl- Method Detection Lamit: 25 mg/L Cl- | CP No. 24 Ferricyanide Method |
| | Sulphate (Ronelab) | CP No. 25 Documented in-house method by |
| | Range: 30-250 mg/L SO4/L | Konelab based on method for the examination |
| | High Range Conc.: 35,000 mg/L SO4/L | of waters and waste waters and associated |
| | Method Detection Limit: 30 mg SO4/L | material HMSO: 1981 |
| | | |
| | | |
| | | Sulphate (Ronelab) Range: 30-250 mg/L SO4/L High Range Conc.: 35,000 mg/L SO4/L |



Cork County Council

Permanent Laboratory: Category A

Chemical Testing Laboratory

| INAB Classification number (P9) Materials/products tested | | Type of test/properties measured Range of measurement | Standard specifications Equipment/techniques used | |
|---|--|--|--|--|
| 766 | Waters | Chemical analysis | Documented in-house methods based on Standard Methods for the Examination of Water& | |
| .05 | Trade Wastes Industrial effluents Urban Wastewater | Biochemical Oxygen Demand 2 - 145,000 mg/l | Wastewater 21 st Edition APHA (See Note 1) | |
| | Municipal Wastewater | Chloride 5 - 1,000 mg/l September 1,000 mg/l | CP No. 7 Argentometric method | |
| | | Biochemical Oxygen Demand 2 - 145,000 mg/l Chloride 5 - 1,000 mg/l pH 2 - 12 Consent of contribution with the contribution of the contributi | CP No. 5 Electrometry | |
| | | Suspended Solids 0.5 - 17,500 mg/l | CP No. 3 Gravimetric | |
| | | Chemical Oxygen Demand 21 - 135 mg/l 120 - 670,000 mg/l | CP No. 6 Reflux - colourmetric method | |
| | | Total phosphorus 0.2 - 5,300 mg/l | US-EPA Approved method/HACH Method CP No.20 | |
| | | Ammonia 0.1 - 1,000 mg/l NH3-N | Documented in-house method CP22 by Konelab based on Method for the Examination of Waters and Associated Material HMSO: 1981. | |

Notes 1. APHA American Public Health Association, USA, 21st Edition



Cork County Council

Permanent Laboratory: Category A

Chemical Testing Laboratory

| INAB Classification number (P9) Materials/products tested | | Type of test/properties measured Range of measurement | Standard specifications Equipment/techniques used | |
|---|---|--|---|--|
| 766 | Waters | Chemical analysis | Documented in-house methods based on Standard Methods for the Examination of Water& | |
| .05 | Trade Wastes Industrial effluents Urban Wastewater Municipal Wastewater | or its different to the state of the state o | Wastewater 21 st Edition APHA (See Note 1) CP. 1 Membrane electrode | |
| | | Orthophosphate as P (Konelab) edited Range: 0.005 - 1.00 mg of P04 P/L High Range: 1000 mg of P04 P/L Method Detection Primit: 0.02 mg O-P04 P/L Consenses | CP No. 23 Ascorbic Acid Method | |
| | | Chloride (Konelab) Range: 25-250 mg/L Cl- High Range Conc.: 86,600 mg /L Cl- Method Detection Limit: 25mg / L Cl- | CP No. 24 Ferricyanide Method | |
| | | Sulphate (Konelab)) Range: 30-250 mg/L SO4 /L High Range Conc.: 35,000 mg/L SO4 /L Method Detection Limit: 30 mg SO4 /L | CP No. 25 Documented in-house method by Konelab based on method for the examination of waters and waste waters and associated material HMSO: 1981 | |

Notes 1. APHA American Public Health Association, USA, 21st Edition

| PT_CD | PT_TYPE | MON_TYPE | EASTING | NORTHING | VERIFIED |
|----------------|---------|----------------------|--|----------|----------|
| Sw01 | Primary | Sampling Sampling | 154840 | 69023 | |
| SW01u | u/s | Sampling | 154678 | 68659 | |
| SW01u SW01d | d/s | Sampling | 154936 | 69981 | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | .©. | | |
| | | | tice of the control o | | |
| | | | - Alle | | |
| | | | 1823 Stay | | |
| | | | S C KOT | | |
| | | | and street | | |
| | | | Lan Can | | |
| | | | | | |
| | | | .059 LOW | | |
| | | 4 | of the | | |
| | | Cancert of | Col. | | |
| | | X.O | | | |
| | | 31501 | | | |
| | | 0 | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

| Sample Date | 15/01/2009 | 15/01/2009 | 15/01/2009 | 15/01/2009 |
|--------------------------|--------------|--------------|------------|---------------------------|
| Sample | Influent | Effluent | Upstream | Downstream |
| Sample Code | GT054 | GT053 | GT055 | GT056 |
| Flow M ³ /Day | * | * | * | * |
| рН | 7.2 | 7.6 | 7.6 | 7.7 |
| Temperature ℃ | * | * | * | * |
| Cond 20°C | 489 | 438 | 200 | 199 |
| SS mg/L | 47 | 77 | 12 | 19 |
| NH ₃ mg/L | 4.9 | 4.9 | <0.1 | <0.1 |
| BOD mg/L | 46 | 32 | <1.0 | <1.0 |
| COD mg/L | 155 | 78 | <21 | <21 |
| TN mg/L | 6.3 | 7.8 | 3.6 | 3.7 |
| Nitrite mg/L | 0.188 | 0.231 | 0.0241 | 0.0121 |
| Nitrate mg/L | 4.78 | 4.29 | 3.25 | 3.09 |
| TP mg/L | 3.8 | 3.4 | <0.20 | <0.20 |
| O-PO4-P mg/L | 0.92 | 0.86 | 0.05 | <0.05 |
| SO4 mg/L | <30 | 30 | <30 | <30 |
| Phenols μg/L | <0.10 | <0.10 | <0.10 | <0.10 |
| Atrazine μg/L | <0.01 | <0.01 | <0.01 | <0.01 |
| Dichloromethane μg/L | <1 | <1 | <1 | <1 |
| Simazine μg/L | <0.01 | <0.1 | <0.01 | <0.01 |
| Toluene μg/L | <1 | <1 | <1 | 10.851 |
| Tributyltin μg/L | not required | not required | * | 10.851 * <1 <0.96 <20 |
| Xylenes μg/L | <1 | <1 | <1 | <1 |
| Arsenic μg/L | < 0.96 | < 0.96 | <0.96 | <0.96 |
| Chromium ug/L | <20 | <20 | <20 | <20 |
| Copper ug/L | <20 | <20 | <20 | <20 \17.311 |
| Cyanide μg/L | <5 | 9 | <5 | <5 FO 1917 |
| Fluoride μg/L | 108 | 86 | 50 | 42 & |
| Lead ug/L | <20 | <20 | <20 | <20 |
| Nickel ug/L | <20 | <20 | <20 | €20 |
| Zinc ug/L | <20 | <20 | <20 | <20 |
| Boron ug/L | <20 | <20 | <20 | <20 |
| Cadmium ug/L | <20 | <20 | <20 | <20 |
| Mercury μg/L | <0.2 | <0.2 | <0.2 | <0.2 |
| Selenium µg/L | 1.5 | <0.74 | <0.74 | <0.74 |
| Barium ug/L | <20 | <20 | 36 | 29 |