



Clare County Council

Tradaree Point Sludge Disposal Facility

Annual Environmental Report 2012

Waste Licence Reg. No. W0037-01

Response Group

23rd May 2013



REPORT CONTROL

| Documer | nt: Trada | Tradaree Point Annual Environmental Report 2012 | | | |
|-----------|---|---|--|-------------------|--|
| Job Numl | ber: CE084 | 478 | | | |
| Project: | Trada | ree Point Sludge Disposal Facility | | | |
| Client: | Clare | e County Council | | | |
| | | | | | |
| D | Chaaliaa | | | | |
| Documer | Document Checking: | | | | |
| Primary A | Primary Author: Paul O Keeffe Initialled: | | | | |
| | | | | | |
| Reviewed | Reviewed By: Ailish Johnston Initialled: | | | | |
| | | | | | |
| | | | | | |
| Issue | Date | Status | | Checked for Issue | |
| 1 | 23/05/13 | For Issue | | NR | |
| 2 | | | | | |



| Co | n | te | n | ts |
|----|---|----|---|----|
|----|---|----|---|----|

| 1.0 | INTRO | DUCTION | N | 5 |
|-----|-------|-----------|--|----|
| | 1.1 | BACKGF | ROUND | 5 |
| | 1.2 | REPORT | TING PERIOD | 5 |
| | 1.3 | SITE DE | SCRIPTION | 5 |
| | 1.4 | FACILIT | Y LAYOUT | 6 |
| 2.0 | FACIL | ITY INFRA | STRUCTURE AND OPERATION | 7 |
| | 2.1 | WASTE | ACTIVITIES CARRIED OUT AT THE FACILITY | 7 |
| | 2.2 | METHO | DS OF DEPOSITION OF SLUDGE | 8 |
| | 2.3 | QUANT | ITY AND COMPOSITION OF SLUDGE DISPOSED | 9 |
| | | 2.3.1 | Sludge Disposed 2012 | 9 |
| | | 2.3.2 | Sludge Disposed 2004-2012 | 9 |
| | 2.4 | CALCUL | ATED REMAINING CAPACITY OF THE FACILITY | 10 |
| | 2.5 | RESTOR | ATION OF FORMER SLUDGE DISPOSAL AREAS & COMPLETED CELLS/PHASES | 10 |
| | 2.6 | TOPOGI | RAPHICAL SURVEY | 11 |
| | 2.7 | LEACHA | TE MANAGEMENT | 11 |
| | | 2.7.1 | Leachate Pumping Records | 11 |
| | 2.8 | ESTIMA | TED ANNUAL AND CUMULATIVE QUANTITIES OF LANDFILL GAS EMITTED | 11 |
| | 2.9 | ESTIMA | TED ANNUAL AND CUMULATIVE QUANTITY OF INDIRECT EMISSIONS TO | |
| | | GROUN | DWATER | 13 |
| 3.0 | MON | ITORING F | RESULTS | 14 |
| | 3.1 | SUMMA | ARY REPORT | 14 |
| | | 3.1.1 | Dust Deposition | 14 |
| | | 3.1.2 | Noise Emissions | 15 |
| | | 3.1.3 | Landfill Gas Emissions | 15 |
| | 3.2 | MONITO | ORING RESULTS AND INTERPRETATION | 18 |
| | | 3.2.1 | Introduction | 18 |
| | | 3.2.2 | Dust Monitoring | 19 |
| | | 3.2.3 | Groundwater Monitoring | 19 |
| | | 3.2.4 | Landfill Gas Monitoring | 22 |
| | | 3.2.5 | Leachate Monitoring | 23 |
| | | 3.2.6 | Noise Monitoring | 25 |
| | | 3.2.7 | Surface Water Monitoring | 26 |
| | | 3.2.8 | Meteorological Monitoring | 28 |
| | | 3.2.9 | Annual Water Balance Calculation and Interpretation for Cells | 28 |
| | | 3.2.10 | Resource and Energy Consumption Summary | 29 |
| | | 3.2.11 | Tank, Pipeline and Bund Integrity Testing and Inspection | 29 |
| | | 3.2.12 | Review of Nuisance Controls | 29 |



| 4.0 | MAN | AGEMENT OF THE FACILITY | 31 |
|-----|-----------|---|-----|
| | 4.1 | MANAGEMENT AND STAFFING STRUCTURE | 31 |
| | 4.2 | ENVIRONMENTAL MANAGEMENT PROGRAMME/ENVIRONMENTAL OBJECTIVES AND | |
| | | TARGETS | 31 |
| | 4.3 | SCHEDULE OF ENVIRONMENTAL OBJECTIVES AND TARGETS | 31 |
| | 4.4 | FACILITY PROCEDURES | 32 |
| | 4.5 | FINANCIAL PROVISION | 32 |
| | 4.6 | Staff Training | 32 |
| | 4.7 | Programme for Public Information | 32 |
| | 4.8 | Facility Notice Board | 33 |
| 5.0 | REPO | RTED INCIDENTS AND COMPLAINTS SUMMARY | 33 |
| | 5.1 | Incidents | 33 |
| | 5.2 | Non Compliance | 33 |
| | 5.3 | Complaints | 33 |
| | 5.4 | Waste Records | 34 |
| 6.0 | FACIL | ITY DEVELOPMENT | 35 |
| | 6.1 | Developments during 2012 | 35 |
| | 6.2 | Proposed developments of the Facility and Associated Timescales | 35 |
| | | Figures | |
| F | igure 1 - | Site Location Map | 36 |
| F | igure 2 - | Site Plan Showing Environmental Monitoring Locations | 38 |
| | | | |
| | | <u>Appendices</u> | |
| Δ | ppendi | (A - Dust Monitoring Results | 41 |
| Δ | ppendix | B - Noise Monitoring Results | 43 |
| Δ | ppendix | C - Landfill Gas Monitoring Results | 45 |
| Δ | ppendix | CD - Groundwater Monitoring Results | 52 |
| Δ | ppendi | ι E - Leachate Monitoring Results and Pumping Data | 54 |
| Δ | ppendi | c F - Surface Water Monitoring Results | 57 |
| Δ | ppendi | G - Copies of Laboratory Reports | 59 |
| Δ | ppendi | (H - Meteorological Data | 124 |
| Δ | ppendix | (I - Water Balance Calculations | 137 |



1.0 INTRODUCTION

Response Group was commissioned by Clare County Council to compile an Annual Environmental Report (AER) required under Condition 11 of Waste Licence Reg. No. W0037-01 for a Sludge Disposal Facility situated at Tradaree Point, Shannon (Clonmoney South), Co. Clare for the period January 2012 to December 2012.

1.1 Background

The Environmental Protection Agency (EPA) issued Shannon Free Airport Development Company Limited with a Waste Licence on 1st May 2003. The ownership of the facility was subsequently passed onto Clare County Council under the same Waste Licence.

Under Condition 11.6, Section 11 of the W0037-01, an Annual Environmental Report (AER) must be prepared and submitted to the EPA for approval. The AER for the facility includes the information specified in Schedule F of the Waste Licence, Content of the Environmental Report, and has been prepared in accordance with the EPA (1999) Waste Licensing – Draft Guidance Note on Environmental Management Systems and Reporting to the Agency, the EPA Guidance Note for the Annual Environmental Report and the EPA AER/PRTR Guidance Document.

1.2 Reporting Period

This AER details the activities carried out at the facility in the period from January 2012 to December 2012 in accordance with W0037-01.

1.3 <u>Site Description</u>

The site is situated approximately 4.5km south east of Shannon Town to the south-west of Bunratty (OS National Grid Reference 143,600E, 160,100N). The site is located on a peninsula, which extends into Shannon Estuary. A grassland constructed clay embankment, average height 5.0 mOD, lies to the south of the site between Shannon Estuary and the site.

The site location is shown in Figure 1.



1.4 Facility Layout

The landfill (sludge disposal facility) is divided into two sections - the capped historic sludge disposal area and the four newly constructed lined cells. The area where the new cells have been constructed has an average elevation of 1.5mOD. The cells are bounded to the south-east and north-east by an open land drain. The average drain bed level is 0.6mOD. This discharges to Shannon Estuary via an outlet pipe under the clay embankment which is controlled by a sluice valve. A 10m wide buffer zone exists along the southern perimeter of the site between the edge of the catchment drain and the capped sludge cells. No sludge or restoration material is stored within this zone.

The layout of the facility is illustrated in Figure 2.

Tradaree Point Wastewater Treatment Plant (WWTP) provides treatment of both domestic and industrial effluent from Shannon Town and Shannon Industrial Estate. The sludge facility accepts waste sludge from the Tradaree Point WWTP. Sludge has been disposed on the site since approximately 1981.



2.0 FACILITY INFRASTRUCTURE AND OPERATION

2.1 Waste Activities Carried Out At the Facility

The facility is licensed to handle a maximum of 2,500 tonnes of waste per annum. This comprises 750 tpa (tonnes per annum) treated dewatered non-hazardous domestic sludge (EWC code 19 08 05) and 1,750 tpa of industrial sludge (EWC code 19 08 12, 19 08 14) in engineered cells within the facility boundary. Waste activities licensed at the facility under the Third and Fourth Schedules of the Waste Management Act 1996, are detailed below.

Table 2.1 Licensed Waste Disposal Activities in Accordance with the Third Schedule of the Waste Management Act

| Class 1 | Deposit on, in or under land (including Landfill)*. This activity is limited to the disposal of treated dewatered non-hazardous domestic and industrial sludge in the existing activity cells within the facility. |
|----------|--|
| Class 4 | Surface impoundment, including placement of liquid or sludge discards into pits, ponds or lagoons |
| Class 5 | Specially engineered landfill, including placement into lined discreet cells which are capped and isolated from one another and the environment. |
| Class 6 | Biological treatment not referred to elsewhere in the Schedule which results in final compounds or mixtures which are disposed of by means of any activity referred to in paragraphs 1 to 5 paragraphs 8 to 10 of this Schedule (including evaporation, drying and calcination). |
| Class 13 | Storage prior to submission to any activity referred to in a preceding paragraph of this schedule, other than temporary storage, pending collection, on the premises where the waste concerned is produced. |



2.2 Methods of Deposition of Sludge

Two different waste effluent streams undergo separate treatment at Tradaree Point WWTP. Industrial wastewater is treated in the Industrial Treatment Plant and domestic wastewater is treated in the Domestic Treatment Plant.

The only waste disposed of at the sludge disposal facility is treated dewatered sludge from the WWTP. No other waste is accepted for disposal at the facility. In the unlikely event of a different waste type being presented for disposal at the facility, a separate storage area is provided to contain the materials separately until such time as it can be removed off site to a suitable facility.

Sludge generated in the WWTP is sent to a dewatering building to the east of the plant. Both domestic and industrial sludge are dewatered using a centrifuge after which the sludge is conveyed into an open trailer. The dewatered sludge is then transported to the landfill area and unloaded using a dumper.

The sludge is further dried naturally in the open air. Older dried sludge are excavated from their initial deposition area and heaped into mounds where they are permitted to re-vegetate by natural succession.

The new cells are being filled sequentially in a similar manner. Cell 1 is currently the active cell and sludge is transported for landfilling on a daily basis between Monday and Friday by a dumper. Transportation to the landfill is facilitated by the provision of a causeway at the cell entrance which provides a dry area for the unloading of the sludge.



2.3 **Quantity and Composition of Sludge Disposed**

2.3.1 Sludge Disposed 2012

The facility is licensed to handle up to 2,500 tonnes of waste sludge per annum. The quantities of mixed industrial and domestic sludge disposed at the facility between January and December 2012 are presented in Table 2.2 overleaf.

As specified in Condition 1.1 of the Waste Licence, only those categories and quantities listed in Part 1 (Activities Licensed) [See also Schedule A] can be accepted at the facility. During 2012, approximately 1055 tonnes of sludge were accepted at the facility. This quantity is below the maximum 2,500 tonnes of waste per annum permitted.

Table 2.2: Quantities of Sludge Disposed in 2012

| Month | Quantity (Kg) |
|----------------|---------------|
| January | 62100 |
| February | 91000 |
| March | 91200 |
| April | 16700 |
| May | 95200 |
| June | 116200 |
| July | 90100 |
| August | 96900 |
| September | 96200 |
| October | 105800 |
| November | 100000 |
| December | 93600 |
| Total (kg) | 1055000 |
| TOTAL (tonnes) | 1055 |

2.3.2 Sludge Disposed 2004-2012

Table 2.3 below details the quantities of sludge disposed at the facility between 2004 and 2012.

| Year | Quantity (Tonnes) Sludge Disposed/Annum |
|------|--|
| 2004 | 1,022 |
| 2005 | 954 |
| 2006 | 408 |
| 2007 | 756 |
| 2008 | 548 |
| 2009 | 732 |
| 2010 | 489 |
| 2011 | 228 |
| 2012 | 1055 |



2.4 <u>Calculated Remaining Capacity of the Facility</u>

In 2006, the quantity of sludge accepted (408 tonnes) was low compared to previous years due to the machinery breakdowns experienced in the WWTP. This increased to 755.5 tonnes in 2007. The volume of sludge disposed during 2008 was 548 tonnes, which was lower than in 2007 – this was due to reduce through put and belt press breakdowns. The quantity of sludge accepted increased to 732 tonnes in 2009 but decreased in 2010 to 489 tonnes. The volume of sludge disposed in 2011 was 228 tonnes. The volume of sludge accepted in 2012 increased to 1055 tonnes.

The total capacity of the four lined cells is 12,029m3. Landfilling in the lined cells commenced in Cell 1 in 2005. In 2012, approximately 1055 tonnes of sludge was disposed of at the facility.

The density of dewatered sludge varies depending on the dry matter concentration. In 2012, the average cake % dry matter reached in the sludge was 26.58%. At this rate, the bulk density is typically calculated at rate of 1.27t/m3 (assuming that the ratio of volatile and fixed sludge is 65%:35%). Therefore, at this density, the volume of waste sludge disposed of at the facility during 2012 was 831m3.

Based on the 2012 figure, it is expected that the landfill should reach its full capacity by 2025. However, if yearly tonnages remain low this figure could be extended.

2.5 Restoration of Former Sludge Disposal Areas and Completed Cells/Phases

A restoration and aftercare management plan for the facility was prepared in consultation with the EPA Restoration and Aftercare Manual and was previously submitted to the Agency in January 2004. The Agency confirmed in a letter (Ref. 37-1/GEN03bd) that the plan was to their satisfaction.

All unlined sludge mounds have been capped along with all unlined cells after EPA approval. Waste sludge continues to be disposed of into the first of the newly lined active cells – Cell 1.

The total capped area occupied by waste in the facility is 15,742m2. Since 2005, a total of 5,170 tonnes of waste has been deposited into Cell 1.



2.6 <u>Topographical Survey</u>

A topographical survey was undertaken during September 2003 as part of Licence Condition 8.10.1. The results of the survey were submitted to the Agency in the 6-month report on Drawing No.1, submitted in October 2003. No additional topographical surveys have taken place at the facility since 2003.

2.7 <u>Leachate Management</u>

2.7.1 <u>Leachate Pumping Records</u>

A total of 48,171 m3 of leachate was pumped during the reporting period. Leachate is collected from the existing sludge disposal area (Cell 1), the inactive cells (Cells 2-4) and the capped unlined area via a network of drains which are connected to a leachate collection sump and from here it is pumped to Tradaree WWTP. The pump has a capacity to pump 75m3 per hour.

The monthly totals of leachate generated during 2012 are detailed in Table 2.4 below.

Month Flow Rate (m³/Month) January 1561 **February** 1840 685 March April 846 May 461 June 4869 July 1362 2511 **August** September 1651 16198 October November 9078 7109 December Total (M³/Year) 48171

Table 2.4: the monthly averages of leachate generated in 2011

2.8 <u>Estimated Annual and Cumulative Quantities of Landfill Gas Emitted</u>

Landfill gas production is a function of the biodegradable portion of the wastes and other factors including the waste density and moisture content. According to the UK EA, total gas generation depends on the waste type being deposited on site and also the degradable carbon content. However the rate of decomposition depends on the site-specific factors. The time taken to decompose will directly influence the period over which landfill gas is generated.

Emissions through the in situ clay base and side walls of the landfill facility are expected to be small. The capped sludge disposal area does not have an engineered base lining. Site investigation results

Page 11 of 138



indicate that in situ clay has a hydraulic conductivity of less than 1×10 -9m/s. Gas levels are being measured in monitoring boreholes installed in the ground along the perimeter of the landfill to check if there are any emissions.

The UK Environment Agency's Guidance on the Management of Landfill Gas (November 2002) suggests that biodegradable wastes may be considered to have an approximate gas yield of between 5 - 10 m3/t/yr over the first ten years of a sites life. In this instance, the waste sludge was dried to an average of 26.58% dry matter in 2012. Assuming that the dry matter content would equate to the biodegradable component of the sludge and based on a total input in 2012 of 280 tonnes of biodegradable waste (26.58% of 1,055 total tonnes), this would indicate that the following upper and lower quantities of landfill gas might be generated:

- At 5 m3/t/yr an approximate production rate of 1,400m3 per annum
- At 10 m3/t/yr an approximate production rate of 2,800m3 per annum

There are a number of significant controlling factors relating to landfill gas generation/extraction rates from biodegradable wastes including placement density, moisture content, quality of containment systems, climatic conditions and quantity of degradable cellulose available.

It must also be stressed that the above figure is based upon an estimation of the amount of available degradable waste deposited within the landfill body and therefore must only be considered to be an approximation.

The most recent landfill gas assessment at Tradaree was undertaken by Tobin Consulting Engineers in April 2008. The purpose of the assessment was to determine the total quantity of landfill gas produced at the facility in order to determine the viability of constructing a landfill gas flare on-site.

The assessment was undertaken using a landfill gas generation model GasSim 2.0. Data from previous assessments undertaken in 2004 and 2007 were used in the assessment. The results show a peak in landfill gas production in 2003 (12.5 m3/hr), with decreasing figures since that time. A total of 9.88 m3/hr was predicted for 2007. The report concluded that owing to this low volume of gas being produced from the facility, it would not be considered a viable option to install a gas collection system and flaring unit. A gas collection system to operate successfully requires a volume of gas in the order of 75 m3/hr.

A copy of the assessment report was included in the AER for the 2008 reporting period.



2.9 <u>Estimated Annual and Cumulative Quantity of Indirect Emissions to Groundwater</u>

Potential sources of indirect emissions into groundwater are:

Landfill Base

The naturally occurring low permeability clay underlying the site provides a natural liner for the capped area of the landfill. Previous site investigation results indicate that in situ clay has a hydraulic conductivity of less than 1 X 10m-9m/s. The new area of the landfill (Cells 1-4) is lined with a geotextile membrane as stipulated in the current waste licence consisting of a composite liner consisting of a 1m layer of compacted soil with a hydraulic conductivity of less than or equal to 1x10-9m/s. This is overlain by a geocomposite layer which in turn is overlain by a 2mm thick high density polyethylene (HDPE) layer.

Landfill Capping

The old sludge disposal areas were capped in 2004/2005. A five layer composite permanent capping was placed over all the old sludge cells as per the requirements of Condition 4.4 of the current licence. The five layers are comprised of the following;

- a) Geocomposite gas collection layer
- b) Barrier/Protection layer
- c) Geotextile protection layer
- d) Surface water drainage layer
- e) Subsoil layer
- f) Topsoil Layer

The capped layer is approximately 1 metre in thickness. The geosynthetic barrier has a minimum permeability of 1 x 10-9m/s. This layer prevents surface water seeping into the sludge body and also facilitates the collection of gas. The surface water drainage layer collects surface water and extends to the system of open surface water drains at the base of the slopes from where it discharges to the existing catchment drains.

Surface Water Collection and Treatment System

Clean surface water from the uncapped existing sludge cells, is collected via a network of gravel drains which is then discharged to the perimeter drain. Visual inspection of the surface water locations and drains is conducted weekly.

Leachate Collection

Leachate is collected in the leachate pumping chamber from a series of collection drains at the site. The leachate is pumped via a 100mm diameter pipe to the effluent treatment plant for treatment.

In summary, as the landfill is contained by the provision of the features outlined above, the risk of indirect emissions to groundwater is greatly minimised.



3.0 MONITORING RESULTS

3.1 Summary Report

This summary report has been compiled in accordance with the emission limit values (ELVs) for the following parameters as specified in Condition 6 and Schedule C of W0037-01:

- Dust
- Noise
- Landfill Gas

3.1.1 <u>Dust Deposition</u>

Dust deposition emission limit values as specified in W0037-01 are detailed in Table 3.1 below.

Table 3.1 Dust Deposition ELV

ELV (mg/m2/day) Note 1 350

Note 1: 30 day composite sample

Annual dust monitoring was conducted by BHP at four locations between 18th July and 15th August 2012. Dust monitoring locations are illustrated in Figure 2. 30-day composite samples were collected in accordance with licence requirements and forwarded to the TelLab accredited laboratory for analysis. The monitoring results are summarised in Table 3.2 below. Copies of the dust monitoring results are included in Appendix A.

Table 3.2 Dust Monitoring Results 2012

| Location | N1 | N3 | N5 | SS2 |
|-------------|-----------|------|-------|-------|
| | mg/m2/day | | | |
| August 2012 | 106.1 | 64.4 | 193.8 | 202.2 |

Measured dust levels at all of the monitoring locations were below the ELV of 350 mg/m3/day.



3.1.2 Noise Emissions

Noise emission limit values as specified in W0037-01 are detailed in Table 3.3 below. Day-time and night-time noise monitoring was conducted by Response Group at four boundary locations (N1, N2, N3, N5) on the 15th November 2012. The noise survey report is attached in Appendix B. The monitoring results are summarised in Table 3.4 and 3.5 below.

Table 3.3 Noise ELV's

| Day Db(A)L _{Aeq} (30 minutes) | Night Db(A)L _{Aeq} (30 minutes) | |
|--|--|--|
| 55 | 45 | |

Table 3.4 Day-time Noise Measurements 2012

| Location | Date | Sampling Interval | L _{Aeq} 30min Db(A) |
|----------|----------|-------------------|------------------------------|
| N1 | 15/11/12 | 30 Minutes | 43.7 |
| N2 | 15/11/12 | 30 Minutes | 41.8 |
| N3 | 15/11/12 | 30 Minutes | 40.6 |
| N5 | 15/11/12 | 30 Minutes | 41.3 |

Table 3.5 Night-time Noise Measurements 2012

| Location | Date | Sampling Interval | L _{Aeq} 30min Db(A) |
|----------|----------|-------------------|------------------------------|
| N1 | 15/11/12 | 30 Minutes | 39.8 |
| N2 | 15/11/12 | 30 Minutes | 38.3 |
| N3 | 15/11/12 | 30 Minutes | 40.1 |
| N5 | 15/11/12 | 30 Minutes | 40.9 |

The average figures show that there are no noise issues on site. All results obtained from the measurements taken at the four locations by day and night are within the daytime and night-time limits of 55Dba and 45Dba. The noises that were most evident on site were the road traffic and the flow of water. It is clear from carrying out this report that the Waste Water Treatment Plant is having a minimal impact on the local environment in terms of Noise Pollution

3.1.3 Landfill Gas Emissions

The trigger levels for landfill gas emissions from the facility measured in any service duct or manhole on, at, or immediately adjacent to, the facility and/or at any other point located outside the body of the waste stipulated in Condition 6.3.1 of W0037-01 are detailed in Table 3.6 below:

Table 3.6 Landfill Gas Concentrations

| Methane | Carbon Dioxide | |
|------------------|----------------|--|
| 20% LEL (1% v/v) | 1.5% v/v | |

During 2012, landfill gas concentrations were measured at the following locations: RD1, RD2, RD3, RD4, RD5, RD6, RD7, RD8, L6, L8, L10 and L12.



3.1.3.1 <u>Methane</u>

Monthly methane concentrations measured at gas monitoring location RD1 were all below the threshold level of 1% v/v in 2012.

Methane levels measured at RD2 exceeded the threshold level of 1% v/v in eight of the monthly monitoring rounds. Methane levels above the threshold level ranged from 1.2% (December) to 32.8% (September).

Methane levels measured at RD3 exceeded the threshold level of 1% v/v in five of the monthly monitoring rounds. Methane levels above the threshold level ranged from 1.4% v/v (October) to 7.4% v/v (January).

Methane levels measured at RD4 exceeded the threshold level of 1% v/v in eight of the twelve monthly monitoring rounds. Methane levels above the threshold level ranged from 1.9% (October) to 21.2% (November).

Methane levels measured at RD5 exceeded the threshold level of 1% v/v in eleven of the 12 monthly monitoring rounds. Methane levels above the threshold level ranged from 1.8% (March) to 29.9% (December).

Methane levels measured at RD6 exceeded the threshold level of 1% v/v in all of the 12 monthly monitoring rounds. Methane levels ranged from 34.9% (March) to 71.3% (September).

Methane levels measured at RD8 could not be taken between July and October as it was flooded. The remaining months were all below the threshold level.

Monthly recorded methane levels in the remaining monitoring boreholes (RD7, L6, L8, L10 and L12) were below 1% v/v.

3.1.3.2 Carbon Dioxide

Carbon dioxide concentrations exceeded the limit of 1.5% v/v at RD1 in 9 of the 12 monthly monitoring rounds – January (3.1%), February (4.4%), March (4.2%), April (5.1%), May (3.8%), June (2.3%), July (2.0%), October (2.1%) and December (6.5%).

At RD2, carbon dioxide levels exceeded the threshold level of 1.5% v/v in 10 of the 12 monthly monitoring rounds – January (4.1%), February (3.9%), March (3.6%), April (5.9%), May (2.2%), August (3.1%), September (3.9%), October (4.1%), November (1.9%) and December (2.9%).

In RD3, carbon dioxide concentrations were above the threshold level of 1.5% v/v in 8 of the 12 monthly monitoring rounds – January (3.0%), February (4.4%), March (1.6%), April (2.9%), August (1.7%),October (2.2%), November (2.5%) and December (2.7%).



In RD4, carbon dioxide concentrations were above the threshold level of 1.5% v/v in 11 of the 12 monthly monitoring rounds – January (6.3%), February (5.3%), April (7.4%), May (6.2%), June (7.1%), July (3.4%), August (2.7%), September (4.7%), October (8.1%), November (3.6%) and December (5.3%).

In RD5, carbon dioxide levels exceeded the threshold level of 1.5% in 11 of the 12 monthly monitoring rounds – February (7.0%), March (5.8%), April (13.9%), May (6.9%), June (11.3%), July (7.8%), August (6.2%), September (16.3%), October (17.0%), November (17.3%) and December (17.2%).

In RD6, carbon dioxide levels exceeded the threshold level of 1.5% v/v in all of the monthly monitoring rounds - January (15.7%), February (12.3%), March (8.8%), April (13.0%), May (13.4%), June (13.9%), July (11.5%), August (13.8%), September (15.6%), October (11.3%), November (13.6%) and December (12.0%).

In RD8, carbon dioxide levels could not be taken between July and October as it was flooded, all other months were below the threshold level of 1.5% v/v.

In L6, carbon dioxide levels exceeded the threshold level of 1.5% v/v in 5 of the 12 monthly monitoring rounds – June (3.5%), July (11.6%), August (6.6%), September (1.6%) and November (2.3%).

Monthly recorded carbon dioxide levels in the remaining monitoring boreholes (RD7, L8, L10 and L12) were below 1.5% v/v.

Landfill gas monitoring results are attached in Appendix C.



3.2 MONITORING RESULTS AND INTERPRETATION

3.2.1 Introduction

Environmental monitoring was conducted at the facility during 2012 in accordance with Schedule D of Waste Licence W0037-01. Details of monitoring and reporting frequencies are presented in Table 3.7 below.

The locations of all environmental monitoring points are illustrated on Figure 2. Monitoring results are presented in Appendices A to F. Copies of the laboratory certificates are included in Appendix G.

Table 3.7 Environmental Monitoring and Reporting Frequency

| Environmental Monitoring | Monitoring Frequency | Reporting Frequency |
|---------------------------------|----------------------|---------------------|
| Requirement | | |
| Groundwater Quality | Biannually/Annually | Biannually |
| Groundwater Levels | Biannually | Biannually |
| Surface Water Quality | Biannually | Biannually |
| Surface Water Visual Inspection | Weekly | Biannually |
| Leachate Quality | Biannually | Biannually |
| Leachate Levels | Quarterly | Biannually |
| Landfill Gas | Monthly | Biannually |
| Dust Deposition | Annually | Annually |
| Noise Emissions | Annually | Annually |
| Meteorological Monitoring | Daily | Annually |
| Ecological Monitoring | Biennial After Yr 1 | Biannually |

In 2012,

Dust analysis and reporting was carried out by BHP, New Road, Thomondgate, Limerick.

Noise monitoring was carried out by Response Group.

Groundwater and leachate level monitoring, groundwater, leachate, surface water and landfill gas analysis and reporting was carried out by BHP, New Road, Thomondgate, Limerick.

Meteorological monitoring and surface water visual inspection is undertaken by facility management personnel at the facility.



3.2.2 Dust Monitoring

3.2.2.1 <u>Dust Monitoring Locations</u>

Dust monitoring was conducted at four monitoring locations in 2012 in accordance with Tables D.4.1 and D.3.1 of W0037-01. Dust monitoring locations are outlined in Table 3.8 below.

Table 3.8 Dust Monitoring Locations

| Location | Easting | Northing |
|----------|---------|----------|
| N1 | 144.001 | 159.988 |
| N3 | 143.727 | 159.831 |
| N5 | 143.937 | 160.076 |
| SS2 | 143.879 | 159.874 |

3.2.2.2 <u>Dust Monitoring Methods</u>

Details of the dust monitoring results attached in Appendix A.

3.2.2.3 **Dust Monitoring Results**

The results of dust monitoring conducted at the facility during 2012 are presented in Table 3.9 below. Dust concentrations and emission limit values as detailed in Schedule C.3 of W0037-01 were discussed in Section 3.1.1.

Table 3.9 Dust Monitoring Results 2012

| Location | N1 | N3 | N5 | SS2 |
|-------------|-----------|------|-------|-------|
| | mg/m²/day | | | |
| August 2012 | 106.1 | 64.4 | 193.8 | 202.2 |

All monitoring results were below the ELV for dust of 350 mg/m2/day.

3.2.3 Groundwater Monitoring

3.2.3.1 Groundwater Monitoring Locations

Groundwater monitoring was conducted at five locations during 2012 in accordance with Schedule D.1.1 and D.6.1 of the current licence. Co-ordinates for all monitoring locations are detailed in Table 3.10 and locations are also illustrated on Figure 2. Monitoring results are attached in Appendix D.

Monitoring location RD2 is located at the southern boundary of the site and RD3 is located at the south-western boundary of the site adjacent to the capped sludge cells. BH3 is located at the north eastern boundary of the site. BH4 and BH5 are both located in the buffer zone adjacent to the southern boundary of the facility and close to Shannon Estuary.



Table 3.10 Groundwater Monitoring Locations

| Location | Easting | Northing |
|----------|---------|----------|
| RD2 | 143.866 | 159.855 |
| RD3 | 143.799 | 159.855 |
| вн3 | 143.952 | 160.085 |
| BH4 | 143.935 | 159.930 |
| BH5 | 143.984 | 159.959 |

3.2.3.2 Groundwater Levels

Groundwater levels were monitored on a biannual basis in accordance with Schedule D.6.1 of W0037-01 and are included in Appendix E with the groundwater monitoring results.

Groundwater levels recorded during 2012 varied between 0.0m below top of casing (BTOC) (in RD3 August 2012) and 2.1m BTOC (in BH3 February 2012).

3.2.3.3 Groundwater Analytical Results

Groundwater monitoring was conducted on a biannual and annual basis in accordance with Schedule D.6.1 of the licence. Monitoring was undertaken in February and August 2012.

Groundwater analytical results are attached in Appendix D.

There are no emission limits stipulated in Waste Licence W0037-01, therefore the groundwater analytical results have been compared to the Interim Guideline Values (IGVs) specified in the EPA document: 'EPA Interim Report – Towards Setting Guideline Values for the Protection of Groundwater in Ireland' (2003).

The Ph in all of the groundwater samples analysed during both monitoring rounds ranged from 6.52 to 7.53, which is within the IGV range of 6.5-9.5.

Electrical conductivity measurements ranged from 2,250 PS/cm in RD3 (August) to 15,140 PS/cm in BH4 (February), which are similar to previous monitoring results. The IGV of 1,000 PS/cm was exceeded in all of the samples analysed.

Ammonia concentrations detected in RD 3 in August was 0.11mg/l. This was the only result below the IGV of 0.2mg/l. The other results were all above the IGV and ranged between 0.23mg/l in BH 5 (February) to 176.1mg/l in BH 3 (February).

Total phosphorus/orthophosphate concentrations in RD2 (0.06mg/l), RD3 (0.09mg/l), BH4 (0.06mg/l) and BH5 (0.11mg/l) exceeded the IGV for orthophosphate of 0.03 mg/l.

Total Oxidised Nitrogen concentrations results ranged between 0.1mg/I RD 3 (February) and 4.5mg/I BH 5 (February).

Total organic carbon concentrations ranged from 1.2mg/l in RD3 (August) to 24.7mg/l in BH5 (February), TOC concentrations were similar to previous monitoring rounds.



Chloride concentrations ranged from 45.3 mg/l in RD3 (August) to 3,470 mg/l in BH5 (February). Chloride concentrations in all of the samples analysed exceeded the IGV of 30 mg/l.

Sodium concentration ranged from 9.07mg/l BH 4 (August) to 13.17mg/l BH 3 (August), which were all below the IGV of 150 mg/l.

Potassium concentrations in all five samples analysed during the August monitoring round were all below the IGV of 5 mg/l. Concentrations ranged from 1.06mg/l in RD3 to 2.96mg/l in RD2.

Iron concentration in RD3 and RD3 was detected at <0.01mg/I (August) which is below the IGV of 0.2mg/I. The Iron concentration measured in BH3 (1.026mg/I), BH4 (1.136mg/I) and BH5 (1.127mg/I) all exceeded the IGV of 0.2 mg/I.

The chromium concentration in BH5 was 0.056 which exceeds the IGV of 0.03mg/l. The remaining samples were below the IGV of 0.03 mg/l, <0.001mg/l in both RD2 and RD3 and 0.016mg/l in both BH3 and BH4.

Total phenol concentrations exceeded the IGV 0.0005mg/l in all the samples analysed during both monitoring rounds. Results ranged from 0.001mg/l RD3 (August) to 0.015mg/l BH3 (February).

Copper concentrations exceeded the IGV of 0.03 in 3 of the samples taken. BH3 was 0.861mg/l, BH4 0.804mg/l and BH5 was 0.606mg/l. RD2 and RD3 were below the IGV with both results reading <0.001mg/l.

Concentrations of arsenic, boron, cadmium, calcium, cyanide, fluoride, lead, magnesium, mercury, nickel, sulphate, tin and zinc were below their respective IGVs and/or laboratory detection limits in all of the samples analysed.

3.2.3.4 Conclusions

Overall, the groundwater results are similar to the 2011 biannual and annual monitoring rounds. This represents an improvement in groundwater quality at the facility since previous monitoring rounds.

Certain parameters such as electrical conductivity, ammonia, chloride, iron, and total phosphorus concentrations remain elevated at most or all monitoring locations compared to the IGV's.

Salinity concentrations measured in December 2010 would appear to confirm that there is saline intrusion into groundwater monitoring wells most notably at location BH4. Measured concentrations ranged from 0.3 ppt in RD3 to 6 ppt in BH4 indicating brackish water (i.e. a mixture of freshwater and seawater with a salinity range of 0.5-30 ppt typical of an estuarine location).

TOC concentrations are broadly similar to those recorded in previous years.



3.2.4 Landfill Gas Monitoring

Measurements of landfill gas were carried out at all gas monitoring boreholes (RD1 to RD8) on a monthly basis in accordance with Table D.2.1 of the Waste Licence. Combined gas and leachate monitoring boreholes (L6, L8, L10, L12) were also monitored on a monthly basis for gas.

All monitoring locations were sampled for methane, carbon dioxide, oxygen, temperature and pressure.

Results are compared against the EPA Guideline Emission Limits for methane (CH4) and carbon dioxide(CO2) at landfills, which are 1% v/v and 1.5% v/v, respectively (EPA Landfill Manuals: Landfill Monitoring, 2^{nd} Edition, 2003). These are also the ELVs specified in Schedule C.2 of Waste Licence W0037-01.

3.2.4.1 Gas Monitoring Locations

Gas monitoring locations are detailed in Table 3.11 below and illustrated in Figure 2. Gas monitoring results are presented in Appendix C.

| Location | Easting | Northing |
|----------|---------|----------|
| RD1 | 143.761 | 159.997 |
| RD2 | 143.876 | 159.883 |
| RD3 | 143.801 | 159.851 |
| RD4 | 143.760 | 160.092 |
| RD5 | 143.906 | 159.999 |
| RD6 | 143.928 | 160.071 |
| RD7 | 144.000 | 159.979 |
| RD8 | 143.939 | 159.938 |
| L6 | 143.867 | 159.959 |
| L8 | 143.924 | 159.995 |
| L10 | 143.944 | 160.015 |
| 112 | 143 940 | 160 064 |

Table 3.11 Gas Monitoring Locations

3.2.4.2 Gas Monitoring Boreholes

Landfill gas measurements were undertaken using an Infrared Gas Analyser. The gas emitted is analysed for its content by % volume of the following constituents:

- Methane (CH₄)
- Carbon Dioxide (CO₂)
- Oxygen (O₂)
- Atmospheric Pressure (mBar)

The LEL (lower explosive limit) for methane, atmospheric pressure (millibars) and temperature (Oc) were also recorded by the gas analyzer and relative pressure was calculated.



3.2.5 <u>Leachate Monitoring</u>

3.2.5.1 <u>Leachate Monitoring Locations</u>

In accordance with Schedule D.1 of the licence, leachate composition and level monitoring was conducted at locations detailed in Table 3.12.

Table 3.12 Leachate Monitoring Locations

| Parameter | Location | Easting | Northing |
|----------------------|----------|---------|----------|
| Leachate Level | L1 | 143.795 | 159.990 |
| | L2 | 143.796 | 159.926 |
| | L3 | 143.843 | 159.890 |
| | L4 | 143.797 | 160.016 |
| | L5 | 143.821 | 159.997 |
| | L7 | 143.895 | 159.928 |
| | L9 | 143.939 | 159.958 |
| | L11 | 143.991 | 160.000 |
| | L13 | 143.976 | 160.052 |
| Leachate Composition | SS3 | 143.806 | 159.951 |

3.2.5.2 <u>Leachate Composition Results</u>

There are no emission limits stipulated in Waste Licence W0037-01, therefore the leachate analytical results have been compared to the Interim Guideline Values (IGVs) listed in the EPA document: 'EPA Interim Report - Towards Setting Guideline Values for the Protection of Groundwater in Ireland' (2003).

Appendix E contains monthly leachate composition results, annual and biannual leachate analytical results.

Leachate monitoring at SS3 was undertaken in February and August 2012 as per Schedule D of the licence.

The electrical conductivity in SS3 was measured at 1,716 μ S/cm in February which exceeds the IGV of 1000 PS/cm. However in August it was 877 μ S/cm which is below the IGV.

The chloride concentration in SS3 was detected at 502.5mg/l in February and 161.7mg/l in August, both of which exceeds the IGV of 30 mg/l; however chloride concentrations have been consistently elevated since 2004.

The ammonia concentration in SS3 was detected at 6.29mg/l in February and 0.87mg/l in August, which exceeds the IGV of 0.15 mg/l; Ammonia concentrations have been consistently elevated since 2004.



Nickel and potassium concentrations were <0.001mg/l and 1.32mg/l respectively, which are below their respective IGVs of 0.02 mg/l and 5 mg/l. This is a change from last year when they both exceeded their IGV.

The iron concentration in SS3 was detected at <0.001mg/l in August, which is below the IGV of 0.02 mg/l.

Comparison of results with the results from previous years, indicate that a number of parameters (Conductivity, ammonia, chloride and total phosphorus) remain consistently elevated above their respective IGVs.



3.2.6 Noise Monitoring

3.2.6.1 Noise Monitoring Locations

Day-time and night-time annual noise monitoring was conducted at four boundary locations at the facility (N1, N2, N3, N5) on the 15th November as stipulated in Table D.4.1 of the licence. Noise monitoring locations are illustrated on Figure 2 and detailed in Table 3.13 below.

Table 3.13 Noise Monitoring Locations

| Location | Easting | Northing |
|----------|---------|----------|
| N1 | 144.001 | 159.988 |
| N3 | 143.727 | 159.831 |
| N5 | 143.937 | 160.076 |
| SS2 | 143.879 | 159.874 |

The noise survey report (including details of the methodology) is attached in Appendix B.

3.2.6.2 Noise Monitoring Results

The noise monitoring results are summarised in Table 3.14 and 3.15.

Table 3.14 Day-time Noise Measurements 2012

| Location | Date | Sampling Interval | L _{Aeq} 30min dB(A) |
|----------|------------|-------------------|------------------------------|
| N1 | 15/11/2012 | 30 | 43.7 |
| N3 | 15/11/2012 | 30 | 40.6 |
| N5 | 15/11/2012 | 30 | 41.3 |
| SS2 | 15/11/2012 | 30 | 41.8 |

Table 3.15 Night-time Noise Measurements 2012

| Location | Date | Sampling Interval | L _{Aeq} 30min dB(A) |
|----------|------------|-------------------|------------------------------|
| N1 | 15/11/2012 | 30 | 39.8 |
| N3 | 15/11/2012 | 30 | 40.1 |
| N5 | 15/11/2012 | 30 | 40.9 |
| SS2 | 15/11/2012 | 30 | 38.3 |

Day-time and night time noise levels at all boundary locations did not exceed the daytime emission limit LAeq of 55dB and 45 dB respectively.

It is noted that the predominant noise source on site were non site related traffic noise and the flow of water.



3.2.7 Surface Water Monitoring

3.2.7.1 Surface Water Monitoring Locations

In total, five surface water locations were monitored in 2012 with differing biannual and annual parameter requirements as outlined in Table D.6.1 of the waste licence (SS1, SS2, SS4, SS6 and SS7).

The surface water monitoring locations are located in the catchment drains along the perimeter of the facility. These drains collect surface water run-off from the site and ultimately discharge to the Shannon Estuary via a sluice gate.

Monitoring location SS1 is located in the catchment drain along the eastern boundary of the facility adjacent to Cell No. 3. Monitoring locations SS2 and SS4 are located in a drain at the southern tip of the landfill. SS6 and SS7 are both estuarine locations. Monitoring location SS6 was dry in August 2012 and SS7 was dry in both February and August, therefore no sample could be collected on the sampling date.

Monitoring locations are listed in Table 3.16 below and are illustrated on Figure 2.

Location Northing Easting SS1 144.000 160.040 SS₂ 143.879 159.874 SS4 143.936 160.003 SS6 143.907 159.862 SS7 143.927 159.873

Table 3.16 Surface Water Monitoring Locations

3.2.7.2 Surface Water Monitoring

Surface water monitoring was conducted on a biannual basis at the five locations detailed in Table 3.16. Sampling involved the submergence of the designated sample container into the surface water body.

During submergence, every effort was made to keep the container steady so as to prevent sediment disturbance. Samples were collected and submitted to an accredited laboratory for analysis in February and August for the range of parameters outlined in Table D.6.1 of W0037-01.

Surface water analytical results are attached in Appendix F.

There is no surface water emission limits stipulated in waste licence W0037-01. Therefore, all surface water monitoring results have been compared to the Thresholds, AA-EQS's (Annual Average Environmental Quality Standard) and MAC-EQS's (Maximum Admissible Concentration Environmental Quality Standard Thresholds) specified in the Surface Water Quality Regulations SI 272 of 2009 applicable to transitional waters (Shannon Estuary at Shannon).



Ammonia levels exceeded the IGV of 0.02mg/l in all the sampled tested. Results range between 0.14mg/l SS6 (February) to 0.36mg/l SS4 (February).

BOD exceeded the IGV of <4mg/l in 2 of the 7 samples tested this year. SS2 in August read 14mg/l and SS4 in August read 10mg/l. All other results were below the IGV/

Chromium exceeded the IGV of 0.03mg/l in 2 of the 3 samples tested. In August SS1 0.036mg/l and SS4 0.032mg/l. The other sample tested SS2 0.028mg/l.

Cyanide exceeded the IGV of 0.01mg/l in SS4 0.016mg/l in August.

There were no other exceedances of the relevant thresholds or EQS's for any of the parameters analysed during both monitoring rounds undertaken in 2012.

The analytical results indicate that surface water quality is generally good at and beyond the facility boundary.

3.2.7.3 <u>Surface Water Visual Inspections</u>

Visual inspections of surface water drains are carried out on a weekly basis and the visual inspection logs are available for inspection at the facility.



2.8 <u>Meteorological Monitoring</u>

Details of meteorological monitoring conducted at the facility in 2008 are attached in Appendix I. Met Eireann publish meteorological data, which is obtained from their weather station at Shannon Airport.

Meteorological data obtained from the Met Eireann weather station at Shannon Airport is summarised in the first three columns of Table 3.17 below.

Table 3.17 Summary Rainfall Data

| Month | Rainfall (mm) Shannon Airport | Evapotranspiration (mm) Shannon Airport | Evaporation (mm) | Estimated Effective Rainfall – Capped Area (mm) | Estimated Effective Rainfall – Active Cell (mm) |
|-------|--|---|---------------------|---|---|
| JAN | 111.8 | 16.3 | 21.1 | 95.5 | 90.7 |
| FEB | 38.6 | 17.9 | 24.7 | 20.7 | 13.9 |
| MAR | 28.3 | 40.1 | 56.3 | 0* | 0* |
| APR | 78.2 | 52.7 | 79.4 | 25.5 | 0* |
| MAY | 38.8 | 77.8 | 110.5 | 0* | 0* |
| JUN | 166.9 | 66.3 | 94.5 | 100.6 | 72.4 |
| JUL | 112.8 | 72.2 | 103.3 | 40.6 | 9.5 |
| AUG | 89.1 | 64.4 | 88.3 | 24.7 | 0.8 |
| SEP | 61.9 | 43.9 | 62.4 | 18 | 0* |
| ОСТ | 85.6 | 24.2 | 34.2 | 61.4 | 51.4 |
| NOV | 121.0 | 12.4 | 16.7 | 108.6 | 104.3 |
| DEC | 113.7 | 12.4 | 15.9 | 101.3 | 97.8 |
| TOTAL | 1046.7 | 500.6 | 707.3 | 596.9 | 440.8 |

^{*}Denotes months where evaporation and/or evapotranspiration exceeded total rainfall

Rainfall data obtained from the Met Eireann weather station at Shannon Airport estimated that the site received approximately 1046.7 mm of rainfall from January 2012 to December 2012.

Effective rainfall for capped and non-capped/active cells was calculated as follows:

Effective Rainfall (mm) = Net Precipitation (mm) – Loss by Evapotranspiration (mm) (for capped cells)

Effective Rainfall (mm) = Net Precipitation (mm) – Loss by Evaporation (mm) (for active cells)

3.2.9 <u>Annual Water Balance Calculation and Interpretation for Cells</u>

The water balance was calculated using the average monthly figure of sludge disposed in 2012, which was 88 tonnes. A water balance is used to calculate the difference between rainfall on landfilled areas and the various losses prior to leachate generation.

Water balance calculations are attached in Appendix I.

The method used is based on equation developed by Ehring (Quality and Quantity Sanitary Landfill Leachate, 1983). This method is based on the use of a mathematical equation, which provides a conservative estimate, which caters for the worst-case scenarios.



The equation is as follows: L0 = [(ER.a) + LW + IR] - [aW]Where:

L₀: Free Leachate Produced

ER: Effective Rainfall (net precipitation after loss by evaporation)

A: Area of Cell(s)

LW: Liquid waste

IR: Infiltration from restored areasaW: Absorptive capacity of waste

a_A: Active areaaR: Restored areaAL: Lagoon area

WA: Waste in active area WR: Waste in restored area

Based on the calculations it is estimated that approximately 2,856 m3 (upper bound) and 2,104 m3 (lower bound) of leachate was produced on site in 2012. As the majority of the landfill is capped the potential for leachate generation is reduced.

3.2.10 Resource and Energy Consumption Summary

The only consumer of electricity at the facility is the leachate pump, which pumps the leachate from the leachate collection sump to the WWTP. The contribution of this sump to the overall electrical output of the entire WWTP is minor. The leachate pump is in operation for approximately 4 hrs per day.

Diesel is used to fuel the vehicles used on site namely the sludge dumper trucks and the tractor. Diesel is stored in a 5,000 litre capacity bunded tank located on site. Approximately 2050 litres of diesel were used in 2012.

Mains water is provided via the public mains supply, however water usage at the facility is not metered.

3.2.11 Tank, Pipeline and Bund Integrity Testing and Inspection

The facility contains one bunded diesel tank as outlined in Section 3.2.10. The bund was installed in 2006 and the integrity assessment report was forwarded to the Agency as part of the 2006 AER. The bund is regularly inspected and tested by site personnel to verify integrity.

3.2.12 Review of Nuisance Controls

The assistant landfill supervisor conducts daily inspections of the landfill and the facility and records any incidents in daily duty sheets which are stored at the facility. The inspections are undertaken to identify any environmental nuisances caused by vermin, birds, flies, mud, dust, litter, and odours. No complaints or incidents were received by the facility in 2012.



Rentokil carry out pest control in the treatment plant but no incidences of vermin have been reported on the landfill site. Birds and flies do not pose a problem at the site as there is no domestic refuse being deposited in the landfill; therefore there are no nuisance controls in place for birds or flies.

According to facility management:

- No complaints regarding odours were received in 2012.
- There is no problem with litter at the facility and no complaints were received in 2012 in this regard.
- There are no noise sensitive locations in the immediate vicinity of the facility and no complaints regarding noise from the facility were received in 2012.

The only vehicles that use the site roads are a tractor owned by Response Engineering Limited and a 5-tonne sludge dumper truck. These are used to deposit the sludge to the landfill from the WWTP. The vehicles travel on a private road between the two sites and do not travel outside the boundary of the two sites.

In general, dust is not a problem encountered at the facility and thus no dust suppression measures are considered necessary. Dust monitoring is currently undertaken as per Table D.3.1 of the licence and no exceedance was detected in 2012.



4.0 MANAGEMENT OF THE FACILITY

4.1 Management and Staffing Structure

Clare County Council has been responsible for the facility since November 2004. The facility was previously managed by Shannon Development. The facility is under the operational control of the landfill manager – Neil Ronan. The assistant landfill managers are Ailish Johnston, Paul O Keeffe and Michael Lynch. In addition, there is one weighbridge operator, John O Brien. The current management structure is outlined in Table 4.1 below.

Table 4.1 Management and Staffing Structure

| | • | • | |
|-----------------|-------------------------------|--|------------------|
| Name | Position | Responsibilities | Replacement |
| Neil Ronan | Landfill Manager | Land Fill Management | Ailish Johnson |
| Ailish Johnston | Landfill Assistant Manager | Landfill management, monthly reporting, environmental monitoring, nuisance control | Paul O Keeffe |
| Paul O'Keeffe | Landfill Assistant Manager | Landfill management, monthly reporting, environmental monitoring, nuisance control | Michael Lynch |
| Michael Lynch | Landfill Assistant Manager | Landfill management, monthly reporting, environmental monitoring, nuisance control | John O Brien |
| John O Brien | Weighbridge operator | Weighing sludge | Henry Greensmith |

4.2 <u>Environmental Management Programme/Environmental Objectives and Targets</u>

The 2011 AER did not specify any environmental objectives and targets for 2012.

4.3 Schedule of Environmental Objectives and Targets for 2012

The licensee conducted a review of the EMS in 2011 and found that no changes to the EMS were required and therefore there are no amendments to the environmental objectives and targets required for the year 2012.



4.4 <u>Facility Procedures</u>

No new procedures were developed or implemented at the site between January 2012 and December 2012.

4.5 <u>Financial Provision</u>

In accordance with Condition 12 of the licence, Charges and Financial Provisions, Clare County Council has the ability to meet any financial commitments or liabilities incurred by the undertaking of the activities relating to the facility. Clare County Council annually in the preparation of the "Book of Estimates" and the passing of these estimates shall make provisions for any capital works and maintenance works required to fulfil the conditions of the waste licence for the facility.

Clare County Council also carries adequate insurance to deal with their liabilities. The type and level of insurance is constantly monitored and updated as required.

4.6 Staff Training

An Environmental Awareness Programme has been developed and implemented at the facility. A copy of the Programme was included in the 2006 AER. The Programme sets out environmental issues relevant to all site staff, contractors and visitors to the facility. Training for all staff involved in the operation of the facility is recorded in the training and awareness programme which includes a sign out section for staff members to record their attendance to courses.

Spill kit and chemical handling training was undertaken for staff employed at the facility in October 2007 and copies of training records were included in the 2007 AER.

No additional environmental training was undertaken in 2012.

4.7 <u>Programme for Public Information</u>

All information and correspondence supplied to the EPA (other than commercially sensitive information) and received from the EPA, is available to the public to view at Tradaree Point WWTP, Shannon (Clonmoney South), Co. Clare. This includes a copy of the waste licence, all reports, monitoring results and interpretations required by the licence and other correspondence between the EPA and the facility. Any member of the public may view the information between the hours of 10.00 and 16.00 and by appointment only, at the below address.



All requests concerning the environmental performance of the facility should be forwarded to: Mr Neil Ronan,
Facility Manager,
Tradaree Point Sludge Disposal Facility,
Shannon (Clonmoney South),
Co. Clare
Tel: 061 364477

4.8 Facility Notice Board

In compliance with Condition 3.3 of Waste Licence W0037-01, a facility notice is in place at the entrance to the landfill site adjacent to the main gate, and contains all the details outlined in Section 3.3.3 of the licence.

5.0 REPORTED INCIDENTS AND COMPLAINTS SUMMARY

During the reporting period January 2012 to December 2012, no incidents occurred which would require reporting to the relevant authorities. No complaints or incidents were reported to the facility between January and December 2012.

5.1 **Incidents**

None recorded.

5.2 Non-compliances

No non-compliances were recorded.

5.3 Complaints

None Received.



5.4 Waste Record

Records of the amount and type of sludge (either industrial or domestic) disposed at the facility are kept on file at the facility. Receipts of incoming sludge are recorded at the weighbridge and filed. The weekly records from the weighbridge are then filed and stored in the administration building of the facility. The total quantity of the waste sludge is recorded on a weekly basis and is logged in a waste register that is kept on site at all times. Quantities of waste sludge disposed of to landfill are recorded in the monthly reports for the WWTP and also the AER.

The following information is recorded in the waste register;

- Name of the person transporting the load
- Date of transportation
- Sludge quantity
- Sludge type
- The name of the machine operator
- The cell in which the sludge is to be disposed

The site caretaker signs the logbook to confirm the sludge has been inspected prior to acceptance to the landfill. The records are then transferred to the site office where they are logged on a computer database.

The weighbridge was last calibrated in December 2011.

Section 2 contains further information regarding sludge management.



6.0 FACILITY DEVELOPMENT

6.1 <u>Developments during 2012</u>

There were no other development works of note undertaken at the facility between January and December 2012.

6.2 <u>Proposed Development of the Facility and Associated Timescales</u>

Facility development works planned for 2013.

Cell 1 is currently active and on reaching its full capacity it will be capped and landfilling of Cell 2 will commence. It is expected that this will occur in 2013.



FIGURE 1 – SITE LOCATION MAP









FIGURE 2 – SITE PLAN SHOWING ENVIRONMENTAL MONITORING LOCATIONS





Tradaree Point AER 2012



APPENDICES

| | Page |
|---|------|
| Appendix A - Dust Monitoring Results | 41 |
| Appendix B - Noise Monitoring Results | 43 |
| Appendix C - Landfill Gas Monitoring Results | 45 |
| Appendix D - Groundwater Monitoring Results | 52 |
| Appendix E - Leachate Monitoring Results and Pumping Data | 54 |
| Appendix F - Surface Water Monitoring Results | 57 |
| Appendix G - Copies of Laboratory Reports | 59 |
| Appendix H - Meteorological Data | 124 |
| Appendix I - Water Balance Calculations | 137 |



APPENDIX A – DUST MONITORING RESULTS



BHP/CL/02D

TEST REPORT

Client: Response Engineering

Shannon Town WWTP

Traderee Shannon Co.Clare

FTAO: Ailish Johnston

BHP Ref. No.: 105419

Order No:

Date Received: 15/08/12 Date Tested: 12/03/12 Test Specification: Nil Item: See below

Issue 2

Analysing Testing Consulting Calibrating

13HP

BHP
New Road
Thomondgate
Limerick
Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mall bhpcem2@bhp.ie

| TEST | Client Reference | Units | Results | Standard Reference |
|-----------------|------------------|-----------|---------|-----------------------|
| | Tradree Landfill | | | |
| Dust Deposition | N1 | mg/m²/day | 106.1 | VDI 2119 Part2 |
| Dust Deposition | N3 | mg/m²/day | 64.4 | VDI 2119 Part2 |
| Dust Deposition | SS2 | mg/m²/day | 202.2 | VDI 2119 Part2 |
| Dust Deposition | N5 | mg/m²/day | 193.8 | VDI 2119 Part2 |
| | | | | |
| | | | | |

Additional Information: All samples are inside the EPA Limit of 350 mg/m²/day.

Sampling occurred during the period 18/07/12-15/08/12

Authorised by:

Date of Issue: 01/03/13

Joan McCarthy Captle Hannam

Test results relate only to this/these items. This test report shall not be duplicated in full without the permission of the test laboratory.

Page 1 of 1



APPENDIX B – NOISE SURVEY REPORT



Tradaree WWTP

Environmental Noise Monitoring 15th November 2012

| Code | Location | Time | Range dB | Average dB | Maximum dB | Background Noise | Compliant |
|------------------|----------------------------------|---------------------|-------------|------------|---------------|--------------------------------|-----------|
| N1 Daytime | Boundary @ Landfill Cell 3 | 10.00 - 10.30 | 30-90 | 43.7 | 53.4 | Road Traffic | Yes |
| N2 Daytime | Boundary @ Landfill Cell 1 | 10.35 - 11.05 | 30-90 | 41.8 | 56.5 | Road Traffic, | Yes |
| N3 Daytime | Boundary @ Lagoon | 11.25 - 11.55 | 30-90 | 40.6 | 58.9 | Road Traffic, Flow of Water | Yes |
| N5 Daytime | Boundary @ Landfill Cell 4 | 09.20 - 09.50 | 30-90 | 41.3 | 55.4 | Road Traffic | Yes |
| N1 Night-Time | Boundary @ Landfill Cell 3 | 01.40 - 02.10 | 30-90 | 39.8 | 48.7 | Road Traffic | Yes |
| N2 Night-Time | Boundary @ Landfill Cell 1 | 02.15 - 02.45 | 30-90 | 38.3 | 48.3 | Road Traffic, | Yes |
| N3 Night-Time | Boundary @ Lagoon | 00.20 - 00.50 | 30-90 | 40.1 | 46.2 | Road Traffic, Flow of Water | Yes |
| N5 Night-Time | Boundary @ Landfill Cell 4 | 01.05 - 01.35 | 30-90 | 40.9 | 49.1 | Road Traffic | Yes |

The weather was mainly dry with a few light showers throughout the Daytime and Night-Time noise measurements.

The Noise meter was an INFOTECH – SLM – 1352A and was calibrated on the morning of the test.

Conclusion:

The average figures show that there are no noise issues on site. All results obtained from the measurements taken at the four locations by day and night are within the daytime and night-time limits of 55dBA and 45dBA. The noises that were most evident on site were the road traffic and the flow of water. It is clear from carrying out this report that the Waste Water Treatment Plant is having a minimal impact on the local environment in terms of Noise Pollution.



APPENDIX C – Landfill Gas Monitoring Results



| | | Lar | ndfill Gas Ana | alysis | | | |
|---------------|--------------|-------------|--------------------|---------------|----------|----------|------|
| <u>.</u> | | |) | | | | |
| Month | January 2012 | | | | | | |
| | | | | | | | |
| Date | Location | CO2 | Methane | 02 | Pressure | Atmosph | Temp |
| | | % | % | % | mBar | Pressure | ОС |
| 12/01/2012 | RD1 | 3.1 | 0.7 | 20.4 | 0.1 | 1019 | 12 |
| | RD2 | 4.1 | 0.9 | 19.3 | 0.1 | 1019 | 12 |
| | RD3 | 3 | 7.4 | 12.1 | 0.9 | 1020 | 12 |
| | RD4 | 6.3 | 7.9 | 5.9 | 2.1 | 1020 | 12 |
| | RD5 | 0.2 | 7.3 | 16.1 | 0.1 | 1019 | 12 |
| | RD6 | 15.7 | 59.5 | 0.1 | 2.3 | 1019 | 12 |
| | RD7 | 1 | 0.1 | 20.1 | 0 | 1019 | 12 |
| | RD8 | 0 | 0 | 20.2 | 0 | 1019 | 12 |
| | L6 | 0.1 | 0.1 | 20.1 | 2.8 | 1019 | 12 |
| | L8 | 0 | 0 | 20 | 1.6 | 1019 | 12 |
| | L10 | 0.1 | 0.1 | 20.1 | 1.1 | 1019 | 12 |
| | L12 | 0.1 | 0.2 | 19.9 | 0.8 | 1019 | 12 |
| Trigger Level | | 1.5% v/v | 1% v/v | | | | |
| | | Shading inc | dicates trigger le | evel exceeded | d | | |

| | | Lanc | Ifill Gas Ana | ılysis | | | |
|---------------|-------------|--------------|------------------|--------------|----------|----------|------|
| | | | | | | | |
| Month | February 20 | 12 | | | | | |
| | | | | | | | |
| Date | Location | CO2 | Methane | 02 | Pressure | Atmosph | Temp |
| | | % | % | % | mBar | Pressure | оС |
| 15/02/2012 | RD1 | 4.4 | 0.2 | 13.6 | | 1036 | 12 |
| | RD2 | 3.9 | 0.8 | 17.2 | | 1036 | 12 |
| | RD3 | 4.4 | 0.5 | 16.9 | | 1037 | 13 |
| | RD4 | 5.3 | 6.1 | 7.3 | | 1036 | 13 |
| | RD5 | 7.0 | 3.0 | 6.8 | | 1037 | 13 |
| | RD6 | 12.3 | 45.6 | 0.5 | | 1036 | 12 |
| | RD7 | 0.2 | 0.0 | 19.9 | | 1036 | 12 |
| | RD8 | 0.2 | 0.0 | 19.8 | | 1036 | 13 |
| | L6 | 0.1 | 0.0 | 20.0 | | 1035 | 11 |
| | L8 | 0.0 | 0.0 | 20.0 | | 1035 | 11 |
| | L10 | 0.0 | 0.0 | 20.0 | | 1035 | 11 |
| | L12 | 0.0 | 0.0 | 20.0 | | 1035 | 12 |
| Trigger Level | | 1.5% v/v | 1% v/v | | | | |
| | | Shading indi | cates trigger le | vel exceeded | | | |



| | | Land | fill Gas Ana | llysis | | | |
|------------|------------|----------|-----------------|--------------|----------|----------|------|
| Month | March 2012 | | | | | | |
| Date | Location | CO2 | Methane | 02 | Pressure | Atmosph | Temp |
| | | % | % | % | mBar | Pressure | οС |
| 07/03/2012 | RD1 | 4.2 | 0.0 | 15.2 | | 1030 | 12.5 |
| | RD2 | 3.6 | 8.3 | 16.1 | | 1030 | 12.9 |
| | RD3 | 1.6 | 0.3 | 18.2 | | 1030 | 13.1 |
| | RD4 | 1.2 | 1.0 | 17.5 | | 1031 | 12.9 |
| | RD5 | 5.8 | 1.8 | 10.5 | | 1031 | 12.8 |
| | RD6 | 8.8 | 34.9 | 8.6 | | 1030 | 13.7 |
| | RD7 | 0.2 | 0.0 | 18.5 | | 1030 | 13.3 |
| | RD8 | 0.1 | 0.0 | 18.5 | | 1030 | 13.6 |
| | L6 | 0.8 | 0.0 | 16.9 | | 1030 | 12.6 |
| | L8 | 0.0 | 0.0 | 18.5 | | 1030 | 12.7 |
| | L10 | 0.0 | 0.0 | 18.5 | | 1030 | 13.0 |
| | L12 | 0.0 | 0.0 | 18.4 | | 1030 | 13.2 |
| Trigger I | _evel | 1.5% v/v | 1% v/v | | | | |
| | | • | ates trigger le | vel exceeded | | | |

| | | Land | fill Gas Ana | llysis | | | |
|---------------|------------|---------------|-----------------|--------------|----------|----------|------|
| | | | | | | | |
| Month | April 2012 | | | | | | |
| | | | | | | | |
| Date | Location | CO2 | Methane | O2 | Pressure | Atmosph | Temp |
| | | % | % | % | mBar | Pressure | οС |
| 23/04/2012 | RD1 | 5.1 | 0.0 | 15.3 | | 993 | 13.8 |
| | RD2 | 5.9 | 18.8 | 15.2 | | 993 | 14.2 |
| | RD3 | 2.9 | 2.2 | 19.5 | | 993 | 14.0 |
| | RD4 | 7.4 | 7.9 | 0.4 | | 993 | 13.9 |
| | RD5 | 13.9 | 11.0 | 0.4 | | 993 | 14.0 |
| | RD6 | 13.0 | 58.0 | 0.7 | | 993 | 13.4 |
| | RD7 | 0.2 | 0.0 | 20.6 | | 993 | 13.9 |
| | RD8 | 0.3 | 0.2 | 20.6 | | 993 | 13.7 |
| | L6 | 0.2 | 0.0 | 20.6 | | 993 | 13.5 |
| | L8 | 0.1 | 0.0 | 20.3 | | 993 | 13.3 |
| | L10 | 0.1 | 0.0 | 20.8 | | 993 | 14.0 |
| | L12 | 0.1 | 0.0 | 20.6 | | 993 | 13.5 |
| Trigger Level | | 1.5% v/v | 1% v/v | | | | |
| | | Shading indic | ates trigger le | vel exceeded | | | |



| | | Land | fill Gas Ana | lysis | | | |
|---------------|----------|----------------|-----------------|--------------|----------|----------|------|
| | | | | | | | |
| Month | May 2012 | | | | | | |
| | | | | | | | |
| Date | Location | CO2 | Methane | 02 | Pressure | Atmosph | Temp |
| | | % | % | % | mBar | Pressure | оС |
| 15/05/2012 | RD1 | 3.8 | 0.1 | 17.5 | | 1020 | 13.2 |
| | RD2 | 2.7 | 8.1 | 18.2 | | 1021 | 12.2 |
| | RD3 | 1.5 | 0.1 | 20.1 | | 1021 | 12.9 |
| | RD4 | 6.7 | 10.8 | 3.9 | | 1021 | 13.5 |
| | RD5 | 6.9 | 5.3 | 12.2 | | 1021 | 12.9 |
| | RD6 | 13.4 | 57.4 | 0.8 | | 1021 | 14.6 |
| | RD7 | 0.0 | 0.0 | 20.8 | | 1021 | 13.3 |
| | RD8 | 0.1 | 0.0 | 20.7 | | 1021 | 12.6 |
| | L6 | 1.4 | 0.0 | 20.0 | | 1020 | 12.9 |
| | L8 | 0.1 | 0.0 | 20.8 | | 1020 | 12.4 |
| | L10 | 0.1 | 0.0 | 20.9 | | 1020 | 13.0 |
| | L12 | 0.0 | 0.0 | 20.8 | | 1020 | 14.2 |
| Trigger Level | | 1.5% v/v | 1% v/v | | | | |
| | | Shading indica | ates trigger le | vel exceeded | | | |

| | | Land | fill Gas Ana | lysis | | | |
|---------------|-----------|----------------|-----------------|--------------|----------|----------|------|
| | | | | | | | |
| Month | June 2012 | | | | | | |
| | | | | | | | |
| Date | Location | CO2 | Methane | O2 | Pressure | Atmosph | Temp |
| | | % | % | % | mBar | Pressure | оС |
| 19/06/2012 | RD1 | 2.3 | 0.1 | 17.9 | | 1017 | 15.1 |
| | RD2 | 1.3 | 2.4 | 19.3 | | 1018 | 14.8 |
| | RD3 | 0.8 | 0.2 | 19.9 | | 1018 | 13.3 |
| | RD4 | 7.1 | 10.6 | 1.3 | | 1018 | 14.7 |
| | RD5 | 11.3 | 13.0 | 0.6 | | 1018 | 14.6 |
| | RD6 | 13.9 | 65.4 | 2.1 | | 1017 | 14.5 |
| | RD7 | 0.0 | 0.0 | 20.5 | | 1018 | 13.8 |
| | RD8 | 0.0 | 0.0 | 20.3 | | 1018 | 13.9 |
| | L6 | 3.5 | 0.1 | 16.8 | | 1017 | 13.6 |
| | L8 | 0.0 | 0.0 | 20.3 | | 1018 | 13.9 |
| | L10 | 0.0 | 0.0 | 20.2 | | 1017 | 14.1 |
| | L12 | 0.0 | 0.0 | 20.2 | | 1017 | 14.0 |
| Trigger Level | | 1.5% v/v | 1% v/v | | | | |
| | | Shading indica | ates trigger le | vel exceeded | | | |



| | | Land | fill Gas Ana | ılysis | | | |
|---------------|-----------|----------------|-----------------|--------------|----------|----------|---------|
| | | | | | | | |
| Month | July 2011 | | | | | | |
| | | | | | | | |
| Date | Location | CO2 | Methane | 02 | Pressure | Atmosph | Temp |
| | | % | % | % | mBar | Pressure | оС |
| 12/07/2012 | RD1 | 2.0 | 0.1 | 18.8 | | 1006 | 14.8 |
| | RD2 | 0.3 | 0.1 | 20.6 | | 1006 | 14.6 |
| | RD3 | 0.4 | 0.1 | 20.9 | | 1007 | 14.8 |
| | RD4 | 3.4 | 0.2 | 13.6 | | 1007 | 15.1 |
| | RD5 | 7.8 | 3.2 | 8.7 | | 1007 | 14.9 |
| | RD6 | 11.5 | 47.3 | 6.7 | | 1007 | 15.2 |
| | RD7 | 0.1 | 0.0 | 21.3 | | 1005 | 14.7 |
| | RD8 | Flooded | Flooded | Flooded | | Flooded | Flooded |
| | L6 | 11.6 | 1.0 | 8.7 | | 1007 | 14.9 |
| | L8 | 0.1 | 0.0 | 21.0 | | 1007 | 14.8 |
| | L10 | 0.1 | 0.0 | 21.0 | | 1007 | 14.9 |
| | L12 | 0.1 | 0.0 | 21.0 | | 1007 | 14.7 |
| Trigger Level | | 1.5% v/v | 1% v/v | | | | |
| | | Shading indica | ates trigger le | vel exceeded | | | |

| | | Land | fill Gas Ana | lysis | | | |
|---------------|-------------|---------------|------------------|--------------|----------|----------|---------|
| | | | | | | | |
| Month | August 2012 | | | | | | |
| | | | | | | | |
| Date | Location | CO2 | Methane | O2 | Pressure | Atmosph | Temp |
| | | % | % | % | mBar | Pressure | оС |
| 15/08/2012 | RD1 | 1.1 | 0.0 | 19.2 | | 985 | 15.8 |
| | RD2 | 3.1 | 18.2 | 14.7 | | 985 | 15.6 |
| | RD3 | 1.7 | 2.6 | 18.3 | | 985 | 15.2 |
| | RD4 | 2.7 | 0.0 | 16.7 | | 985 | 15.8 |
| | RD5 | 6.2 | 0.4 | 12.3 | | 985 | 16.1 |
| | RD6 | 13.8 | 60.3 | 4.3 | | 984 | 16.4 |
| | RD7 | 0.0 | 0.0 | 20.4 | | 984 | 15.7 |
| | RD8 | Flooded | Flooded | Flooded | | Flooded | Flooded |
| | L6 | 6.6 | 0.2 | 14.3 | | 985 | 16.2 |
| | L8 | 0.1 | 0.0 | 20.4 | | 984 | 15.9 |
| | L10 | 0.1 | 0.0 | 20.4 | | 984 | 15.7 |
| | L12 | 0.0 | 0.0 | 20.6 | | 984 | 16.1 |
| Trigger Level | | 1.5% v/v | 1% v/v | | | | |
| | | Shading indic | ates trigger lev | vel exceeded | | | |



| | | Land | fill Gas Anal | ysis | | | |
|---------------|----------------|----------------|------------------|-------------|----------|----------|---------|
| Month | September 2012 | | |] | | | |
| Date | Location | CO2 | Methane | 02 | Pressure | Atmosph | Temp |
| | | % | % | % | mBar | Pressure | оС |
| 24/09/2012 | RD1 | 1.4 | 0.2 | 20.2 | | 993 | 15.1 |
| | RD2 | 3.9 | 32.8 | 12.2 | | 993 | 15.7 |
| | RD3 | 1.5 | 1.5 | 19.9 | | 993 | 14.8 |
| | RD4 | 4.7 | 0.3 | 15.5 | | 993 | 14.7 |
| | RD5 | 16.3 | 15.9 | 1.0 | | 993 | 15.5 |
| | RD6 | 15.6 | 71.3 | 1.8 | | 993 | 15.7 |
| | RD7 | 0.1 | 0.2 | 20.6 | | 993 | 14.9 |
| | RD8 | Flooded | Flooded | Flooded | | Flooded | Flooded |
| | L6 | 1.6 | 0.3 | 19.6 | | 993 | 15.3 |
| | L8 | 0.1 | 0.2 | 20.8 | | 993 | 15.1 |
| | L10 | 0.1 | 0.3 | 20.6 | | 993 | 15.1 |
| | L12 | 0.1 | 0.3 | 20.4 | | 993 | 14.8 |
| Trigger Level | | 1.5% v/v | 1% v/v | | | | |
| | | Shading indica | ates trigger lev | el exceeded | | | |

| | | Landi | fill Gas Anal | ysis | | | |
|---------------|--------------|----------------|-------------------|-------------|----------|----------|---------|
| | | | | | | | |
| Month | October 2012 | | | | | | |
| | | | | | | | |
| Date | Location | CO2 | Methane | 02 | Pressure | Atmosph | Temp |
| | | % | % | % | mBar | Pressure | оС |
| 16/10/2012 | RD1 | 2.1 | 0.3 | 18.3 | | 997 | 9.2 |
| | RD2 | 4.1 | 28.0 | 13.1 | | 997 | 9.1 |
| | RD3 | 2.2 | 1.4 | 19.2 | | 997 | 9.3 |
| | RD4 | 8.1 | 1.9 | 8.5 | | 997 | 9.1 |
| | RD5 | 17.0 | 24.8 | 0.2 | | 997 | 9.4 |
| | RD6 | 11.3 | 53.2 | 5.7 | | 997 | 9.1 |
| | RD7 | 0.1 | 0.2 | 19.8 | | 997 | 9.1 |
| | RD8 | Flooded | Flooded | Flooded | | Flooded | Flooded |
| | L6 | 0.6 | 0.2 | 19.8 | | 997 | 9.5 |
| _ | L8 | 0.1 | 0.2 | 19.9 | | 997 | 9.3 |
| | L10 | 0.1 | 0.2 | 19.7 | | 997 | 9.3 |
| | L12 | 0.1 | 0.2 | 19.6 | | 997 | 9.4 |
| Trigger Level | | 1.5% v/v | 1% v/v | | | | |
| | | Shading indica | ates trigger leve | el exceeded | | | |



| | | Land | fill Gas Anal | ysis | | | |
|---------------|-------------|----------------|-------------------|-------------|----------|----------|------|
| Month | November 20 |)12 | | 1 | | | |
| | | | | | | | |
| Date | Location | CO2 | Methane | O2 | Pressure | Atmosph | Temp |
| | | % | % | % | mBar | Pressure | οС |
| 14/11/2012 | RD1 | 0.3 | 0.3 | 18.2 | | 1019 | 14 |
| | RD2 | 1.9 | 1.0 | 19.8 | | 1019 | 14 |
| | RD3 | 2.5 | 0.7 | 19.7 | | 1019 | 14 |
| | RD4 | 3.6 | 21.2 | 9.6 | | 1019 | 14 |
| | RD5 | 17.3 | 26.8 | 0.3 | | 1019 | 14 |
| | RD6 | 13.6 | 62.6 | 0.8 | | 1019 | 14 |
| | RD7 | 0.1 | 0.3 | 20.5 | | 1019 | 14 |
| | RD8 | 0.4 | 0.6 | 19.1 | | 1019 | 14 |
| | L6 | 2.3 | 0.5 | 17.4 | | 1019 | 14 |
| | L8 | 0.1 | 0.3 | 20.6 | | 1019 | 14 |
| | L10 | 0.1 | 0.3 | 20.5 | | 1019 | 14 |
| | L12 | 0.1 | 0.3 | 20.5 | | 1019 | 14 |
| Trigger Level | | 1.5% v/v | 1% v/v | | | | |
| | | Shading indica | ates trigger leve | el exceeded | | | |

| | | Land | fill Gas Anal | ysis | | | |
|---------------|-------------|----------|------------------|-------------|----------|----------|------|
| | | | | | | | |
| Month | December 20 | 12 | | | | | |
| | | 1 | 1 | | 1 | | |
| Date | Location | CO2 | Methane | 02 | Pressure | Atmosph | Temp |
| | | % | % | % | mBar | Pressure | оС |
| 06/12/2012 | RD1 | 6.5 | 0.4 | 11.3 | | 1007 | 7 |
| | RD2 | 2.9 | 1.2 | 20.1 | | 1007 | 7 |
| | RD3 | 2.7 | 0.7 | 20.7 | | 1007 | 7 |
| | RD4 | 5.3 | 7.7 | 6.8 | | 1007 | 7 |
| | RD5 | 17.2 | 29.9 | 0.5 | | 1007 | 7 |
| | RD6 | 12.0 | 49.0 | 2.8 | | 1007 | 7 |
| | RD7 | 0.2 | 0.3 | 21.0 | | 1007 | 7 |
| | RD8 | 0.2 | 0.3 | 21.2 | | 1007 | 7 |
| | L6 | 0.2 | 0.6 | 21.3 | | 1007 | 7 |
| | L8 | 0.2 | 0.3 | 21.2 | | 1007 | 7 |
| | L10 | 0.2 | 0.3 | 20.7 | | 1007 | 7 |
| | L12 | 0.2 | 0.3 | 20.7 | | 1007 | 7 |
| Trigger Level | | 1.5% v/v | 1% v/v | | | | _ |
| | | | ates trigger lev | el exceeded | | | |



APPENDIX D – GROUNDWATER MONITORING RESULTS



Biannual/Annual Groundwater Monitoring Results 2012

| | | EPA | В | H 3 | В | BH 4 | В | H 5 | R | D 2 | R | .D 3 |
|-----------------------|----------------------|-----------|-------|----------|--------|----------|-------|----------|-------|----------|-------|----------|
| PARAMETER | UNIT | IGV | Feb | Aug | Feb | Aug | Feb | Aug | Feb | Aug | Feb | Aug |
| рН | | ≥6.5-≤9.5 | 6.84 | 6.80 | 6.71 | 6.93 | 6.79 | 6.95 | 6.52 | 7.48 | 7.04 | 7.53 |
| Temperature | °C | 25 | 10.4 | 12.9 | 10.8 | 13.2 | 10.8 | 13.5 | 10.4 | 12.5 | 11.2 | 13.1 |
| Conductivity | μS/cm | 1000 | 14330 | 10540 | 15140 | 14010 | 11280 | 10420 | 4450 | 3680 | 2820 | 2250 |
| Nitrite | mg/l | - | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 | < 0.1 |
| Nitrate | mg/l | - | 3.56 | 1.67 | 2.83 | 1.19 | 19.84 | 1.16 | 3.1 | 1.65 | 0.27 | 1.15 |
| Total Ammonia | NH3-N | 0.2 | 176.1 | 6.31 | 146.3 | 6.26 | 0.23 | 6.95 | 4.99 | 6.27 | 1.21 | 0.11 |
| Chloride | Cl mg/l | 30 | 851.3 | 38.2 | 1680.7 | 52.1 | 3470 | 54.3 | 880.8 | 93.8 | 394 | 45.3 |
| DO | % O ₂ sat | NAC | | 92.3 | | 90.1 | | 87.6 | | 89.6 | | 91.6 |
| Arsenic | As mg/l | 0.01 | | < 0.001 | | < 0.001 | | < 0.001 | | < 0.001 | | < 0.001 |
| Boron | B mg/l | 1 | | 0.003 | | 0.002 | | 0.002 | | 0.003 | | 0.004 |
| Cadmium | Cd mg/l | 0.005 | | < 0.001 | | < 0.001 | | < 0.001 | | < 0.001 | | < 0.001 |
| Calcium | Ca mg/l | 200 | | 26.1 | | 19.7 | | 13.6 | | 28.2 | | 22.2 |
| Chromium | Cr mg/l | 0.03 | | 0.016 | | 0.016 | | 0.056 | | < 0.001 | | < 0.001 |
| Copper | Cu mg/l | 0.03 | | 0.861 | | 0.804 | | 0.606 | | < 0.001 | | < 0.001 |
| Cyanide | Cn mg/l | 0.01 | | < 0.001 | | < 0.001 | | 0.009 | | < 0.001 | | < 0.001 |
| Fluoride | F mg/l | 1 | | 0.26 | | 0.12 | | 0.39 | | 0.45 | | 0.39 |
| Iron | Fe mg/l | 0.2 | | 1.026 | | 1.136 | | 1.127 | | < 0.001 | | < 0.001 |
| Lead | Pb mg/l | 0.01 | | < 0.001 | | < 0.001 | | < 0.001 | | < 0.001 | | < 0.001 |
| Magnesium | Mg mg/l | 50 | | 1.14 | | 2.05 | | 1.09 | | 1.05 | | 1.12 |
| Mercury | Hg mg/l | 0.001 | | < 0.0002 | | < 0.0002 | | < 0.0002 | | < 0.0002 | | < 0.0002 |
| Nickel | Ni mg/l | 0.02 | | < 0.001 | | < 0.001 | | < 0.001 | | < 0.001 | | < 0.001 |
| Potassium | K mg/l | 5 | | 1.32 | | 1.37 | | 1.12 | | 2.96 | | 1.06 |
| Sodium | Na mg/l | 150 | | 13.17 | | 9.07 | | 10.11 | | 12.02 | | 10.05 |
| Sulphate | SO ₄ mg/l | 200 | | 65.7 | | 10.4 | | 7.5 | | 15.4 | | 61.1 |
| Tin | Sn mg/l | - | | < 0.001 | | < 0.001 | | < 0.001 | | < 0.001 | | < 0.001 |
| Total Phosphorus | P mg/l | 0.03 | | 0.03 | | 0.06 | | 0.11 | | 0.06 | | 0.09 |
| Orthophosphate | P mg/l | 0.03 | | 0.01 | | 0.03 | | 0.04 | | 0.05 | | 0.06 |
| Total Organic | | | 40.0 | 4.5 | 10.5 | 4. | | 4.5 | 10.0 | | 24 - | |
| Carbon Total Oxidised | C mg/l | NAC | 19.9 | 12 | 19.3 | 14 | 24.7 | 18 | 19.9 | 16 | 24.6 | 1.2 |
| Nitrogen | N mg/l | NAC | 0.8 | 0.4 | 0.6 | 0.3 | 4.5 | 0.3 | 0.7 | 0.4 | 0.1 | 0.3 |
| Total Phenols | mg/l | 0.0005 | 0.015 | 0.012 | 0.008 | 0.008 | 0.012 | 0.006 | 0.004 | 0.007 | 0.006 | 0.001 |
| Zinc | Zn mg/l | 0.1 | | 0.056 | | 0.064 | | 0.028 | | 0.028 | | 0.032 |
| Solids Total | mg/l | - | | 212 | | 213 | | 230 | | 202 | | 181 |

IGV = Interim Guideline Value – from the EPA document "Towards Setting Guideline Values for the Protection of Groundwater in Ireland Results are Shaded where they Exceed the EPA IGV

NAC = No Abnormal change

n/a = not analysed

n/r = not recorded

 $Analysis\ conducted\ by\ BHP\ Laboratories,\ New\ Road,\ Thomondgate,\ Limerick\ on\ 29^{th}\ February\ and\ 29^{th}\ August\ 2012.$



APPENDIX E – LEACHATE MONITORING RESULTS AND PUMPING DATA



Biannual / Annual Leachate Monitoring Results 2012

| | | EPA | 9 | SS3 |
|-------------------------------|-------|-----------|-------|---------|
| Parameter | Unit | IGV | Feb | Aug |
| Ammonia | mg/l | 0.15 | 6.29 | 0.87 |
| Arsenic | mg/l | 0.01 | | <0.001 |
| BOD Total 5 Day with ATU | mg/l | - | 57 | 4 |
| Boron | mg/l | 1 | | 0.007 |
| Cadmium | mg/l | 0.005 | | <0.001 |
| Calcium | mg/l | 200 | | 18.4 |
| Chloride | mg/l | 30 | 502.5 | 161.7 |
| Chromium | mg/l | 0.03 | | 0.020 |
| COD Total | mg/l | - | 105 | 47 |
| Conductivity | uS/cm | 1000 | 1716 | 877 |
| Copper | mg/l | 0.03 | | <0.001 |
| Cyanide (Total) | mg/l | 0.01 | | <0.001 |
| Dissolved Oxygen | % | NAC | | |
| Flouride | mgF/l | | | 0.11 |
| Groundwater Level | m | - | | |
| Iron | mg/l | 0.2 | | <0.001 |
| Lead | mg/l | 0.01 | | <0.001 |
| Magnesium | mg/l | 50 | | 1.61 |
| Mercury | mg/l | 0.001 | | <0.0002 |
| Mn (Dissolved | | | | |
| Nickel | mg/l | 0.02 | | <0.001 |
| Nitrate | mg/l | | 36.1 | 13.3 |
| Nitrite | mg/l | | 0.2 | <0.1 |
| pH Value | Units | 6.5 - 9.5 | 6.59 | 7.06 |
| Phenol | ug/l | | | |
| Potassium | mg/l | 5 | | 1.32 |
| Sodium | mg/l | 150 | | 13.12 |
| Solids Suspended | | - | | |
| Solids Total | mg/l | | | |
| Sulphate | mg/l | 200 | | 13.7 |
| Surfactant Anionic | ug/l | | | |
| Temperature | °C | 25 | 9.3 | 11.5 |
| Tin | mg/l | | | <0.001 |
| Total Organic Carbon | mg/l | NAC | | |
| Total Oxidised Nitrogen (TON) | mg/l | NAC | 8.1 | 3.0 |
| Total Phosphorus | mg/l | 0.01 | | 0.06 |
| Zinc | mg/l | 0.1 | | 0.021 |
| | | | | |

IGV = Interim Guideline Value - from the EPA Document "Towards Setting Guideline Values for the Protection of Groundwater in Ireland"
Results are shaded where they exceeded the EPA IGV

NAC = No abnormal Change

n/a = not analysed

n/r = not recorded

Analysis conducted by BHP Laboratories, New Road, Thomondgate, Limerick on 29th February and 29th August 2012.



Capped Cells Annual Leachate Monitoring Results 2012

| | | EPA | | L 1 | | L 2 | | L 3 | | L 4 | | L 5 |
|--------------------------|-------|-----------|------|---------|------|---------|------|---------|------|---------|------|---------|
| Parameter | Unit | IGV | Apr | Aug |
| Ammonia | mg/l | 0.15 | 6.31 | 6.88 | 6.52 | 7.09 | 7.12 | 6.21 | 4.21 | 3.66 | 6.89 | 6.26 |
| Arsenic | mg/l | 0.01 | | <0.001 | | <0.001 | | <0.001 | | <0.001 | | <0.001 |
| BOD Total 5 Day with ATU | mg/l | - | 88 | 83 | 227 | 114 | 140 | 27 | 92 | 27 | 184 | 52 |
| Boron | mg/l | 1 | | 0.008 | | 0.006 | | 0.005 | | 0.008 | | 0.005 |
| Cadmium | mg/l | 0.005 | | <0.001 | | <0.001 | | <0.001 | | <0.001 | | <0.001 |
| Calcium | mg/l | 200 | | 22.1 | | 20.1 | | 13.2 | | 22.4 | | 20.1 |
| Chloride | mg/l | 30 | 50.6 | 172.4 | 740 | 132.3 | 36 | 130.3 | 60 | 127.6 | 56 | 161.7 |
| Chromium | mg/l | 0.03 | | 0.064 | | 0.028 | | 0.060 | | 0.020 | | 0.021 |
| COD Total | mg/l | - | 212 | 163 | 297 | 185 | 265 | 50 | 264 | 63 | 233 | 154 |
| Conductivity | uS/cm | 1000 | 2210 | 1789 | 4220 | 3100 | 1600 | 1491 | 1826 | 1544 | 2560 | 2330 |
| Copper | mg/l | 0.03 | | 0.712 | | 0.891 | | 0.202 | | 0.312 | | 0.429 |
| Cyanide (Total) | mg/l | 0.01 | | <0.001 | | 0.026 | | 0.017 | | 0.032 | | 0.039 |
| Dissolved Oxygen | % | NAC | | | | | | | | | | |
| Fluoride | mgF/l | | | 0.29 | | 0.23 | | 0.23 | | 0.35 | | 0.11 |
| Iron | mg/l | 0.2 | | 2.041 | | 3.697 | | 1.049 | | 5.204 | | 3.229 |
| Lead | mg/l | 0.01 | | <0.001 | | <0.001 | | <0.001 | | <0.001 | | <0.001 |
| Magnesium | mg/l | 50 | | 2.11 | | 1.81 | | 2.11 | | 1.96 | | 1.35 |
| Mercury | mg/l | 0.001 | | <0.0002 | | <0.0002 | | <0.0002 | | <0.0002 | | <0.0002 |
| Mn (Dissolved | | | | | | | | | | | | |
| Nickel | mg/l | 0.02 | | <0.001 | | <0.001 | | <0.001 | | <0.001 | | <0.001 |
| Nitrate | mg/l | | <0.1 | 13.7 | <0.1 | 11.7 | <0.1 | 21.9 | <0.1 | 24.5 | <0.1 | 13.3 |
| Nitrite | mg/l | | <0.0 | <0.1 | 2.4 | <0.1 | 0.6 | <0.1 | 2.4 | <0.1 | 1.1 | <0.1 |
| pH Value | Units | 6.5 - 9.5 | 6.57 | 6.88 | 6.38 | 6.67 | 6.51 | 6.75 | 6.54 | 6.69 | 6.55 | 6.78 |
| Phenol | ug/l | | | | | | | | | | | |
| Potassium | mg/l | 5 | | 1.31 | | 1.06 | | 1.13 | | 1.31 | | 1.06 |
| Sodium | mg/l | 150 | | 13.12 | | 16.1 | | 18.12 | | 12.01 | | 11.21 |
| Solids Suspended | | - | | | | | | | | | | |
| Solids Total | mg/l | | | | | | | | | | | |
| Sulphate | mg/l | 200 | | 10.7 | | 14.2 | | 13.1 | | 11.4 | | 14.6 |
| Surfactant Anionic | ug/l | | | | | | | | | | | |
| Temperature | °C | 25 | 11.1 | 12.4 | 11.5 | 12.8 | 11.3 | 13.1 | 11.6 | 12.8 | 11.1 | 13.5 |
| Tin | mg/l | | | <0.001 | | <0.001 | | <0.001 | | <0.001 | | <0.001 |
| Total Organic Carbon | mg/l | NAC | | | | | | | | | | |
| Total Oxidised Nitrogen | mg/l | NAC | <0.1 | 3.1 | 0.5 | 2.6 | 0.13 | 4.9 | 0.54 | 5.5 | 0.25 | 3.0 |
| Total Phosphorus | mg/l | 0.01 | | 0.06 | | 0.07 | | 0.12 | | 0.05 | | 0.08 |
| Zinc | mg/l | 0.1 | | 0.032 | | 0.040 | | 0.028 | | 0.032 | | 0.056 |

IGV = Interim Guideline Value - from the EPA Document "Towards Setting Guideline Values for the Protection of Groundwater in Ireland"

Results are shaded where they exceeded the EPA IGV

NAC = No abnormal Change

n/a = not analysed

n/r = not recorded

Analysis conducted by BHP Laboratories, New Road, Thomondgate, Limerick, on 11th April and 29th August 2012



APPENDIX F – SURFACE WATER MONITORING RESULTS



Biannual/Annual Surface Water Monitoring Results 2012

| | | EPA | S | S1 | S | S2 | S | S4 | S | S6 | S | S7 |
|-------------------------------|-------|-----------|------|---------|------|---------|------|---------|------|-----|-----|-----|
| Parameter | Unit | IGV | Feb | Aug | Feb | Aug | Feb | Aug | Feb | Aug | Feb | Aug |
| Ammonia | mg/l | 0.02 | 0.29 | 0.18 | 0.19 | 0.21 | 0.36 | 0.21 | 0.14 | n/a | n/a | |
| Arsenic | mg/l | 0.02 | | <0.001 | | <0.001 | | <0.001 | | n/a | | |
| BOD Total 5 Day with | | | | | | | | | | | | |
| ATU | mg/l | ≤4 | 3 | 2 | 2 | 14 | 2 | 10 | 2 | n/a | n/a | |
| Boron | mg/l | 1 | | 0.001 | | 0.002 | | 0.001 | | n/a | | |
| Cadmium | mg/l | 0.005 | | <0.001 | | <0.001 | | <0.001 | | n/a | | |
| Calcium | mg/l | 200 | | 26.1 | | 32.1 | | 30.3 | | n/a | | |
| Chloride | mg/l | 30 | | | | | | | | | | |
| Chromium | mg/l | 0.03 | | 0.036 | | 0.028 | | 0.032 | | n/a | | |
| COD Total | mg/l | - | 32 | 22 | 29 | 40 | 29 | 24 | 31 | n/a | n/a | |
| Conductivity | uS/cm | 1000 | | 467 | | 504 | | 512 | | n/a | | |
| Copper | mg/l | 0.03 | | <0.001 | | <0.001 | | <0.001 | | n/a | | |
| Cyanide (Total) | mg/l | 0.01 | | <0.001 | | 0.01 | | 0.016 | | n/a | | |
| Dissolved Oxygen | % | NAC | 96.4 | 85.5 | 98.1 | 76.2 | 97.6 | 78.4 | 92.1 | n/a | n/a | |
| Fluoride | mgF/l | 5.0 | | 0.12 | | 0.11 | | 0.12 | | n/a | | |
| Groundwater Level | m | - | | | | | | | | | | |
| Iron | mg/l | 0.2 | | <0.001 | | <0.001 | | <0.001 | | n/a | | |
| Lead | mg/l | 0.01 | | <0.001 | | <0.001 | | <0.001 | | n/a | | |
| Magnesium | mg/l | 50 | | 2.02 | | 1.99 | | 2.01 | | n/a | | |
| Mercury | mg/l | 0.001 | | <0.0002 | | <0.0002 | | <0.0002 | | n/a | | |
| Mn (Dissolved | Ug/l | | | | | | | | | | | |
| Nickel | mg/l | 0.05 | | <0.001 | | <0.001 | | <0.001 | | n/a | | |
| Nitrate | mg/l | - | | 21.1 | | 11.1 | | 14.2 | | n/a | | |
| Nitrite | mg/l | - | | <0.05 | | <0.05 | | <0.05 | | n/a | | |
| pH Value | Units | 6.5 - 9.5 | 7.65 | 7.66 | 7.95 | 7.70 | 7.96 | 7.44 | 8.06 | n/a | n/a | |
| Phenol | ug/l | | | | | | | | | | | |
| Potassium | mg/l | 5 | | 1.63 | | 1.71 | | 1.82 | | n/a | | |
| Sodium | mg/l | 150 | | 14.07 | | 12.01 | | 13.67 | | n/a | | |
| Solids Suspended | | 50 | 39 | 31 | 23 | 46 | 40 | 86 | 103 | n/a | n/a | |
| Solids Total | mg/l | | | | | | | | | | | |
| Sulphate | mg/l | 200 | | 15.1 | | 28.1 | | 29.3 | | n/a | | |
| Surfactant Anionic | ug/l | | | | | | | | | | | |
| Temperature | ОС | 25 | 8.9 | 9.9 | 9.4 | 10.1 | 8.8 | 10.2 | 9.1 | n/a | n/a | |
| Tin | mg/l | - | | <0.001 | | <0.001 | | <0.001 | | n/a | | |
| Total Organic Carbon | mg/l | NAC | | | | | | | | | | |
| Total Oxidised Nitrogen (TON) | mg/l | NAC | | 4.74 | | 2.49 | | 3.19 | | n/a | | |
| Total Phosphorus | mg/l | - | | 0.03 | | 0.03 | | 0.04 | | n/a | | |
| Zinc | mg/l | 0.1 | | 0.012 | | 0.058 | | 0.060 | | n/a | | |
| | | | | | | | | | | | | |

IGV = Interim Guideline Value - from the EPA Document "Towards Setting Guideline Values for the Protection of Groundwater in Ireland" Results are shaded where they exceeded the EPA IGV

NAC = No abnormal Change

n/a = not analysed Borehole was Dry

n/r = not recorded

Analysis conducted by BHP Laboratories, New Road, Thomondgate, Limerick on 29th February and on 29th August



APPENDIX G – COPIES OF LABORATORY REPORTS

| | 1 |
|----------------------------------|------|
| | Page |
| Ground Water Monitoring Reports | 60 |
| Leachate Monitoring Reports | 81 |
| Surface Water Monitoring Results | 106 |



Groundwater Monitoring Test Reports



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 102746.3

Order No.:

Date Received: 29/02/12 Date Completed: 06/03/12 Test Specification: Nil

Item :See below

New Road Thomondgate Limerick Ireland Tel +353 61 455399

Analysing Testing

Consulting Calibrating

Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|-------------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring BH3 | | | |
| pН | | (4) | 6.84 | APHA - 4500 - H ⁺ |
| Temperature | | ° C | 10.4 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 176.1 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 14330 | APHA - 2510 - B |
| T.O.C | | mg/l | 19.9 | APHA - 5310 - C |
| Phenols | | mg/l | 0.015 | APHA - 5530 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | 3.56 | APHA - 4110 - B |
| Total oxidised Nitro | gen (as N) | mg/l | 0.8 | APHA - 4110 - B |
| Chloride | 78490 0000 | mg/l | 851.3 | APHA - 4110 - B |
| | | | | |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 06/03/2012



TEST REPORT

Client: Response Engineering Traderee TP

Traderee TP Shannon

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105680.3

Order No.:

Date Received: 29/08/12 Date Completed: 11/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

13HP

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mall bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|--|--------|---------|------------------------------|
| | Biannual Landfill Monitoring BH3 | | | |
| pН | | (4) | 6.80 | APHA - 4500 - H ⁺ |
| Temperature | | ° C | 12.9 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 6.31 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 10540 | APHA - 2510 - B |
| T.O.C | | mg/l | 12 | APHA - 5310 - C |
| Phenols | | mg/l | 0.012 | APHA - 5530 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | 1.67 | APHA - 4110 - B |
| Total oxidised Nitrog | gen (as N) | mg/l | 0.4 | APHA - 4110 - B |
| Chloride | STATE OF THE STATE | mg/l | 38.2 | APHA - 4110 - B |
| | | | 1 | |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Client: Response Engineering Traderee TP

Traderee TP Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105683.3

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

|3|**-|**|2

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mall bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------------|-----------------------------------|----------------------|---------|-----------------------|
| | Annual Landfill Monitoring BH3 | | | |
| Dissolved Oxygen | | % O ₂ sat | 92.3 | APHA - 4500-O-G |
| List I Organics | | mg/l | <0.01 | GC-MS |
| List II Organics | | mg/l | <0.01 | GC-MS |
| Detergents (as MBAS) | 1 | mg/l | <0.001 | APHA - 5540 - C |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 3 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 26.1 | APHA - 3120 - B |
| Total Chromium | | ug/l | 16 | APHA - 3120 - B |
| Copper | | ug/l | 861 | APHA - 3120 - B |
| Cyanide | | mg/l | < 0.001 | APHA - 4500 - CN-I |
| Fluoride | | mg/l | 0.26 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Client: Response Engineering Traderee TP

Traderee TP Shannon

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105683.3

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

3112

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mall bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|-----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring BH3 | | | |
| Iron | | ug/l | 1029 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | | mg/l | 1.14 | APHA - 3120 - B |
| Mercury | | ug/l | <0.2 | APHA - 3120 - B |
| Nickel | | ug/l | <1 | APHA - 3120 - B |
| Potassium | | mg/l | 1.32 | APHA - 3120 - B |
| Sodium | | mg/l | 13.17 | APHA - 3120 - B |
| Tin | | ug/l | <1 | APHA - 3120 - B |
| Zinc | | ug/l | 56 | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | 65.7 | APHA - 4110 - B |
| Total Phosphorus (as P) | | mg/l | 0.03 | APHA - 4500 - P |
| OrthoPhosphate (as P) | | mg/l | 0.01 | APHA - 4500 - P-1 |
| Residue on Evaporation | | mg/l | 212 | APHA - 2540- B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 102746.4

Order No.:

Date Received: 29/02/12 Date Completed: 06/03/12

Test Specification: Nil Item :See below

New Road Thomondgate Limerick Ireland Tel +353 61 455399

Analysing Testing

Consulting

Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|-------------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring BH4 | | | |
| pН | | (-) | 6.71 | APHA - 4500 - H ⁺ |
| Temperature | | ° C | 10.8 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 146.3 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 15140 | APHA - 2510 - B |
| T.O.C | | mg/l | 19.3 | APHA - 5310 - C |
| Phenols | | mg/l | 800.0 | APHA - 5530 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | 2.83 | APHA - 4110 - B |
| Total oxidised Nitrogen (as N) | | mg/l | 0.6 | APHA - 4110 - B |
| Chloride | and the said | mg/l | 1680.7 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 06/03/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105680.4

Order No.:

Date Received: 29/08/12 Date Completed: 11/09/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|-------------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring BH4 | | | |
| pН | | (4.) | 6.93 | APHA - 4500 - H ⁺ |
| Temperature | | °C | 13.2 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 6.26 | APHA-4500-NH ₃ -D |
| Conductivity | | µScm⁻¹ | 14010 | APHA - 2510 - B |
| T.O.C | | mg/l | 14 | APHA - 5310 - C |
| Phenols | | mg/l | 0.008 | APHA - 5530 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | 1.19 | APHA - 4110 - B |
| Total oxidised Nitrog | en (as N) | mg/l | 0.3 | APHA - 4110 - B |
| Chloride | 2000 0000 | mg/l | 52.1 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105683.4

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------------|-----------------------------------|----------------------|---------|-----------------------|
| | Annual Landfill Monitoring BH4 | | | |
| Dissolved Oxygen | | % O ₂ sat | 90.1 | APHA - 4500-O-G |
| List I Organics | | mg/l | <0.01 | GC-MS |
| List II Organics | | mg/l | <0.01 | GC-MS |
| Detergents (as MBAS) | 1 | mg/l | <0.001 | APHA - 5540 - C |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 2 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 19.7 | APHA - 3120 - B |
| Total Chromium | | ug/l | 16 | APHA - 3120 - B |
| Copper | | ug/l | 804 | APHA - 3120 - B |
| Cyanide | | mg/l | <0.001 | APHA - 4500 - CN-E |
| Fluoride | | mg/l | 0.12 | APHA - 4110 - B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105683.4

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|-----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring BH4 | | | |
| Iron | | ug/l | 1136 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | | mg/l | 2.05 | APHA - 3120 - B |
| Mercury | | ug/l | <0.2 | APHA - 3120 - B |
| Nickel | | ug/l | <1 | APHA - 3120 - B |
| Potassium | | mg/l | 1.37 | APHA - 3120 - B |
| Sodium | | mg/l | 9.07 | APHA - 3120 - B |
| Tin | | ug/l | <1 | APHA - 3120 - B |
| Zinc | | ug/l | 64 | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | 10.4 | APHA - 4110 - B |
| Total Phosphorus (as P) | | mg/l | 0.06 | APHA - 4500 - P |
| OrthoPhosphate (as P) | | mg/l | 0.03 | APHA - 4500 - P-E |
| Residue on Evaporation | | mg/l | 213 | APHA - 2540- B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 102746.5

Order No.:

Date Received: 29/02/12 Date Completed: 06/03/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|-------------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring BH5 | | | |
| pН | | (4) | 6.79 | APHA - 4500 - H ⁺ |
| Temperature | | 0 C | 10.8 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 0.23 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 11280 | APHA - 2510 - B |
| T.O.C | | mg/l | 24.7 | APHA - 5310 - C |
| Phenols | | mg/l | 0.012 | APHA - 5530 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | 19.84 | APHA - 4110 - B |
| Total oxidised Nitrog | en (as N) | mg/l | 4.5 | APHA - 4110 - B |
| Chloride | 20000 000000 | mg/l | 3470 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 06/03/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105680.5

Order No.:

Date Received: 29/08/12 Date Completed: 11/09/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| | Reference |
|-------|------------------------------|
| | |
| 6.95 | APHA - 4500 - H ⁺ |
| 13.5 | APHA - 2550 - B |
| 6.95 | APHA-4500-NH3-D |
| 10420 | APHA - 2510 - B |
| 18 | APHA - 5310 - C |
| 0.006 | APHA - 5530 - D |
| <0.1 | APHA - 4110 - B |
| 1.16 | APHA - 4110 - B |
| 0.3 | APHA - 4110 - B |
| 54.3 | APHA - 4110 - B |
| | 0.3 |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105683.5

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Testing Consulting Calibrating

Analysing

New Road Thomondgate Limerick

Ireland Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------------|-----------------------------------|----------------------|---------|-----------------------|
| | Annual Landfill Monitoring BH5 | | | |
| Dissolved Oxygen | | % O ₂ sat | 87.6 | APHA - 4500-O-G |
| List I Organics | | mg/l | <0.01 | GC-MS |
| List II Organics | | mg/l | <0.01 | GC-MS |
| Detergents (as MBAS) | | mg/l | < 0.001 | APHA - 5540 - C |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 2 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 13.6 | APHA - 3120 - B |
| Total Chromium | | ug/l | 56 | APHA - 3120 - B |
| Copper | | ug/l | 606 | APHA - 3120 - B |
| Cyanide | | mg/l | 0.009 | APHA - 4500 - CN-I |
| Fluoride | | mg/l | 0.39 | APHA - 4110 - B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Client: Response Engineering Traderee TP

Traderee TP Shannon

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105683.5

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

|3|**-**||2

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mall bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|-----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring BH5 | | | |
| Iron | | ug/l | 1127 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | | mg/l | 1.09 | APHA - 3120 - B |
| Mercury | | ug/l | <0.2 | APHA - 3120 - B |
| Nickel | | ug/l | <1 | APHA - 3120 - B |
| Potassium | | mg/l | 1.12 | APHA - 3120 - B |
| Sodium | | mg/l | 10.11 | APHA - 3120 - B |
| Tin | | ug/l | <1 | APHA - 3120 - B |
| Zinc | | ug/l | 28 | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | 7.5 | APHA - 4110 - B |
| Total Phosphorus (as P) | | mg/l | 0.11 | APHA - 4500 - P |
| OrthoPhosphate (as P) | | mg/l | 0.04 | APHA - 4500 - P- |
| Residue on Evaporation | | mg/l | 230 | APHA - 2540- B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 102746.1

Order No.:

Date Received: 29/02/12 Date Completed: 06/03/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|-------------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring RD2 | | | |
| pΗ | | (4) | 6.52 | APHA - 4500 - H ⁺ |
| Temperature | | 0 C | 10.4 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 4.99 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 4450 | APHA - 2510 - B |
| T.O.C | | mg/l | 19.9 | APHA - 5310 - C |
| Phenols | | mg/l | 0.004 | APHA - 5530 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | 3.1 | APHA - 4110 - B |
| Total oxidised Nitrog | en (as N) | mg/l | 0.7 | APHA - 4110 - B |
| Chloride | 2000 0000 | mg/l | 880.8 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 06/03/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105680.1

Order No.:

Date Received: 29/08/12 Date Completed: 11/09/12

Test Specification: Nil Item :See below

Thomondgate Limerick Ireland Tel +353 61 455399

Analysing Testing

Consulting

New Road

Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|-------------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring RD2 | | | |
| pН | | (4) | 7.48 | APHA - 4500 - H ⁺ |
| Temperature | | ° C | 12.5 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 6.27 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 3680 | APHA - 2510 - B |
| T.O.C | | mg/l | 16 | APHA - 5310 - C |
| Phenols | | mg/l | 0.007 | APHA - 5530 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | 1.65 | APHA - 4110 - B |
| Total oxidised Nitrog | en (as N) | mg/l | 0.4 | APHA - 4110 - B |
| Chloride | assa abaas | mg/l | 93.8 | APHA - 4110 - B |
| | | 10.000 | | |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105683.1

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------------|-----------------------------------|----------------------|---------|-----------------------|
| | Annual Landfill Monitoring RD2 | | | |
| Dissolved Oxygen | | % O ₂ sat | 89.6 | APHA - 4500-O-G |
| List I Organics | | mg/l | <0.01 | GC-MS |
| List II Organics | | mg/l | <0.01 | GC-MS |
| Detergents (as MBAS) | | mg/l | <0.001 | APHA - 5540 - C |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 3 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 28.2 | APHA - 3120 - B |
| Total Chromium | | ug/l | <1 | APHA - 3120 - B |
| Copper | | ug/l | <1 | APHA - 3120 - B |
| Cyanide | | mg/l | <0.001 | APHA - 4500 - CN-I |
| Fluoride | 1 | mg/l | 0.45 | APHA - 4110 - B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Client: Response Engineering Traderee TP

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105683.1

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

|3H|2

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mall bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|----------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring | | | |
| | RD2 | - 1 | | |
| Iron | | ug/l | <1 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | | mg/l | 1.05 | APHA - 3120 - B |
| Mercury | | ug/l | <0.2 | APHA - 3120 - B |
| Nickel | | ug/l | <1 | APHA - 3120 - B |
| Potassium. | | mg/l | 2.96 | APHA - 3120 - B |
| Sodium | | mg/l | 12.02 | APHA - 3120 - B |
| Tin | | ug/l | <1 | APHA - 3120 - B |
| Zinc | | ug/l | 28 | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | 15.4 | APHA - 4110 - B |
| Total Phosphorus (as P) | | mg/l | 0.06 | APHA - 4500 - P |
| OrthoPhosphate (as P) | | mg/l | 0.05 | APHA - 4500 - P-E |
| Residue on Evaporation | | mg/l | 202 | APHA - 2540- B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 102746.2

Order No.:

Date Received: 29/02/12 Date Completed: 06/03/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|-------------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring RD3 | | | |
| pН | | (4.) | 7.04 | APHA - 4500 - H ⁺ |
| Temperature | | °C | 11.2 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 1.21 | APHA-4500-NH ₃ -D |
| Conductivity | | µScm⁻¹ | 2820 | APHA - 2510 - B |
| T.O.C | | mg/l | 24.6 | APHA - 5310 - C |
| Phenols | | mg/l | 0.006 | APHA - 5530 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | 0.27 | APHA - 4110 - B |
| Total oxidised Nitrog | en (as N) | mg/l | 0.1 | APHA - 4110 - B |
| Chloride | 2000 2000 | mg/l | 394 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 06/03/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105680.2

Order No.:

Date Received: 29/08/12 Date Completed: 11/09/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|-------------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring RD3 | | | |
| pН | | (4.) | 7.53 | APHA - 4500 - H ⁺ |
| Temperature | | ° C | 13.1 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 0.11 | APHA-4500-NH ₃ -D |
| Conductivity | | µScm⁻¹ | 2250 | APHA - 2510 - B |
| T.O.C | | mg/l | 1.2 | APHA - 5310 - C |
| Phenols | | mg/l | 0.001 | APHA - 5530 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | and a second | mg/l | 1.15 | APHA - 4110 - B |
| Total oxidised Nitrog | en (as N) | mg/l | 0.3 | APHA - 4110 - B |
| Chloride | as east character | mg/l | 45.3 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105683.2

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------------|-----------------------------------|----------------------|---------|-----------------------|
| | Annual Landfill Monitoring RD3 | | | |
| Dissolved Oxygen | | % O ₂ sat | 91.6 | APHA - 4500-O-G |
| List I Organics | | mg/l | <0.01 | GC-MS |
| List II Organics | | mg/l | <0.01 | GC-MS |
| Detergents (as MBAS) | 1 | mg/l | <0.001 | APHA - 5540 - C |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 4 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 22.2 | APHA - 3120 - B |
| Total Chromium | | ug/l | <1 | APHA - 3120 - B |
| Copper | | ug/l | <1 | APHA - 3120 - B |
| Cyanide | | mg/l | <0.001 | APHA - 4500 - CN-E |
| Fluoride | | mg/l | 0.39 | APHA - 4110 - B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105683.2

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|-----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring RD3 | | | |
| Iron | | ug/l | <1 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | | mg/l | 1.12 | APHA - 3120 - B |
| Mercury | | ug/l | <0.2 | APHA - 3120 - B |
| Nickel | | ug/l | <1 | APHA - 3120 - B |
| Potassium | | mg/l | 1.06 | APHA - 3120 - B |
| Sodium | | mg/l | 10.05 | APHA - 3120 - B |
| Tin | | ug/l | <1 | APHA - 3120 - B |
| Zinc | | ug/l | 32 | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | 61.1 | APHA - 4110 - B |
| Total Phosphorus (as P) | | mg/l | 0.09 | APHA - 4500 - P |
| OrthoPhosphate (as P) | | mg/l | 0.06 | APHA - 4500 - P-1 |
| Residue on Evaporation | | mg/l | 181 | APHA - 2540- B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



Leachate Monitoring Test Reports



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 102748

Order No.:

Date Received: 29/02/12 Date Completed: 06/03/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|--|--------|---------|------------------------------|
| | Biannual Landfill Monitoring SS3-Leachate | | | |
| Н | | (-) | 6.59 | APHA - 4500 - H ⁺ |
| Temperature | | °C | 9.3 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 6.29 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 1716 | APHA - 2510 - B |
| 3.O.D | | mg/l | 57 | APHA - 5210 - B |
| C.O.D | | mg/l | 105 | APHA - 5220 - D |
| Nitrite (as NO ₂) | | mg/l | 0.2 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | 36.1 | APHA - 4110 - B |
| Total oxidised Nitroge | an (as N) | mg/l | 8.1 | APHA - 4110 - B |
| Chloride | partie. | mg/l | 502.5 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 06/03/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105681.1

Order No.:

Date Received: 29/08/12 Date Completed: 10/09/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|--|--------------------|---------|------------------------------|
| | Biannual Landfill Monitoring SS3-Leachate | | | |
| рН | | (-) | 7.06 | APHA - 4500 - H ⁺ |
| Temperature | | ° C | 11.5 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 0.87 | APHA-4500-NH3-D |
| Conductivity | | µScm ⁻¹ | 877 | APHA - 2510 - B |
| B.O.D | | mg/l | 4 | APHA - 5210 - B |
| C.O.D | | mg/l | 47 | APHA - 5220 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | rana varianti | mg/l | 13.3 | APHA - 4110 - B |
| Total oxidised Nitrog | en (as N) | mg/l | 3.0 | APHA - 4110 - B |
| Chloride | SERVICE CONTRACTOR | mg/l | 161.7 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105684.6

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12

Test Specification: Nil Item :See below

New Road Thomondgate Limerick Ireland Tel +353 61 455399

Analysing Testing

Consulting

Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------------|-----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring SS3 | | | |
| Detergents (as MBAS) | | mg/l | <0.001 | APHA - 5540 - C |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 7 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 18.4 | APHA - 3120 - B |
| Total Chromium | | ug/l | 20 | APHA - 3120 - B |
| Copper | | ug/l | <1 | APHA - 3120 - B |
| Cyanide | | mg/l | <0.001 | APHA - 4500 - CN-I |
| Fluoride | | mg/l | 0.11 | APHA - 4110 - B |
| Iron | | ug/l | <1 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | | mg/l | 1.61 | APHA - 3120 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105684.6

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12

Test Specification: Nil Item :See below

New Road Thomondgate Limerick Ireland

Analysing Testing

Consulting

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| nal Landfill Monitoring | | | |
|-------------------------|------|--------------------------------------|---|
| | | 1 | |
| | ug/l | <0.2 | APHA - 3120 - B |
| | ug/l | <1 | APHA - 3120 - B |
| | mg/l | 1.32 | APHA - 3120 - B |
| | mg/l | 13.12 | APHA - 3120 - B |
| | ug/l | <1 | APHA - 3120 - B |
| | ug/l | 21 | APHA - 3120 - B |
| | mg/l | 13.7 | APHA - 4110 - B |
| | mg/l | 0.06 | APHA - 4500 - P |
| | mg/l | 0.02 | APHA - 4500 - P-E |
| | | mg/l mg/l ug/l ug/l mg/l | mg/l 1.32 mg/l 13.12 ug/l <1 ug/l 21 mg/l 13.7 mg/l 0.06 |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 103348.1

Order No.:

Date Received: 11/04/12 Date Completed: 20/04/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|--|--------|---------|------------------------------|
| | Biannual Landfill Monitoring | | | |
| | L1-Leachate | | | |
| pН | | (-) | 6.57 | APHA - 4500 - H ⁺ |
| Temperature | | ° C | 11.1 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 6.31 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 2210 | APHA - 2510 - B |
| B.O.D | | mg/l | 88 | APHA - 5210 - B |
| C.O.D | | mg/l | 212 | APHA - 5220 - D |
| Nitrite (as NO ₂) | | mg/l | <0.05 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | <0.1 | APHA - 4110 - B |
| Total oxidised Nitrog | gen (as N) | mg/l | <0.1 | APHA - 4110 - B |
| Chloride | 53 (36° 530 556) | mg/l | 50.6 | APHA - 4110 - B |
| Chloride | 19-19-0 (19-19-0) 19-19-0 (19-19-0) | mg/l | 50.6 | APHA - 4110 - |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 23/04/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105681.2

Order No.:

Date Received: 29/08/12 Date Completed: 10/09/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| Biannual Landfill Monitoring L1-Leachate | | | |
|--|--------------------|-------|------------------------------|
| L1-Leachate | 1 | | 1 |
| | | | |
| pH | (-) | 6.88 | APHA - 4500 - H ⁺ |
| Temperature | ° C | 12.4 | APHA - 2550 - B |
| Total Ammonia | mg/l | 6.88 | APHA-4500-NH3-D |
| Conductivity | µScm ⁻¹ | 1789 | APHA - 2510 - B |
| B.O.D | mg/l | 83 | APHA - 5210 - B |
| C.O.D | mg/l | 163 | APHA - 5220 - D |
| Nitrite (as NO ₂) | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | mg/l | 13.7 | APHA - 4110 - B |
| Total oxidised Nitrogen (as N) | mg/l | 3.1 | APHA - 4110 - B |
| Chloride | mg/l | 172.4 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105684.1

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------------|-------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring L1 | | | |
| Detergents (as MBAS) | | mg/l | <0.001 | APHA - 5540 - C |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 8 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 22.1 | APHA - 3120 - B |
| Total Chromium | | ug/l | 64 | APHA - 3120 - B |
| Copper | | ug/l | 712.0 | APHA - 3120 - B |
| Cyanide | | mg/l | <0.001 | APHA - 4500 - CN-I |
| Fluoride | | mg/l | 0.29 | APHA - 4110 - B |
| Iron | | ug/l | 2041 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | 1 | mg/l | 2.11 | APHA - 3120 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105684.1

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12

Test Specification: Nil Item :See below

New Road Thomondgate Limerick Ireland Tel +353 61 455399

Analysing Testing

Consulting

Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|----------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring | | | |
| Mercury | | ug/l | <0.2 | APHA - 3120 - B |
| Nickel | | ug/l | <1 | APHA - 3120 - B |
| Potassium | | mg/l | 1.31 | APHA - 3120 - B |
| Sodium | | mg/l | 13.12 | APHA - 3120 - B |
| Tin | | ug/l | <1 | APHA - 3120 - B |
| Zinc | | ug/l | 32 | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | 10.7 | APHA - 4110 - B |
| Total Phosphorus (as P) | | mg/l | 0.06 | APHA - 4500 - P |
| OrthoPhosphate (as P) | | mg/l | 0.03 | APHA - 4500 - P-E |
| | | | | |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 103348.2

Order No.:

Date Received: 11/04/12 Date Completed: 20/04/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring | | | |
| | L2-Leachate | | | |
| pН | | (-) | 6.38 | APHA - 4500 - H ⁺ |
| Temperature | | °C | 11.5 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 6.52 | APHA-4500-NH ₃ -D |
| Conductivity | | µScm⁻¹ | 4220 | APHA - 2510 - B |
| B.O.D | | mg/l | 227 | APHA - 5210 - B |
| C.O.D | | mg/l | 297 | APHA - 5220 - D |
| Nitrite (as NO ₂) | | mg/l | 2.4 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | <0.1 | APHA - 4110 - B |
| Total oxidised Nitrog | en (as N) | mg/l | 0.5 | APHA - 4110 - B |
| Chloride | 2000 00000 | mg/l | 740 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 23/04/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105681.3

Order No.:

Date Received: 29/08/12 Date Completed: 10/09/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| Biannual Landfill Monitoring L2-Leachate pH | | | |
|---|--------|-------|------------------------------|
| | | | |
| Hq | | | |
| | - | 6.67 | APHA - 4500 - H ⁺ |
| Temperature | °c | 12.8 | APHA - 2550 - B |
| Total Ammonia | mg/l | 7.09 | APHA-4500-NH3-D |
| Conductivity | µScm⁻¹ | 3100 | APHA - 2510 - B |
| B.O.D | mg/l | 114 | APHA - 5210 - B |
| C.O.D | mg/l | 185 | APHA - 5220 - D |
| Nitrite (as NO ₂) | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | mg/l | 11.7 | APHA - 4110 - B |
| Total oxidised Nitrogen (as N) | mg/l | 2.6 | APHA - 4110 - B |
| Chloride | mg/l | 132.3 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105684.2

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------------|----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring L2 | | | |
| Detergents (as MBAS) | | mg/l | <0.001 | APHA - 5540 - C |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 6 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 20.1 | APHA - 3120 - B |
| Total Chromium | | ug/l | 28 | APHA - 3120 - B |
| Copper | | ug/l | 891.0 | APHA - 3120 - B |
| Cyanide | | mg/l | 0.026 | APHA - 4500 - CN-I |
| Fluoride | | mg/l | 0.23 | APHA - 4110 - B |
| Iron | | ug/l | 3697 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | 1 | mg/l | 1.81 | APHA - 3120 - B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105684.2

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring L2 | | | |
| Mercury | | ug/l | <0.2 | APHA - 3120 - B |
| Nickel | | ug/l | <1 | APHA - 3120 - B |
| Potassium | | mg/l | 1.06 | APHA - 3120 - B |
| Sodium | | mg/l | 16.1 | APHA - 3120 - B |
| Tin | | ug/l | <1 | APHA - 3120 - B |
| Zinc | | ug/l | 40 | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | 14.2 | APHA - 4110 - B |
| Total Phosphorus (as P) | | mg/l | 0.07 | APHA - 4500 - P |
| OrthoPhosphate (as P) | | mg/l | 0.03 | APHA - 4500 - P-E |
| | | | | |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 103348.3

Order No.:

Date Received: 11/04/12 Date Completed: 20/04/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring | | | |
| | L3-Leachate | | | |
| ρH | | (4.) | 6.51 | APHA - 4500 - H ⁺ |
| l'emperature | | ° C | 11.3 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 7.12 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 1600 | APHA - 2510 - B |
| B.O.D | | mg/l | 140 | APHA - 5210 - B |
| C.O.D | | mg/l | 265 | APHA - 5220 - D |
| Nitrite (as NO ₂) | | mg/l | 0.6 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | <0.1 | APHA - 4110 - B |
| Total oxidised Nitrog | en (as N) | mg/l | 0.13 | APHA - 4110 - B |
| Chloride | tota partic | mg/l | 36 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 23/04/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

BHP Ref. No.: 105681.4

Order No.:

Date Received: 29/08/12 Date Completed: 10/09/12

Test Specification: Nil Item :See below

FTAO: Ailish Johnson

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring | | | |
| | L3-Leachate | | | |
| pН | | (-) | 6.75 | APHA - 4500 - H ⁺ |
| Temperature | | ° C | 13.1 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 6.21 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 1491 | APHA - 2510 - B |
| B.O.D | | mg/l | 27 | APHA - 5210 - B |
| C.O.D | | mg/l | 50 | APHA - 5220 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | 21.9 | APHA - 4110 - B |
| Total oxidised Nitrogen (| as N) | mg/l | 4.9 | APHA - 4110 - B |
| Chloride | 0.000 | mg/l | 130.3 | APHA - 4110 - B |
| Total oxidised Nitrogen (| as N) | mg/l | 4.9 | API |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105684.3

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------------|----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring L3 | | | |
| Detergents (as MBAS) | | mg/l | <0.001 | APHA - 5540 - C |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 5 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 13.2 | APHA - 3120 - B |
| Total Chromium | | ug/l | 60 | APHA - 3120 - B |
| Copper | | ug/l | 202 | APHA - 3120 - B |
| Cyanide | | mg/l | 0.017 | APHA - 4500 - CN- |
| Fluoride | | mg/l | 0.23 | APHA - 4110 - B |
| Iron | | ug/l | 1049 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | | mg/l | 2.11 | APHA - 3120 - B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105684.3

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Calibrating

Analysing Testing

Consulting

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| nnual Landfill Monitoring | | | |
|---------------------------|------|--------------------------------------|---|
| | | | |
| | | | |
| | ug/l | <0.2 | APHA - 3120 - B |
| | ug/l | <1 | APHA - 3120 - B |
| | mg/l | 1.13 | APHA - 3120 - B |
| | mg/l | 18.12 | APHA - 3120 - B |
| | ug/l | <1 | APHA - 3120 - B |
| | ug/l | 28 | APHA - 3120 - B |
| | mg/l | 13.1 | APHA - 4110 - B |
| | mg/l | 0.12 | APHA - 4500 - P |
| | mg/l | 0.08 | APHA - 4500 - P-E |
| | | | |
| | | mg/l mg/l ug/l ug/l mg/l | mg/l 1.13 mg/l 18.12 ug/l <1 ug/l 28 mg/l 13.1 mg/l 0.12 |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 103348.4 Order No.:

Date Received: 11/04/12 Date Completed: 20/04/12

Test Specification: Nil Item :See below

New Road

Analysing Testing

Consulting

| Thomondgate |
|-----------------------|
| Limerick |
| Ireland |
| Tel +353 61 455399 |
| Fax + 353 61 455447 |
| E Mail bhpcem2@bhp.le |
| W 673W |

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring | | | |
| | L4-Leachate | | | |
| pН | | (4) | 6.54 | APHA - 4500 - H ⁺ |
| Temperature | | °C | 11.6 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 4.21 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 1826 | APHA - 2510 - B |
| B.O.D | | mg/l | 92 | APHA - 5210 - B |
| C.O.D | | mg/l | 264 | APHA - 5220 - D |
| Nitrite (as NO ₂) | | mg/l | 2.4 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | <0.1 | APHA - 4110 - B |
| Total oxidised Nitro | gen (as N) | mg/l | 0.54 | APHA - 4110 - B |
| Chloride | 013/03/01/01/01/01 | mg/l | 60 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 23/04/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105681.5

Order No.:

Date Received: 29/08/12 Date Completed: 10/09/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring | | | |
| | L4-Leachate | | | |
| pН | | (=) | 6.69 | APHA - 4500 - H ⁺ |
| Temperature | | °C | 12.8 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 3.66 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 1544 | APHA - 2510 - B |
| B.O.D | | mg/l | 27 | APHA - 5210 - B |
| C.O.D | | mg/l | 63 | APHA - 5220 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | 24.5 | APHA - 4110 - B |
| Total oxidised Nitrog | gen (as N) | mg/l | 5.5 | APHA - 4110 - B |
| Chloride | | mg/l | 127.6 | APHA - 4110 - B |
| Ciliotide | | mgı | 127.0 | APRA-4110-1 |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105684.4

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------------|----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring L4 | | | |
| Detergents (as MBAS) | | mg/l | <0.001 | APHA - 5540 - C |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 8 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 22.4 | APHA - 3120 - B |
| Total Chromium | | ug/l | 20 | APHA - 3120 - B |
| Copper | | ug/l | 312 | APHA - 3120 - B |
| Cyanide | | mg/l | 0.032 | APHA - 4500 - CN-I |
| Fluoride | | mg/l | 0.35 | APHA - 4110 - B |
| Iron | | ug/l | 5204 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | | mg/l | 1.96 | APHA - 3120 - B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105684.4

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--|-------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring L4 | | | |
| Mercury | | ug/l | ⊲0.2 | APHA - 3120 - B |
| Nickel | | ug/l | <1 | APHA - 3120 - B |
| Potassium | | mg/l | 1.31 | APHA - 3120 - B |
| Sodium | | mg/l | 12.01 | APHA - 3120 - B |
| Tin | | ug/l | <1 | APHA - 3120 - B |
| Zinc | | ug/l | 32 | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | 11.4 | APHA - 4110 - B |
| Total Phosphorus (as | (P) | mg/l | 0.05 | APHA - 4500 - P |
| OrthoPhosphate (as I | P) | mg/l | 0.02 | APHA - 4500 - P-E |
| Total Phosphorus (as OrthoPhosphate (as I | 35 | 2000 | 65.50 | |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 103348.5

Order No.:

Date Received: 11/04/12 Date Completed: 20/04/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|------------------------------|--------|---------|------------------------------|
| | Biannual Landfill Monitoring | | | |
| | L5-Leachate | | | |
| pH | | (-) | 6.55 | APHA - 4500 - H ⁺ |
| Temperature | | °C | 11.1 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 6.89 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 2560 | APHA - 2510 - B |
| B.O.D | | mg/l | 184 | APHA - 5210 - B |
| C.O.D | | mg/l | 233 | APHA - 5220 - D |
| Nitrite (as NO ₂) | | mg/l | 1.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | | mg/l | <0.1 | APHA - 4110 - B |
| Total oxidised Nitrog | en (as N) | mg/l | 0.25 | APHA - 4110 - B |
| Chloride | 2000 | mg/l | 56 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 23/04/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

BHP Ref. No.: 105681.6 Order No.:

Date Received: 29/08/12 Date Completed: 10/09/12

Test Specification: Nil Item :See below

FTAO: Ailish Johnson

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|-------------------------------|--|--------|---------|------------------------------|
| | Biannual Landfill Monitoring | | | |
| | L5-Leachate | | | |
| pН | | (4) | 6.78 | APHA - 4500 - H ⁺ |
| Temperature | | ° C | 13.5 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 6.26 | APHA-4500-NH3-D |
| Conductivity | | µScm⁻¹ | 2330 | APHA - 2510 - B |
| B.O.D | | mg/l | 52 | APHA - 5210 - B |
| C.O.D | | mg/l | 154 | APHA - 5220 - D |
| Nitrite (as NO ₂) | | mg/l | <0.1 | APHA - 4110 - B |
| Nitrate (as NO ₃) | W. 100 St. 100 | mg/l | 13.3 | APHA - 4110 - B |
| Total oxidised Nitro | ogen (as N) | mg/l | 3.0 | APHA - 4110 - B |
| Chloride | 535 FC 2 500 536 | mg/l | 161.7 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105684.5

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------------|----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring L5 | | | |
| Detergents (as MBAS) | | mg/l | <0.001 | APHA - 5540 - C |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 5 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 20.1 | APHA - 3120 - B |
| Total Chromium | | ug/l | 21 | APHA - 3120 - B |
| Copper | | ug/l | 429 | APHA - 3120 - B |
| Cyanide | | mg/l | 0.039 | APHA - 4500 - CN- |
| Fluoride | | mg/l | 0.11 | APHA - 4110 - B |
| Iron | | ug/l | 3229 | APHA - 3120 - B |
| Lead | 1 | ug/l | <1 | APHA - 3120 - B |
| Magnesium | | mg/l | 1.35 | APHA - 3120 - B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105684.5

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring L5 | | | |
| Mercury | | ug/l | <0.2 | APHA - 3120 - B |
| Nickel | | ug/l | <1 | APHA - 3120 - B |
| Potassium | | mg/l | 1.06 | APHA - 3120 - B |
| Sodium | | mg/l | 11.21 | APHA - 3120 - B |
| Tin | | ug/l | <1 | APHA - 3120 - B |
| Zinc | | ug/l | 56 | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | 14.6 | APHA - 4110 - B |
| Total Phosphorus (as P) | | mg/l | 0.08 | APHA - 4500 - P |
| OrthoPhosphate (as P) | | mg/l | 0.04 | APHA - 4500 - P-E |
| | | | | |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



Surface Water Monitoring Test Reports



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 102747.1 Order No.:

Date Received: 29/02/12

Date Completed: 06/03/12 Test Specification: Nil Item :See below

New Road Thomondgate Limerick Ireland Tel +353 61 455399

Analysing Testing

Consulting

Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|------------------------|-------------------------------------|----------------------|---------|------------------------------|
| | Biannual Landfill Monitoring SS1 | | | |
| рН | | - °C | 7.65 | APHA - 4500 - H ⁺ |
| Temperature | | °C | 8.9 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 0.29 | APHA-4500-NH3-D |
| B.O.D | | mg/l | 3 | APHA - 5210 - B |
| C.O.D | | mg/l | 32 | APHA - 5220 - D |
| Total Suspended Solids | | mg/l | 39 | APHA - 2540 - B |
| Dissolved Oxygen | | % O ₂ sat | 96.4 | APHA - 4500-O-G |
| | | | | |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 06/03/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105682.1

Order No.:

Date Received: 29/08/12 Date Completed: 10/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|------------------------|-------------------------------------|----------------------|---------|------------------------------|
| | Biannual Landfill Monitoring SS1 | | | |
| рН | | - °C | 7.66 | APHA - 4500 - H ⁺ |
| Temperature | | °C | 9.9 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 0.18 | APHA-4500-NH3-D |
| B.O.D | | mg/l | 2 | APHA - 5210 - B |
| C.O.D | | mg/l | 22 | APHA - 5220 - D |
| Total Suspended Solids | | mg/l | 31 | APHA - 2540 - B |
| Dissolved Oxygen | | % O ₂ sat | 85.5 | APHA - 4500-O-G |
| | | | | |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012

Test results relate only to this/these items. This test report shall not be duplicated in full without the permission of the test laboratory.

Page 1 of 1



TEST REPORT

Client: Response Engineering Traderee TP

Traderee TP Shannon

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105685.1

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

|3|**-**||2

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mall bhpoem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------|-----------------------------------|--------------------|---------|-----------------------|
| | Annual Landfill Monitoring SS1 | | | |
| Conductivity | | μScm ⁻¹ | 467 | APHA - 2510 - B |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 1 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 26.1 | APHA - 3120 - B |
| Total Chromium | | ug/l | 36 | APHA - 3120 - B |
| Copper | | ug/l | <1 | APHA - 3120 - B |
| Cyanide | | mg/l | <0.001 | APHA - 4500 - CN-I |
| Fluoride | | mg/l | 0.12 | APHA - 4110 - B |
| Iron | | ug/l | <1 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | | mg/l | 2.02 | APHA - 3120 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Client: Response Engineering Traderee TP

Traderee TP Shannon

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105685.1

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

|3|**-**||2

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mall bhpoem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|-----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring SS1 | | | |
| Mercury | | ug/l | <0.2 | APHA - 3120 - B |
| Nickel | | ug/l | <1 | APHA - 3120 - B |
| Potassium | | mg/l | 1.63 | APHA - 3120 - B |
| Sodium | | mg/l | 14.07 | APHA - 3120 - B |
| Tin | | ug/l | <1 | APHA - 3120 - B |
| Zinc | | ug/l | 12 | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | 15.1 | APHA - 4110 - B |
| Total Phosphorus (as P) | | mg/l | 0.03 | APHA - 4500 - P |
| OrthoPhosphate (as P) | | mg/l | 0.01 | APHA - 4500 - P-E |
| Nitrate (as NO ₃) | | mg/l | 21.1 | APHA - 4110 - B |
| Nitrite (as NO ₂) | 2 1 | mg/l | <0.05 | APHA - 4110 - B |
| Total Oxidised Nitrogen | (as N) | mg/l | 4.74 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 102747.2 Order No.:

Date Received: 29/02/12 Date Completed: 06/03/12

Test Specification: Nil Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|------------------------|-------------------------------------|----------------------|---------|------------------------------|
| | Biannual Landfill Monitoring SS2 | | | |
| pН | | (+) | 7.95 | APHA - 4500 - H ⁺ |
| Temperature | | °C | 9.4 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 0.19 | APHA-4500-NH3-D |
| B.O.D | | mg/l | 2 | APHA - 5210 - B |
| C.O.D | | mg/l | 29 | APHA - 5220 - D |
| Total Suspended Solids | | mg/l | 23 | APHA - 2540 - B |
| Dissolved Oxygen | | % O ₂ sat | 98.1 | APHA - 4500-O-G |
| | | | | |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 06/03/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105682.2

Order No.:

Date Received: 29/08/12 Date Completed: 10/09/12

Test Specification: Nil Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|------------------------|-------------------------------------|----------------------|---------|------------------------------|
| | Biannual Landfill Monitoring SS2 | | | |
| pН | | (+) | 7.70 | APHA - 4500 - H ⁺ |
| Temperature | | ° C | 10.1 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 0.21 | APHA-4500-NH3-D |
| B.O.D | | mg/l | 14 | APHA - 5210 - B |
| C.O.D | | mg/l | 40 | APHA - 5220 - D |
| Total Suspended Solids | | mg/l | 46 | APHA - 2540 - B |
| Dissolved Oxygen | | % O ₂ sat | 76.2 | APHA - 4500-O-G |
| | | | | |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012

Test results relate only to this/these items. This test report shall not be duplicated in full without the permission of the test laboratory.

Page 1 of 1



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105685.2

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

New Road Thomondgate Limerick Ireland

Analysing Testing

Consulting Calibrating

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------|-----------------------------------|--------------------|---------|-----------------------|
| | Annual Landfill Monitoring SS2 | | | |
| Conductivity | | μScm ⁻¹ | 504 | APHA - 2510 - B |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 2 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 32.1 | APHA - 3120 - B |
| Total Chromium | | ug/l | 28 | APHA - 3120 - B |
| Copper | | ug/l | <1 | APHA - 3120 - B |
| Cyanide | | mg/l | 0.01 | APHA - 4500 - CN-I |
| Fluoride | | mg/l | 0.11 | APHA - 4110 - B |
| Iron | | ug/l | <1 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | | mg/l | 1.99 | APHA - 3120 - B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105685.2

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|-----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring SS2 | | | |
| Mercury | | ug/l | <0.2 | APHA - 3120 - B |
| Nickel | | ug/l | <1 | APHA - 3120 - B |
| Potassium | | mg/l | 1.71 | APHA - 3120 - B |
| Sodium | | mg/l | 12.01 | APHA - 3120 - B |
| Tin | | ug/l | <1 | APHA - 3120 - B |
| Zinc | | ug/l | 58 | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | 28.1 | APHA - 4110 - B |
| Total Phosphorus (as P) | | mg/l | 0.03 | APHA - 4500 - P |
| OrthoPhosphate (as P) | | mg/l | 0.01 | APHA - 4500 - P-E |
| Nitrate (as NO ₃) | | mg/l | 11.1 | APHA - 4110 - B |
| Nitrite (as NO ₂) | | mg/l | <0.05 | APHA - 4110 - B |
| Total Oxidised Nitrogen | (as N) | mg/l | 2.49 | APHA - 4110 - B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 102747.3

Order No.:

Date Received: 29/02/12 Date Completed: 06/03/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|------------------------|-------------------------------------|----------------------|---------|------------------------------|
| | Biannual Landfill Monitoring SS4 | | | |
| рН | | - °C | 7.96 | APHA - 4500 - H ⁺ |
| Temperature | | °C | 8.8 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 0.36 | APHA-4500-NH ₃ -D |
| B.O.D | | mg/l | 2 | APHA - 5210 - B |
| C.O.D | | mg/l | 29 | APHA - 5220 - D |
| Total Suspended Solids | | mg/l | 40 | APHA - 2540 - B |
| Dissolved Oxygen | | % O ₂ sat | 97.6 | APHA - 4500-O-G |
| | | | | |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 06/03/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105682.3

Order No.:

Date Received: 29/08/12 Date Completed: 10/09/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|------------------------|-------------------------------------|----------------------|---------|------------------------------|
| | Biannual Landfill Monitoring SS4 | | | |
| pН | | (-) | 7.44 | APHA - 4500 - H ⁺ |
| Temperature | | ° C | 10.2 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 0.21 | APHA-4500-NH ₃ -D |
| B.O.D | | mg/l | 10 | APHA - 5210 - B |
| C.O.D | | mg/l | 24 | APHA - 5220 - D |
| Total Suspended Solids | | mg/l | 86 | APHA - 2540 - B |
| Dissolved Oxygen | | % O ₂ sat | 78.4 | APHA - 4500-O-G |
| | | | | |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105685.3

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12

Test Specification: Nil

Thomondgate Item :See below Limerick Ireland

Tel +353 61 455399

Analysing Testing

Consulting

New Road

Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------|-----------------------------------|--------------------|---------|-----------------------|
| | Annual Landfill Monitoring SS4 | | | |
| Conductivity | | μScm ⁻¹ | 512 | APHA - 2510 - B |
| Arsenic | | ug/l | <1 | APHA - 3120 - B |
| Boron | | ug/l | 1 | APHA - 3120 - B |
| Cadmium | | ug/l | <1 | APHA - 3120 - B |
| Calcium | | mg/l | 30.3 | APHA - 3120 - B |
| Total Chromium | | ug/l | 32 | APHA - 3120 - B |
| Copper | | ug/l | <1 | APHA - 3120 - B |
| Cyanide | | mg/l | 0.016 | APHA - 4500 - CN-E |
| Fluoride | | mg/l | 0.12 | APHA - 4110 - B |
| Iron | | ug/l | <1 | APHA - 3120 - B |
| Lead | | ug/l | <1 | APHA - 3120 - B |
| Magnesium | | mg/l | 2.01 | APHA - 3120 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105685.3

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|-----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring SS4 | | | |
| Mercury | | ug/l | <0.2 | APHA - 3120 - B |
| Nickel | | ug/l | <1 | APHA - 3120 - B |
| Potassium | | mg/l | 1.82 | APHA - 3120 - B |
| Sodium | | mg/l | 13.67 | APHA - 3120 - B |
| Tin | | ug/l | <1 | APHA - 3120 - B |
| Zinc | | ug/l | 60 | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | 29.3 | APHA - 4110 - B |
| Total Phosphorus (as P) | | mg/l | 0.04 | APHA - 4500 - P |
| OrthoPhosphate (as P) | | mg/l | 0.01 | APHA - 4500 - P-E |
| Nitrate (as NO ₃) | | mg/l | 14.2 | APHA - 4110 - B |
| Nitrite (as NO ₂) | | mg/l | <0.05 | APHA - 4110 - B |
| Total Oxidised Nitrogen | (as N) | mg/l | 3.19 | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 102747.5

Order No.:

Date Received: 29/02/12 Date Completed: 06/03/12

Test Specification: Nil Item :See below

New Road Thomondgate Limerick

Analysing Testing

Consulting

| TEST | Client Reference | Units | Results | Standard Reference |
|------------------------|-------------------------------------|----------------------|---------|------------------------------|
| | Biannual Landfill Monitoring SS6 | | | |
| pН | | - °C | 8.06 | APHA - 4500 - H ⁺ |
| Temperature | | °C | 9.1 | APHA - 2550 - B |
| Total Ammonia | | mg/l | 0.14 | APHA-4500-NH3-D |
| B.O.D | | mg/l | 2 | APHA - 5210 - B |
| C.O.D | | mg/l | 31 | APHA - 5220 - D |
| Total Suspended Solids | | mg/l | 103 | APHA - 2540 - B |
| Dissolved Oxygen | | % O ₂ sat | 92.1 | APHA - 4500-O-G |
| | | | | |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 06/03/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105682.5

Order No.:

Date Received: 29/08/12 Date Completed: 10/09/12

Test Specification: Nil Item :See below

Thomondgate Limerick Ireland Tel +353 61 455399

Analysing Testing

Consulting

New Road

Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|------------------------|-------------------------------------|----------------------|---------|------------------------------|
| | Biannual Landfill Monitoring SS6 | | | |
| рН | | - °C | Dry | APHA - 4500 - H ⁺ |
| Temperature | | °C | Dry | APHA - 2550 - B |
| Total Ammonia | | mg/l | Dry | APHA-4500-NH ₃ -D |
| B.O.D | | mg/l | Dry | APHA - 5210 - B |
| C.O.D | | mg/l | Dry | APHA - 5220 - D |
| Total Suspended Solids | | mg/l | Dry | APHA - 2540 - B |
| Dissolved Oxygen | | % O ₂ sat | Dry | APHA - 4500-O-G |
| | | | | |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 11/09/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105685.4

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|----------------|-----------------------------------|--------------------|---------|-----------------------|
| | Annual Landfill Monitoring SS6 | | | |
| Conductivity | | μScm ⁻¹ | Dry | APHA - 2510 - B |
| Arsenic | | ug/l | n/a | APHA - 3120 - B |
| Boron | | ug/l | n/a | APHA - 3120 - B |
| Cadmium | | ug/l | n/a | APHA - 3120 - B |
| Calcium | | mg/l | n/a | APHA - 3120 - B |
| Total Chromium | | ug/l | n/a | APHA - 3120 - B |
| Copper | | ug/l | n/a | APHA - 3120 - B |
| Cyanide | | mg/l | n/a | APHA - 4500 - CN-E |
| Fluoride | | mg/l | n/a | APHA - 4110 - B |
| Iron | | ug/l | n/a | APHA - 3120 - B |
| Lead | | ug/l | n/a | APHA - 3120 - B |
| Magnesium | | mg/l | n/a | APHA - 3120 - B |

Additional information: All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Client: Response Engineering Traderee TP

Traderee TP Shannon

Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 105685.4

Order No.:

Date Received: 29/08/12 Date Completed: 28/09/12 Test Specification: Nil

Item :See below

Analysing Testing Consulting Calibrating

|3|**-**||2

New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mall bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|--------------------------------|-----------------------------------|-------|---------|-----------------------|
| | Annual Landfill Monitoring SS6 | | | |
| Mercury | | ug/l | Dry | APHA - 3120 - B |
| Nickel | | ug/l | n/a | APHA - 3120 - B |
| Potassium | | mg/l | n/a | APHA - 3120 - B |
| Sodium | | mg/l | n/a | APHA - 3120 - B |
| Tin | | ug/l | n/a | APHA - 3120 - B |
| Zinc | | ug/l | n/a | APHA - 3120 - B |
| Sulphate (as SO ₄) | | mg/l | n/a | APHA - 4110 - B |
| Total Phosphorus (as P) | | mg/l | n/a | APHA - 4500 - P |
| OrthoPhosphate (as P) | | mg/l | n/a | APHA - 4500 - P-E |
| Nitrate (as NO ₃) | | mg/l | n/a | APHA - 4110 - B |
| Nitrite (as NO ₂) | 200 | mg/l | n/a | APHA - 4110 - B |
| Total Oxidised Nitrogen | (as N) | mg/l | n/a | APHA - 4110 - B |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 04/10/2012



TEST REPORT

Response Engineering Traderee TP Client:

Shannon Co. Clare

FTAO: Ailish Johnson

BHP Ref. No.: 102747.6

Order No.:

Date Received: 29/02/12 Date Completed: 06/03/12

Test Specification: Nil

Item :See below

Analysing Testing Consulting



New Road Thomondgate Limerick Ireland

Tel +353 61 455399 Fax + 353 61 455447 E Mail bhpcem2@bhp.le

| TEST | Client Reference | Units | Results | Standard Reference |
|------------------------|-------------------------------------|----------------------|---------|------------------------------|
| | Biannual Landfill Monitoring SS7 | | | |
| pН | | (5-1) | Dry | APHA - 4500 - H ⁺ |
| Temperature | | ° C | Dry | APHA - 2550 - B |
| Total Ammonia | | mg/l | Dry | APHA-4500-NH3-D |
| B.O.D | | mg/l | Dry | APHA - 5210 - B |
| C.O.D | | mg/l | Dry | APHA - 5220 - D |
| Total Suspended Solids | | mg/l | Dry | APHA - 2540 - B |
| Dissolved Oxygen | | % O ₂ sat | Dry | APHA - 4500-O-G |
| | | | | |

Additional information : All Methods are from Standard Methods for the Examination of Water

and Wastewater, 20th Edition.

For and on behalf of BHP laboratories :

Pat O'Sullivan Issue Date 06/03/2012



Appendix H – Meteorological Data



| Year | Month | Day | Mean Realative Humidity (%) | Mean MSL Pressure (hpa) | Mean Wind Speed (kt) | Predominant Wind Direction (degrees) | Potential Evapotranspiration (mm) | Evaporation (mm) |
|---------|-------|-----|--------------------------------|----------------------------|-------------------------|---|---|---------------------|
| 2012 | 1 | 1 | 83.7 | 998.7 | 13 | 230 | 0.3 | 0.2 |
| 2012 | 1 | 2 | 83.8 | 1001.5 | 14.1 | 235 | 0.8 | 1 |
| 2012 | 1 | 3 | 77.5 | 998.8 | 23.7 | 260 | 1 | 1.3 |
| 2012 | 1 | 4 | 87.5 | 1014.9 | 21.2 | 250 | 0.6 | 0.9 |
| 2012 | 1 | 5 | 81 | 1015.8 | 18.7 | 285 | 0.5 | 0.7 |
| 2012 | 1 | 6 | 96.4 | 1025.6 | 11 | 245 | 0.3 | 0.4 |
| 2012 | 1 | 7 | 83.5 | 1027 | 9.1 | 255 | 0.6 | 0.7 |
| 2012 | 1 | 8 | 89.7 | 1028 | 9.4 | 235 | 0.5 | 0.5 |
| 2012 | 1 | 9 | 88.5 | 1029 | 7.3 | 220 | 0.4 | 0.5 |
| 2012 | 1 | 10 | 95.2 | 1030 | 8.7 | 210 | 0.3 | 0.5 |
| 2012 | 1 | 11 | 97.5 | 1030.8 | 10.9 | 230 | 0.3 | 0.4 |
| 2012 | 1 | 12 | 95.2 | 1031 | 8.2 | 245 | 0.3 | 0.4 |
| 2012 | 1 | 13 | 95 | 1032.7 | 4.8 | 130 | 0.3 | 0.4 |
| 2012 | 1 | 14 | 78.4 | 1021.8 | 13.1 | 110 | 0.7 | 0.9 |
| 2012 | 1 | 15 | 72.5 | 1016.2 | 13.8 | 115 | 1.1 | 1.3 |
| 2012 | 1 | 16 | 85.1 | 1019.1 | 10.1 | 100 | 0.7 | 0.9 |
| 2012 | 1 | 17 | 88.9 | 1018.4 | 12 | 155 | 0.5 | 0.6 |
| 2012 | 1 | 18 | 90.2 | 1021.4 | 7.2 | 235 | 0.3 | 0.4 |
| 2012 | 1 | 19 | 85.8 | 1021.9 | 12.8 | 255 | 0.7 | 0.9 |
| 2012 | 1 | 20 | 90.7 | 1023.6 | 16.1 | 250 | 0.6 | 0.8 |
| 2012 | 1 | 21 | 86.3 | 1018.9 | 17.4 | 255 | 0.6 | 0.8 |
| 2012 | 1 | 22 | 80.4 | 1019.4 | 12.8 | 255 | 0.7 | 0.8 |
| 2012 | 1 | 23 | 95 | 1020.8 | 4.9 | 250 | 0.3 | 0.4 |
| 2012 | 1 | 24 | 96.9 | 1016.4 | 12.3 | 235 | 0.4 | 0.6 |
| 2012 | 1 | 25 | 85.2 | 1003.1 | 13.4 | 175 | 0.7 | 1 |
| 2012 | 1 | 26 | 84.6 | 1004.4 | 12 | 245 | 0.6 | 0.8 |
| 2012 | 1 | 27 | 85 | 1022.1 | 7.4 | 270 | 0.4 | 0.5 |
| 2012 | 1 | 28 | 96.6 | 1031 | 5.8 | 115 | 0.2 | 0.3 |
| 2012 | 1 | 29 | 97.4 | 1026.4 | 4.8 | 200 | 0.4 | 0.6 |
| 2012 | 1 | 30 | 96.8 | 1019.5 | 10.1 | 105 | 0.5 | 0.7 |
| 2012 | 1 | 31 | 82.5 | 1023.5 | 10.2 | 80 | 0.7 | 0.9 |
| lanuary | | • | | | | | 16.3 | 21.1 |



| Year | Month | Day | Mean Realative Humidity (%) | Mean MSL Pressure (hpa) | Mean Wind Speed (kt) | Predominant Wind Direction (degrees) | Potential Evapotranspiration (mm) | Evaporation (mm) |
|---------|-------|-----|--------------------------------|----------------------------|-------------------------|---|---|---------------------|
| 2012 | 2 | 1 | 74.2 | 1033.8 | 7.9 | 75 | 0.6 | 0.8 |
| 2012 | 2 | 2 | 77.7 | 1035.8 | 8.2 | 95 | 0.6 | 0.8 |
| 2012 | 2 | 3 | 82.8 | 1035.4 | 9.9 | 115 | 0.7 | 0.9 |
| 2012 | 2 | 4 | 92.7 | 1028.8 | 6.9 | 165 | 0.5 | 0.6 |
| 2012 | 2 | 5 | 92.2 | 1030.1 | 5.1 | 250 | 0.4 | 0.5 |
| 2012 | 2 | 6 | 97 | 1034 | 4.3 | 270 | 0.4 | 0.5 |
| 2012 | 2 | 7 | 91.7 | 1035.4 | 10.2 | 120 | 0.5 | 0.7 |
| 2012 | 2 | 8 | 89.2 | 1034.9 | 14.1 | 140 | 0.6 | 0.9 |
| 2012 | 2 | 9 | 92 | 1035.2 | 5.9 | 135 | 0.6 | 0.8 |
| 2012 | 2 | 10 | 94.8 | 1032.2 | 1.9 | 55 | 0.5 | 0.6 |
| 2012 | 2 | 11 | 93.9 | 1032.3 | 4 | 245 | 0.4 | 0.6 |
| 2012 | 2 | 12 | 95.9 | 1037.2 | 3 | 235 | 0.4 | 0.5 |
| 2012 | 2 | 13 | 87.7 | 1036.5 | 7.8 | 300 | 0.6 | 0.8 |
| 2012 | 2 | 14 | 84.8 | 1036.5 | 7.3 | 295 | 0.7 | 0.9 |
| 2012 | 2 | 15 | 82.5 | 1036.3 | 8.4 | 285 | 0.8 | 1 |
| 2012 | 2 | 16 | 88.9 | 1031.3 | 10.8 | 245 | 0.7 | 1 |
| 2012 | 2 | 17 | 97.5 | 1022.5 | 14.5 | 240 | 0.5 | 0.8 |
| 2012 | 2 | 18 | 82.5 | 1014.5 | 12.7 | 280 | 0.5 | 0.9 |
| 2012 | 2 | 19 | 82.1 | 1028.2 | 6.1 | 255 | 0.7 | 1.1 |
| 2012 | 2 | 20 | 83.9 | 1025.8 | 9.2 | 160 | 0.7 | 1 |
| 2012 | 2 | 21 | 86 | 1021.2 | 9.4 | 165 | 0.9 | 1.2 |
| 2012 | 2 | 22 | 94.6 | 1015.4 | 16.4 | 240 | 0.7 | 1 |
| 2012 | 2 | 23 | 92.9 | 1022.5 | 11.5 | 220 | 0.7 | 1 |
| 2012 | 2 | 24 | 86.9 | 1027.9 | 7.6 | 295 | 0.5 | 0.7 |
| 2012 | 2 | 25 | 89 | 1029.5 | 2.5 | 345 | 0.6 | 0.8 |
| 2012 | 2 | 26 | 92.1 | 1026.5 | 6.3 | 180 | 0.7 | 1 |
| 2012 | 2 | 27 | 92.1 | 1023 | 9.5 | 205 | 0.6 | 0.9 |
| 2012 | 2 | 28 | 85 | 1023 | 4.7 | 205 | 0.8 | 1 |
| 2012 | 2 | 29 | 84.2 | 1019 | 10.5 | | 1 | 1.4 |
| ebruary | | | | | | 9 | 17.9 | 24.7 |



| Year | Month | Day | Mean Realative Humidity (%) | Mean MSL Pressure (hpa) | Mean Wind Speed (kt) | Predominant Wind Direction (degrees) | Potential Evapotranspiration (mm) | Evaporation (mm) |
|-------|-------|-----|--------------------------------|----------------------------|-------------------------|---|---|---------------------|
| 2012 | 3 | 1 | 84 | 1022.9 | 6.5 | 110 | 1 | 1.4 |
| 2012 | 3 | 2 | 86.8 | 1018.8 | 13.7 | 115 | 0.9 | 1.5 |
| 2012 | 3 | 3 | 82.9 | 1011.1 | 10.4 | 180 | 0.8 | 1.2 |
| 2012 | 3 | 4 | 83.9 | 1023.2 | 7.5 | 260 | 0.9 | 1.4 |
| 2012 | 3 | 5 | 82.7 | 1030 | 4.8 | 250 | 1 | 1.5 |
| 2012 | 3 | 6 | 90.5 | 1019.5 | 10.7 | 155 | 0.7 | 1 |
| 2012 | 3 | 7 | 78.5 | 1017.9 | 16.5 | 260 | 1 | 1.7 |
| 2012 | 3 | 8 | 78 | 1029.1 | 10.9 | 240 | 1.5 | 2.1 |
| 2012 | 3 | 9 | 90.1 | 1031.2 | 11 | 220 | 1.2 | 1.6 |
| 2012 | 3 | 10 | 92.9 | 1038.5 | 5.9 | 245 | 0.8 | 1.1 |
| 2012 | 3 | 11 | 90.4 | 1039 | 2.4 | 280 | 0.8 | 1.1 |
| 2012 | 3 | 12 | 87.5 | 1035.2 | 3.5 | 155 | 0.8 | 1.1 |
| 2012 | 3 | 13 | 84.5 | 1033.4 | 5.8 | 125 | 1 | 1.3 |
| 2012 | 3 | 14 | 82 | 1028.1 | 8.6 | 145 | 1.3 | 1.8 |
| 2012 | 3 | 15 | 83 | 1020.6 | 7.7 | 155 | 1 | 1.4 |
| 2012 | 3 | 16 | 88.4 | 1012 | 8.2 | 215 | 0.7 | 1 |
| 2012 | 3 | 17 | 87 | 1009.8 | 5.8 | 185 | 1.1 | 1.5 |
| 2012 | 3 | 18 | 80 | 1022.8 | 7.6 | 310 | 1.5 | 2.2 |
| 2012 | 3 | 19 | 79.1 | 1031 | 9.2 | 200 | 1.3 | 1.8 |
| 2012 | 3 | 20 | 75.1 | 1032.2 | 9.1 | 180 | 1.5 | 2 |
| 2012 | 3 | 21 | 76.2 | 1031.4 | 8.6 | 150 | 1.1 | 1.5 |
| 2012 | 3 | 22 | 80.4 | 1025 | 8.5 | 90 | 1.4 | 1.9 |
| 2012 | 3 | 23 | 84.8 | 1021.3 | 12.1 | 120 | 1.2 | 1.7 |
| 2012 | 3 | 24 | 76.7 | 1021.9 | 13.1 | 115 | 1.7 | 2.3 |
| 2012 | 3 | 25 | 76.7 | 1029.8 | 8.5 | 130 | 2.4 | 3.2 |
| 2012 | 3 | 26 | 71.4 | 1033.2 | 6.4 | 95 | 2.2 | 3.1 |
| 2012 | 3 | 27 | 65.2 | 1034.8 | 6.2 | 100 | 2.6 | 3.5 |
| 2012 | 3 | 28 | 68.8 | 1034.7 | 3.1 | 65 | 2.2 | 3.1 |
| 2012 | 3 | 29 | 74.7 | 1033.5 | 3.5 | 330 | 2.2 | 3 |
| 2012 | 3 | 30 | 88.2 | 1030.1 | 5.4 | 330 | 1 | 1.5 |
| 2012 | 3 | 31 | 76.9 | 1024.5 | 6.4 | 25 | 1.3 | 1.8 |
| March | 1 1 | • | 1 - 4 | | | | 40.1 | 56.3 |



| Year | Month | Day | Mean Realative Humidity (%) | Mean MSL Pressure (hpa) | Mean Wind Speed (kt) | Predominant Wind Direction (degrees) | Potential Evapotranspiration (mm) | Evaporation (mm) |
|-------|-------|-----|--------------------------------|----------------------------|-------------------------|---|---|---------------------|
| 2012 | 4 | 1 | 76.6 | 1022.1 | 3.6 | 25 | 1.6 | 2.2 |
| 2012 | 4 | 2 | 86.6 | 1013.8 | 4.2 | 310 | 0.9 | 1.2 |
| 2012 | 4 | 3 | 78.8 | 1010.4 | 11.5 | 335 | 1.4 | 2.3 |
| 2012 | 4 | 4 | 60.1 | 1021.1 | 13 | 350 | 2 | 2.8 |
| 2012 | 4 | 5 | 65.5 | 1024.5 | 7.4 | 20 | 1.9 | 2.9 |
| 2012 | 4 | 6 | 85.6 | 1020.5 | 6.7 | 300 | 1.2 | 1.8 |
| 2012 | 4 | 7 | 85 | 1018.7 | 8 | 325 | 1.1 | 1.4 |
| 2012 | 4 | 8 | 88.6 | 1014.8 | 10.4 | 255 | 0.9 | 1.3 |
| 2012 | 4 | 9 | 91 | 991.5 | 12.9 | 235 | 0.9 | 1.6 |
| 2012 | 4 | 10 | 82 | 990.2 | 9.5 | 255 | 1.8 | 2.8 |
| 2012 | 4 | 11 | 81.8 | 1000.5 | 6.1 | 290 | 2 | 2.9 |
| 2012 | 4 | 12 | 80.1 | 1006.8 | 7.3 | 295 | 1.7 | 2.4 |
| 2012 | 4 | 13 | 75.6 | 1006.7 | 4.6 | 320 | 1.9 | 2.6 |
| 2012 | 4 | 14 | 70.1 | 1014 | 7.8 | 335 | 2.2 | 3.2 |
| 2012 | 4 | 15 | 65.5 | 1026 | 4.1 | 340 | 1.7 | 2.4 |
| 2012 | 4 | 16 | 79.1 | 1016.7 | 12.7 | 155 | 1.5 | 2.2 |
| 2012 | 4 | 17 | 91 | 991.5 | 16.2 | 240 | 1.4 | 2.5 |
| 2012 | 4 | 18 | 85.3 | 986.1 | 11.2 | 315 | 2 | 3.2 |
| 2012 | 4 | 19 | 78 | 993.3 | 10.3 | 285 | 2.2 | 3.5 |
| 2012 | 4 | 20 | 78.5 | 994.8 | 8.5 | 260 | 2.1 | 3.2 |
| 2012 | 4 | 21 | 78.3 | 1000.8 | 11.1 | 270 | 2.1 | 3.5 |
| 2012 | 4 | 22 | 80.5 | 1002.9 | 10.8 | 255 | 1.9 | 2.9 |
| 2012 | 4 | 23 | 79.7 | 997.5 | 8.2 | 315 | 1.8 | 2.6 |
| 2012 | 4 | 24 | 78.5 | 998.2 | 5.2 | 140 | 2.1 | 3 |
| 2012 | 4 | 25 | 85.2 | 984.7 | 15.6 | 15 | 1 | 1.5 |
| 2012 | 4 | 26 | 78.5 | 997.8 | 14.7 | 340 | 1.7 | 2.4 |
| 2012 | 4 | 27 | 63.2 | 1014.8 | 10 | 360 | 2.5 | 3.7 |
| 2012 | 4 | 28 | 67.8 | 1022 | 10.6 | 25 | 2.5 | 3.9 |
| 2012 | 4 | 29 | 63.9 | 1015 | 14.9 | 15 | 2.8 | 4.5 |
| 2012 | 4 | 30 | 77 | 1010.7 | 16.6 | 20 | 1.9 | 3 |
| April | | | | | | 10 | 52.7 | 79.4 |



| Year | Month | Day | Mean Realative Humidity (%) | Mean MSL Pressure (hpa) | Mean Wind Speed (kt) | Predominant Wind Direction (degrees) | Potential Evapotranspiration (mm) | Evaporation (mm) |
|------|-------|-----|--------------------------------|----------------------------|-------------------------|---|---|---------------------|
| 2012 | 5 | 1 | 81.7 | 1017.5 | 15.9 | 30 | 1.5 | 2.4 |
| 2012 | 5 | 2 | 78.2 | 1022.6 | 5.2 | 35 | 3 | 4.3 |
| 2012 | 5 | 3 | 75.5 | 1014.2 | 5.1 | 30 | 2.6 | 3.4 |
| 2012 | 5 | 4 | 82.3 | 1009.5 | 8.4 | 15 | 1.5 | 2.1 |
| 2012 | 5 | 5 | 66.1 | 1013.1 | 7 | 40 | 1.9 | 2.7 |
| 2012 | 5 | 6 | 58 | 1012.7 | 9.2 | 100 | 2.8 | 4.1 |
| 2012 | 5 | 7 | 79.7 | 1004.2 | 8.5 | 190 | 2.4 | 3.5 |
| 2012 | 5 | 8 | 72.8 | 1005.5 | 7.8 | 330 | 2.5 | 3.7 |
| 2012 | 5 | 9 | 81.5 | 1004.9 | 6.6 | 40 | 1.5 | 2.2 |
| 2012 | 5 | 10 | 92.2 | 1003.8 | 7.1 | 300 | 1.1 | 1.6 |
| 2012 | 5 | 11 | 68.8 | 1028.7 | 9.8 | 295 | 2 | 2.7 |
| 2012 | 5 | 12 | 73.6 | 1040.6 | 7.1 | 245 | 2.9 | 4.4 |
| 2012 | 5 | 13 | 78.7 | 1027.7 | 15.3 | 220 | 2.1 | 3.7 |
| 2012 | 5 | 14 | 72.7 | 1017.3 | 14.3 | 265 | 2.6 | 4.5 |
| 2012 | 5 | 15 | 66.5 | 1024.2 | 10.9 | 295 | 3 | 4.7 |
| 2012 | 5 | 16 | 69.8 | 1026 | 3.5 | 270 | 2 | 2.8 |
| 2012 | 5 | 17 | 76 | 1014.5 | 5 | 90 | 1.5 | 2 |
| 2012 | 5 | 18 | 75.4 | 1008.9 | 8.1 | 15 | 2 | 2.9 |
| 2012 | 5 | 19 | 79.2 | 1012.2 | 8.8 | 20 | 1.4 | 2 |
| 2012 | 5 | 20 | 74.5 | 1012.4 | 4 | 125 | 2.8 | 3.7 |
| 2012 | 5 | 21 | 77.2 | 1010.8 | 8.9 | 125 | 2.6 | 3.5 |
| 2012 | 5 | 22 | 84.3 | 1014.9 | 11.9 | 145 | 2.4 | 3.4 |
| 2012 | 5 | 23 | 80 | 1023 | 12.6 | 120 | 2.4 | 3.6 |
| 2012 | 5 | 24 | 70.6 | 1026.9 | 6.4 | 110 | 4.5 | 5.9 |
| 2012 | 5 | 25 | 72 | 1021.7 | 6.8 | 85 | 2.5 | 3 |
| 2012 | 5 | 26 | 52.2 | 1017.4 | 11.8 | 80 | 5.7 | 7.7 |
| 2012 | 5 | 27 | 69.3 | 1017.4 | 6.5 | 130 | 4.4 | 5.8 |
| 2012 | 5 | 28 | 70.3 | 1016.1 | 10 | 120 | 3.2 | 4.6 |
| 2012 | 5 | 29 | 76.5 | 1016.6 | 8.5 | 135 | 2.6 | 3.5 |
| 2012 | 5 | 30 | 77.3 | 1016.9 | 6.3 | 180 | 3.1 | 4.2 |
| 2012 | 5 | 31 | 94.7 | 1018.9 | 7.1 | 225 | 1.3 | 1.9 |
| May | 111 | | | | | | 77.8 | 110.5 |



| Year | Month | Day | Mean Realative Humidity (%) | Mean MSL Pressure (hpa) | Mean Wind Speed (kt) | Predominant Wind Direction (degrees) | Potential Evapotranspiration (mm) | Evaporation (mm) |
|------|-------|-----|--------------------------------|----------------------------|-------------------------|---|---|---------------------|
| 2012 | 6 | 1 | 84.4 | 1019.1 | 3.2 | 180 | 2.4 | 3.2 |
| 2012 | 6 | 2 | 87.9 | 1010.8 | 6.6 | 70 | 1.7 | 2.3 |
| 2012 | 6 | 3 | 89.1 | 1009 | 7.8 | 15 | 0.9 | 1.3 |
| 2012 | 6 | 4 | 71.6 | 1016.8 | 7 | 120 | 2.9 | 4 |
| 2012 | 6 | 5 | 87.6 | 1006.5 | 9 | 95 | 1.4 | 1.9 |
| 2012 | 6 | 6 | 83.5 | 998.1 | 4 | 150 | 2.3 | 3.1 |
| 2012 | 6 | 7 | 95 | 988.9 | 11.5 | 345 | 0.8 | 1.2 |
| 2012 | 6 | 8 | 77.8 | 1000.1 | 20.8 | 280 | 2.1 | 3.3 |
| 2012 | 6 | 9 | 68.8 | 1010 | 5.6 | 245 | 4.3 | 6.1 |
| 2012 | 6 | 10 | 75.8 | 1008.1 | 3.9 | 310 | 2.4 | 3.2 |
| 2012 | 6 | 11 | 79 | 1007 | 5.1 | 280 | 2.6 | 3.4 |
| 2012 | 6 | 12 | 84.4 | 1012.2 | 7.4 | 305 | 2.1 | 3 |
| 2012 | 6 | 13 | 74.3 | 1014.7 | 4.4 | 310 | 3.2 | 4.4 |
| 2012 | 6 | 14 | 83.5 | 1005.4 | 14 | 80 | 1.8 | 2.9 |
| 2012 | 6 | 15 | 90 | 990.2 | 14.4 | 90 | 1 | 1.4 |
| 2012 | 6 | 16 | 87.2 | 1001.6 | 10.4 | 285 | 1 | 1.4 |
| 2012 | 6 | 17 | 74.8 | 1015.6 | 3.9 | 265 | 1.5 | 1.9 |
| 2012 | 6 | 18 | 85.6 | 1014.5 | 6.1 | 130 | 2.1 | 2.9 |
| 2012 | 6 | 19 | 73.3 | 1016.3 | 5.6 | 130 | 3.1 | 4.3 |
| 2012 | 6 | 20 | 80.2 | 1013.9 | 8.5 | 105 | 2.4 | 3.3 |
| 2012 | 6 | 21 | 93.8 | 1003.3 | 8.5 | 250 | 1.2 | 1.8 |
| 2012 | 6 | 22 | 82.4 | 1010.2 | 15 | 260 | 3.1 | 5.1 |
| 2012 | 6 | 23 | 86 | 1013.3 | 10.7 | 215 | 1.9 | 2.7 |
| 2012 | 6 | 24 | 80.9 | 1014.1 | 8.6 | 260 | 3.6 | 5.3 |
| 2012 | 6 | 25 | 80.7 | 1016.9 | 7.2 | 110 | 2.3 | 3.1 |
| 2012 | 6 | 26 | 88.8 | 1015 | 9 | 215 | 2.4 | 3.5 |
| 2012 | 6 | 27 | 86.7 | 1012.7 | 8.6 | 145 | 2.6 | 3.7 |
| 2012 | 6 | 28 | 87 | 997.6 | 9.6 | 155 | 2.7 | 3.9 |
| 2012 | 6 | 29 | 87 | 994.9 | 12.3 | 235 | 2.3 | 3.5 |
| 2012 | 6 | 30 | 85.7 | 1005.1 | 11.7 | 255 | 2.2 | 3.4 |
| June | | 9 | | | | | 66.3 | 94.5 |



| Year | Month | Day | Mean Realative Humidity (%) | Mean MSL Pressure (hpa) | Mean Wind Speed (kt) | Predominant Wind Direction (degrees) | Potential Evapotranspiration (mm) | Evaporation (mm) |
|------|-------|-----|--------------------------------|----------------------------|-------------------------|---|---|---------------------|
| 2012 | 7 | 1 | 88.2 | 1009.4 | 9.1 | 240 | 1.7 | 2.4 |
| 2012 | 7 | 2 | 88.5 | 1006.7 | 7.5 | 240 | 2.9 | 4.1 |
| 2012 | 7 | 3 | 94.2 | 1004.8 | 8.2 | 130 | 1.4 | 1.9 |
| 2012 | 7 | 4 | 84.3 | 1003.5 | 6.8 | 95 | 2.2 | 3.1 |
| 2012 | 7 | 5 | 80.8 | 1009.6 | 4.1 | 320 | 2.9 | 3.9 |
| 2012 | 7 | 6 | 89.9 | 1009.9 | 5.1 | 325 | 1.3 | 1.7 |
| 2012 | 7 | 7 | 86.1 | 1008.3 | 9.5 | 330 | 2.6 | 3.6 |
| 2012 | 7 | 8 | 85.5 | 1011.7 | 8.2 | 330 | 1.2 | 1.7 |
| 2012 | 7 | 9 | 84.5 | 1013.4 | 9.0 | 325 | 1.8 | 2.5 |
| 2012 | 7 | 10 | 83.5 | 1014.6 | 10.0 | 275 | 2.4 | 3.4 |
| 2012 | 7 | 11 | 78.0 | 1014.2 | 7.5 | 280 | 3 | 4.3 |
| 2012 | 7 | 12 | 93.4 | 1007.8 | 7.0 | 75 | 1.5 | 2.3 |
| 2012 | 7 | 13 | 87.3 | 1003.2 | 7.4 | 350 | 2.1 | 2.9 |
| 2012 | 7 | 14 | 75.3 | 1010.6 | 8.3 | 295 | 2.6 | 3.7 |
| 2012 | 7 | 15 | 81.8 | 1015.7 | 7.7 | 230 | 2.4 | 3.4 |
| 2012 | 7 | 16 | 95.8 | 1016.3 | 13.1 | 245 | 1.4 | 2.3 |
| 2012 | 7 | 17 | 91.8 | 1019.7 | 11.0 | 225 | 2.5 | 3.8 |
| 2012 | 7 | 18 | 90.7 | 1012.3 | 10.0 | 255 | 2.3 | 3.5 |
| 2012 | 7 | 19 | 78.5 | 1014.5 | 7.0 | 295 | 3.2 | 4.6 |
| 2012 | 7 | 20 | 72.0 | 1020.0 | 4.6 | 305 | 3 | 4.1 |
| 2012 | 7 | 21 | 72.5 | 1023.2 | 5.7 | 200 | 3.2 | 4.4 |
| 2012 | 7 | 22 | 83.6 | 1019.6 | 11.8 | 170 | 2.5 | 3.5 |
| 2012 | 7 | 23 | 95.5 | 1015.9 | 7.8 | 190 | 1,6 | 2.3 |
| 2012 | 7 | 24 | 94.1 | 1016.9 | 5.0 | 320 | 1.6 | 2.2 |
| 2012 | 7 | 25 | 89.7 | 1020.7 | 5.2 | 355 | 2.5 | 3.4 |
| 2012 | 7 | 26 | 81.0 | 1020.5 | 6.2 | 300 | 3.3 | 4.6 |
| 2012 | 7 | 27 | 76.2 | 1018.6 | 10.6 | 285 | 3.6 | 5.6 |
| 2012 | 7 | 28 | 77.8 | 1013.5 | 10.3 | 275 | 3 | 4.4 |
| 2012 | 7 | 29 | 77.5 | 1013.4 | 9.5 | 260 | 3 | 4.6 |
| 2012 | 7 | 30 | 80.8 | 1014.0 | 6.5 | 210 | 2.1 | 3 |
| 2012 | 7 | 31 | 93.3 | 1005.8 | 11.5 | 145 | 1.4 | 2.1 |
| July | | | 1 1 | | | | 72.2 | 103.3 |



| Year | Month | Day | Mean Realative Humidity (%) | Mean MSL Pressure (hpa) | Mean Wind Speed (kt) | Predominant Wind Direction (degrees) | Potential Evapotranspiration (mm) | Evaporation (mm) |
|--------|-------|-----|--------------------------------|----------------------------|-------------------------|---|---|---------------------|
| 2012 | 8 | 1 | 82.5 | 998.1 | 14.1 | 160 | 2.2 | 3.5 |
| 2012 | 8 | 2 | 79.6 | 1003.2 | 11.0 | 145 | 2.4 | 3.5 |
| 2012 | 8 | 3 | 88.6 | 1001.3 | 10.4 | 125 | 1.2 | 1.6 |
| 2012 | 8 | 4 | 84.9 | 1003.1 | 9.3 | 15 | 1.6 | 2.1 |
| 2012 | 8 | 5 | 88.0 | 1008.3 | 7.0 | 335 | 1.4 | 1.8 |
| 2012 | 8 | 6 | 91.0 | 1011.3 | 6.8 | 240 | 1.4 | 2.1 |
| 2012 | 8 | 7 | 89.2 | 1016.6 | 5.6 | 110 | 1.8 | 2.4 |
| 2012 | 8 | 8 | 90.4 | 1022.8 | 3.7 | 200 | 2.3 | 3 |
| 2012 | 8 | 9 | 87.6 | 1026.5 | 2.6 | 125 | 3.3 | 4.3 |
| 2012 | 8 | 10 | 73.5 | 1024.3 | 7.2 | 100 | 4.2 | 5.6 |
| 2012 | 8 | 11 | 77.5 | 1014.0 | 11.4 | 90 | 2.7 | 3.8 |
| 2012 | 8 | 12 | 88.0 | 1006.1 | 8.3 | 110 | 2.4 | 3.3 |
| 2012 | 8 | 13 | 85.5 | 1001.2 | 8.4 | 145 | 1.7 | 2.1 |
| 2012 | 8 | 14 | 77.6 | 1004.6 | 9.0 | 135 | 2 | 2.5 |
| 2012 | 8 | 15 | 86.3 | 990.3 | 18.0 | 85 | 1.7 | 2.6 |
| 2012 | 8 | 16 | 82.4 | 1000.7 | 12.0 | 155 | 2.8 | 3.2 |
| 2012 | 8 | 17 | 90.2 | 1003.0 | 5.8 | 120 | 2 | 2.3 |
| 2012 | 8 | 18 | 81.3 | 1009.4 | 10.3 | 155 | 2 | 2.5 |
| 2012 | 8 | 19 | 85.7 | 1012.8 | 12.2 | 135 | 1.7 | 2.1 |
| 2012 | 8 | 20 | 81.8 | 1015.8 | 8.2 | 240 | 2.6 | 3.6 |
| 2012 | 8 | 21 | 84.3 | 1014.1 | 11.8 | 230 | 2.4 | 3.6 |
| 2012 | 8 | 22 | 87.5 | 1015.9 | 12.4 | 240 | 2.3 | 3.4 |
| 2012 | 8 | 23 | 85.2 | 1010.7 | 7.9 | 155 | 1.2 | 1.4 |
| 2012 | 8 | 24 | 93.0 | 998.5 | 9.8 | 70 | 1.1 | 1.6 |
| 2012 | 8 | 25 | 85.1 | 1006.8 | 9.3 | 295 | 2.4 | 3.6 |
| 2012 | 8 | 26 | 86.8 | 1012.4 | 8.8 | 135 | 1.7 | 2.5 |
| 2012 | 8 | 27 | 86.0 | 1001.5 | 12.4 | 225 | 1.8 | 2.7 |
| 2012 | 8 | 28 | 78.2 | 1006.2 | 12.0 | 165 | 2.3 | 3.1 |
| 2012 | 8 | 29 | 86.1 | 1002.4 | 13.3 | 160 | 1.9 | 3 |
| 2012 | 8 | 30 | 71.7 | 1025.1 | 9.1 | 295 | 2.5 | 3.5 |
| 2012 | 8 | 31 | 85.5 | 1030.5 | 7.7 | 235 | 1.4 | 2 |
| August | 1-1 | • | | 101 | | | 64.4 | 88.3 |



| Year | Month | Day | Mean Realative Humidity (%) | Mean MSL Pressure (hpa) | Mean Wind Speed (kt) | Predominant Wind Direction (degrees) | Potential Evapotranspiration (mm) | Evaporation (mm) |
|--------|-------|-----|--------------------------------|----------------------------|-------------------------|---|---|---------------------|
| 2012 | 9 | 1 | 88.2 | 1024.0 | 10.8 | 220 | 1.9 | 2.9 |
| 2012 | 9 | 2 | 87.4 | 1025.2 | 5.4 | 265 | 1.1 | 1.6 |
| 2012 | 9 | 3 | 89.8 | 1025.1 | 6.4 | 120 | 1.7 | 2.3 |
| 2012 | 9 | 4 | 83.2 | 1027.4 | 7.2 | 295 | 1.8 | 2.7 |
| 2012 | 9 | 5 | 82.5 | 1031.2 | 2.7 | 350 | 2.1 | 2.8 |
| 2012 | 9 | 6 | 85.1 | 1027.1 | 7.0 | 255 | 2.4 | 3.5 |
| 2012 | 9 | 7 | 90.7 | 1024.6 | 5.4 | 225 | 1.4 | 1.8 |
| 2012 | 9 | 8 | 81.7 | 1017.2 | 6.8 | 155 | 2 | 2.8 |
| 2012 | 9 | 9 | 88.1 | 1003.7 | 10.3 | 215 | 1.5 | 2.1 |
| 2012 | 9 | 10 | 92.1 | 1005.8 | 6.9 | 225 | 0.9 | 1.2 |
| 2012 | 9 | 11 | 78.8 | 1015.6 | 10.3 | 265 | 1.6 | 2.4 |
| 2012 | 9 | 12 | 86.9 | 1016.9 | 9.3 | 290 | 1.8 | 2.7 |
| 2012 | 9 | 13 | 88.2 | 1018.8 | 13.8 | 240 | 1.4 | 2.1 |
| 2012 | 9 | 14 | 83.5 | 1016.9 | 13.3 | 270 | 1.9 | 2.9 |
| 2012 | 9 | 15 | 87.6 | 1016.5 | 8.7 | 245 | 1.3 | 1.8 |
| 2012 | 9 | 16 | 85.6 | 1010.3 | 10.6 | 250 | 1.2 | 1.8 |
| 2012 | 9 | 17 | 86.0 | 1010.3 | 11.2 | 230 | 1.3 | 1.8 |
| 2012 | 9 | 18 | 77.5 | 1018.8 | 9.8 | 285 | 1.9 | 2.8 |
| 2012 | 9 | 19 | 85.8 | 1023.2 | 6.7 | 230 | 1.1 | 1.6 |
| 2012 | 9 | 20 | 88.3 | 1017.2 | 7.2 | 205 | 1.1 | 1.5 |
| 2012 | 9 | 21 | 81.8 | 1018.4 | 6.5 | 25 | 1.4 | 2 |
| 2012 | 9 | 22 | 80.9 | 1018.7 | 6.4 | 120 | 1.6 | 2.2 |
| 2012 | 9 | 23 | 84.5 | 1006.8 | 7.1 | 105 | 1.2 | 1.7 |
| 2012 | 9 | 24 | 94.9 | 995.0 | 4.9 | 315 | 0.6 | 0.8 |
| 2012 | 9 | 25 | 90.3 | 990.4 | 10.9 | 330 | 0.9 | 1.2 |
| 2012 | 9 | 26 | 78.7 | 1000.3 | 13.8 | 330 | 1.9 | 2.6 |
| 2012 | 9 | 27 | 86.0 | 1010.7 | 7.0 | 270 | 1.1 | 1.5 |
| 2012 | 9 | 28 | 87.2 | 1012.3 | 10.0 | 255 | 1.4 | 1.9 |
| 2012 | 9 | 29 | 82.8 | 1019.0 | 9.0 | 245 | 1.3 | 1.8 |
| 2012 | 9 | 30 | 87.0 | 1010.5 | 13.7 | 220 | 1.1 | 1.6 |
| eptemb | er | 9 5 | | | | | 43.9 | 62.4 |



| Year | Month | Day | Mean Realative Humidity (%) | Mean MSL Pressure (hpa) | Mean Wind Speed (kt) | Predominant Wind Direction (degrees) | Potential Evapotranspiration (mm) | Evaporation (mm) |
|---------|-------|-----|--------------------------------|----------------------------|-------------------------|---|---|---------------------|
| 2012 | 10 | 1 | 83.7 | 1007.0 | 11.7 | 190 | 1.4 | 1.9 |
| 2012 | 10 | 2 | 83.2 | 1001.1 | 12.7 | 195 | 1.4 | 2 |
| 2012 | 10 | 3 | 83.3 | 1002.0 | 12.8 | 245 | 1.4 | 2.1 |
| 2012 | 10 | 4 | 90.2 | 1004.5 | 6.9 | 190 | 0.9 | 1.3 |
| 2012 | 10 | 5 | 86.4 | 1007.0 | 4.8 | 245 | 0.7 | 1 |
| 2012 | 10 | 6 | 91.3 | 1015.9 | 2.7 | 350 | 0.9 | 1.3 |
| 2012 | 10 | 7 | 91.9 | 1019.5 | 6.1 | 80 | 0.7 | 1 |
| 2012 | 10 | 8 | 90.1 | 1014.3 | 7.5 | 50 | 0.8 | 1 |
| 2012 | 10 | 9 | 88.9 | 1015.5 | 4.5 | 20 | 0.7 | 1 |
| 2012 | 10 | 10 | 91.9 | 1009.4 | 6.5 | 110 | 0.7 | 0.9 |
| 2012 | 10 | 11 | 85.9 | 1004.2 | 9.9 | 305 | 0.6 | 0.9 |
| 2012 | 10 | 12 | 88.8 | 1006.6 | 5.2 | 245 | 0.7 | 1.1 |
| 2012 | 10 | 13 | 87.3 | 1006.4 | 5.8 | 250 | 0.9 | 1.3 |
| 2012 | 10 | 14 | 90.9 | 1005.5 | 5.7 | 280 | 0.7 | 1 |
| 2012 | 10 | 15 | 94.5 | 998.4 | 9.2 | 165 | 0.4 | 0.7 |
| 2012 | 10 | 16 | 78.1 | 996.1 | 11.1 | 260 | 1.1 | 1.6 |
| 2012 | 10 | 17 | 92.4 | 981.7 | 9.4 | 60 | 0.7 | 1 |
| 2012 | 10 | 18 | 95.5 | 992.1 | 8.1 | 285 | 0.6 | 0.9 |
| 2012 | 10 | 19 | 89.3 | 1007.1 | 5.8 | 340 | 0.7 | 1 |
| 2012 | 10 | 20 | 86.8 | 1011.3 | 8.0 | 130 | 1 | 1.3 |
| 2012 | 10 | 21 | 85.3 | 1015.8 | 10.5 | 115 | 1.1 | 1.5 |
| 2012 | 10 | 22 | 90.5 | 1021.1 | 6.2 | 90 | 0.7 | 1 |
| 2012 | 10 | 23 | 95.3 | 1026.0 | 4.4 | 25 | 0.6 | 0.7 |
| 2012 | 10 | 24 | 91.8 | 1021.9 | 10.0 | 30 | 0.7 | 0.9 |
| 2012 | 10 | 25 | 92.9 | 1017.7 | 12.3 | 30 | 0.7 | 0.9 |
| 2012 | 10 | 26 | 70.1 | 1020.3 | 11.7 | 30 | 0.8 | 1.2 |
| 2012 | 10 | 27 | 74.4 | 1027.5 | 5.5 | 290 | 0.6 | 0.8 |
| 2012 | 10 | 28 | 83.7 | 1013.4 | 12.0 | 245 | 0.6 | 0.9 |
| 2012 | 10 | 29 | 91.3 | 1010.4 | 4.5 | 325 | 0.4 | 0.6 |
| 2012 | 10 | 30 | 85.9 | 1004.2 | 8.9 | 215 | 0.6 | 0.8 |
| 2012 | 10 | 31 | 85.9 | 980.4 | 7.6 | 205 | 0.4 | 0.6 |
| October | | | | | | | 24.2 | 34.2 |



| Year | Month | Day | Mean Realative Humidity (%) | Mean MSL Pressure (hpa) | Mean Wind Speed (kt) | Predominant Wind Direction (degrees) | Potential Evapotranspiration (mm) | Evaporation (mm) |
|--------|-------|-----|--------------------------------|----------------------------|-------------------------|---|---|---------------------|
| 2012 | 11 | 1 | 86.0 | 980.1 | 8.6 | 250 | 0.6 | 0.8 |
| 2012 | 11 | 2 | 84.3 | 988.3 | 9.7 | 215 | 0.8 | 1.1 |
| 2012 | 11 | 3 | 82.3 | 990.5 | 11.9 | 195 | 0.9 | 1.1 |
| 2012 | 11 | 4 | 89.4 | 989.5 | 9.6 | 345 | 0.5 | 0.7 |
| 2012 | 11 | 5 | 89.1 | 1013.4 | 6.6 | 325 | 0.6 | 0.8 |
| 2012 | 11 | 6 | 83.1 | 1025.1 | 9.6 | 265 | 0.6 | 0.8 |
| 2012 | 11 | 7 | 87.3 | 1023.8 | 10.5 | 235 | 0.6 | 0.8 |
| 2012 | 11 | 8 | 92.5 | 1018.7 | 7.2 | 240 | 0.4 | 0.6 |
| 2012 | 11 | 9 | 89.5 | 1002.7 | 8.4 | 190 | 0.5 | 0.7 |
| 2012 | 11 | 10 | 89.2 | 997.7 | 7.8 | 255 | 0.4 | 0.6 |
| 2012 | 11 | 11 | 88.7 | 1012.9 | 6.0 | 260 | 0.5 | 0.6 |
| 2012 | 11 | 12 | 96.5 | 1012.8 | 9.5 | 200 | 0.3 | 0.5 |
| 2012 | 11 | 13 | 94.2 | 1015.1 | 9.4 | 145 | 0.3 | 0.5 |
| 2012 | 11 | 14 | 92.0 | 1021.3 | 5.7 | 160 | 0.4 | 0.5 |
| 2012 | 11 | 15 | 97.4 | 1020.9 | 4.3 | 150 | 0.3 | 0.4 |
| 2012 | 11 | 16 | 93.2 | 1012.4 | 3.0 | 215 | 0.3 | 0.4 |
| 2012 | 11 | 17 | 88.8 | 1009.8 | 6.9 | 235 | 0.3 | 0.4 |
| 2012 | 11 | 18 | 92.7 | 1006.5 | 12.3 | 130 | 0.4 | 0.6 |
| 2012 | 11 | 19 | 89.8 | 994.6 | 13.8 | 170 | 0.5 | 0.7 |
| 2012 | 11 | 20 | 84.7 | 996.0 | 12.6 | 145 | 0.3 | 0.4 |
| 2012 | 11 | 21 | 86.3 | 1002.6 | 10.4 | 160 | 0.3 | 0.4 |
| 2012 | 11 | 22 | 84.3 | 994.9 | 12.3 | 175 | 0.6 | 0.8 |
| 2012 | 11 | 23 | 86.3 | 1007.7 | 7.0 | 210 | 0.1 | 0.1 |
| 2012 | 11 | 24 | 95.0 | 1009.9 | 3.4 | 325 | 0.1 | 0.2 |
| 2012 | 11 | 25 | 93.3 | 1000.9 | 7.9 | 90 | 0.3 | 0.4 |
| 2012 | 11 | 26 | 80.7 | 1011.1 | 13.6 | 330 | 0.7 | 0.8 |
| 2012 | 11 | 27 | 81.3 | 1019.2 | 8.1 | 325 | 0.3 | 0.3 |
| 2012 | 11 | 28 | 89.3 | 1023.3 | 3.0 | 315 | 0.1 | 0.2 |
| 2012 | 11 | 29 | 96.7 | 1016.1 | 5.0 | 120 | 0.2 | 0.2 |
| 2012 | 11 | 30 | 96.2 | 1012.3 | 5.8 | 45 | 0.2 | 0.3 |
| ovembe | er . | | | <u>.</u> | | | 12.4 | 16.7 |



| Year | Month | Day | Mean Realative Humidity (%) | Mean MSL Pressure (hpa) | Mean Wind Speed (kt) | Predominant Wind Direction (degrees) | Potential Evapotranspiration (mm) | Evaporation (mm) |
|--------|-------|-----|--------------------------------|----------------------------|-------------------------|---|---|---------------------|
| 2012 | 12 | 1 | 94.9 | 1019.9 | 3.2 | 255 | 0.2 | 0.3 |
| 2012 | 12 | 2 | 97.8 | 1013.7 | 9.3 | 220 | 0.3 | 0.4 |
| 2012 | 12 | 3 | 86.7 | 1009.5 | 9.1 | 255 | 0.2 | 0.2 |
| 2012 | 12 | 4 | 87.0 | 1007.7 | 9.6 | 260 | 0.5 | 0.7 |
| 2012 | 12 | 5 | 87.9 | 1016.2 | 5.0 | 280 | 0.1 | 0.2 |
| 2012 | 12 | 6 | 87.5 | 1009.9 | 12.3 | 215 | 0.4 | 0.6 |
| 2012 | 12 | 7 | 81.8 | 1016.4 | 9.0 | 290 | 0.3 | 0.4 |
| 2012 | 12 | 8 | 93.1 | 1028.0 | 4.9 | 235 | 0.3 | 0.3 |
| 2012 | 12 | 9 | 94.9 | 1024.9 | 5.8 | 250 | 0.3 | 0.4 |
| 2012 | 12 | 10 | 93.1 | 1026.8 | 4.3 | 75 | 0 | 0.1 |
| 2012 | 12 | 11 | 82.2 | 1025.6 | 10.9 | 100 | 0.7 | 0.8 |
| 2012 | 12 | 12 | 84.5 | 1011.6 | 11.5 | 120 | 0.8 | 1 |
| 2012 | 12 | 13 | 84.7 | 997.1 | 12.5 | 110 | 0.4 | 0.4 |
| 2012 | 12 | 14 | 91.5 | 975.9 | 11.8 | 225 | 0.5 | 0.6 |
| 2012 | 12 | 15 | 88.5 | 984.3 | 8.7 | 195 | 0.3 | 0.4 |
| 2012 | 12 | 16 | 87.5 | 990.6 | 10.1 | 160 | 0.5 | 0.7 |
| 2012 | 12 | 17 | 89.0 | 1001.1 | 12.0 | 245 | 0.2 | 0.2 |
| 2012 | 12 | 18 | 93.7 | 1012.6 | 9.3 | 115 | 0.3 | 0.3 |
| 2012 | 12 | 19 | 94.1 | 1003.4 | 11.0 | 120 | 0.3 | 0.4 |
| 2012 | 12 | 20 | 99.1 | 999.9 | 3.6 | 115 | 0.2 | 0.3 |
| 2012 | 12 | 21 | 96.8 | 1005.6 | 8.8 | 120 | 0.2 | 0.3 |
| 2012 | 12 | 22 | 95.2 | 992.7 | 11.7 | 185 | 0.4 | 0.6 |
| 2012 | 12 | 23 | 86.1 | 998.3 | 13.3 | 220 | 0.7 | 0.8 |
| 2012 | 12 | 24 | 88.0 | 991.7 | 7.7 | 150 | 0.4 | 0.4 |
| 2012 | 12 | 25 | 92.7 | 994.5 | 6.5 | 240 | 0.2 | 0.3 |
| 2012 | 12 | 26 | 85.7 | 999.0 | 13.1 | 245 | 0.6 | 0.8 |
| 2012 | 12 | 27 | 91.0 | 1005.6 | 7.8 | 190 | 0.3 | 0.4 |
| 2012 | 12 | 28 | 85.8 | 1000.3 | 16.1 | 185 | 0.7 | 0.9 |
| 2012 | 12 | 29 | 80.7 | 994.3 | 12.3 | 205 | 0.8 | 1 |
| 2012 | 12 | 30 | 83.8 | 1002.2 | 19.0 | 240 | 0.8 | 1.1 |
| 2012 | 12 | 31 | 91.0 | 996.0 | 14.0 | 250 | 0.5 | 0.6 |
| ecembe | r | • | 1111 | | | | 12.4 | 15.9 |



Appendix I – Water Balance Calculations



Water Balance Calculations 2012

Upper Bound 10% infiltration of actual rainfall on the area covered with capping and Cell 1.

| ed _ | 3 | | | - 4 | | 8 | 9 | | | 1 | 80 | 8 | 84 |
|--|---------|----------|-------|--------|-------|---------|--------|--------|-----------|---------|----------|----------|---------|
| Total Leachate produced | 543.23 | 89.86 | -3.47 | 36.67 | -3.47 | 471.28 | 101.96 | 70.37 | 24.87 | 317.81 | 623.28 | 583.38 | 2855.78 |
| Volume of Leachate Capped (m3) | 150.34 | 32.59 | 0 | 40 | 0.00 | 158.36 | 64 | 39 | 28.34 | 96.66 | 170.96 | 159.47 | 939.64 |
| Effective Rainfall (m) - Capped Area | 0.0955 | 0.0207 | 0 | 0.0255 | 0 | 0.1006 | 0.0406 | 0.0247 | 0.0180 | 0.0614 | 0.1086 | 0.1013 | |
| Final Capped Area (m2) | 15742 | 15742 | 15742 | 15742 | 15742 | 15742 | 15742 | 15742 | 15742 | 15742 | 15742 | 15742 | |
| Volume of free leachate | 392.89 | 57.28 | -3.47 | -3.47 | -3.47 | 312.92 | 38.05 | 31.49 | -3.47 | 221.15 | 452.32 | 423.92 | 1916.14 |
| Absorptive Capadty (m3) | 3,468 | 3.468 | 3.468 | 3.468 | 3,468 | 3.468 | 3,468 | 3.468 | 3,468 | 3.468 | 3.468 | 3.468 | 20.0 |
| Effective Rainfall x Active Area | 396.359 | 60.743 | 0 | 0 | 0 | 316.388 | 41,515 | 34.96 | 0 | 224.618 | 455.791 | 427.386 | |
| Volume of waste (t) | 88 | 88 | 88 | 88 | 88 | 88 | 88 | 88 | 88 | 88 | 88 | 88 | |
| Effective Rainfall (m) - Active Cell | 0.0907 | 0.0139 | 0 | 0 | 0 | 0.0724 | 0.0095 | 0.0080 | 0 | 0.0514 | 0.1043 | 0.0978 | |
| Active cell (m2) | 4370 | 4370 | 4370 | 4370 | 4370 | 4370 | 4370 | 4370 | 4370 | 4370 | 4370 | 4370 | |
| Period (Jan 2012 - Active cell Dec 2012) (m2) | January | February | March | April | May | June | July | August | September | October | November | December | TOTAL |

| | | NAME OF TAXABLE | | NAME OF TAXABLE PARTY | | 200000000000000000000000000000000000000 | THE PERSON | WINN NOW A | | |
|---------------------------------|---------------------|--|------------------------|--|-------------------------------|---|------------------------------|--|--------------------------------------|-------------------------------|
| Period (Jan 2012 - Dec 2012) | Active cell (m2) | Effective Rainfall (m) - Active Cell | Volume of waste (t) | Effective Rainfall x Active Area | Absorptive Capadty (m3) | Volume of free leachate | Final Capped Area (m2) | Effective Rainfall (m) - Capped Area | Volume of Leachate Capped (m3) | Total Leachate produced |
| January | 4370 | 0.0907 | 88 | 396.359 | 3.468 | 392.89 | 15742 | 0.0955 | 30.07 | 422.96 |
| February | 4370 | 0.0139 | 88 | 60.743 | 3.468 | 27.28 | 15742 | 0.0207 | 6.52 | 63.79 |
| March | 4370 | 0.0000 | 88 | 0 | 3,468 | -3.47 | 15742 | 000000 | 0 | -3.47 |
| April | 4370 | 0.0000 | 88 | 0 | 3.468 | -3.47 | 15742 | 0.0255 | 8 | 4.56 |
| May | 4370 | 0.0000 | 88 | 0 | 3.468 | -3.47 | 15742 | 000000 | 00'0 | -3.47 |
| June | 4370 | 0.0724 | 88 | 316 | 3,468 | 312.92 | 15742 | 9001.0 | 31.67 | 344.59 |
| July | 4370 | 0.0095 | 88 | 42 | 3,468 | 38,05 | 15742 | 90,0406 | 13 | 50.83 |
| August | 4370 | 0.0080 | 88 | 32 | 3.468 | 31.49 | 15742 | 0.0247 | 8 | 39.27 |
| September | 4370 | 0.0000 | 88 | 0.000 | 3,468 | -3.47 | 15742 | 0.0180 | 2.67 | 2.20 |
| October | 4370 | 0.0514 | 88 | 224.618 | 3.468 | 221.15 | 15742 | 0.0614 | 19.33 | 240.48 |
| November | 4370 | 0.1043 | 88 | 455.791 | 3,468 | 452.32 | 15742 | 9801.0 | 34.19 | 486.51 |
| December | 4370 | 0.0978 | 88 | 427.386 | 3.468 | 423.92 | 15742 | 0.1013 | 31.89 | 455.81 |
| TOTAL | | | | | | 1916.14 | | | 187.93 | 2104.07 |



Guidance to completing the PRTR workbook

AER Returns Workbook

| REFERENCE YEAR | 2012 |
|----------------|------|
| | |

1. FACILITY IDENTIFICATION

| Parent Company Name | Clare County Council |
|----------------------------|-----------------------|
| Facility Name | Tradaree Point E.T.P. |
| PRTR Identification Number | W0037 |
| Licence Number | W0037-01 |

| Waste or IPPC Classes of Activity | |
|---|--|
| No. | class_name |
| | Swaging by explosives where the production area exceeds 100 |
| 3.7 | square metres. |
| 3.1 | The initial melting or production of iron and steel |
| | Storage prior to submission to any activity referred to in a |
| | preceding paragraph of this Schedule, other than temporary |
| | storage, pending collection, on the premises where the waste |
| 3.13 | concerned is produced. |
| | |
| | The production, recovery or processing of non-ferrous metals, their |
| | compounds or other alloys including antimony, arsenic, beryllium, |
| | chromium, lead, magnesium, manganese, phosphorus, selenium, |
| | cadmium, or mercury, by thermal, chemical, or electrolytic means |
| 3.4 | in installations with a batch capacity exceeding 0.5 tonnes. |
| | The reaction of aluminium or its alloys with chlorine or its |
| 3.5 | compounds, not included in paragraph 5.13. |
| | The roasting, sintering or calcining of metallic ores in plants with a |
| 3.6 | capacity exceeding 1,000 tonnes per year. |
| Address 1 | Tradaree Point E.T.P. |
| Address 2 | Shannon, (Clonmoney South) |
| Address 3 | Co. Clare |
| Address 4 | |
| | |
| | Clare |
| Country | |
| Coordinates of Location | |
| River Basin District | IEGBNISH |
| NACE Code | |
| | Treatment and disposal of non-hazardous waste |
| | Ms Ailish Johnston, Response Group |
| AER Returns Contact Email Address | |
| AER Returns Contact Position | · · |
| AER Returns Contact Telephone Number | |
| AER Returns Contact Mobile Phone Number | |
| AER Returns Contact Fax Number | |
| Production Volume | |
| Production Volume Units | |
| Number of Installations | - |
| Number of Operating Hours in Year | |
| Number of Employees | |
| User Feedback/Comments | |
| Web Address | |

2. PRTR CLASS ACTIVITIES

| Activity Number | Activity Name |
|-----------------|---------------|
| 50.1 | General |
| 50.1 | General |

| 3. SOLVEN IS REGULATIONS (S.I. No. 543 of 2002) |
|---|
| ls it applicable? |
| Have you been granted an exemption? |
| If applicable which activity class applies (as per |
| Schedule 2 of the regulations) ? |
| Is the reduction scheme compliance route being used ? |

| 4. WASTE IMPORTED/ACCEPTED ONTO SITE | Guidance on waste imported/accepted onto site |
|---|---|
| Do you import/accept waste onto your site for on- | |
| site treatment (either recovery or disposal | |
| activities) ? | |

This question is only applicable if you are an IPPC or Quarry site

09/07/2013 09:21

18

| SECTION A: SECTOR SPECIFIC PRIR PO | LLUTANTS | | | | | _ | | |
|------------------------------------|-----------------|-------|-------------|----------------------------|--|-------------------|------------------------|----------------------|
| | RELEASES TO AIR | | | | Please enter all quantities in this section in KGs | | | |
| | POLLUTANT | | | METHOD | | | QUANTITY | |
| | | | | Method Used | | | | |
| No. Annex II | Name | M/C/E | Method Code | Designation or Description | Emission Point 1 | T (Total) KG/Year | A (Accidental) KG/Year | F (Fugitive) KG/Year |
| | | | | | 0.0 | 1 | 0.0 | 0.0 |

| PRTR# : W0037 | Facility Name : Tradaree Point E.T.P. | Filename : W0037_2012.xls | Return Year : 2012 |

* Select a row by double-clicking on the Pollutant Name (Column B) then click the delete button

SECTION B: REMAINING PRTR POLLUTANTS

4.1 RELEASES TO AIR

| | RELEASES TO AIR | Please enter all quantities in this section in KGs | | | | | | | | | |
|--------------|----------------------|--|-------------|----------------------------|------------------|-------------------|------------------------|----------------------|--|--|--|
| | POLLUTANT | | M | ETHOD | | | QUANTITY | | | | |
| | | | | Method Used | | | | | | | |
| No. Annex II | Name | M/C/E | Method Code | Designation or Description | Emission Point 1 | T (Total) KG/Year | A (Accidental) KG/Year | F (Fugitive) KG/Year | | | |
| | | | | | 0.0 | 0.0 | 0.0 | 0.0 | | | |
| 03 | Carbon dioxide (CO2) | E | ESTIMATE | | 4323.3 | 4323.3 | 0.0 | 0.0 | | | |
| 01 | Methane (CH4) | E | ESTIMATE | | 3107.3 | 3107.3 | 0.0 | 0.0 | | | |

^{*} Select a row by double-clicking on the Pollutant Name (Column B) then click the delete button

Link to previous years emissions data

| SEC | CTION C : REMAINING POLLUTANT EM | ISSIONS (As required in your Licence) | | | | | | | | |
|-----|----------------------------------|---------------------------------------|--------|-------------|----------------------------|-----------------------------|------------------------|-----|----------------------|----------------------|
| | | RELEASES TO AIR | | | | Please enter all quantities | s in this section in K | Gs | | |
| | | POLLUTANT | METHOD | | | QUANTITY | | | | |
| | | | | | Method Used | | | | | |
| | Pollutant No. | Name | M/C/E | Method Code | Designation or Description | Emission Point 1 | T (Total) KG/Year | Α | (Accidental) KG/Year | F (Fugitive) KG/Year |
| 210 | | Dust | M | ALT | vdi 2119 Part 2 | 2.3 | | 2.3 | 0.0 | 0.0 |

 * Select a row by double-clicking on the Pollutant Name (Column B) then click the delete button

Additional Data Requested from Landfill operators

For the purposes of the National Inventory on Greenhouse Gases, landfill operators are requested to provide summary data on landfill gas

| | npany the figures for total methane generated. Operators should only report their Net (total) KG/yr for Section A: Sector specific PRTR pollutants above. Please complete the | | | | | |
|--|---|-------|-------------|-------------------|-------------------------|----------------------------|
| Landfill: | Tradaree Point E.T.P. | | | | _ | |
| Please enter summary data on the | | | | | | |
| quantities of methane flared and / or | | | | | | |
| utilised | | | Meti | hod Used | | |
| | | | | Designation or | Facility Total Capacity | |
| | T (Total) kg/Year | M/C/E | Method Code | Description | m3 per hour | |
| Total estimated methane generation (as per | | | | Modelled by Tobin | | |
| site model) | 3107.3 | E | ESTIMATE | engineers | N/A | |
| Methane flared | 0.0 | | | | 0.0 | (Total Flaring Capacity) |
| Methane utilised in engine/s | 0.0 | | | | 0.0 | (Total Utilising Capacity) |
| Net methane emission (as reported in Section | | | | Modelled by Tobin | | |
| A above) | 3107.3 | Е | ESTIMATE | engineers | N/A | |
| | | | | | | |

4.2 RELEASES TO WATERS

Link to previous years emissions data

| PRTR#: W0037 | Facility Name: Tradaree Point E.T.P. | Filename: W0037_2012.xls | Return Year: 2012 | 09/07/2013 09:22

SECTION A: SECTOR SPECIFIC PRTR POLLUTANTS

Data on ambient monitoring of storm/surface water or groundwater, conducted as part of your licence requirements, should NOT be submitted under AER / PRTR Reporting as this only concerns Releases from your facility

| | RELEASES TO WATERS | | | | Please enter all quantities | in this section in KGs | 5 | |
|--------------|--------------------|-------|-------------|----------------------------|-----------------------------|------------------------|------------------------|----------------------|
| PO | LLUTANT | | | | | | QUANTITY | |
| | | | | Method Used | | | | |
| No. Annex II | Name | M/C/E | Method Code | Designation or Description | Emission Point 1 | T (Total) KG/Year | A (Accidental) KG/Year | F (Fugitive) KG/Year |
| | | | | | 0. | 0 0 | 0.0 | 0.0 |

^{*} Select a row by double-clicking on the Pollutant Name (Column B) then click the delete button

SECTION B: REMAINING PRTR POLLUTANTS

| | RELEASES TO WATERS | Please enter all quantities in this section in KGs | | | | | | | | |
|--------------|--------------------|--|-------------|----------------------------|------------------|-------------------|------------------------|----------------------|--|--|
| POI | LUTANT | | | | | | QUANTITY | | | |
| | | | | Method Used | | | | | | |
| No. Annex II | Name | M/C/E | Method Code | Designation or Description | Emission Point 1 | T (Total) KG/Year | A (Accidental) KG/Year | F (Fugitive) KG/Year | | |
| | | | | | 0.0 | 0.0 | 0.0 | 0.0 | | |

^{*} Select a row by double-clicking on the Pollutant Name (Column B) then click the delete button

SECTION C : REMAINING POLLUTANT EMISSIONS (as required in your Licence)

| | RELEASES TO WATERS | | Please enter all quantities in this section in KGs | | | | | | | | |
|---------------|--------------------|-------|--|----------------------------|------------------|-------------------|------------------------|----------------------|--|--|--|
| POI | LLUTANT | | | | | | QUANTITY | | | | |
| | | | | Method Used | | | | | | | |
| Pollutant No. | Name | M/C/E | Method Code | Designation or Description | Emission Point 1 | T (Total) KG/Year | A (Accidental) KG/Year | F (Fugitive) KG/Year | | | |
| | | | | | 0 | .0 0 | .0 0.0 | 0.0 | | | |

 $^{^{\}star}$ Select a row by double-clicking on the Pollutant Name (Column B) then click the delete button

SECTION A: PRTR POLLUTANTS

| OEOTION ATTRIKT OEEOTANTO | | | | | | | | | |
|---------------------------|---|----------|------------------|----------------------------|-----------------------------|------------------------|-----------------------|----------------------|--|
| OFFSITE TRANS | SFER OF POLLUTANTS DESTINED FOR WASTE-W | ATER TRE | EATMENT OR SEWER | | Please enter all quantities | in this section in KGs | | | |
| PO | LLUTANT | | METHO | D | QUANTITY | | | | |
| | | | Meti | hod Used | | | | | |
| No. Annex II | Name | M/C/E | Method Code | Designation or Description | Emission Point 1 | T (Total) KG/Year | A (Accidental) KG/Yea | F (Fugitive) KG/Year | |
| | | | | | 0.0 |) (| 0.0 | .0 0.0 | |

^{*} Select a row by double-clicking on the Pollutant Name (Column B) then click the delete button

SECTION B: REMAINING POLLUTANT EMISSIONS (as required in your Licence)

| OF | FSITE TRANSFER OF POLLUTANTS DESTINED FOR | WER | Please enter all quantities in this section in KGs | | | | | |
|---------------|---|-------|--|----------------------------|------------------|-------------------|-----------------------|------------------------|
| | POLLUTANT | | M | ETHOD | | | | |
| | | | | Method Used | | | | |
| Pollutant No. | Name | M/C/E | Method Code | Designation or Description | Emission Point 1 | T (Total) KG/Year | A (Accidental) KG/Yea | r F (Fugitive) KG/Year |
| | | | | | 0. | 0 | 0.0 | 0.0 |

^{*} Select a row by double-clicking on the Pollutant Name (Column B) then click the delete button

4.4 RELEASES TO LAND

Link to previous years emissions data

| PRTR# : W0037 | Facility Name : Tradaree Point E.T.P. | Filename : W0037_2012.xls | Return Year : 2012 |

09/07/2013 09:23

SECTION A: PRTR POLLUTANTS

| | RELEASES TO LAND | | | | Please enter all quantities | 3 | |
|--------------|------------------|--------|-------------|----------------------------|-----------------------------|-------------------|------------------------|
| PO | LLUTANT | METHOD | | | | | QUANTITY |
| | | | | Method Used | | | |
| No. Annex II | Name | M/C/E | Method Code | Designation or Description | Emission Point 1 | T (Total) KG/Year | A (Accidental) KG/Year |
| | | | | | 0.0 | | 0.0 |

^{*} Select a row by double-clicking on the Pollutant Name (Column B) then click the delete button

SECTION B: REMAINING POLLUTANT EMISSIONS (as required in your Licence)

| | RELEASES TO LAND | | | | Please enter all quantities | | |
|---------------|------------------|--------|-------------|----------------------------|-----------------------------|-------------------|------------------------|
| PO | LLUTANT | METHOD | | | | | QUANTITY |
| | | | | Method Used | | | |
| Pollutant No. | Name | M/C/E | Method Code | Designation or Description | Emission Point 1 | T (Total) KG/Year | A (Accidental) KG/Year |
| | | | | | 0.0 | | 0.0 0.0 |

^{*} Select a row by double-clicking on the Pollutant Name (Column B) then click the delete button

5. ONSITE TREATMENT & OFFSITE TRANSFERS OF WASTE | PRTR#: W0037 | Facility Name: Tradaree Point E.T.P. | Filename: W0037_2012.xls | Return Year: 2012 |

09/07/2013 09:24

| | | | | | TTTTTT . TTOOOT Tability Ttallio . Tradarco Tollic E.T.I. | I I nondino . vv | /001/ | do 1 (otalii 1 otal . 2012 | | | | | 00/01/2010 00.24 |
|---|----------------------|----------------|-----------|----------------------------------|---|--------------------|-------|------------------------------|-------------|--|--|---|--|
| | | | | Please enter a | all quantities on this sheet in Tonnes | | | | | | | | 5 |
| | | Firm and Works | | Quantity (Tonnes per Year) | | Waste Treatment | | Method Used | Location of | Haz Waste: Name and Licence/Permit No of Next Destination Facility Non Haz Waste: Name and Licence/Permit No of Recover/Disposer | Haz Waste: Address of Next Destination Facility Non Haz Waste: Address of Recover/Disposer | Name and License / Permit No. and Address of Final Recoverer / Disposer (HAZARDOUS WASTE ONLY) | Actual Address of Final Destination i.e. Final Recovery / Disposal Site (HAZARDOUS WASTE ONLY) |
| | | European Waste | | | | | | | | | | | |
| | Transfer Destination | Code | Hazardous | | Description of Waste | Operation | M/C/E | Method Used | Treatment | | | | |
| - | Within the Country | 19 07 03 | No | | landfill leachate other than those mentioned in 19 07 02 | D8 | М | Volume Calculation | | Shannon Town Wastewater offireatment Plant, D0045 | Tradaree point,Clonmoney South,Shannon,Co. Clare,Ireland | | |

^{*} Select a row by double-clicking the Description of Waste then click the delete button

Link to previous years waste data
Link to previous years waste summary data & percentage change