

EPA Application Form

7.5 - Noise Emissions - Attachment





Amendments to this Application Form Attachment

Version No.	Date	Amendment since previous version	Reason
V.1.0	July 2017	N/A	Online application form attachment
As above	Mar 2018	Identification of required fields	Assist correct completion of attachment
		N&C.	
		14. of differs?	
		oses ad fair	

* indicates required field



Noise Emissions (see Note i at the end of this attachment)

Note: An assessment of the impacts of noise, where applicable, should be uploaded in Tab 7 – 'Emissions Overview' of the application form.

Provide detail of measures to reduce noise emissions (list techniques)

(See Note ii at the end of this attachment)

Site activities will only take place during the hours of 07:00 and 18:00 Monday to Friday and 07:00 and 14:00 on Saturdays. There will be no activities on site on Sundays or Public Holidays;

Perimeter screening mounds will be maintained along the site boundary to facilitate noise attenuation;

Screening mounds are planted with tree and shrub species and will be improved where required;

All haul routes will be kept clean and maintained in a good state of repair;

Heavy goods vehicles entering and leaving the existing the Site will have tailgates securely fastened; all mobile plant used at the proposed development will have noise emission levels that comply with relevant guidance; Plant will be operated in a proper manner with respect to minimising noise emissions, e.g. no unnecessary revving of engines, plant used intermittently not left idling;

Plant will be subject to regular maintenance, ite. all moving parts kept well lubricated, the integrity of silencers and acoustic hoods maintained; and

Plant will be fitted with effective whaust silencers and maintained in good working order to meet manufacturers' noise rating levels. Defective silencers will be replaced.

Following the *Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4)* (2012 as amended) complete the table below, inputting summary details of noise monitoring points (see Note iii at the end of this attachment) and proposed noise limit criteria.

^{*} indicates required field



	Easting 2	Northing 3	Monitoring point type ⁴	Proposed Noise Limit Criteria				
Monitoring point code ¹				Max. noise level daytime dB L _{Ar,T} (30 mins)	Max. noise level evening dB L _{Ar,T} (30 mins)	Max. noise level night dB L _{eq,T} (15-30 mins)	How was the noise limit derived? 5	Proposed monitoring frequency
N1	269143	239338	Boundary	55	not applicable	not applicable	EQS	annual
N2	269529	239275	Boundary	55	not applicable	not applicable	EQS	annual
N3	269029	239048	Boundary	55	not applicable	not offer applicable	EQS	annual
					outloges out of are			
				Consent of copyright	Louter rev			
				त्र विद्वारोगी.				
				Couser				

¹ The following convention should be observed when labelling noise monitoring points: N1, N2,.....The monitoring locations should be identified on an accompanying site plan drawing(s) uploaded in Tab 3 – 'Site' of the application form.

² Six Digit GPS Irish National Grid Reference of Monitoring Point

³ Six Digit GPS Irish National Grid Reference of Monitoring Point

⁴ Monitoring point type options: 'Boundary', 'Noise Sensitive Location' or 'Permanent Noise Monitoring'

⁵ Derived noise limit options: 'BAT', 'EQS', or 'Derogation'

^{*} indicates required field



				Proposed Noise Limit Criteria				
Monitoring point code ¹	Easting ²	Northing 3	Monitoring point type ⁴	Max. noise level daytime dB L _{Ar,T} (30 mins)	Max. noise level evening dB L _{Ar,T} (30 mins)	Max. noise level night dB L _{eq,T} (15-30 mins)	How was the noise limit derived? 5	Proposed monitoring frequency
						ري. ا		
						ather it.		
					व्याप्त, व्याप			
					uposes of for			
				ac	ion or red			
				cor itsp	O			
				ot of cops				
				For the per				

Note: Map(s)/drawing(s) uploaded under 'Site Plans' in Tab 3 of the application form should identify the emission and monitoring points.

^{*} indicates required field



Was an assessment for tonal and impulsive noise carried out? 6 (Yes/No)	No
If 'Yes' was tonal or impulsive noise identified to be present? (Yes/No)	

For emissions outside the EPA Noise Guidance Note limit, see the Agency's *Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4)* (2012) (available on www.epa.ie), a full evaluation of the existing abatement/treatment system must be provided. A planned programme of improvement towards meeting upgraded standards is required to be uploaded with this document. This programme should highlight specific goals and a time scale, together with options for modification, upgrading or replacement, as required, to bring the emissions within the limits as set out in the Guidance Note.

Consent of copyright owner required for any other use

⁶ Refer to section 5 of the Agency's Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4) (2012 as amended).

^{*} indicates required field



Note i This part of the application form collects data on noise emissions namely measures used to reduce noise and noise levels at a reference distance under normal operation. As noise emissions can arise from different sources on a site, the EPA usually considers the total emission from the site. Please note that emission limit values and monitoring requirements in any proposed licence shall be based on the information supplied hereunder.

Note ii Measures are usually required to reduce, minimise or prevent emissions from occurring. They may involve the application of a single technique or a combination of techniques including housing, insulation and appropriate location of equipment. List all techniques proposed/employed. Technique(s) employed must comply with BAT. Highlight additional measures required for the purposes of protecting the environment. The measures or techniques to be taken must be capable of complying with the proposed/known emission level(s).

The measures required shall be informed by the following:

- 1. BAT techniques
- 2. Stricter measures/techniques than BAT
- 3. BAT determined by competent authority in consultation with the applicant
- 4. Other measures

Noise emissions differ from other emissions in that they are generally instead at a reference (12 digit, 6E, 6N) must be given for each monitoring point. Noise emissions differ from other emissions in that they are generally instead at a reference distance from the source(s). This reference distance should be, where possible, the boundary of the installation but in certain circumstances it is a noise sensitive location outside the boundary of the installation. Noise levels along a boundary will vary due to the location and positioning of noise sources and the 'worst case' should always be selected. Sufficient points should be identified to fully describe the noise levels from the installation. For waste activities, traffic noise emissions should be taken into account especially if it. The Agency's Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4) (2012) and Guidance Note on Noise assessment of Wind Turbine Operations at EPA licensed Sites (NG3)(as appropriate) should be consulted when setting proposed sound limits.

^{*} indicates required field