

# **EPA Application Form**

7.4.2 - Emissions to Atmosphere - Minor and Potential Emissions - Attachment

	For inspection to
Organisation Name:	Advanced Environmental Solutions (Ireland) Ltd.
Application I.D.:	LA001502



# Amendments to this Application Form Attachment

Version No.	Date	Amendment since previous version	Reason
V.1.0	July 2017	N/A	Online application form attachment
		ت.	
		offering	
		Ses of tot and	





### **EMISSIONS TO ATMOSPHERE**

Emissions to air/atmosphere include the following:

#### **Main Emissions**

Main emissions include all emissions of environmental significance. Where a **mass emission threshold** is specified in a BAT document (BAT Conclusions, National BAT note or BREF), emissions which exceed this threshold prior to abatement are regarded as significant, i.e., 'main emissions'. (In some cases emissions below the threshold can still be significant and qualify as Main Emissions).

#### **Minor Emissions**

Emissions below the mass emission threshold <u>may</u> be considered minor emissions and therefore do not generally need to be specifically controlled by the conditions or schedules of the licence (i.e., setting of ELVs, abatement control measures, or monitoring requirements). Emissions may also be deemed minor by virtue of their source/nature (e.g., laboratory fume hoods, workspace extractions, passive vents from storage tanks, HVAC exhausts), or composition (e.g., water vapour emissions).

For combustion plant such as boilers, these can be considered minor where the sated thermal input is < 1MW where natural gas is the main fuel, and for liquid and solid fuels where its < 250kW.

#### **Fugitive Emissions**

Fugitive emissions include emissions from non-point sources and diffuse sources.

#### **Potential Emissions**

These are emissions which only operate under abnormal process conditions. Typical examples include bursting discs, pressure relief valves, and emergency generators. Bypasses and flares may also fall within this category, depending on how they are operated or designed to operate. Although the Agency does not normally set controls in dicences for potential emissions, it may do so for the purposes of environmental protection.

This attachment collects information on main and fugitive emissions to atmosphere. Waste gas means the final gaseous emission from a stack or abatement equipment.

For main and fugitive emissions to atmosphere, complete the separate '*Emissions to Atmosphere - Main* and *Fugitive Emissions'* attachment.



## EMISSIONS TO ATMOSPHERE - Minor Emissions - one row per emission point NOT APPLICABLE

In completing this attachment for minor emissions, the applicant should supply sufficient information to justify the determination of the emission as minor. Notwithstanding the guidance provided on minor emissions, the Agency may consider any emission to be significant (i.e., a main emission) on the basis of environmental impact.

Complete the table below with summary details for all minor emission points to atmosphere.

Emission Point	Easting <sup>(2)</sup>	ting <sup>(2)</sup> Northing <sup>(3)</sup>	orthing <sup>(3)</sup> Description of source of emission(s)	Emission details <sup>(4)</sup>				Abatement system employed				
Code <sup>(1)</sup>	Easting	Lasting	Northing	Northing	Northing	Northing		Parameter/ Material	mg/Nm <sup>3(5)</sup>	kg/h	kg/year	(if relevant)
				at V <sup>E</sup>	ى.							
				Pection Purpose's officially offi								
				roses of for								
				otion purper tealt								
				A70								
			Consent of con	מ								
			Consent									

<sup>&</sup>lt;sup>(1)</sup> The following convention should be observed when labelling <u>minor</u> atmospheric emission points:

A3-1, A3-2, A3-3,...etc.

<sup>&</sup>lt;sup>(2)</sup> Six Digit GPS Irish National Grid Reference.

<sup>&</sup>lt;sup>(3)</sup> Six Digit GPS Irish National Grid Reference.

<sup>&</sup>lt;sup>(4)</sup> The maximum emission should be stated for each parameter emitted; the concentration should be based on the maximum 30 minute mean and must be the **PRE-ABATEMENT** level.

<sup>(5)</sup> Concentrations should be based on Normal conditions of temperature and pressure, (i.e. 0oC101.3kPa). Wet/dry should be clearly stated. Include reference oxygen conditions for combustion sources.



Emission	Easting <sup>(2)</sup>	Nouthing (3)	Northing <sup>(3)</sup> Description of source of emission(s)	Emission details <sup>(4)</sup>				Abatement system employed
Point Code <sup>(1)</sup>		Northing		Parameter/ Material	mg/Nm <sup>3(5)</sup>	kg/h	kg/year	(if relevant)
				- et Ne	ى.			
				MNY any other				
				apposes of for				
				ection Pt red				
			For	P to				
			wof col	2				
			Conser	Spection purposes only of any other use				

\*add rows to the table as necessary

Note: Map(s)/drawing(s) uploaded under 'Site Plans' in Tab 3 of the application form should identify the emission and monitoring points.



# **EMISSIONS TO ATMOSPHERE –** <u>Potential</u> Emissions to Atmosphere

Potential emissions are emissions that are not active under normal operation and would include by-passes or pressure relief valves.

Complete the table below with summary details of all <u>potential emissions</u> to atmosphere

Emission Point Code <sup>6</sup>	Description of source of emission	Malfunction which could cause an emission	Emission details (Potential max. emissions) <sup>(7)</sup>				
			Parameter/Material	mg/Nm <sup>3</sup>	kg/hour		
			A USE.				
		For inspection purposes of for any of	¢.				
		or the terms of t					
		citon put require					
		COLIDS OF THE DEST OF					
		Consent of constitute					
		Conserv					

\*add rows to the table as necessary

<sup>&</sup>lt;sup>6</sup> The following convention should be observed when labelling potential atmospheric emission points:

A4-1, A4-2, A4-3,...etc.

<sup>&</sup>lt;sup>7</sup> Estimate the potential maximum emission for each malfunction identified.