

# **EPA Application Form**

# 7.3.1 - Emissions to Sewer Attachment

	n Pittose di Foi d
	r inspection men
Organisation Name:	FORGE HILL RECYCLING GOODING
	Consent
Application I.D.:	LA001661



# **Amendments to this Application Form Attachment**

Version No.	Date	Amendment since previous version	Reason
V.1.0	July 2017	N/A	Online application form attachment
		nge.	
		ov. ov diter.	
		OSE of the late	

Page 2 of 8



# **Emissions to Sewer Attachment** (See Note i at end of this attachment)

The information contained in this attachment will be forwarded to the relevant Water Services Authority in which the sewer is vested or by which the sewer is controlled, under Section 99E of the EPA Act 1992 as amended or Section 52 of the Waste Management Act 1996 as amended. Please ensure that you have provided all the information in this attachment that the Water Services Authority require for deciding whether to authorise your discharge to sewer.

# Waste Water to Sewer - Emission Point Details (See Note ii at the end of this attachment) - one row per emission point

Complete the table below for each emission point to sewer

Emission Point	What is the Emission Source?	Emission P	oint Grid Ref.	Volume to be emitted		Period of emission (average)		Measures to reduce/minimise
Code 1		Easting <sup>2</sup>	Northing <sup>3</sup>	Max. rate/ hour (m³)	Max./day m³)	days/year	hr/day	/prevent emissions (list techniques
FW-1	Staff toilets and waste water, run off from yards	535655.113	5746721.528	30 ection net	100	365	24	Manual shut-off valve on the foul sewer line
			and a	of codylight				
			Causer					

<sup>\*</sup> add rows to the table as necessary

<sup>&</sup>lt;sup>1</sup> The following convention should be observed when labelling sewer emission points: SE1, SE2, ..., etc.,

<sup>&</sup>lt;sup>2</sup> Six Digit GPS Irish National Grid Reference

<sup>&</sup>lt;sup>3</sup> Six Digit GPS Irish National Grid Reference



### **Waste Water to Sewer - Emission Monitoring Points**

Complete the table below with an individual record (i.e., row) for each monitoring/sampling point. A National Grid Reference (12 digit, 6E, 6N) must be entered for each monitoring/sampling point.

Emission Point Code	Monitoring/Sampling Point Code	Monitoring/Sampling Point Grid Ref.		
		Easting <sup>1</sup>	Northing <sup>2</sup>	
FW-1	FW-1	535655	574672	
			use.	
			ather	
			यात्र. यात्र	
			es a for	

* add rows to the table as necessary  Waste Water to Sewer- Emissions  Complete the table below for each emission point – add a new row for each parameter (See Note iii at the end of this attachment for further information)								
Emission Point Code	Parameter	Monitoring Point Code	Max. Hourly (mg/l)	Max. Daily (kg/day)	Annual (kg/year)	Proposed Monitoring Frequency	Monitoring / Sa Sample Method	Analysis Method and Technique
FW-1	рН	FW-1	-	-	-	Continuous	On line flow meter	Standard Method
FW-1	BOD	FW-1	-	200	73000	Weekly	Composite Sample	Standard Method
FW-1	Temperature	FW-1	-	-	-	continuous	Composite Sample	Standard Method
FW-1	Toxicity	FW-1	-	-	-	As may be	Composite Sample	Standard Method



Emission Point Code	Parameter	Parameter Monitoring Point Code	Proposed Emission Limits			Monitoring / Sampling		
			Max. Hourly (mg/l)	Max. Daily (kg/day)	Annual (kg/year)	Proposed Monitoring Frequency	Sample Method	Analysis Method and Technique
						required		
FW-1	COD	FW-1	-	400	146000	Weekly	Composite Sample	Standard Method
FW-1	Total Suspended Solids	FW-1	-	50	18250	Weekly	Composite Sample	Standard Method
FW-1	Oils, Fats and Greases	FW-1	-	-	-	Monthly	Composite Sample	Standard Method
FW-1	Detergents	FW-1	-	-	-	Quarterly et 1	Composite Sample	Standard Method
FW-1	Mineral Oil	FW-1	-	-	-	Bi-amhually	Composite Sample	Standard Method
FW-1	Total Nitrogen	FW-1	-	-	ta jispelian of copyright our	Bi-annually	Composite Sample	Standard Method
FW-1	Total Hydrocarbons	FW-1	-	-	For install	Bi-annually	Composite Sample	Standard Method
FW-1	Sulphate	FW-1	-	-	of or -	Quarterly	Composite Sample	Standard Method
FW-1	VOC	FW-1	-	Cor	-	Quarterly	Composite Sample	Standard Method
FW-1	Heavy Metals	FW-1	-	-	-	Annually	Composite Sample	Standard Method



Fusionism			Proposed Emission Limits			Monitoring / Sampling		
Emission Point Code	Parameter	Monitoring Point Code	Max. Hourly (mg/l)	Max. Daily (kg/day)	Annual (kg/year)	Proposed Monitoring Frequency	Sample Method	Analysis Method and Technique

<sup>\*</sup> add rows to the table as necessary

Consent of convirient owner required for any other tise.



# **Equivalent Levels of Protection**

amended) upload a document that describes how the environ	d to Article 15(1) of the Industrial Emissions Directive (or Section 86A(8) of the EPA Act 1992 as nment as a whole is provided with an equivalent level of protection and will not lead to higher levels f Protection (Sewer)' attachment template (select Document Type: 'Equivalent Level of Protection'
Equivalent Level of Protection (Sewer) filename:	
Waste Water Treatment Plant	of Itse.
	Agency must obtain the consent of the Water Services Authority to which the sewer is vested or of the Water Services Authority, the agglomeration, the treatment plant name and the letter of
Provide the name of the Water Services Authority applicable to your application:	For the partial to the state of
Enter the name of the agglomeration to which trade effluent <sup>4</sup> discharges	Consent of copyrise
Enter the Treatment Plant Name:	
• , , ,	scharge to sewer, by way of a letter of consent/agreement from the operator of the sewer. Where ons and discharge limitations (select Document Type: 'Sewer Discharge Consent' in the application
Sewer Discharge Consent filename:	

 $<sup>^{4}</sup>$  Trade effluent has the meaning given in the Water Services Act 2007 as amended.



Note i

This part of the application form collects data on waste water emissions to sewer. In this context waste water involves trade effluent or other matter other than domestic sewage or storm water. Please note that emission limit values and monitoring requirements in any proposed licence shall be based on the information supplied hereunder.

Note ii

Complete the table for each emission point having regard to the guidance hereunder.

The following convention should be observed when labelling emission points: Sewer SE1, SE2, SE3,...etc.

Describing the source of the emission helps explain the nature of the emission such as process or contaminated run-off etc.

A National Grid Reference (12 digit, 6E, 6N) must be given for each emission point.

Measures are usually required to reduce, minimise or prevent emissions from occurring. They may involve the application of a single technique or a combination of techniques including process integrated, recovery, abatement and treatment techniques. List all techniques proposed/employed. Technique(s) employed be capable of providing an equivalent level of protection and complying with the proposed/known emission level(s).

Note iii

Complete the table for each emission point having regard to the guidance herewader.

Characterise the emissions (identify the parameters) under normal operation. The parameters also cover volumes and rates of emission. Those substances which are likely to be emitted in significant quantities, having regard to their potential to transfer pollution from one medium to another must be identified and the applicant must determine emission levels having considered the following:

#### To identify the chemical parameters:

- 1. Substances listed in the Schedule of EPA (Industrial Emissions)/(Integrated Pollution Control)(Licensing) Regulations 2013.
- 2. IED chapters III, IV, V VI where relevant.
- 3. The fate of materials/substances, intermediates, products and by products used or produced through the process particularly substances of very high concern, substances carrying the Hazard statement H400 to 413 (hazardous to the aquatic environment) and hazardous substances with damaging effects on sensitive plants and ecosystems.
- 4. Any reaction substances likely to appear as a result of treatment or natural breakdown processes with damaging effects on sensitive plants and ecosystems.
- 5. Any substances with the potential to cause odour nuisance off site.
- 6. List I and List II substances listed in the Annex to EU Directive 2006/11/EC (as amended).
- 7. Any substances likely to cause corrosion, congealing or unsafe environment of the sewer network.