

# EPA Application Form

## 7.5 - Noise Emissions - Attachment

**Organisation Name: \***

Roadstone Limited

**Application I.D.: \***

LA003602

*For inspection purposes only.  
Consent of copyright owner required for any other use.*

## Authorisation Application Form

### Amendments to this Application Form Attachment

Version No.	Date	Amendment since previous version	Reason
V.1.0	July 2017	N/A	Online application form attachment
As above	Mar 2018	Identification of required fields	Assist correct completion of attachment

For inspection purposes only.  
Consent of copyright owner required for any other use.

\* indicates required field

## Authorisation Application Form

### Noise Emissions (see **Note i** at the end of this attachment)

Note: An assessment of the impacts of noise, where applicable, should be uploaded in Tab 7 – ‘Emissions Overview’ of the application form.

Provide detail of measures to reduce noise emissions (list techniques)

(See **Note ii** at the end of this attachment)

- During the initial phases where extraction and infilling are in operating in tandem, every effort should be made to double up on HGV trips in order to reduce the number of empty Heavy Goods Vehicles (HGVs) travelling to and from the site.
- HGVs will only be allowed to import material to the site during the proposed operational hours.
- All equipment will be regularly maintained to ensure that they are operating effectively and not producing additional noise emissions or potential tonal sources.
- Where practicable the number of machines in simultaneous operation will be minimised.
- All vehicle engines will be switched off when not in use.
- Plant and machinery used on-site will comply with the EC (Construction Plant and Equipment) Permissible, Noise Levels Regulations, 1988 (S.I. No. 320 of 1988).
- All contractors will employ the best practicable means to minimise noise emissions and will be obliged to comply with the general recommendations of BS 5228-1: 2009 and “*Environmental Good Practice Site Guide*” 2005 compiled by CIRIA and the UK Environmental Agency.

For information purposes only:  
Consent of copyright owner required for any other use.

Following the *Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4)* (2012 as amended) complete the table below, inputting summary details of noise monitoring points (see **Note iii** at the end of this attachment) and proposed noise limit criteria.

## Authorisation Application Form

Monitoring point code <sup>1</sup>	Easting <sup>2</sup>	Northing <sup>3</sup>	Monitoring point type <sup>4</sup>	Proposed Noise Limit Criteria				Proposed monitoring frequency
				Max. noise level daytime dB L <sub>Ar,T</sub> (30 mins)	Max. noise level evening dB L <sub>Ar,T</sub> (30 mins)	Max. noise level night dB L <sub>Eq,T</sub> (15-30 mins)	How was the noise limit derived? <sup>5</sup>	
N1	189941	72292	Boundary	55	45	45	EQS	Annual
N2	189628	72690	Noise Sensitive Location	55	45	45	EQS	Annual
N3	188987	72724	Boundary	55	45	45	EQS	Annual
N4	190243	72714	Boundary	55	45	45	EQS	Annual

**Note:** Map(s)/drawing(s) uploaded under 'Site Plans' in Tab 3 of the application form should identify the emission and monitoring points.

For inspection purposes only.  
Consent of copyright owner required for any other use.

- 
- 1 The following convention should be observed when labelling noise monitoring points:  
N1, N2,.....The monitoring locations should be identified on an accompanying site plan drawing(s) uploaded in Tab 3 – 'Site' of the application form.
  - 2 Six Digit GPS Irish National Grid Reference of Monitoring Point
  - 3 Six Digit GPS Irish National Grid Reference of Monitoring Point
  - 4 Monitoring point type options: 'Boundary', 'Noise Sensitive Location' or 'Permanent Noise Monitoring'
  - 5 Derived noise limit options: 'BAT', 'EQS', or 'Derogation'

\* indicates required field

### Authorisation Application Form

Was an assessment for tonal and impulsive noise carried out? <sup>6</sup> (Yes/No)	No
If 'Yes' was tonal or impulsive noise identified to be present? (Yes/No)	N/A

For emissions outside the EPA Noise Guidance Note limit, see the Agency's *Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4)* (2012) (available on [www.epa.ie](http://www.epa.ie)), a full evaluation of the existing abatement/treatment system must be provided. A planned programme of improvement towards meeting upgraded standards is required to be uploaded with this document. This programme should highlight specific goals and a time scale, together with options for modification, upgrading or replacement, as required, to bring the emissions within the limits as set out in the Guidance Note.

For inspection purposes only.  
Consent of copyright owner required for any other use.

<sup>6</sup> Refer to section 5 of the Agency's *Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4)* (2012 as amended).

\* indicates required field

## Authorisation Application Form

- Note i** This part of the application form collects data on noise emissions namely measures used to reduce noise and noise levels at a reference distance under normal operation. As noise emissions can arise from different sources on a site, the EPA usually considers the total emission from the site. Please note that emission limit values and monitoring requirements in any proposed licence shall be based on the information supplied hereunder.
- Note ii** Measures are usually required to reduce, minimise or prevent emissions from occurring. They may involve the application of a single technique or a combination of techniques including housing, insulation and appropriate location of equipment. List all techniques proposed/employed. Technique(s) employed must comply with BAT. Highlight additional measures required for the purposes of protecting the environment. The measures or techniques to be taken must be capable of complying with the proposed/known emission level(s).  
The measures required shall be informed by the following:
1. BAT techniques
  2. Stricter measures/techniques than BAT
  3. BAT determined by competent authority in consultation with the applicant
  4. Other measures
- Note iii** An individual record (i.e. row) is required for each monitoring point. A National Grid Reference (12 digit, 6E, 6N) must be given for each monitoring point. Noise emissions differ from other emissions in that they are generally limited at a reference distance from the source(s). This reference distance should be, where possible, the boundary of the installation but in certain circumstances it is a noise sensitive location outside the boundary of the installation. Noise levels along a boundary will vary due to the location and positioning of noise sources and the 'worst case' should always be selected. Sufficient points should be identified to fully describe the noise levels from the installation. For waste activities, traffic noise emissions should be taken into account especially if it. The Agency's Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4) (2012) and Guidance Note on Noise assessment of Wind Turbine Operations at EPA licensed Sites (NG3)(as appropriate) should be consulted when setting proposed sound limits.