

EPA Application Form

7.4.1 - Emissions to Atmosphere - Main and Fugitive

Emissions - Attachment

Organisation Name: *

S. Wilkin and Sons ltd.

Application I.D.: *

Page 1 of 14



Amendments to this Application Form Attachment

Version No.	Date	Amendment since previous version	Reason				
V.1.0	July 2017	N/A	Online application form attachment				
As above	Mar 2017	Identification of required fields	Assist correct completion of attachment				
		All and a second s					
		net					
		See off at					
Conson for inspection professional constrained for any or constraine							



EMISSIONS TO ATMOSPHERE

Emissions to air/atmosphere include the following:

Main Emissions

Main emissions include all emissions of environmental significance. Where a **mass emission threshold** is specified in a BAT document (BAT Conclusions, National BAT note or BREF), emissions which exceed this threshold prior to abatement are regarded as significant, i.e., 'main emissions'. (In some cases emissions below the threshold can still be significant and qualify as Main Emissions).

Minor Emissions

Emissions below the mass emission threshold <u>may</u> be considered minor emissions and therefore do not generally need to be specifically controlled by the conditions or schedules of the licence (i.e., setting of ELVs, abatement control measures, or monitoring requirements). Emissions may also be deemed minor by virtue of their source/nature (e.g., laboratory fume hoods, workspace extractions, passive vents from storage tanks, HVAC exhausts), or composition (e.g., water vapour emissions).

For combustion plant such as boilers, these can be considered minor where the rated thermal input is < 1MW where natural gas is the main fuel, and for liquid and solid fuels where its < 250kW.

In completing the separate '*Emissions to Atmosphere - Minor and Potentia*l' attachment for minor emissions, the applicant should supply sufficient information to justify the determination of the emission as minor. Notwithstanding this guidance, the Agency may consider any emission to be significant (i.e., a main emission) on the basis of environmental impact.

Fugitive Emissions

Fugitive emissions include emissions from non-point sources and diffuse sources.

Potential Emissions

These are emissions which only operate under abnormal process conditions. Typical examples include bursting discs, pressure relief valves, and emergency generators. Bypasses and flares may also fall within this category, depending on how they are operated or designed to operate. Although the Agency does not normally set controls in licences for potential emissions, it may do so for the purposes of environmental protection.

This attachment collects information on <u>main</u> and <u>fugitive</u> emissions to atmosphere. Waste gas means the final gaseous emission from a stack or abatement equipment.

For minor and potential emissions to atmosphere, complete the separate '*Emissions to Atmosphere - Minor and Potential*' attachment.



Main Emissions to Atmosphere - Waste Gas Emission Point Details - one row per emission point *

Complete the following table with summary details for all main emission points to atmosphere.

(Guidance on completing the table is included in Note i at the end of this attachment)

The applicant should address in particular any emissions which may contain the principal polluting substances listed in the First Schedule of Environmental Protection Agency (Integrated Pollution Control) (Licensing) Regulations 2013/ (Industrial Emissions)(Licensing) Regulations 2013.

Please note that the determination of any emission limit values and monitoring requirements in a proposed licence if granted will be based on the information supplied hereunder.

Emission Point Code			Typical Days	Measures to reduce /minimise / prevent emissions (list techniques) ¹	Source of Waste Gases	Minimum Discharge	Reference Conditions			
	Easting ³	Northing ⁴	Usage/ Year	Where EQS considerations require measures stricter than BAT, highlight these measures in bold	only any or 2	Height Above Ground (m)	Pressure ⁵	Temp. 6	% Oxygen	Moisture ⁸
B1	Pending	Pending	24/7	D PHP COL	500 Kw Boiler (Gas)	Pending	Pending	Pending	Pending	Pending
				. nspectionne						
				Fortiet						
<u></u>				entot						
	1	1	1	Cons	1	1		1	11	

¹ Detailed descriptions and schematics of all abatement systems should be included in the Operational Report (Tab 4.8 – 'Reports').

² Options: Boiler, Gas Turbine, Incineration, Co-Incineration, CHP, Kiln, Engine, Indirect drying activity (e.g. milk drying), Other Combustion activity (e.g., oven), Distillation/Chemical reaction, Solvent based coating activity, Other coating activity (provide description), Composting Tunnels, General extraction from buildings <u>or</u> Other (provide a description if 'Other' is selected).

³ Six Digit GPS Irish National Grid Reference.

⁴ Six Digit GPS Irish National Grid Reference.

⁵ **Options:** 101.325kPa <u>or</u> No correction.

⁶ **Options:** 273.15K or No correction.

⁷ **Options:** 3%, 6%, 10%, 11%, 15%, 18% <u>or</u> No correction.

⁸ **Options:** Wet <u>or</u> Dry.



Emission	Emission Pc	Emission Point Grid Ref. Typical Days		Measures to reduce /minimise / prevent emissions (list techniques) ¹	Source of Waste Gases	Minimum Discharge	Reference Conditions			
Point Code	Easting ³	Northing ⁴	Usage/ Year	Where EQS considerations require measures stricter than BAT, highlight these measures in bold	2	Height Above Ground (m)	Pressure ⁵	Temp. 6	% Oxygen 7	Moisture ⁸
					x 15°.					
				For inspection particular For inspection particular For inspection particular Consent of constitution	AV. ary other					
					or of the second					
				ion purequi						
				insectionit						
				Former						
				C ^{o,}						

*add rows to the table as necessary



Emission Points from Combustion, Incineration or Co-incineration Sources Only

Complete the table below for each emission point to atmosphere from a combustion source, waste incineration or co-incineration plant

Emission Point Code	Primary Fuel Type ⁹ (where applicable)	Secondary Fuel Type ¹⁰ (where applicable)	LCP Plant Reference (where applicable)	Waste incineration or co- incineration plant reference (where applicable)
Boiler 1	Gas		<i>.</i>	
			et USC	
			es offy any other use.	
			ses afor a	
			ourpositiet	
			action berte	
		TIS		
*add rows to the table as n	necessary	Consent of convit	30	

⁹ Options: Coal, Lignite, Heavy Fuel Oil, Other Fuel Oil, Peat, Natural Gas, Biogas, Solid Biomass, Waste, Gas Oil, Other or None

¹⁰ Options: Coal, Lignite, Heavy Fuel Oil, Other Fuel Oil, Peat, Natural Gas, Biogas, Solid Biomass, Waste, Gas Oil, Other or None



Emission Points with Solvent Emissions Only

Complete the table below for each emission point associated with a solvent activity

Emission Point Code	Are specific Hazardous Substances ¹¹ Emitted?	Mass Flow of Emitted Hazardous Substances (g/hour)	Halogenated VOCs ¹² Emitted?	Mass Flow of Emitted Halogenated VOCs (g/hour)
				~
				other
				ould' and
				11502citon purposes only only other
				tion per real
				HSPOLOW.
			çó	Rite
			Content of C	
add rows to the	table as necessary	1	Conse.	1

¹¹ Emissions of volatile organic compounds referred to in Article 58 (Substances or mixtures which, because of their content of volatile organic compounds classified as carcinogens, mutagens, or toxic to reproduction under Regulation (EC) No. 1272/2008, are assigned or need to carry the hazard statements H340, H350,H350i, H360D or H360F) of the Industrial Emissions Directive.

¹² Halogenated volatile organic compounds which are assigned or need to carry the hazard statements H341 or H351.



Waste Gas Emission Monitoring Points

Complete the table below for each emission point, by entering the Emission Point Code, the associated Monitoring Point Code and the grid reference of the Monitoring Point. *

Emission Doint Code	Monitoring Doint Code ¹³	Monitoring Poin	ng Point Grid Reference		
Emission Point Code	Monitoring Point Code ¹³	Easting ¹⁴	Northing ¹⁵		
Boiler 1	Boiler 1	Pending Installation	Pending Installation		
			net		
		urposed and	or .		
		Dection Perfect			
		Fortheast			
*add rows to the table as necessary	- CONE	For instead of the second seco			

 ¹³ To include monitoring and sampling points
¹⁴ Six Digit GPS Irish National Grid Reference

¹⁵ Six Digit GPS Irish National Grid Reference



Waste Gas - Abatement /Treatment Control

Complete the table below for each emission point with an abatement/treatment system (one table per emission point)

Emission Point Code: _____

Control ¹⁶ parameter	Monitoring to be carried out ¹⁷	Additional notes (where relevant)
		. 15 ^{6.}
		other
		Kot Bart
	aurosure	
	citon Per row	
	x Hast of	
	Fo on the	
d rows to the table as necessary	Consent of	
	Cote	

 ¹⁶ List the operating parameters of the treatment/abatement system which control its function.
¹⁷ List the monitoring of the control parameter to be carried out.



Waste Gas Emissions

Complete the table below for all main emission points to atmosphere (include one row for each identified parameter) *

Emission			Proposed Emission Limits ¹⁸			18	BAT Associated	Sampling / Monitoring EPA Guidance for Monitoring - AG2 Index of Preferred Methods			
Point Code	Parameter	Monitoring Point Code	Max. Hourly 19	Max. Daily 20	Average Month 21	Average Annual	How was the Proposed Emission Limit Derived?	Emission Range (if applicable)	Proposed Monitoring Frequency	Proposed Monitoring and Analysis Method ²³	Compliant with BAT Monitoring Requirement?
								<i>d</i>			
								et USC			
								Votter			
							OTION	SIL ,			
							100 sited for				
							The real				
						వ	ecte who				
						corini	But				
						E COBY					

* For continuous monitoring 'EN15267 approved CEMS' is the standard method. For periodic monitoring please refer to the EPA guidance document 'AG2 Index of Preferred Methods' linked above *add rows to the table as necessary

- ¹⁹ Specify the proposed limit <u>and the units.</u>
- ²⁰ Specify the proposed limit <u>and the units.</u>
- ²¹ Specify the proposed limit <u>and the units.</u>
- ²² Specify the proposed limit <u>and the units.</u>

¹⁸ For emissions outside the BAT Conclusion, BREF or BAT guidance limit, a full evaluation of the existing abatement/treatment system must be provided. A planned programme of improvement towards meeting upgraded standards is required. This should highlight specific goals and a time scale, together with options for modification, upgrading or replacement as required to bring emissions within the limits set out in the BAT Conclusion(s), BREF(s) or BAT guidance note(s). These notes can be found on the EPA website at www.epa.ie.

²³ For continuous monitoring 'EN15267 approved CEMS' is the standard method. For periodic monitoring please refer to the EPA guidance document 'AG2 Index of Preferred Methods'.



Minor and/or Potential Emissions to Atmosphere²⁴

Are there any minor or potential emission point(s) to atmosphere at the installation/facility?	No
(Yes/No) *	

If 'Yes' complete and upload the *Emissions to Atmosphere – Minor and Potential Emissions* template with details of minor and potential emissions (select Document Type: '<u>Minor - Potential Emissions</u>' in the application form)

Emissions to Atmosphere - Minor - Potential Emissions file name:	
	A VEC.
	A. NOT
	soll's total.
	atteos ited
	. nepection purpose only any other use.
	A CONTRACT OF A
×	ion tradit
. 8	
Consent of	
C ^{o,}	

²⁴ Refer to page 3 for guidance on what constitutes a minor or potential emission.



Yes

Fugitive Emission to Atmosphere

Fugitive emissions must be controlled by way of appropriate controls and techniques to minimise emissions. (Additional information on fugitive emission is included in Note ii at the end of this attachment)

Are there any sources of fugitive emissions at the installation/facility?²⁵ (Yes/No) *

If 'Yes' provide summary details of the fugitive emissions in the table below:

Type of Fugitive Emission	Emission Type Applicable? (Yes/No)	Description of fugitive emissions source(s)	Maximum Level	Units	Descriptor/Location
Dust	Yes	Poultry House(s)		mg/m²/day	Dust deposition
VOC ²⁶		Poultry House(s)		%	of solvent input
Ammonia	Yes	Poultry House(s)		ug/m³	at the nearest European Site
Nitrogen	Yes	Poultry House(s)		kgN/ha/yr	at the nearest European Site
Odour	Yes	Poultry House(s)		Odour Units	at boundary of installation
		Cor			

²⁵ For waste activities, dust and odour emissions should be considered and described in the table below where applicable.

²⁶ In relation to activities listed in Chapter V (for installations using Organic Solvents) of the Industrial Emissions Directive (2010/75/EU):

⁻ specify how the requirements in relation to fugitive emissions will be met.



Provide details of the techniques to be used to reduce / minimise / prevent fugitive emissions in text bow below

Note i Complete the table for each emission point having regard to the guidance hereunder.

The following convention should be observed when labelling emission points:

Boiler Emissions A1-1, A1-2, A1-3,...etc.

Main Emissions A2-1. A2-2. A2-3....etc.

only any other use. A3-1, A3-2, A3-3,...etc. (NOTE: Minor emission points are to be included in the 'Emissions to Atmosphere - Minor and Potential' Minor Emissions attachment)

Potential Emissions A4-1, A4-2, A4-3,...etc. (NOTE: Potential emission points are to be included in the 'Emissions to Atmosphere - Minor and Potential' attachment)

A National Grid Reference (12 digit, 6E, 6N) must be provided for each emission point.

Measures are usually required to reduce, minimise or prevent emissions from occurring. They may involve the application of a single technique or a combination of techniques including process integrated, recovery, abatement and treatment techniques. List all techniques proposed/employed. Technique(s) employed must comply with BAT. Highlight additional measures required for the purposes of protecting the environment i.e. AQS considerations. The measures or techniques to be taken must be capable of complying with the proposed/known emission level(s).

The measures required shall be informed by the following:

1. BAT techniques with BAT-AEL

2. BAT techniques without BAT-AEL

3. Stricter measures/techniques than BAT (due to AQS)

4. BAT determined by competent authority in consultation with the applicant

5. Measures to minimise pollution over long distances or in the territory of other states.

6. Emerging techniques

7. Less strict measures than BAT (due to derogation)

8. Other measures

Select from the drop down list the source of the emission as it helps explain the nature of the emission.

Particular attention should be paid to ensuring that emissions data (volumetric flow and pollutant concentrations) are presented at the required reference conditions for oxygen, temperature, pressure and moisture.



Note ii Fugitive emissions include the following:

- Dust from area sources such as a quarry.
- Odour from volume sources such as a pig unit, waste water treatment plant, waste handling etc.
- VOCs from processes using solvent not captured in waste gases.
- Ammonia and nitrogen from pig and poultry units.

Processes that can give rise to fugitive emissions include:

o Leaks from valve seals, pump seals and flanges;

- o Breathing and working losses from liquid storage facilities;
- o Dust emissions from solids stored in the open;

o Loading and unloading operations; o Cleaning operations; and, o Emissions from waste water treatment (e.g. volatile organics). The measures taken to reduce/ prevent fugitive emissions to atmosphere must be addressed, and the facilities and operations required to control omissions must be detailed emissions must be detailed.