EPA Application Form

7.4.1 - Emissions to Atmosphere - Main and Fugitive

Emissions - Attachment

Organisation Name:*

Application I.D.: *

HealthBeacon Ltd

LA006978

of copyright

Page 1 of 15

Amendments to this Application Form Attachment

Version No.	Date	Amendment since previous version	Reason					
V.1.0	July 2017	N/A	Online application form attachment					
As above	Mar 2017	Identification of required fields	Assist correct completion of attachment					
		دى.						
		in a other tree						
		oses of for any						
Consent of contribution provided in the contribution of the contributication of the contribution of the co								



EMISSIONS TO ATMOSPHERE

Emissions to air/atmosphere include the following:

Main Emissions

Main emissions include all emissions of environmental significance. Where a **mass emission threshold** is specified in a BAT document (BAT Conclusions, National BAT note or BREF), emissions which exceed this threshold prior to abatement are regarded as significant, i.e., 'main emissions'. (In some cases emissions below the threshold can still be significant and qualify as Main Emissions).

Minor Emissions

Emissions below the mass emission threshold <u>may</u> be considered minor emissions and therefore do not generally need to be specifically controlled by the conditions or schedules of the licence (i.e., setting of ELVs, abatement control measures, or monitoring requirements). Emissions may also be deemed minor by virtue of their source/nature (e.g., laboratory fume hoods, workspace extractions, passive vents from storage tanks, HVAC exhausts), or composition (e.g., water vapour emissions).

For combustion plant such as boilers, these can be considered minor where the sate thermal input is < 1MW where natural gas is the main fuel, and for liquid and solid fuels where its < 250kW.

In completing the separate '*Emissions to Atmosphere - Minor and Potential*' attachment for minor emissions, the applicant should supply sufficient information to justify the determination of the emission as prinor. Notwithstanding this guidance, the Agency may consider any emission to be significant (i.e., a main emission) on the basis of environmental impact.

Fugitive Emissions

Fugitive emissions include emissions from non-point sources and diffuse sources.

Potential Emissions

These are emissions which only operate under abnormal process conditions. Typical examples include bursting discs, pressure relief valves, and emergency generators. Bypasses and flares may also fall within this category, depending on how they are operated or designed to operate. Although the Agency does not normally set controls in licences for potential emissions, it may do so for the purposes of environmental protection.

This attachment collects information on <u>main</u> and <u>fugitive</u> emissions to atmosphere. Waste gas means the final gaseous emission from a stack or abatement equipment.

For minor and potential emissions to atmosphere, complete the separate '*Emissions to Atmosphere - Minor and Potential*' attachment.



Main Emissions to Atmosphere - Waste Gas Emission Point Details - one row per emission point *

Complete the following table with summary details for all main emission points to atmosphere.

(Guidance on completing the table is included in Note i at the end of this attachment)

The applicant should address in particular any emissions which may contain the principal polluting substances listed in the First Schedule of Environmental Protection Agency (Integrated Pollution Control) (Licensing) Regulations 2013/ (Industrial Emissions)(Licensing) Regulations 2013.

Please note that the determination of any emission limit values and monitoring requirements in a proposed licence if granted will be based on the information supplied hereunder.

There will be no Main Emissions to Atmosphere at the proposed facility.

Emission	Emission Po	oint Grid Ref.	Typical Days	Measures to reduce /minimise / prevent emissions (list techniques) ¹	Source of Waste Gases	Minimum Discharge	Reference Conditions			
Point Code	Easting ³	Northing ⁴	Usage/ Year	Where EQS considerations require measures stricter than BAT, highlight these measures in bold	2	Height Above Ground (m)	Pressure ⁵	Temp. 6	% Oxygen 7	Moisture ⁸
				USPOLI ONIC						
				for prite						
				consent o						

.e.

¹ Detailed descriptions and schematics of all abatement systems should be included in the Operational Report (Tab 4.8 – '*Reports*').

² **Options:** Boiler, Gas Turbine, Incineration, Co-Incineration, CHP, Kiln, Engine, Indirect drying activity (e.g. milk drying), Other Combustion activity (e.g., oven), Distillation/Chemical reaction, Solvent based coating activity, Other coating activity (provide description), Composting Tunnels, General extraction from buildings <u>or</u> Other (provide a description if '**Other**' is selected).

³ Six Digit GPS Irish National Grid Reference.

⁴ Six Digit GPS Irish National Grid Reference.

⁵ **Options:** 101.325kPa <u>or</u> No correction.

⁶ **Options:** 273.15K or No correction.

⁷ **Options:** 3%, 6%, 10%, 11%, 15%, 18% <u>or</u> No correction.

⁸ **Options:** Wet <u>or</u> Dry.



Emission Point Code	Emission Po	oint Grid Ref.	Typical Days	Measures to reduce /minimise / prevent emissions (list techniques) ¹	Source of Waste Gases	Minimum Discharge	Reference Conditions			
	Easting ³	Northing ⁴	Usage/ Year	Where EQS considerations require measures stricter than BAT, highlight these measures in bold	2	Height Above Ground (m)	Pressure ⁵	Temp. 6	% Oxygen 7	Moisture ⁸
					19 ^{50.}					
				Consent of contraction of the section of the sectio	NY. DY offer					
				Constant and the second s	d fot to					
				ion put chu						
				tite of the of t						
				feonyt.						
				consent						

Emission Points from Combustion, Incineration or Co-incineration Sources Only

Complete the table below for each emission point to atmosphere from a combustion source, waste incineration or co-incineration plant

There will be no emissions from Combustion, Incineration or Co-incineration sources with the exception of minor emissions from a small gas boiler present on-site which is used for the purposes of space heating.

Emission Point Code	Primary Fuel Type ⁹ (where applicable)	Secondary Fuel Type ¹⁰ (where applicable)	LCP Plant Reference (where applicable)	Waste incineration or co- incineration plant reference (where applicable)
			therus	
			MY any or	
			ose o for	
			A PULLEQUIL	
			ection met	
		Form	<u>Ş</u> T	
		ofcolt		
*add rows to the table as no		OIISOIL		

⁹ Options: Coal, Lignite, Heavy Fuel Oil, Other Fuel Oil, Peat, Natural Gas, Biogas, Solid Biomass, Waste, Gas Oil, Other or None

¹⁰ Options: Coal, Lignite, Heavy Fuel Oil, Other Fuel Oil, Peat, Natural Gas, Biogas, Solid Biomass, Waste, Gas Oil, Other or None



Emission Points with Solvent Emissions Only

Complete the table below for each emission point associated with a solvent activity

No solvent activities will be carried out on-site thus there will be no solvent emissions to atmosphere associated with the proposed facility.

Emission Point Code	Are specific Hazardous Substances ¹¹ Emitted?	Mass Flow of Emitted Hazardous Substances (g/hour)	Halogenated VOCs ¹² Emitted?	Mass Flow of Emitted Halogenated VOCs (g/hour)
				A USC.
				W. Notothe
				ion pupper officiant official
				Purpequiree
				nection teres
			ŶÓ	N. 59
			, of c	04.
			Consent of C	

¹¹ Emissions of volatile organic compounds referred to in Article 58 (Substances or mixtures which, because of their content of volatile organic compounds classified as carcinogens, mutagens, or toxic to reproduction under Regulation (EC) No. 1272/2008, are assigned or need to carry the hazard statements H340, H350,H350i, H360D or H360F) of the Industrial Emissions Directive.

¹² Halogenated volatile organic compounds which are assigned or need to carry the hazard statements H341 or H351.



Waste Gas Emission Monitoring Points

Complete the table below for each emission point, by entering the Emission Point Code, the associated Monitoring Point Code and the grid reference of the Monitoring Point. *

Not applicable

Monitoring Doint Code ¹³	Monitoring Point Grid Reference			
Wonitoring Point Code	Easting ¹⁴	Northing ¹⁵		
	only.	317		
	11Poses all			
	tion per redu			
	inspect own			
	FORTHE			
ي	a ot			
Cons				
	Monitoring Point Code ¹³	Monitoring Point Code ¹³ Easting ¹⁴		

¹³ To include monitoring and sampling points

¹⁴ Six Digit GPS Irish National Grid Reference

¹⁵ Six Digit GPS Irish National Grid Reference



Waste Gas - Abatement /Treatment Control

Complete the table below for each emission point with an abatement/treatment system (one table per emission point)

Emission Point Code: _____

Not applicable

Control ¹⁶ parameter	Monitoring to be carried out ¹⁷	Additional notes (where relevant)
		Met use.
	్ రోగ్ భా గ	or and or
	ion puppine	
	CONTRACTONIC	
	and copy	
	Consent	

¹⁶ List the operating parameters of the treatment/abatement system which control its function.

¹⁷ List the monitoring of the control parameter to be carried out.



Waste Gas Emissions

Complete the table below for all main emission points to atmosphere (include one row for each identified parameter) *

Not applicable

Emission			Proposed Emission Limits ¹⁸				BAT Associated	EPA Guidance	Sampling / Monito	-	
Point Code	Parameter	Monitoring Point Code	Max. Hourly ¹⁹	Max. Daily 20	Average Month 21	Average Annual 22	How was the Proposed Emission Limit Derived?	Emission Range (if applicable)	Proposed Monitoring Frequency	Proposed Monitoring and Analysis Method ²³	Compliant with BAT Monitoring Requirement?
								other use.			
							1.	Votte			
							rposes only a	>			
							aupose ind				
							tion per requ				
						کنې ر	eot on the				
						FOLDI	\$ ³				
						For pyr					
					¢.	nsent					

¹⁸ For emissions outside the BAT Conclusion, BREF or BAT guidance limit, a full evaluation of the existing abatement/treatment system must be provided. **A planned programme of improvement towards meeting upgraded standards is required**. This should highlight specific goals and a time scale, together with options for modification, upgrading or replacement as required to bring emissions within the limits set out in the BAT Conclusion(s), BREF(s) or BAT guidance note(s). These notes can be found on the EPA website at <u>www.epa.ie</u>.

- ¹⁹ Specify the proposed limit <u>and the units.</u>
- ²⁰ Specify the proposed limit **and** the units.
- ²¹ Specify the proposed limit **and** the units.
- ²² Specify the proposed limit <u>and the units.</u>

²³ For continuous monitoring 'EN15267 approved CEMS' is the standard method. For periodic monitoring please refer to the EPA guidance document <u>'AG2 Index of Preferred</u> <u>Methods'</u>.



* For continuous monitoring 'EN15267 approved CEMS' is the standard method. For periodic monitoring please refer to the EPA guidance document 'AG2 Index of Preferred Methods' linked above *add rows to the table as necessary

Consent of contribution purposes only any other use.



Minor and/or Potential Emissions to Atmosphere ²⁴

Are there any minor <u>or</u> potential emission point(s) to atmosphere at the installation/facility? **Yes** (Yes/No) *

If 'Yes' complete and upload the *Emissions to Atmosphere – Minor and Potential Emissions* template with details of minor and potential emissions (select Document Type: 'Minor - Potential Emissions' in the application form)

Emissions to Atmosphere - Minor - Potential Emissions file name:	Attachment-7-4-2
	Se.
	other bee.
	MIN: and
	Moses of M. and
	- Dector Nation
	ATTY & T
	COP JUL
ALL	FORTHER
COLEC	
č	

²⁴ Refer to page 3 for guidance on what constitutes a minor or potential emission.



Yes

Fugitive Emission to Atmosphere

Fugitive emissions must be controlled by way of appropriate controls and techniques to minimise emissions. (Additional information on fugitive emission is included in Note ii at the end of this attachment)

Are there any sources of fugitive emissions at the installation/facility?²⁵ (Yes/No) *

If '**Yes**' provide summary details of the fugitive emissions in the table below:

Type of Fugitive Emission	Emission Type Applicable? (Yes/No)	Description of fugitive emissions source(s)	Maximum Level	Units	Descriptor/Location
Dust	No	atty and the		mg/m²/day	Dust deposition
VOC ²⁶	No	MIROSE ONY ANY OF		%	of solvent input
Ammonia	No	Spection the real		ug/m³	at the nearest European Site
Nitrogen	No	For Treat		kgN/ha/yr	at the nearest European Site
Odour	No	The sharps waste being accepted on-site will not be odorous due to nature of the autoinjector waste material. Minimal exposure to biological material means little risk of odour. In addition, waste will be stored in sealed containers and following the transfer process will again be sealed into larger containers.	Not Known	Odour Units	at boundary of installation

²⁵ For waste activities, dust and odour emissions should be considered and described in the table below where applicable.

²⁶ In relation to activities listed in Chapter V (for installations using Organic Solvents) of the Industrial Emissions Directive (2010/75/EU):

⁻ specify how the requirements in relation to fugitive emissions will be met.

Provide details of the techniques to be used to reduce / minimise / prevent fugitive emissions in text bow below

Sharps waste arriving on-site will only be accepted in sealed sharps waste bin containers. Sharps waste bins should only be opened and sharps waste should only be handled/processed/stored in the designated, enclosed waste processing area. Sharps waste generated in this area will be subsequently transferred to the designated waste storage area and placed in sealed UN approved containers.

A Standard Operating Procedure (SOP) defining safe procedures for processing will be in place. This SOP will explicitly state the requirements for sharps waste to only be handled in the aforementioned designated areas in a tightly controlled manner. All staff involved in the handling and processing of waste arriving on-site will be provided training in this SOP. Regular inspections will take place to ensure adherence to SOP's and to ensure wastes are not being exposed outside designated areas. The sharps waste being accepted on-site will generally not be odorous due to nature of the autoinjector waste material. Minimal exposure to biological material means little risk of odour. Sharps waste receptacles contained in the waste processing area will be sealable in order to prevent the release of any possible odour from these receptacles.

With the adoption of the above control measures, and considering the small volume of sharps waste that will be present on-site at any one point in time, as well as the negligible levels of residual biological material contained in sharps bin, it is considered that there is no likelihood that the proposed facility will give rise to any odours of significance.

Note i Complete the table for each emission point having regard to the guidance hereunder.

The following convention should be observed when labelling emission points:

Boiler Emissions A1-1, A1-2, A1-3,...etc.

Main Emissions A2-1, A2-2, A2-3,...etc.

Minor Emissions A3-1, A3-2, A3-3,...etc. (NOTE: Minor emission points are to be included in the 'Emissions to Atmosphere - Minor and Potential' attachment)

Potential Emissions A4-1, A4-2, A4-3,...etc. (NOTE: Potential emission points are to be included in the '*Emissions to Atmosphere - Minor and Potential*' attachment)

A National Grid Reference (12 digit, 6E, 6N) must be provided for each emission point.

Measures are usually required to reduce, minimise or prevent emissions from occurring. They may involve the application of a single technique or a combination of techniques including process integrated, recovery, abatement and treatment techniques. List all techniques proposed/employed. Technique(s) employed must comply with BAT. Highlight additional measures required for the purposes of protecting the environment i.e. AQS considerations. The measures or techniques to be taken must be capable of complying with the proposed/known emission level(s).

The measures required shall be informed by the following:

1. BAT techniques with BAT-AEL

épa

- 2. BAT techniques without BAT-AEL
- 3. Stricter measures/techniques than BAT (due to AQS)
- 4. BAT determined by competent authority in consultation with the applicant
- 5. Measures to minimise pollution over long distances or in the territory of other states.
- 6. Emerging techniques
- 7. Less strict measures than BAT (due to derogation)
- 8. Other measures
- Select from the drop down list the source of the emission as it helps explain the nature of the emission.
- Particular attention should be paid to ensuring that emissions data (volumetric flow and pollutant concentrations) are presented at the required reference conditions for oxygen, temperature, pressure and moisture.

150.

Note ii Fugitive emissions include the following:

- Dust from area sources such as a guarry.
- Odour from volume sources such as a pig unit, waste water treatment plant, waste handling etc. For inspection purposes only and
- VOCs from processes using solvent not captured in waste gases.
- Ammonia and nitrogen from pig and poultry units.

Processes that can give rise to fugitive emissions include:

- o Leaks from valve seals, pump seals and flanges;
- o Breathing and working losses from liquid storage facilities;
- o Dust emissions from solids stored in the open;
- o Loading and unloading operations;
- o Cleaning operations; and,
- o Emissions from waste water treatment (e.g. volatile organics).

The measures taken to reduce/prevent fugitive emissions to atmosphere must be addressed, and the facilities and operations required to control emissions must be detailed.