

Amendments to this Application Form Attachment

Version No.	Date	Amendment since previous version	Reason		
V.1.0	July 2017	N/A	Online application form attachment		
As above	Mar 2018	Identification of required fields	Assist correct completion of attachment		
		ay ay other			
		1005-5 off of all			
		Consent of copyright owned required			



Noise Emissions (see Note i at the end of this attachment)

Note: An assessment of the impacts of noise, where applicable, should be uploaded in Tab 7 – 'Emissions Overview' of the application form.

Provide detail of measures to reduce noise	A facility of this nature and scale will not give rise to any noise emissions of significance. There will be no plant
emissions (list techniques)	or equipment situated on-site giving rise to significant levels of noise. All waste handling and storage activities
(See Note ii at the end of this attachment)	will take place indoors in designated areas. It is not envisaged that vehicle noise associated with the proposed
	activity will be significant given the type and volume of traffic transporting waste to the site (<1 consignment
	contained in a commercial van per day). In addition, the existing noise environment is already characterized
	by heavy traffic, tram noise, and commercial, light industrial and industrial noise. It is therefore envisaged that
	there will be a negligible impact on the local environment or surrounding receptors in terms of noise.
	mert
	In the context of a waste activity of this nature and scale, and given the existing noise characteristics of the
	local area, it is not considered necessary coccarry out periodic noise monitoring at Noise Sensitive Locations
	surrounding the proposed facility.

Following the *Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4)* (2012 as amended) complete the table below, inputting summary details of noise monitoring points (see Note iii at the end of this attachment) and proposed noise limit criteria.

Puredi

				attofor				
Monitoring point code ¹	Easting 2	Northing ³	Monitoring point type ⁴	Max. noise level daytime dB L _{Ar,T} (30 mins)	Max. noise level evening dB L _{Ar,T} (30 mins)	Max. noise level night dB L _{eq,τ} (15-30 mins)	How was the noise limit derived? ⁵	Proposed monitoring frequency

¹ The following convention should be observed when labelling noise monitoring points:

* indicates required field

N1, N2,.....The monitoring locations should be identified on an accompanying site plan drawing(s) uploaded in Tab 3 – 'Site' of the application form.

² Six Digit GPS Irish National Grid Reference of Monitoring Point

³ Six Digit GPS Irish National Grid Reference of Monitoring Point

⁴ Monitoring point type options: 'Boundary', 'Noise Sensitive Location' or 'Permanent Noise Monitoring'

⁵ Derived noise limit options: 'BAT', 'EQS', or 'Derogation'



	Proposed Noise Limit Criter			ise Limit Criteria	I			
Monitoring point code ¹	Easting 2	Northing ³	Monitoring point type ⁴	Max. noise level daytime dB L _{Ar,T} (30 mins)	Max. noise level evening dB L _{Ar,T} (30 mins)	Max. noise level night dB L _{eq,T} (15-30 mins)	How was the noise limit derived? ⁵	Proposed monitoring frequency
				For inspect		et use.		
					mily any	otte		
					urposes of for			
				es	tion Puretreat			
				FOLIDSO				
				at of cop?				
				Conset				

* indicates required field




				Proposed Noise Limit Criteria				
Monitoring point code ¹	Easting 2	Northing ³	Monitoring point type ⁴	Max. noise level daytime dB L _{Ar,T} (30 mins)	Max. noise level evening dB L _{Ar,T} (30 mins)	Max. noise level night dB L _{eq,τ} (15-30 mins)	How was the noise limit derived? ⁵	Proposed monitoring frequency

Note: Map(s)/drawing(s) uploaded under 'Site Plans' in Tab 3 of the application form should identify the emission and monitoring points.



Was an assessment for tonal and impulsive noise carried out? ⁶ (Yes/No)	No
If 'Yes' was tonal or impulsive noise identified to be present? (Yes/No)	Not applicable

For emissions outside the EPA Noise Guidance Note limit, see the Agency's *Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4)* (2012) (available on www.epa.ie), a full evaluation of the existing abatement/treatment system must be provided. <u>A planned programme of improvement towards meeting upgraded standards is required to be uploaded with this document</u>. This programme should highlight specific goals and a time scale, together with options for modification, upgrading or replacement, as required, to bring the emissions within the limits as set out in the Guidance Note.



⁶ Refer to section 5 of the Agency's Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4) (2012 as amended).



Note i This part of the application form collects data on noise emissions namely measures used to reduce noise and noise levels at a reference distance under normal operation. As noise emissions can arise from different sources on a site, the EPA usually considers the total emission from the site. Please note that emission limit values and monitoring requirements in any proposed licence shall be based on the information supplied hereunder.

- Note ii Measures are usually required to reduce, minimise or prevent emissions from occurring. They may involve the application of a single technique or a combination of techniques including housing, insulation and appropriate location of equipment. List all techniques proposed/employed. Technique(s) employed must comply with BAT. Highlight additional measures required for the purposes of protecting the environment. The measures or techniques to be taken must be capable of complying with the proposed/known emission level(s).
 - The measures required shall be informed by the following:

1. BAT techniques

- 2. Stricter measures/techniques than BAT
- 3. BAT determined by competent authority in consultation with the applicant
- 4. Other measures
- Poses office any other use. Note iii An individual record (i.e. row) is required for each monitoring point. A National Grid Reference (12 digit, 6E, 6N) must be given for each monitoring point. Noise emissions differ from other emissions in that they are generally mixed at a reference distance from the source(s). This reference distance should be, where possible, the boundary of the installation but in certain circumstances it is a noise sensitive location outside the boundary of the installation. Noise levels along a boundary will vary due to the location and positioning of noise sources and the 'worst case' should always be selected. Sufficient points should be identified to fully describe the noise levels from the installation. For waste activities, traffic noise emissions should be taken into account especially if it. The Agency's Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4) (2012) and Guidance Note on Noise assessment of Wind Turbine Operations at EPA licensed Sites (NG3)(as appropriate) should be consulted when setting proposed sound limits.