

# Appendix 3

## Soil Sampling Analysis Results

*For inspection purposes only.  
Consent of copyright owner required for any other use.*



## Amended Report

---

**Report No.:** 18-29228-2

**Initial Date of Issue:** 03-Oct-2018      **Date of Re-Issue:** 03-Oct-2018

**Client:** Priority Geotechnical Ltd

**Client Address:** Unit 12  
Owenacurra Business Park  
Midleton  
County Cork  
Ireland

**Contact(s):** Colette Kelly

**Project:** P18175 Scotch Corner

**Quotation No.:**      **Date Received:** 25-Sep-2018


**Order No.:** 11073      **Date Instructed:** 25-Sep-2018

**No. of Samples:** 3

**Turnaround (Wkdays):** 5      **Results Due:** 01-Oct-2018

**Date Approved:** 03-Oct-2018

**Approved By:**



**Details:** Martin Dyer, Laboratory Manager

---

For inspection purposes only.  
Consent of copyright owner required for any other use.

**Project: P18175 Scotch Corner**

<b>Client: Priority Geotechnical Ltd</b>	<b>Chemtest Job No.:</b>				18-29228	18-29228	18-29228
Quotation No.:	<b>Chemtest Sample ID.:</b>				694540	694541	694542
	Sample Location:				TP01	TP08	TP13
	Sample Type:				SOIL	SOIL	SOIL
	Top Depth (m):				3.50	1.50	3.00
	Date Sampled:				21-Sep-2018	21-Sep-2018	21-Sep-2018
<b>Determinand</b>	<b>Accred.</b>	<b>SOP</b>	<b>Units</b>	<b>LOD</b>			
Moisture	N	2030	%	0.020	47	28	48
Dry Matter	N		%	N/A	53	72	52

For inspection purposes only.  
 Consent of copyright owner required for any other use.

## Results - Single Stage WAC

Project: P18175 Scotch Corner

Chemtest Job No: 18-29228				Landfill Waste Acceptance Criteria			
Chemtest Sample ID: 694540				Limits			
Sample Ref:					Inert Waste Landfill	Stable, Non- reactive hazardous waste in non- hazardous Landfill	Hazardous Waste Landfill
Sample ID:							
Sample Location: TP01							
Top Depth(m): 3.50							
Bottom Depth(m):							
Sampling Date: 21-Sep-2018							
Determinand	SOP	Accred.	Units				
Total Organic Carbon	2625	U	%	7.3	3	5	6
Loss On Ignition	2610	U	%	12	--	--	10
Total BTEX	2760	U	mg/kg	< 0.010	6	--	--
Total PCBs (7 Congeners)	2815	U	mg/kg	< 0.10	1	--	--
TPH Total WAC (Mineral Oil)	2670	U	mg/kg	< 10	500	--	--
Total (Of 17) PAH's	2700	N	mg/kg	< 2.0	100	--	--
pH	2010	U		7.6	--	>6	--
Acid Neutralisation Capacity	2015	N	mol/kg	0.014	--	To evaluate	To evaluate
Eluate Analysis			10:1 Eluate mg/l	10:1 Eluate mg/kg	Limit values for compliance leaching test using BS EN 12457 at L/S 10 l/kg		
Arsenic	1450	U	0.0014	< 0.050	0.5	2	25
Barium	1450	U	0.012	< 0.50	20	100	300
Cadmium	1450	U	< 0.00010	< 0.010	0.04	1	5
Chromium	1450	U	< 0.0010	< 0.050	0.5	10	70
Copper	1450	U	< 0.0010	< 0.050	2	50	100
Mercury	1450	U	< 0.00050	< 0.0050	0.01	0.2	2
Molybdenum	1450	U	0.0019	< 0.050	0.5	10	30
Nickel	1450	U	< 0.0010	< 0.050	0.4	10	40
Lead	1450	U	< 0.0010	< 0.010	0.5	10	50
Antimony	1450	U	< 0.0010	< 0.010	0.06	0.7	5
Selenium	1450	U	< 0.0010	< 0.010	0.1	0.5	7
Zinc	1450	U	< 0.0010	< 0.50	4	50	200
Chloride	1220	U	1.4	14	800	15000	25000
Fluoride	1220	U	0.11	1.1	10	150	500
Sulphate	1220	U	21	210	1000	20000	50000
Total Dissolved Solids	1020	N	85	810	4000	60000	100000
Phenol Index	1920	U	< 0.030	< 0.30	1	-	-
Dissolved Organic Carbon	1610	U	15	150	500	800	1000

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	47

### Waste Acceptance Criteria

Landfill WAC analysis (specifically leaching test results) must not be used for hazardous waste classification purposes. This analysis is only applicable for hazardous waste landfill acceptance and does not give any indication as to whether a waste may be hazardous or non-hazardous.

## Results - Single Stage WAC

Project: P18175 Scotch Corner

Chemtest Job No: 18-29228				Landfill Waste Acceptance Criteria			
Chemtest Sample ID: 694541				Limits			
Sample Ref:					Inert Waste Landfill	Stable, Non- reactive hazardous waste in non- hazardous Landfill	Hazardous Waste Landfill
Sample ID:							
Sample Location: TP08							
Top Depth(m): 1.50							
Bottom Depth(m):							
Sampling Date: 21-Sep-2018							
Determinand	SOP	Accred.	Units				
Total Organic Carbon	2625	U	%	7.2	3	5	6
Loss On Ignition	2610	U	%	14	--	--	10
Total BTEX	2760	U	mg/kg	0.066	6	--	--
Total PCBs (7 Congeners)	2815	U	mg/kg	< 0.10	1	--	--
TPH Total WAC (Mineral Oil)	2670	U	mg/kg	930	500	--	--
Total (Of 17) PAH's	2700	N	mg/kg	< 2.0	100	--	--
pH	2010	U		8.0	--	>6	--
Acid Neutralisation Capacity	2015	N	mol/kg	0.0070	--	To evaluate	To evaluate
Eluate Analysis			10:1 Eluate mg/l	10:1 Eluate mg/kg	Limit values for compliance leaching test using BS EN 12457 at L/S 10 l/kg		
Arsenic	1450	U	0.0018	< 0.050	0.5	2	25
Barium	1450	U	0.0068	< 0.50	20	100	300
Cadmium	1450	U	< 0.0010	< 0.010	0.04	1	5
Chromium	1450	U	< 0.0010	< 0.050	0.5	10	70
Copper	1450	U	0.0010	< 0.050	2	50	100
Mercury	1450	U	< 0.00050	< 0.0050	0.01	0.2	2
Molybdenum	1450	U	0.0022	< 0.050	0.5	10	30
Nickel	1450	U	0.0014	< 0.050	0.4	10	40
Lead	1450	U	< 0.0010	< 0.010	0.5	10	50
Antimony	1450	U	< 0.0010	< 0.010	0.06	0.7	5
Selenium	1450	U	< 0.0010	< 0.010	0.1	0.5	7
Zinc	1450	U	0.0013	< 0.50	4	50	200
Chloride	1220	U	5.1	51	800	15000	25000
Fluoride	1220	U	2.8	28	10	150	500
Sulphate	1220	U	24	240	1000	20000	50000
Total Dissolved Solids	1020	N	110	1100	4000	60000	100000
Phenol Index	1920	U	< 0.030	< 0.30	1	-	-
Dissolved Organic Carbon	1610	U	11	110	500	800	1000

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	28

### Waste Acceptance Criteria

Landfill WAC analysis (specifically leaching test results) must not be used for hazardous waste classification purposes. This analysis is only applicable for hazardous waste landfill acceptance and does not give any indication as to whether a waste may be hazardous or non-hazardous.

## Results - Single Stage WAC

**Project: P18175 Scotch Corner**

Chemtest Job No: 18-29228 Chemtest Sample ID: 694542 Sample Ref: Sample ID: Sample Location: TP13 Top Depth(m): 3.00 Bottom Depth(m): Sampling Date: 21-Sep-2018				Landfill Waste Acceptance Criteria Limits			
				Inert Waste Landfill	Stable, Non-reactive hazardous waste in non-hazardous Landfill	Hazardous Waste Landfill	
Determinand	SOP	Accred.	Units				
Total Organic Carbon	2625	U	%	11	3	5	
Loss On Ignition	2610	U	%	38	--	10	
Total BTEX	2760	U	mg/kg	2.6	6	--	
Total PCBs (7 Congeners)	2815	U	mg/kg	< 0.10	1	--	
TPH Total WAC (Mineral Oil)	2670	U	mg/kg	< 10	500	--	
Total (Of 17) PAH's	2700	N	mg/kg	< 2.0	100	--	
pH	2010	U		8.1	--	>6	
Acid Neutralisation Capacity	2015	N	mol/kg	0.0080	--	To evaluate	
Eluate Analysis			10:1 Eluate mg/l	10:1 Eluate mg/kg	Limit values for compliance leaching test using BS EN 12457 at L/S 10 l/kg		
Arsenic	1450	U	0.0015	< 0.050	0.5	2	25
Barium	1450	U	0.012	< 0.50	20	100	300
Cadmium	1450	U	< 0.0010	< 0.010	0.04	1	5
Chromium	1450	U	< 0.0010	< 0.050	0.5	10	70
Copper	1450	U	0.0019	< 0.050	2	50	100
Mercury	1450	U	< 0.00050	< 0.0050	0.01	0.2	2
Molybdenum	1450	U	0.0020	< 0.050	0.5	10	30
Nickel	1450	U	< 0.0010	< 0.050	0.4	10	40
Lead	1450	U	< 0.0010	< 0.010	0.5	10	50
Antimony	1450	U	0.0040	0.040	0.06	0.7	5
Selenium	1450	U	< 0.0010	< 0.010	0.1	0.5	7
Zinc	1450	U	< 0.0010	< 0.50	4	50	200
Chloride	1220	U	2.6	26	800	15000	25000
Fluoride	1220	U	0.14	1.4	10	150	500
Sulphate	1220	U	39	390	1000	20000	50000
Total Dissolved Solids	1020	N	100	990	4000	60000	100000
Phenol Index	1920	U	< 0.030	< 0.30	1	-	-
Dissolved Organic Carbon	1610	U	15	150	500	800	1000

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	48

### Waste Acceptance Criteria

Landfill WAC analysis (specifically leaching test results) must not be used for hazardous waste classification purposes. This analysis is only applicable for hazardous waste landfill acceptance and does not give any indication as to whether a waste may be hazardous or non-hazardous.

SOP	Title	Parameters included	Method summary
1020	Electrical Conductivity and Total Dissolved Solids (TDS) in Waters	Electrical Conductivity and Total Dissolved Solids (TDS) in Waters	Conductivity Meter
1220	Anions, Alkalinity & Ammonium in Waters	Fluoride; Chloride; Nitrite; Nitrate; Total; Oxidisable Nitrogen (TON); Sulfate; Phosphate; Alkalinity; Ammonium	Automated colorimetric analysis using 'Aquakem 600' Discrete Analyser.
1450	Metals in Waters by ICP-MS	Metals, including: Antimony; Arsenic; Barium; Beryllium; Boron; Cadmium; Chromium; Cobalt; Copper; Lead; Manganese; Mercury; Molybdenum; Nickel; Selenium; Tin; Vanadium; Zinc	Filtration of samples followed by direct determination by inductively coupled plasma mass spectrometry (ICP-MS).
1610	Total/Dissolved Organic Carbon in Waters	Organic Carbon	TOC Analyser using Catalytic Oxidation
1920	Phenols in Waters by HPLC	Phenolic compounds including: Phenol, Cresols, Xylenols, Trimethylphenols Note: Chlorophenols are excluded.	Determination by High Performance Liquid Chromatography (HPLC) using electrochemical detection.
2010	pH Value of Soils	pH	pH Meter
2015	Acid Neutralisation Capacity	Acid Reserve	Titration
2030	Moisture and Stone Content of Soils(Requirement of MCERTS)	Moisture content	Determination of moisture content of soil as a percentage of its as received mass obtained at <37°C.
2610	Loss on Ignition	loss on ignition (LOI)	Determination of the proportion by mass that is lost from a soil by ignition at 550°C.
2625	Total Organic Carbon in Soils	Total organic Carbon (TOC)	Determined by high temperature combustion under oxygen, using an Eltra elemental analyser.
2670	Total Petroleum Hydrocarbons (TPH) in Soils by GC-FID	TPH (C6–C40); optional carbon banding e.g. 3-band – GRO, DRO & LRO*TPH C8–C40	Dichloromethane extraction / GC-FID
2700	Speciated Polynuclear Aromatic Hydrocarbons (PAH) in Soil by GC-FID	Acenaphthene; Acenaphthylene; Anthracene; Benzo[a]Anthracene; Benzo[a]Pyrene; Benzo[b]Fluoranthene; Benzo[ghi]Perylene; Benzo[k]Fluoranthene; Chrysene; Dibenzo[ah]Anthracene; Fluoranthene; Fluorene; Indeno[123cd]Pyrene; Naphthalene; Phenanthrene; Pyrene	Dichloromethane extraction / GC-FID
2760	Volatile Organic Compounds (VOCs) in Soils by Headspace GC-MS	Volatile organic compounds, including BTEX and halogenated Aliphatic/Aromatics.(cf. USEPA Method 8260)*please refer to UKAS schedule	Automated headspace gas chromatographic (GC) analysis of a soil sample, as received, with mass spectrometric (MS) detection of volatile organic compounds.
2815	Polychlorinated Biphenyls (PCB) ICES7Congeners in Soils by GC-MS	ICES7 PCB congeners	Acetone/Hexane extraction / GC-MS
640	Characterisation of Waste (Leaching)	Waste material including soil, sludges and granular waste	ComplianceTest for Leaching of Granular Waste Material and Sludge

## Report Information

### **Key**

---

- U UKAS accredited
- M MCERTS and UKAS accredited
- N Unaccredited
- S This analysis has been subcontracted to a UKAS accredited laboratory that is accredited for this analysis
- SN This analysis has been subcontracted to a UKAS accredited laboratory that is not accredited for this analysis
- T This analysis has been subcontracted to an unaccredited laboratory
- I/S Insufficient Sample
- U/S Unsuitable Sample
- N/E not evaluated
- < "less than"
- > "greater than"

Comments or interpretations are beyond the scope of UKAS accreditation

The results relate only to the items tested

Uncertainty of measurement for the determinands tested are available upon request

None of the results in this report have been recovery corrected

All results are expressed on a dry weight basis

The following tests were analysed on samples as received and the results subsequently corrected to a dry weight basis TPH, BTEX, VOCs, SVOCs, PCBs, Phenols

For all other tests the samples were dried at < 37°C prior to analysis

All Asbestos testing is performed at the indicated laboratory

Issue numbers are sequential starting with 1 all subsequent reports are incremented by 1

### **Sample Deviation Codes**

---

- A - Date of sampling not supplied
- B - Sample age exceeds stability time (sampling to extraction)
- C - Sample not received in appropriate containers
- D - Broken Container
- E - Insufficient Sample (Applies to LOI in Trommel Fines Only)

### **Sample Retention and Disposal**

---

All soil samples will be retained for a period of 45 days from the date of receipt

All water samples will be retained for 14 days from the date of receipt

Charges may apply to extended sample storage

If you require extended retention of samples, please email your requirements to:

[customerservices@chemtest.com](mailto:customerservices@chemtest.com)