

EPA Application Form

7.5 - Noise Emissions - Attachment

Organisation Name: *

Noel Lawler Sand & Gravel Ltd

Application I.D.: *

LA007210



Amendments to this Application Form Attachment

Version No.	Date	Amendment since previous version	Reason
V.1.0	July 2017	N/A	Online application form attachment
As above	Mar 2018	Identification of required fields	Assist correct completion of attachment
		Jeg.	
		as or others	
		ose od karik	

^{*} indicates required field



Noise Emissions (see Note i at the end of this attachment)

Note: An assessment of the impacts of noise, where applicable, should be uploaded in Tab 7 – 'Emissions Overview' of the application form.

Provide detail of measures to reduce noise emissions (list techniques)

(See Note ii at the end of this attachment)

The following general mitigation measures will be in operation at the site:

- All plant on-site will be maintained in accordance with manufacturer's recommendations. In particular, exhaust and silencer systems will be maintained in a satisfactory condition.
- All restoration plant and equipment to be used on-site will be modern equipment and will comply with the European Communities (Construction Plant and Equipment) (Permissible Noise Levels) Regulations.
- Any plant introduced to the site will not be excessively noisy. Where possible, noise data provided by suppliers will be consulted.
- Keeping site access and haul roads level and in good repair to reduce the potential for vibration from lorries.
- Tailgate slap during tipping events will be prevented by using rubber stops or powered tailgates.
- Communication through plant homs will be prohibited.
- Unnecessary revving of truck engines will be prohibited.
- Monitoring of noise may form part of the restoration environmental management system, as per planning/licence conditions.

Following the *Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4)* (2012 as amended) complete the table below, inputting summary details of noise monitoring points (See Note iii at the end of this attachment) and proposed noise limit criteria.

^{*} indicates required field



		ng Northing	Monitoring point type ⁴	Proposed Noise Limit Criteria				
Monitoring point code ¹	Easting ²			Max. noise level daytime dB L _{Ar,T} (30 mins)	Max. noise level evening dB L _{Ar,T} (30 mins)	Max. noise level night dB L _{eq,T} (15-30 mins)	How was the noise limit derived? 5	Proposed monitoring frequency
N1	680625	695379	To represent dwelling further northwest	55	45	45	Current planning condition no. 07/723	Annual
N2	680756	695059	To represent dwelling adjacent to access road	55	45	45	Current planning condition no. 07/723	Annual
N3	681052	694976	To represent nearest dwelling to S of pit	55	45abl and	45	Current planning condition no. 07/723	Annual
N4	681547	695191	To represent dwellings SE of pit	55 got its got to the first to	owner 45	45	Current planning condition no. 07/723	Annual
				Consentor				

¹ The following convention should be observed when labelling noise monitoring points: N1, N2,.....The monitoring locations should be identified on an accompanying site plan drawing(s) uploaded in Tab 3 – 'Site' of the application form.

² Six Digit GPS Irish National Grid Reference of Monitoring Point

³ Six Digit GPS Irish National Grid Reference of Monitoring Point

⁴ Monitoring point type options: 'Boundary', 'Noise Sensitive Location' or 'Permanent Noise Monitoring'

⁵ Derived noise limit options: 'BAT', 'EQS', or 'Derogation'

^{*} indicates required field



				Proposed Noise Limit Criteria				
Monitoring point code ¹	Easting ²	Northing 3	Monitoring point type ⁴	Max. noise level daytime dB L _{Ar,T} (30 mins)	Max. noise level evening dB L _{Ar,T} (30 mins)	Max. noise level night dB L _{eq,T} (15-30 mins)	How was the noise limit derived? 5	Proposed monitoring frequency
						TUSE.		
				Consent of convince	ज्योत्रं अप्र	other		
					uposes of for			
				وخ	don Priced			
				For its of	lo.			
				atofcol.				
				Courseit				

Note: Map(s)/drawing(s) uploaded under 'Site Plans' in Tab 3 of the application form should identify the emission and monitoring points.

^{*} indicates required field



Was an assessment for tonal and impulsive noise carried out? 6 (Yes/No)	No
If 'Yes' was tonal or impulsive noise identified to be present? (Yes/No)	N/A

For emissions outside the EPA Noise Guidance Note limit, see the Agency's Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4) (2012) (available on www.epa.ie), a full evaluation of the existing abatement/treatment system must be provided. A planned programme of improvement towards meeting upgraded standards is required to be uploaded with this document. This programme should highlight specific goals and a time scale, together with options for modification, upgrading or replacement, as required, to bring the emissions within the limits as set out in the Guidance Note.

Consent of copyright owner required for any other use

Refer to section 5 of the Agency's Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4) (2012 as amended).

^{*} indicates required field



Note i This part of the application form collects data on noise emissions namely measures used to reduce noise and noise levels at a reference distance under normal operation. As noise emissions can arise from different sources on a site, the EPA usually considers the total emission from the site. Please note that emission limit values and monitoring requirements in any proposed licence shall be based on the information supplied hereunder.

Note ii Measures are usually required to reduce, minimise or prevent emissions from occurring. They may involve the application of a single technique or a combination of techniques including housing, insulation and appropriate location of equipment. List all techniques proposed/employed. Technique(s) employed must comply with BAT. Highlight additional measures required for the purposes of protecting the environment. The measures or techniques to be taken must be capable of complying with the proposed/known emission level(s).

The measures required shall be informed by the following:

- 1. BAT techniques
- 2. Stricter measures/techniques than BAT
- 3. BAT determined by competent authority in consultation with the applicant
- 4. Other measures

Noise emissions differ from other emissions in that they are generally finited at a reference (12 digit, 6E, 6N) must be given for each monitoring point. Noise emissions differ from other emissions in that they are generally finited at a reference distance from the source(s). This reference distance should be, where possible, the boundary of the installation but in certain circumstances it is a noise sensitive location outside the boundary of the installation. Noise levels along a boundary will vary due to the location and positioning of noise sources and the 'worst case' should always be selected. Sufficient points should be identified to fully describe the noise levels from the installation. For waste activities, traffic noise emissions should be taken into account especially if it. The Agency's Guidance Note for Noise: Licence Applications, Surveys and Assessments in Relation to Scheduled Activities (NG4) (2012) and Guidance Note on Noise assessment of Wind Turbine Operations at EPA licensed Sites (NG3)(as appropriate) should be consulted when setting proposed sound limits.

^{*} indicates required field