EPA Application Form

7.4.1 - Emissions to Atmosphere - Main and Fugitive

Emissions - Attachment

of copylight

Ballyfaskin Enterprises Ltd

Organisation Name:*

Application I.D.: *

LA007359

Amendments to this Application Form Attachment

Version No.	Date	Amendment since previous version	Reason					
V.1.0	July 2017	N/A	Online application form attachment					
As above	Mar 2017	Identification of required fields	Assist correct completion of attachment					
		<u>ي</u> ې.						
		offer 18						
		Second to all						
Consend Constant of Constant o								





EMISSIONS TO ATMOSPHERE

Emissions to air/atmosphere include the following:

Main Emissions

Main emissions include all emissions of environmental significance. Where a **mass emission threshold** is specified in a BAT document (BAT Conclusions, National BAT note or BREF), emissions which exceed this threshold prior to abatement are regarded as significant, i.e., 'main emissions'. (In some cases emissions below the threshold can still be significant and qualify as Main Emissions).

Minor Emissions

Emissions below the mass emission threshold <u>may</u> be considered minor emissions and therefore do not generally need to be specifically controlled by the conditions or schedules of the licence (i.e., setting of ELVs, abatement control measures, or monitoring requirements). Emissions may also be deemed minor by virtue of their source/nature (e.g., laboratory fume hoods, workspace extractions, passive vents from storage tanks, HVAC exhausts), or composition (e.g., water vapour emissions).

For combustion plant such as boilers, these can be considered minor where the sate of the main fuel, and for liquid and solid fuels where its < 250kW.

In completing the separate '*Emissions to Atmosphere - Minor and Potential*' attachment for minor emissions, the applicant should supply sufficient information to justify the determination of the emission as minor. Notwithstanding this guidance, the Agency may consider any emission to be significant (i.e., a main emission) on the basis of environmental impact.

Fugitive Emissions

Fugitive emissions include emissions from non-point sources and diffuse sources.

Potential Emissions

These are emissions which only operate under abnormal process conditions. Typical examples include bursting discs, pressure relief valves, and emergency generators. Bypasses and flares may also fall within this category, depending on how they are operated or designed to operate. Although the Agency does not normally set controls in licences for potential emissions, it may do so for the purposes of environmental protection.

This attachment collects information on <u>main</u> and <u>fugitive</u> emissions to atmosphere. Waste gas means the final gaseous emission from a stack or abatement equipment.

For minor and potential emissions to atmosphere, complete the separate '*Emissions to Atmosphere - Minor and Potential*' attachment.



Main Emissions to Atmosphere - Waste Gas Emission Point Details - one row per emission point *

Complete the following table with summary details for all main emission points to atmosphere.

(Guidance on completing the table is included in Note i at the end of this attachment)

The applicant should address in particular any emissions which may contain the principal polluting substances listed in the First Schedule of Environmental Protection Agency (Integrated Pollution Control) (Licensing) Regulations 2013/ (Industrial Emissions)(Licensing) Regulations 2013.

Please note that the determination of any emission limit values and monitoring requirements in a proposed licence if granted will be based on the information supplied hereunder.

Emission			Typical Days	Measures to reduce /minimise / prevent emissions (list techniques) ¹	Source of Waste Gases	Minimum Discharge		Reference Conditions		
Point Code	Where EQS considerations require measures	offor any oth 2	Height Above Ground (m)	Pressure ⁵	Temp. 6	% Oxygen 7	Moisture ⁸			
Centre Point (of site)	179000	123374	365	Reduced protein in growing pig diet putche Cleanliness Covered/sealed skips for carcasses	Slurry tanks & pigs	4m	-	-	-	-
				entofcot						
				Const						

¹ Detailed descriptions and schematics of all abatement systems should be included in the Operational Report (Tab 4.8 – '*Reports*').

³ Six Digit GPS Irish National Grid Reference.

⁴ Six Digit GPS Irish National Grid Reference.

⁵ **Options:** 101.325kPa <u>or</u> No correction.

- ⁶ **Options:** 273.15K or No correction.
- ⁷ **Options:** 3%, 6%, 10%, 11%, 15%, 18% <u>or</u> No correction.
- ⁸ **Options:** Wet <u>or</u> Dry.

² Options: Boiler, Gas Turbine, Incineration, Co-Incineration, CHP, Kiln, Engine, Indirect drying activity (e.g. milk drying), Other Combustion activity (e.g., oven), Distillation/Chemical reaction, Solvent based coating activity, Other coating activity (provide description), Composting Tunnels, General extraction from buildings <u>or</u> Other (provide a description if 'Other' is selected).



Emission	Emission Po			ission Point Grid Ref. Typical Days		Measures to reduce /minimise / prevent emissions (list techniques) ¹	Source of Waste Gases	Minimum Discharge	Reference Conditions			
Point Code	Easting ³	Northing ⁴	Usage/ Year	Where EQS considerations require measures stricter than BAT, highlight these measures in bold	2	Height Above Ground (m)	Pressure ⁵	Temp. 6	% Oxygen 7	Moisture ⁸		
					. 11 ⁵⁰ .							
				Consent Configured	N. N. of other							
					ed tot of							
				in Purch	F							
				A HERONAL								
				FO OFFIC								
				consent								

*add rows to the table as necessary



Emission Points from Combustion, Incineration or Co-incineration Sources Only

Complete the table below for each emission point to atmosphere from a combustion source, waste incineration or co-incineration plant

Emission Point Code	Primary Fuel Type ⁹ (where applicable)	Secondary Fuel Type ¹⁰ (where applicable)	LCP Plant Reference (where applicable)	Waste incineration or co- incineration plant reference (where applicable)
None				
			of USC.	
			N. M. Offer	
			Dupost officer and other use.	
			Purpequired	
			Oection Victor	
		and in	BY X C	
*add rows to the table as	necessary	Consent of cop	3.	
		Consent		

⁹ Options: Coal, Lignite, Heavy Fuel Oil, Other Fuel Oil, Peat, Natural Gas, Biogas, Solid Biomass, Waste, Gas Oil, Other or None

¹⁰ **Options:** Coal, Lignite, Heavy Fuel Oil, Other Fuel Oil, Peat, Natural Gas, Biogas, Solid Biomass, Waste, Gas Oil, Other <u>or</u> None



Emission Points with Solvent Emissions Only

Complete the table below for each emission point associated with a solvent activity

Emission Point Code	Are specific Hazardous Substances ¹¹ Emitted?	Mass Flow of Emitted Hazardous Substances (g/hour)	Halogenated VOCs ¹² Emitted?	Mass Flow of Emitted Halogenated VOCs (g/hour)
None				
				or inspection net required to any other to
				ourpose
				- Dection Ferre
				of instant
				COX.
*add rows to th	e table as necessary		Collect	

¹¹ Emissions of volatile organic compounds referred to in Article 58 (Substances or mixtures which, because of their content of volatile organic compounds classified as carcinogens, mutagens, or toxic to reproduction under Regulation (EC) No. 1272/2008, are assigned or need to carry the hazard statements H340, H350,H350i, H360D or H360F) of the Industrial Emissions Directive.

¹² Halogenated volatile organic compounds which are assigned or need to carry the hazard statements H341 or H351.



Waste Gas Emission Monitoring Points

Complete the table below for each emission point, by entering the Emission Point Code, the associated Monitoring Point Code and the grid reference of the Monitoring Point. *

Emission Doint Code	Monitoring Doint Code ¹³	Monitoring Point Grid Reference			
Emission Point Code	Monitoring Point Code ¹³	Easting ¹⁴	Northing ¹⁵		
None					
			at Use.		
			atte		
		off off	ot ot		
		Purpoquiree			
		oectionnet.			
		Formight			
*add rows to the table as necessary		, of corr			
	دمع	For inspection purposes only For inspection owner required For ins			

¹³ To include monitoring and sampling points

¹⁴ Six Digit GPS Irish National Grid Reference

¹⁵ Six Digit GPS Irish National Grid Reference



Waste Gas - Abatement /Treatment Control

Complete the table below for each emission point with an abatement/treatment system (one table per emission point)

Emission Point Code: _____

Control ¹⁶ parameter	Monitoring to be carried out ¹⁷	Additional notes (where relevant)
None		
		se ^{o.}
		offer
	, c	NY and
	nuppos	5
	adion to reas	
	A Instituto	
	Food St.	
*add rows to the table as necessary	Conservor	·

¹⁶ List the operating parameters of the treatment/abatement system which control its function.

¹⁷ List the monitoring of the control parameter to be carried out.



Waste Gas Emissions

Complete the table below for all main emission points to atmosphere (include one row for each identified parameter) *

Emission			Proposed Emission Limits ¹⁸				BAT Associated	Sampling / Monitoring EPA Guidance for Monitoring - AG2 Index of Preferred Methods			
Point Code	Parameter	Monitoring Point Code	Max. Hourly 19	Max. Daily 20	Average Month 21	Average Annual 22	How was the Proposed Emission Limit Derived?	Emission Range (if applicable)	Proposed Monitoring Frequency	Proposed Monitoring and Analysis Method ²³	Compliant with BAT Monitoring Requirement?
								· 1150.			
								other			
							control	2113			
							o ^{sered}				
							On Patrecht				
							Section Particout				
						FOLD	tight				
						ofcop)				

* For continuous monitoring 'EN15267 approved CEMS' is the standard method. For periodic monitoring please refer to the EPA guidance document 'AG2 Index of Preferred Methods' linked above *add rows to the table as necessary

- ¹⁹ Specify the proposed limit <u>and the units.</u>
- ²⁰ Specify the proposed limit <u>and the units.</u>
- ²¹ Specify the proposed limit <u>and the units.</u>
- ²² Specify the proposed limit <u>and the units.</u>

¹⁸ For emissions outside the BAT Conclusion, BREF or BAT guidance limit, a full evaluation of the existing abatement/treatment system must be provided. A planned programme of improvement towards meeting upgraded standards is required. This should highlight specific goals and a time scale, together with options for modification, upgrading or replacement as required to bring emissions within the limits set out in the BAT Conclusion(s), BREF(s) or BAT guidance note(s). These notes can be found on the EPA website at <u>www.epa.ie</u>.

²³ For continuous monitoring 'EN15267 approved CEMS' is the standard method. For periodic monitoring please refer to the EPA guidance document <u>'AG2 Index of Preferred</u> <u>Methods'</u>.



Minor and/or Potential Emissions to Atmosphere ²⁴

Are there any minor or potential emission point(s) to atmosphere at the installation/facility?	Yes
(Yes/No) *	

If 'Yes' complete and upload the *Emissions to Atmosphere – Minor and Potential Emissions* template with details of minor and potential emissions (select Document Type: '<u>Minor - Potential Emissions</u>' in the application form)

Emissions to Atmosphere - Minor - Potential Emissions file name:

ne:	7.4.1-Air-Minor
	othernse.
	7.4.1-Air-Minor
	inspection Ptress
	Forting
Conse	<i>y</i>

²⁴ Refer to page 3 for guidance on what constitutes a minor or potential emission.



Fugitive Emission to Atmosphere

Fugitive emissions must be controlled by way of appropriate controls and techniques to minimise emissions. (Additional information on fugitive emission is included in Note ii at the end of this attachment)

Are there any sources of fugitive emissions at the installation/facility?²⁵ (Yes/No) *

If 'Yes' provide summary details of the fugitive emissions in the table below:

Type of Fugitive Emission	Emission Type Applicable? (Yes/No)	Description of fugitive emissions source(s)	Maximum Level	Units	Descriptor/Location
Dust	Yes	Dust from pig confinement Buildings	N/A	mg/m²/day	Dust deposition
VOC ²⁶	Yes	Non methane VOC emitted from slurry stores via ventilation from pig confinement buildings		%	of solvent input
Ammonia	Yes	Assuming mitigation 16.4tons will be emitted based on the pig numbers proposed. Emission source is the ventilation system of the pig confinement buildings. Standard national baseline levels are reported as 1.5 ug/m ³ NH ₃ ; levels adjoining intensive agricultural sites are reported are 8 - 9 ug/m ³ NH ₃ . The nearest European site is 3.9 km – therefore no effect.	1.5	ug/m³	at the nearest European Site
Nitrogen	Yes	As per ammonia		kgN/ha/yr	at the nearest European Site
Odour	Yes	Total odour units of licensed numbers is 119,485 o.us – revised numbers with mitigation will produce 119,193 o.u. therefore no significant change	N/A	Odour Units	at boundary of installation

²⁵ For waste activities, dust and odour emissions should be considered and described in the table below where applicable.

²⁶ In relation to activities listed in Chapter V (for installations using Organic Solvents) of the Industrial Emissions Directive (2010/75/EU):

⁻ specify how the requirements in relation to fugitive emissions will be met.

Provide details of the techniques to be used to reduce / minimise / prevent fugitive emissions in text bow below

Note i Complete the table for each emission point having regard to the guidance hereunder.

The following convention should be observed when labelling emission points:

Boiler Emissions A1-1, A1-2, A1-3,...etc.

Main Emissions A2-1, A2-2, A2-3,...etc.

Minor Emissions A3-1, A3-2, A3-3,...etc. (NOTE: Minor emission points are to be included in the 'Emissions to Atmosphere - Minor and Potential' attachment)

Potential Emissions A4-1, A4-2, A4-3,...etc. (NOTE: Potential emission points are to be included in the '*Emissions to Atmosphere - Minor and Potential*' attachment)

A National Grid Reference (12 digit, 6E, 6N) must be provided for each emission point.

Measures are usually required to reduce, minimise or prevent emissions from occurring. They may involve the application of a single technique or a combination of techniques including process integrated, recovery, abatement and treatment techniques. List all techniques proposed/employed. Technique(s) employed must comply with BAT. Highlight additional measures required for the purposes of protecting the environment i.e. AQS considerations. The measures or techniques to be taken must be capable of complying with the proposed/known emission level(s).

The measures required shall be informed by the following:

1. BAT techniques with BAT-AEL

2. BAT techniques without BAT-AEL

- 3. Stricter measures/techniques than BAT (due to AQS)
- 4. BAT determined by competent authority in consultation with the applicant
- 5. Measures to minimise pollution over long distances or in the territory of other states.

6. Emerging techniques

- 7. Less strict measures than BAT (due to derogation)
- 8. Other measures

Select from the drop down list the source of the emission as it helps explain the nature of the emission.

Particular attention should be paid to ensuring that emissions data (volumetric flow and pollutant concentrations) are presented at the required reference conditions for oxygen, temperature, pressure and moisture.



Note ii Fugitive emissions include the following:

epa

- Dust from area sources such as a quarry.
- Odour from volume sources such as a pig unit, waste water treatment plant, waste handling etc.
- VOCs from processes using solvent not captured in waste gases.
- Ammonia and nitrogen from pig and poultry units.

Processes that can give rise to fugitive emissions include:

- o Leaks from valve seals, pump seals and flanges;
- o Breathing and working losses from liquid storage facilities;
- o Dust emissions from solids stored in the open;
- o Loading and unloading operations;

o Loading and unloading operations; o Cleaning operations; and, o Emissions from waste water treatment (e.g. volatile organics). The measures taken to reduce/ prevent fugitive emissions to atmosphere must be detailed consent of copyright owner required to emissions must be detailed.