

# P88-GX



## Mechanical version

Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, modular fuel tank and collection basin with leak control float.

Fuel Tank Capacity l.	160
-----------------------	-----

## Rated Technical Data

Prime Power (PRP)	80.00 kVA
Prime Power (PRP)	64.00 kW
Limited Power (LTP)	88.00 kVA
Limited Power (LTP)	70.40 kW
Rated Power Factor (cos $\phi$ )	0.8
Windings	Three phases Series Star
Rated three-phase concatenated voltage	400 V
Rated phase-neutral voltage	230 V
Rated frequency	50 Hz
Fuel type	Diesel

## Dimensions And Noise

Length	2260 mm
Width	1040 mm
Height	1820 mm
Weight	1500 kg
Sound pressure 7 m.	65.0 dBA

## Fuel Consumption

Fuel Cons. at 100% (L.T.P.)	20.50 l/h
Fuel Cons. at 100% (P.R.P.)	18.70 l/h
Fuel Cons. at 75% (P.R.P.)	14.00 l/h
Fuel Cons. at 50% (P.R.P.)	9.70 l/h
Fuel Cons. at 25% (P.R.P.)	5.20 l/h

# P88-GX



## General Alternator Data

Alternator brand	STAMFORD
Alternator model	UCI224G
P.R.P. Power	85.0 kVA
L.T.P. Power	90.8 kVA
Winding	Three phases Series Star
Terminals Number	12.00 nr.
IP Protection	23
Electronic regulator	AS440
Precision	± 1.00 %

## General Engine Data

Engine brand	PERKINS
Engine model	1104A-44TG2
Cylinders	4
R.P.M.	1500
Cubic capacity	4.40
Air intake	Turbo
Standard voltage	12 Vdc
Sae	-
BMEP	1335 kPa
Cooling	Water
Flywheel P.R.P. Power	71.9 Kw
Flywheel Stand-by Power	79.1 kW
Electronic regulator	On request
Precision class	G2
Oil quantity	8.00
Engine Antifreeze capacity	7.00
Radiator type	Tropicalized
Heat from radiator	46.00 kW
Heat from exhaust	53.00 kW
Heat from radiation	13.00 kW
Exhaust temperature	555 ° C
Cooling air flow	89.00 m <sup>3</sup> /min
Combustion air flow	4.80 m <sup>3</sup> /min
Exhaust gas flow	12.50 m <sup>3</sup> /min
EU Stage	Not available

# P88-GX



## Standard Reference Conditions

Standard reference conditions temperature 25° C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortion. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values.

Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. The manufacturer reserves the right to revise the information without notice per our policy of continuous product development and improvement.